

Mail.XML Version 25.0

System Messages Specification

September 10, 2021

Working Group Chair

Bob Schimek, Quad

Technical Director

Shariq Mirza, DTAC Associate, Assurety Consulting & Solutions

Editor:

Shariq Mirza, DTAC Associate, Assurety Consulting & Solutions

Copyright (c) 2021 – Delivery Technology Advocacy Council (“DTAC”). All Rights Reserved.

Mail.dat is a registered trademark of DTAC

Mail.XML is a trademark of DTAC



Copyright and Legal Notices

© 2021 Delivery Technology Advocacy Council. All Rights Reserved.

Copyright 2021 – Delivery Technology Advocacy Council (“DTAC”) is the “Copyright Owner” of “Mail.XML®”. All rights reserved by the Copyright Owner under the laws of the United States, Belgium, the European Economic Community, and all states, domestic and foreign. This document may be downloaded and copied provided that all copies retain and display the copyright and any other proprietary notices contained in this document. This document may not be sold, modified, edited, or taken out of context such that it creates a false or misleading statement or impression as to the purpose or use of the Mail.XML® specification, which is an open standard. Use of this Standard, in accord with the foregoing limited permission, shall not create for the user any rights in or to the copyright, which rights are exclusively reserved to the Copyright Owner.

DTAC and the members of the Mail.XML® Specifications - Committee (collectively and individually, "Presenters") make no representations or warranties, express or implied, including, but not limited to, warranties of merchantability, fitness for a particular purpose, title, or non-infringement. The presenters do not make any representation or warranty that the contents of this document are free from error, suitable for any purpose of any user, or that implementation of such contents will not infringe any third-party patents, copyrights, trademarks or other rights. By making use of this document, the user assumes all risks and waives all claims against Presenters.

In no event shall Presenters be liable to user (or other person) for direct, indirect, special or consequential damages arising from or related to any use of this document, including, without limitation, lost profits, business interruption, loss of programs, or other data on your information handling system even if Presenters are expressly advised of the possibility of such damages.

Some states do not allow the disclaimer or limitation of damages, so the disclaimers set forth above apply to the maximum extent permitted under applicable law

Abstract

This document describes the messaging protocol for use by mailers and their consignees. The Mail.XML™ Transaction Protocol defines the roles and responsibilities of Shippers and Consignees and defines the format and method for message exchange. This messaging protocol is designed to be XML and Web-Services compliant.

Mail.XML and Mail.dat are trademarks of DTAC.

About Mail.XML™

Mail.XML™ is bringing a paradigm change to the industry by increasing business function specific B2B (Business to Business) communication within the industry that supports automation and in the end enables cost avoidance and higher profits through improved competence and effectiveness of communication. Mail.XML is designed to increase efficiency and lower costs by removing many manual data entry processes and enabling quick near real time communication between business partners. Mail.XML currently supports container based scheduling, pick up and drop off business processes, as well as identifying different business entities responsible for performing different services such as quality of mailing, address correction, and delivery confirmation on a mailing. The core focus of Mail.XML is communication between industry members and from industry to the final mail processing and delivery organization that delivers the mail to the end consumer, e.g., USPS. In the next few versions of Mail.XML the focus moves across mailing supply chain channels, and includes advanced functions such as payment; automated verification; enabling first, second, and third-party communication and incorporating presort planning, printing, and distribution processes.

What's New in Mail.XML Version 25.0?

With this release, the Mail.XML Messaging Protocol moves to Version 25.0. This release supports structure changes required by mailing industry and Postal Service.

Changes supported by Mail.XML 25.0 include:

- CR 2501 – Creates a new simpleType in the base schema called `machinabilityIndicatorType` that defines machinability.
 - Modify `PeriodicalLineItemData` to use the new `machinabilityIndicatorType`
 - Modify `PostageStatementLineItemData` to use the new `machinabilityIndicatorType`
- CR 2502 - Add enumerations to `serviceCodeType` to support Non-Standard Parcel Sizes.
- CR 2503 – Support USPS Tracking Plus Extra Service
 - Modify existing `serviceCodeType` to add 2 new enumeration values for USPS Tracking Plus
 - Modify existing `serviceSubCode` to add new enumerations for USPS Tracking Plus retention lengths.
- CR 2504 – Add new elements to the `CampaignData` block to accommodate new Informed Delivery features.
- CR 2506 - Modify `MaildatMPUInfoType` to use the new `machinabilityIndicatorType`
- CR 2507 – Remove fields related to ZAP certification status

About Mail.XML Schema Modularization

Today Mail.XML messages are grouped into 8 message types.

- Transportation Messages (TM)
- Mailing Messages (MM)
- Data Distribution Messages (DD)
- Dynamic Payment Template Messages
- Identification Messages (ID)
- Supply Chain Messages (SC)
- Informed Visibility (IV)
- System Messages
- Base: Shared simple types
- Definitions: Shared complex types and elements

The simple types shared across 2 or more modules are found in the Base schema. Likewise, the shared definitions module contains complex type definitions and elements that are shared across 2 or more modules.

Mail.XML Module Versioning Rules

The following versioning rules will be followed:

The Mail.XML wrapper schema**(.xsd) will always be given the next higher version number (or Errata designation) when any update is made to base, defs or any module. The name of the .xsd file will indicate the new version and the new version number will be used in the namespace and target declarations: xmlns:mailxml=<http://delivery-tech.org/Specs/mailxml25.0/mailxml>
targetNamespace=<http://delivery-tech.org/Specs/mailxml25.0/mailxml>

- When updates are made, only those modules that are updated will be given the next higher version number (or Errata letter designation).
- If updates are made to the base or defs, then the base and defs xsds will be given the next higher version number (or Errata designation) and all modules that call to them will also be given the next higher version number (or Errata designation).

For example:

- If the wrapper version is labeled as xmlns:mailxml="http://deliverytech.org/Specs/mailxml25.0A/mailxml" then at least one of the XSDs is at same version such as filename ='Mail.XML_25.0A.xsd' <- Errata A
- If the wrapper version is labeled as xmlns:mailxml="http://deliverytech.org/Specs/mailxml25.0B/mailxml" then at least one of the XSDs is at same version such as filename ='Mail.XML_25.0B.xsd' <- Errata B
- If the wrapper version is labeled as xmlns:mailxml="http://deliverytech.org/Specs/mailxml25.0/mailxml" then at least one of the XSDs is at same version such as filename ='Mail.XML_25.0.xsd' <- Major Version

Mail.XML 25.0 XSD Modules:

The following Mail.XML XSD modules/namespaces are used:

Note: Actual xsd filenames include the version number (e.g. *mailxml_base_25.0.xsd*).

- mailxml_tm.xsd: This module contains all the transportation (or FAST) messages and the attributes, elements and complex types that are unique to these messages. Namespace=mailxml_tm:
- mailxml_mm.xsd: This module contains all the mailing messages (eDoc) and the attributes, elements and complex types that are unique to these messages. Namespace=mailxml_mm:
- mailxml_iv.xsd: This module contains informed visibility messages and the attributes, elements and complex types that are unique to these messages. Namespace=mailxml_iv:
- mailxml_dd.xsd: This module contains all the data distribution messages and the attributes, elements and complex types that are unique to these messages. Namespace=mailxml_dd:
- mailxml_id.xsd: This module contains all the identification messages and the attributes, elements and complex types that are unique to these messages. Namespace=mailxml_id:
- mailxml_sc.xsd: This module contains all the supply chain messages and the attributes, elements and complex types that are unique to these messages. Namespace=mailxml_sc:
- mailxml_defs.xsd: This module contains all the common definitions of attributes, elements and mailxml_base.xsd: This module contains simple types that are shared across two or more modules that make up Mail.XML. These can be considered a building block for any message group. Namespace=mailxml_base:
- mailxml.xsd: This module contains the system messages of Mail.XML and is used to build custom profiles for Mail.XML. Namespace=mailxml:

The Mail.XML™ 25 Messaging Documentation Set

The Mail.XML Messaging Specification has been organized into a set of documents. This *Schemas Specification* is one document in a set of documents that make up the Mail.XML Specification 25.0. Updates in this Specification are NOT backwardly compatible with previous versions. Other documents in the specification set include:

- Mail.XML™ 25.0: Transportation Messaging Specification documents all transportation messages
- Mail.XML™ 25.0: Mailing Messaging Specification documents all mailing messages
- Mail.XML™ 25.0: Informed Visibility Specification documents all informed visibility messages
- Mail.XML™ 25.0: Data Distribution Messaging Specification documents all data distribution messages
- Mail.XML™ 25.0: Identification Messaging Specification documents all identification messages
- Mail.XML™ 25.0: Supply Chain Messaging Specification documents all supply chain messages
- Mail.XML™ 25.0: System Messaging Specification documents all systems and fault messages
- Mail.XML™ 25.0: Simple Types Specification documents all simple types used across Mail.XML messages
- Mail.XML™ 25.0: Common Definitions Specification documents all shared elements and complex types.
- Mail.XML™ 25.0: Schemas contains the .XSDs that make up the Mail.XML Messaging Specification

Table of Contents

ABSTRACT	3
ABOUT MAIL.XML™	3
WHAT'S NEW IN MAIL.XML VERSION 25.0?	3
ABOUT MAIL.XML SCHEMA MODULARIZATION	4
MAIL.XML MODULE VERSIONING RULES	4
MAIL.XML 25.0 XSD MODULES:.....	5
THE MAIL.XML™ 25 MESSAGING DOCUMENTATION SET	5
1 INDEX.....	8
2 ELEMENTS	8

1 Index

Schema **mailxml_25.0.xsd**

schema location: ..\MailXML v25.0\XSDs\mailxml_25.0.xsd
attributeFormDefault: **qualified**
elementFormDefault: **qualified**
targetNamespace: **http://delivery-tech.org/Specs/mailxml25.0/mailxml**

Elements

[DeliveryResponse](#)
[Fault](#)
[MessageResponseRetrievalRequest](#)
[MessageResponseRetrievalResponse](#)
[NotificationResponse](#)
[SystemVersionQueryRequest](#)
[SystemVersionQueryResponse](#)

Complex types


[messageResponseNotAvailableResponseType](#)
[messageResponseRetrievalRequestType](#)
[messageResponseRetrievalResponseType](#)

2 Elements


element **DeliveryResponse**

diagram	<p>DeliveryRespon...</p> <p>Response sent to USPS by a customer when any delivery is pushed. For example when a delivery point validation delivery is pushed by USPS this response is returned by the receiver.</p> <p>mailxml:1:UserLicenseCode</p> <p>mailxml:1:MaildatJobID</p> <p>mailxml:1:CustomerGroupID</p> <p>mailxml:1:MailingGroupID</p> <p>mailxml:1:PushMessageID</p> <p>mailxml:1:DeliveryType</p> <p>mailxml:1:ReturnInfo</p>
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml
children	mailxml:UserLicenseCode mailxml:MaildatJobID mailxml:CustomerGroupID mailxml:MailingGroupID mailxml:PushMessageID mailxml:DeliveryType mailxml:ReturnInfo
used by	element messageResponseRetrievalResponseType/QueryResults
annotation	documentation Response sent to USPS by a customer when any delivery is pushed. For example when a delivery point validation delivery is pushed by USPS this response is returned by the receiver.


element **DeliveryResponse/UserLicenseCode**

diagram			
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml		
type	mailxml_base:userLicenseCodeType		
facets	Kind	Value	Annotation
	minLength	1	
	maxLength	4	
	whiteSpace	preserve	


element **DeliveryResponse/MaildatJobID**

diagram			
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml		
type	mailxml_base:jobIDType		
facets	Kind	Value	Annotation
	minLength	1	
	maxLength	8	
	whiteSpace	preserve	


element **DeliveryResponse/CustomerGroupID**

diagram			
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml		
type	mailxml_base:s25		
facets	Kind	Value	Annotation
	minLength	1	
	maxLength	25	
	whiteSpace	preserve	


element **DeliveryResponse/MailingGroupID**

diagram			
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml		
type	xs:nonNegativeInteger		


element **DeliveryResponse/PushMessageID**

diagram			
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml		
type	mailxml_base:s25		
facets	Kind	Value	Annotation
	minLength	1	
	maxLength	25	
	whiteSpace	preserve	

element **DeliveryResponse/DeliveryType**

diagram			
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml		
type	xs:string		

element **DeliveryResponse/ReturnInfo**

diagram			
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml		
type	mailxml_defs:basicReturnInfoType		
children	mailxml_defs:ReturnCode mailxml_defs:ReturnDescription mailxml_defs:errorWarning mailxml_defs:ContainerErrorWarningBlock		

element **Fault**

diagram						
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml					
children	mailxml:ErrorWarning					
used by	element messageResponseRetrievalResponseType/QueryResults					
attributes	Name	Type	Use	Default	Fixed	Annotation
	mailxml:TrackingID	mailxml_base:s20				
annotation	documentation A fault message.					

attribute **Fault/@TrackingID**

namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml		
type	mailxml_base:s20		
facets	Kind	Value	Annotation
	minLength	1	
	maxLength	20	
	whiteSpace	preserve	

element **Fault/ErrorWarning**

diagram	<p>The diagram shows the structure of the mailxml:1:ErrorWarning element. It is a container element that contains a sequence of child elements. The children are: mailxml_defs:fs:Code, mailxml_defs:fs:Severity, mailxml_defs:fs:KeyIDvalues, mailxml_defs:fs:SubmissionDate, mailxml_defs:fs:ErrorDescription, mailxml_defs:fs:Action, mailxml_defs:fs:TrackingID, mailxml_defs:fs:SubmitterTrac..., and mailxml_defs:fs:MailxmlDetail.</p>
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml
type	mailxml_defs:errorWarningType
children	mailxml_defs:Code mailxml_defs:Severity mailxml_defs:KeyIDvalues mailxml_defs:SubmissionDate mailxml_defs:ErrorDescription mailxml_defs:Action mailxml_defs:TrackingID mailxml_defs:SubmitterTrackingID mailxml_defs:MailxmlDetail


element **MessageResponseRetrievalRequest**

diagram	<p>The diagram shows the structure of the MessageResponseRetrieval... element. It is a container element that contains a sequence of child elements. The children are: mailxml:1:SubmittingParty, mailxml:1:SubmittingSoftware, and mailxml:1:MessageResponse (1..∞).</p> <p>Request to send responses once more when the response was interrupted by a system fault.</p>
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml
children	mailxml:SubmittingParty mailxml:SubmittingSoftware mailxml:MessageResponse
annotation	documentation Request to send responses once more when the response was interrupted by a system fault.


element **MessageResponseRetrievalRequest/SubmittingParty**

diagram						
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml					
type	mailxml_defs:participantIDType					
attributes	Name	Type	Use	Default	Fixed	Annotation
	mailxml_defs:MailerID6	mailxml_base:mailerID6Type				
	mailxml_defs:MailerID9	mailxml_base:mailerID9Type				
	mailxml_defs:CRID	mailxml_base:CRIDType				
	mailxml_defs:SchedulerID	mailxml_base:s12				
	mailxml_defs:MaildatUserLicense	mailxml_base:userLicenseCodeType				
	mailxml_defs:ShippingAgentID	mailxml_base:s12				
	mailxml_defs:ReceivingAgentID	mailxml_base:s12				


element **MessageResponseRetrievalRequest/SubmittingSoftware**

diagram						
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml					
type	mailxml_defs:submittingSoftwareType					
attributes	Name	Type	Use	Default	Fixed	Annotation
	mailxml_defs:SoftwareName	xs:string	required			
	mailxml_defs:Vendor	xs:string	required			
	mailxml_defs:Version	xs:string	required			
	mailxml_defs:ApprovalDate	xs:date				
	mailxml_defs:ApprovalKey	xs:string				

element **MessageResponseRetrievalRequest/MessageResponse**

diagram						
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml					
type	mailxml:messageResponseRetrievalRequestType					
attributes	Name	Type	Use	Default	Fixed	Annotation
	mailxml:TrackingID	mailxml_base:s20	required			

element **MessageResponseRetrievalResponse**

diagram	 <p>Response to the Message Response Retrieval Request that resends interrupted responses.</p>					
---------	--	--	--	--	--	--

namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml
children	mailxml:MessageResponseRetrievalAccept mailxml:MessageResponseRetrievalReject
annotation	documentation Response to the Message Response Retrieval Request that resends interrupted responses.

element **MessageResponseRetrievalResponse/MessageResponseRetrievalAccept**

diagram						
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml					
type	mailxml:messageResponseRetrievalResponseType					
children	mailxml:QueryResults mailxml_defs:QueryError					
attributes	Name mailxml:TrackingID	Type mailxml_base:s20	Use required	Default	Fixed	Annotation


element **MessageResponseRetrievalResponse/MessageResponseRetrievalReject**

diagram						
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml					
type	mailxml:messageResponseNotAvailableResponseType					
children	mailxml:ReturnInfo					
attributes	Name mailxml:TrackingID	Type mailxml_base:s20	Use required	Default	Fixed	Annotation


element NotificationResponse

diagram	<p>NotificationResponse Standard response to a USPS notification to indicate the notification has been received.</p>
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml
children	mailxml:UserLicenseCode mailxml:MaildatJobID mailxml:CustomerGroupID mailxml:MailingGroupID mailxml:PushMessageID mailxml:NotificationDate mailxml:ReturnInfo
used by	element messageResponseRetrievalResponseType/QueryResults
annotation	documentation Standard response to a USPS notification to indicate the notification has been received.


element NotificationResponse/UserLicenseCode

element	NotificationResponse/UserLicenseCode		
diagram			
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml		
type	mailxml_base:userLicenseCodeType		
facets	Kind	Value	Annotation
	minLength	1	
	maxLength	4	
	whiteSpace	preserve	


element NotificationResponse/MaildatJobID

element: NotificationResponse/MaildatJobID			
diagram			
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml		
type	mailxml_base:jobIDType		
facets	Kind	Value	Annotation
	minLength	1	
	maxLength	8	
	whiteSpace	preserve	


element **NotificationResponse/CustomerGroupID**

diagram	 The diagram shows the element <code>mailxml:1:CustomerGroupID</code> with a dashed border and a small icon to the left.		
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml		
type	mailxml_base:s25		
facets	Kind	Value	Annotation
	minLength	1	
	maxLength	25	
	whiteSpace	preserve	


element **NotificationResponse/MailingGroupID**

diagram	 The diagram shows the element <code>mailxml:1:MailingGroupID</code> with a dashed border and a small icon to the left.		
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml		
type	xs:nonNegativeInteger		

element **NotificationResponse/PushMessageID**

diagram	 The diagram shows the element <code>mailxml:1:PushMessageID</code> with a dashed border and a small icon to the left.		
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml		
type	mailxml_base:s25		
facets	Kind	Value	Annotation
	minLength	1	
	maxLength	25	
	whiteSpace	preserve	

element **NotificationResponse/NotificationDate**

diagram	 The diagram shows the element <code>mailxml:1:NotificationDate</code> with a dashed border and a small icon to the left.		
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml		
type	xs:date		


element **NotificationResponse/ReturnInfo**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml
type	mailxml_defs:basicReturnInfoType
children	mailxml_defs:ReturnCode mailxml_defs:ReturnDescription mailxml_defs:errorWarning mailxml_defs:ContainerErrorWarningBlock

element **SystemVersionQueryRequest**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml
children	mailxml:TrackingID mailxml:SubmittingParty mailxml:SubmittingSoftware
annotation	documentation Query request for the receiving system version information.

element **SystemVersionQueryRequest/TrackingID**

diagram			
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml		
type	mailxml_base:s20		
facets	Kind	Value	Annotation
	minLength	1	
	maxLength	20	
	whiteSpace	preserve	

element **SystemVersionQueryRequest/SubmittingParty**

diagram	<p>The diagram illustrates the structure of the mailxml_defs:participantIDType element. It is a container for several attributes, each represented by a dashed box with a solid border. The attributes are:</p> <ul style="list-style-type: none"> mailxml_defs:fs:MailerID6 mailxml_defs:fs:MailerID9 mailxml_defs:fs:CRID mailxml_defs:fs:SchedulerID mailxml_defs:fs:MaildatUserLi... mailxml_defs:fs:ShippingAgen... mailxml_defs:fs:ReceivingAge... <p>The element is also shown as a container for the mailxml:1:SubmittingParty element, which is represented by a solid box with a dashed border.</p>					
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml					
type	mailxml_defs:participantIDType					
attributes	Name	Type	Use	Default	Fixed	Annotation
	mailxml_defs:MailerID6	mailxml_base:mailerID6Type				
	mailxml_defs:MailerID9	mailxml_base:mailerID9Type				
	mailxml_defs:CRID	mailxml_base:CRIDType				
	mailxml_defs:SchedulerID	mailxml_base:s12				
	mailxml_defs:MaildatUserLicense	mailxml_base:userLicenseCodeType				
	mailxml_defs:ShippingAgentID	mailxml_base:s12				
	mailxml_defs:ReceivingAgentID	mailxml_base:s12				

element **SystemVersionQueryRequest/SubmittingSoftware**

diagram						
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml					
type	mailxml_defs:submittingSoftwareType					
attributes	Name	Type	Use	Default	Fixed	Annotation
	mailxml_defs:SoftwareName	xs:string	required			
	mailxml_defs:Vendor	xs:string	required			
	mailxml_defs:Version	xs:string	required			
	mailxml_defs:ApprovalDate	xs:date				
	mailxml_defs:ApprovalKey	xs:string				

element **SystemVersionQueryResponse**

diagram						
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml					
children	mailxml:QueryResults mailxml_defs:QueryError					
used by	element	messageResponseRetrievalResponseType/QueryResults				
annotation	documentation	Response to a query for the receiving system version information.				

element **SystemVersionQueryResponse/QueryResults**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml
children	mailxml:TrackingID mailxml:SubmitterTrackingID mailxml:SoftwareStatus mailxml:ReturnInfo


element **SystemVersionQueryResponse/QueryResults/TrackingID**

diagram			
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml		
type	mailxml_base:s20		
facets	Kind	Value	Annotation
	minLength	1	
	maxLength	20	
	whiteSpace	preserve	


element **SystemVersionQueryResponse/QueryResults/SubmitterTrackingID**

diagram			
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml		
type	mailxml_base:s20		
facets	Kind	Value	Annotation
	minLength	1	
	maxLength	20	
	whiteSpace	preserve	

element **SystemVersionQueryResponse/QueryResults/SoftwareStatus**

diagram	 <p>The diagram shows the structure of the <code>mailxml_defs:submittingSoftwareType</code> element. It is a container element with a dashed border. Inside, there is an <code>attributes</code> group containing five elements: <code>mailxml_defs:fs:SoftwareName</code>, <code>mailxml_defs:fs:Vendor</code>, <code>mailxml_defs:fs:Version</code>, <code>mailxml_defs:fs:ApprovalDate</code>, and <code>mailxml_defs:fs:ApprovalKey</code>. The first three are solid boxes, while the last two are dashed boxes. A separate box on the left, <code>mailxml:nl:SoftwareStatus</code>, is connected to the container by a line.</p>					
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml					
type	mailxml_defs:submittingSoftwareType					
attributes	Name	Type	Use	Default	Fixed	Annotation
	mailxml_defs:SoftwareName	xs:string	required			
	mailxml_defs:Vendor	xs:string	required			
	mailxml_defs:Version	xs:string	required			
	mailxml_defs:ApprovalDate	xs:date				
	mailxml_defs:ApprovalKey	xs:string				

element **SystemVersionQueryResponse/QueryResults/ReturnInfo**

diagram	 <p>The diagram shows the structure of the <code>mailxml_defs:basicReturnInfoType</code> element. It is a container element with a dashed border. Inside, there is a sequence of four elements: <code>mailxml_defs:fs:ReturnCode</code>, <code>mailxml_defs:fs:ReturnDescrip...</code>, <code>mailxml_defs:fs:errorWarning</code>, and <code>mailxml_defs:fs:ContainerErr...</code>. The first two are solid boxes, and the last two are dashed boxes. A separate box on the left, <code>mailxml:nl:ReturnInfo</code>, is connected to the container by a line. The container has a cardinality of 0..∞, and each child element also has a cardinality of 0..∞.</p>					
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml					
type	mailxml_defs:basicReturnInfoType					
children	mailxml_defs:ReturnCode mailxml_defs:ReturnDescription mailxml_defs:errorWarning mailxml_defs:ContainerErrorWarningBlock					

complexType **messageResponseNotAvailableResponseType**

diagram						
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml					
children	mailxml:ReturnInfo					
used by	element MessageResponseRetrievalResponse/MessageResponseRetrievalReject					
attributes	Name	Type	Use	Default	Fixed	Annotation
	mailxml:TrackingID	mailxml_base:s20	required			

attribute **messageResponseNotAvailableResponseType/@TrackingID**

namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml		
type	mailxml_base:s20		
facets	Kind	Value	Annotation
	minLength	1	
	maxLength	20	
	whiteSpace	preserve	

element **messageResponseNotAvailableResponseType/ReturnInfo**

diagram			
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml		
type	mailxml_defs:returnInfoType		
children	mailxml_defs:ConsigneeFacility mailxml_defs:ErrorWarning mailxml_defs:ContainerErrorWarningBlock		


complexType **messageResponseRetrievalRequestType**

diagram						
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml					
used by	element MessageResponseRetrievalRequest/MessageResponse					
attributes	Name	Type	Use	Default	Fixed	Annotation
	mailxml:TrackingID	mailxml_base:s20	required			

attribute **messageResponseRetrievalRequestType/@TrackingID**

namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml		
type	mailxml_base:s20		
facets	Kind	Value	Annotation
	minLength	1	
	maxLength	20	
	whiteSpace	preserve	

complexType **messageResponseRetrievalResponseType**

diagram						
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml					
children	mailxml:QueryResults mailxml_defs:QueryError					
used by	element MessageResponseRetrievalResponse/MessageResponseRetrievalAccept					
attributes	Name	Type	Use	Default	Fixed	Annotation
	mailxml:TrackingID	mailxml_base:s20	required			

attribute **messageResponseRetrievalResponseType/@TrackingID**

namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml		
type	mailxml_base:s20		
facets	Kind	Value	Annotation
	minLength	1	

	maxLength 20
	whiteSpace preserve

element **messageResponseRetrievalResponseType/QueryResults**

diagram



namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml
children	mailxml:Fault mailxml_tm:AllApptCloseoutResponse mailxml_tm:ApptInductionCloseoutResponse mailxml_tm:CustomerSupplierAgreementQueryResponse mailxml_tm:DeliveryApptCancelCreateResponse mailxml_tm:DeliveryApptCancelResponse mailxml_tm:DeliveryApptContentRemoveResponse mailxml_tm:DeliveryApptCreateResponse mailxml_tm:DeliveryApptQueryResponse mailxml_tm:DeliveryApptShellCancelResponse mailxml_tm:DeliveryApptShellCreateResponse mailxml_tm:DeliveryApptShellUpdateResponse mailxml_tm:DeliveryApptStatusQueryResponse mailxml_tm:DeliveryApptTransportationUpdateResponse mailxml_tm:DeliveryApptUpdateResponse mailxml_tm:DeliveryContentCancelResponse mailxml_tm:DeliveryContentCreateResponse mailxml_tm:DeliveryContentQueryResponse mailxml_tm:DeliveryContentUpdateResponse mailxml_tm:GoodsReceiptResponse mailxml_tm:OpenApptQueryResponse mailxml_tm:PartnerApptQueryResponse mailxml_tm:PartnerContentAssignmentResponse mailxml_tm:PickupApptCancelResponse mailxml_tm:PickupApptCreateResponse mailxml_tm:PickupApptUpdateResponse mailxml_tm:RecurringApptQueryResponse mailxml_tm:StaleContentQueryResponse mailxml_tm:USPSDeliveryContentUpdatedQueryResponse mailxml_dd:ByForConflictQueryResponse mailxml_dd:DeliveryPointValidationQueryResponse mailxml_dd:AddressCorrectionQueryResponse mailxml_dd:DataQualityVerificationReportQueryResponse mailxml_dd:NixieDetailQueryResponse mailxml_dd:NonComplianceDataWithPostageOwedReportQueryResponse mailxml_dd:ScanSTCReconciliationQueryResponse mailxml_iv:ContainerVisibilityQueryResponse mailxml_iv:MPSVisQueryResponse mailxml_iv:StartTheClockQueryResponse mailxml_mm:BeginCombinedMailingResponse mailxml_mm:BundleDetailCancelResponse mailxml_mm:BundleDetailCreateResponse mailxml_mm:CloseMailingGroupResponse mailxml_mm:ComponentQueryResponse mailxml_mm:ComponentUpdateResponse mailxml_mm:ConsolidatedPeriodicalStatementCreateResponse mailxml_mm:ContainerBundleReportCancelResponse mailxml_mm:ContainerBundleReportCreateResponse mailxml_mm:ContainerBundleReportQueryResponse mailxml_mm:ContainerManifestCreateResponse mailxml_mm:ContainerManifestUpdateResponse mailxml_mm:ContainerManifestCancelResponse mailxml_mm:ContainerUpdateResponse mailxml_mm:CustomerMailReportCreateResponse mailxml_mm:EndCombinedMailingResponse mailxml_mm:InternationalPostageStatementCreateResponse mailxml_mm:InternationalPostageStatementQueryResponse mailxml_mm:InvoiceQueryResponse mailxml_mm:MailPieceCancelResponse mailxml_mm:MailPieceCreateResponse mailxml_mm:MailPieceUpdateResponse mailxml_mm:MailingGroupQueryResponse mailxml_mm:ManifestCreateResponse mailxml_mm:ManifestCancelResponse

	<p> mailxml_mm:ManifestPaymentExtractQueryResponse mailxml_mm:OpenMailingGroupResponse mailxml_mm:PaymentMessageQueryResponse mailxml_mm:PeriodicalStatementCreateResponse mailxml_mm:PeriodicalStatementQueryResponse mailxml_mm:PostageStatementCancelResponse mailxml_mm:PostageStatementCreateResponse mailxml_mm:PostageStatementQueryResponse mailxml_mm:PostageStatementStatusQueryResponse mailxml_mm:QualificationReportCreateResponse mailxml_mm:QualificationReportDetailCreateResponse mailxml_mm:QualificationReportQueryResponse mailxml_mm:QualificationReportSummaryCreateResponse mailxml_mm:ReconciliationReportQueryResponse mailxml_mm:SummaryZipDestinationReportCreateResponse mailxml_mm:TMSDataLoggerQueryResponse mailxml_id:CastofCharactersCancelResponse mailxml_id:CastofCharactersCreateResponse mailxml_id:CastofCharactersUpdateResponse mailxml_id:CustomerRelationIdentifyQueryResponse mailxml_id:CustomerRelationIdentifyUpdateResponse mailxml_id:IncentiveEnrollmentCreateResponse mailxml_id:USPSCRIDCreateValidateResponse mailxml_id:USPSMIDCreateValidateResponse mailxml_sc:ContainerStatusQueryResponse mailxml_sc:OriginalContainerLinkageCancelResponse mailxml_sc:OriginalContainerLinkageCreateResponse mailxml_sc:PostageAdjustmentCreateResponse mailxml_sc:SiblingContainerCancelResponse mailxml_sc:SiblingContainerCreateResponse mailxml:DeliveryResponse mailxml:NotificationResponse mailxml:SystemVersionQueryResponse mailxml:ReturnInfo </p>
--	---

element **messageResponseRetrievalResponseType/QueryResults/ReturnInfo**

diagram	
namespace	http://delivery-tech.org/Specs/mailxml25.0/mailxml
type	mailxml_defs:basicReturnInfoType
children	mailxml_defs:ReturnCode mailxml_defs:ReturnDescription mailxml_defs:errorWarning

	mailxml_defs:ContainerErrorWarningBlock
--	--