



***Mail.XML Version 23.0***  
**System Messages Specification**

**September 23, 2019**

**Working Group Chair**

Bob Schimek, Assurety Consulting, Inc.

**Technical Director**

Shariq Mirza, Idealliance

**Editor:**

Shariq Mirza, Idealliance

Copyright (c) International Digital Enterprise Alliance, Inc. [Idealliance] (2004 – 2019). All Rights Reserved.

Mail.dat is a registered trademark of Idealliance

Mail.XML is a trademark of Idealliance



## Copyright and Legal Notices

**© 2001 – 2019 International Digital Enterprise Alliance, Inc. All Rights Reserved.**

This document may be downloaded and copied provided that the above copyright notice and this Notice are included on all such copies. This document itself may not be modified in any way, except as needed for the purpose of developing International Digital Enterprise Alliance, Inc. (“Idealliance”) specifications. Use of the specification or standard set forth in this document shall not create for the user any rights in or to such specification or standard or this document, which rights are exclusively reserved to Idealliance or its licensors or contributors.

Use of this document and any specification or standard contained herein is voluntary. By making use of this document or any specification or standard contained herein, the user assumes all risks and waives all claims against Idealliance, its licensors and contributors. By making this document available, Idealliance is not providing any professional services or advice to any person or entity. Any person or entity utilizing this document or any specification or standard contained herein should rely upon the advice of a competent professional before using any such information.

NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE REGARDING THE ACCURACY, ADEQUACY, COMPLETENESS, LEGALITY, RELIABILITY OR USEFULNESS OF ANY INFORMATION CONTAINED IN THIS DOCUMENT OR IN ANY SPECIFICATION OR STANDARD OR OTHER PRODUCT MADE AVAILABLE BY IDEALLIANCE. THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN AND INCLUDED IN ANY SPECIFICATION OR STANDARD OR OTHER PRODUCT OR SERVICE OF IDEALLIANCE IS PROVIDED ON AN "AS IS" BASIS. IDEALLIANCE DISCLAIMS ALL WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY ACTUAL OR ASSERTED WARRANTY OF NON-INFRINGEMENT OF PROPRIETARY RIGHTS, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE.

IN NO EVENT SHALL IDEALLIANCE, ITS LICENSEES, CONTRIBUTORS OR THEIR RESPECTIVE OFFICERS, DIRECTORS, EMPLOYEES, AGENTS, REPRESENTATIVES, SUPPLIERS OR CONTENT OR SERVICE PROVIDERS BE LIABLE FOR DAMAGES OF ANY KIND, INCLUDING WITHOUT LIMITATION, DIRECT, INDIRECT, COMPENSATORY, SPECIAL, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES (INCLUDING WITHOUT LIMITATION DAMAGES FROM DATA LOSS OR BUSINESS INTERRUPTION) EVEN IF MADE AWARE OF THE POSSIBILITY OF SUCH DAMAGES, WHETHER IN AN ACTION UNDER CONTRACT, TORT OR ANY OTHER THEORY, ARISING OUT OF OR IN CONNECTION WITH THE USE, INABILITY TO USE OR PERFORMANCE OF THIS DOCUMENT, THE SPECIFICATION OR STANDARD CONTAINED HEREIN, OR ANY OTHER DOCUMENT OR SPECIFICATION OR STANDARD MADE AVAILABLE BY IDEALLIANCE.

Some states do not allow the disclaimer or limitation of damages, so the disclaimers set forth above apply to the maximum extent permitted under applicable law.

Idealliance takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed or implicated with respect to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available. Idealliance does not represent that it has made any effort to identify any such rights. Information on Idealliance's procedures with respect to rights in Idealliance specifications can be found at the Idealliance website at [www.Idealliance.org](http://www.Idealliance.org). Copies of third-party claims of rights, assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification, can be obtained from the President of Idealliance at [patent-disclosure@Idealliance.org](mailto:patent-disclosure@Idealliance.org).

Idealliance requests interested parties to disclose any copyrights, trademarks, service marks, patents, patent applications, or other proprietary or intellectual property rights which may cover technology that may be required to implement this specification. Please address the information to the President of Idealliance at [patent-disclosure@Idealliance.org](mailto:patent-disclosure@Idealliance.org).

## **Abstract**

This document describes the messaging protocol for use by mailers and their consignees. The Mail.XML™ Transaction Protocol defines the roles and responsibilities of Shippers and Consignees and defines the format and method for message exchange. This messaging protocol is designed to be XML and Web-Services compliant.

*Mail.XML and Mail.dat are trademarks of Idealliance.*

## **About Mail.XML™**

Mail.XML™ is bringing a paradigm change to the industry by increasing business function specific B2B (Business to Business) communication within the industry that supports automation and in the end enables cost avoidance and higher profits through improved competence and effectiveness of communication. Mail.XML is designed to increase efficiency and lower costs by removing many manual data entry processes and enabling quick near real time communication between business partners. Mail.XML currently supports container based scheduling, pick up and drop off business processes, as well as identifying different business entities responsible for performing different services such as quality of mailing, address correction, and delivery confirmation on a mailing. The core focus of Mail.XML is communication between industry members and from industry to the final mail processing and delivery organization that delivers the mail to the end consumer, e.g., USPS. In the next few versions of Mail.XML the focus moves across mailing supply chain channels, and includes advanced functions such as payment; automated verification; enabling first, second, and third party communication and incorporating presort planning, printing, and distribution processes.

## **What's New in Mail.XML Version 23.0?**

With this release, the Mail.XML Messaging Protocol moves to Version 23.0. In addition to minor cleanup, this release supports Mail.dat modernization and provides a new message for mailers to notify USPS of transportation dispatch details.

Changes supported by Mail.XML 23.0 include:

- Add a new element as part of MailCharacteristic Incentive block to allow users to provide data associated with Group ID for Electronic Sample of Mailpiece (eMailpieceSampleGroupID).
- Updates to ContainerScanQueryRequest to allow users to enter more than one ContainerID to request for status on more than one containers.

## **About Mail.XML Schema Modularization**

Today Mail.XML messages are grouped into 8 message types.

- Transportation Messages (TM)

- Mailing Messages (MM)
- Data Distribution Messages (DD)
- Dynamic Payment Template Messages
- Identification Messages (ID)
- Supply Chain Messages (SC)
- Informed Visibility (IV)
- System Messages
- Base: Shared simple types
- Definitions: Shared complex types and elements

The simple types shared across 2 or more modules are found in the Base schema. Likewise the shared definitions module contains complex type definitions and elements that are shared across 2 or more modules.

## **Mail.XML Module Versioning Rules**

The following versioning rules will be followed:

- The Mail.XML wrapper schema\*\*.xsd) will always be given the next higher version number (or Errata designation) when any update is made to base, defs or any module. The name of the .xsd file will indicate the new version and the new version number will be used in the namespace and target declarations: `xmlns:Mail.XML="http://Idealliance.org/Specs/Mail.XML23.0/Mail.XML"`  
`targetNamespace="http://Idealliance.org/Specs/Mail.XML23.0/Mail.XML"`
- When updates are made, only those modules that are updated will be given the next higher version number (or Errata letter designation).
- If updates are made to the base or defs, then the base and defs xsds will be given the next higher version number (or Errata designation) and all modules that call to them will also be given the next higher version number (or Errata designation).

For example:

- If the wrapper version is labeled as  
`xmlns:Mail.XML="http://Idealliance.org/Specs/Mail.XML15.0A/Mail.XML"` then at least one of the XSDs is at same version such as filename ='Mail.XML\_15.0.A.xsd' <- Errata A
- If the wrapper version is labeled as  
`xmlns:Mail.XML="http://Idealliance.org/Specs/Mail.XML15.0B/Mail.XML"` then at least one of the XSDs is at same version such as filename ='Mail.XML\_15.0B.xsd' <- Errata B

- If the wrapper version is labeled as `xmlns:Mail.XML="http://Idealliance.org/Specs/Mail.XML15.0/Mail.XML"` then at least one of the XSDs is at same version such as filename ='Mail.XML\_15.0.xsd' <- Major Version

## Mail.XML 23.0 XSD Modules:

The following Mail.XML XSD modules/namespaces are used:

- `Mail.XML_tm.xsd`: This module contains all the transportation (or FAST) messages and the attributes, elements and complex types that are unique to these messages. Namespace=`Mail.XML_tm`:
- `Mail.XML_mm.xsd`: This module contains all the mailing messages (eDoc) and the attributes, elements and complex types that are unique to these messages. Namespace=`Mail.XML_mm`:
- `Mail.XML_iv.xsd`: This module contains informed visibility messages and the attributes, elements and complex types that are unique to these messages. Namespace=`Mail.XML_iv`:
- `Mail.XML_dd.xsd`: This module contains all the data distribution messages and the attributes, elements and complex types that are unique to these messages. Namespace=`Mail.XML_dd`:
- `Mail.XML_id.xsd`: This module contains all the identification messages and the attributes, elements and complex types that are unique to these messages. Namespace=`Mail.XML_id`:
- `Mail.XML_sc.xsd`: This module contains all the supply chain messages and the attributes, elements and complex types that are unique to these messages. Namespace=`Mail.XML_sc`:
- `Mail.XML_defs.xsd`: This module contains all the common definitions of attributes, elements and complex types that are used across two or more message types. Namespace=`Mail.XML_defs`:
- `Mail.XML_base.xsd`: This module contains simple types that are shared across two or more modules that make up Mail.XML. These can be considered a building block for any message group. Namespace=`Mail.XML_base`:
- `Mail.XML.xsd`: This module contains the system messages of Mail.XML and is used to build custom profiles for Mail.XML. Namespace=`Mail.XML`:

## The Mail.XML™ 23 Messaging Documentation Set

The Mail.XML Messaging Specification has been organized into a set of documents. This *Schemas Specification* is one document in a set of documents that make up the Mail.XML Specification 23.0. Updates in this Specification are NOT backwardly compatible with previous versions. Other documents in the specification set include:

- Mail.XML™ 23.0: Transportation Messaging Specification documents all transportation messages
- Mail.XML™ 23.0: Mailing Messaging Specification documents all mailing messages
- Mail.XML™ 23.0: Informed Visibility Specification documents all informed visibility messages

- Mail.XML™ 23.0: Data Distribution Messaging Specification documents all data distribution messages
- Mail.XML™ 23.0: Identification Messaging Specification documents all identification messages
- Mail.XML™ 23.0: Supply Chain Messaging Specification documents all supply chain messages
- Mail.XML™ 23.0: System Messaging Specification documents all systems and fault messages
- Mail.XML™ 23.0: Simple Types Specification documents all simple types used across Mail.XML messages
- Mail.XML™ 23.0: Common Definitions Specification documents all shared elements and complex types.
- Mail.XML™ 23.0: Schemas contains the .XSDs that make up the Mail.XML Messaging Specification

## Table of Contents

Abstract .....	iii
About Mail.XML™ .....	iii
What's New in Mail.XML Version 23.0? .....	iii
About Mail.XML Schema Modularization .....	iii
Mail.XML Module Versioning Rules .....	iv
The Mail.XML™ 23 Messaging Documentation Set .....	v
1 Index.....	8
2 Elements.....	10

# 1 Index

schema location: [C:\WORK\idealliance\2-XML\23.0 - internal edits\MailXMLV23-9-23-19\mailxml\\_tm\\_23.0.xsd](C:\WORK\idealliance\2-XML\23.0 - internal edits\MailXMLV23-9-23-19\mailxml_tm_23.0.xsd)  
attribute form default: qualified  
element form default: qualified  
targetNamespace: [http://idealliance.org/Specs/mailxml23.0/mailxml\\_tm](http://idealliance.org/Specs/mailxml23.0/mailxml_tm)

Elements

[ActualConsigneeFacility](#)  
[ActualEndUnload](#)  
[ActualStartUnload](#)  
[ActualTruckArrival](#)  
[AllApptCloseoutDelivery](#)  
[AllApptCloseoutNotification](#)  
[AllApptCloseoutResponse](#)  
[AllDeliveryApptCloseoutRequest](#)  
[AllPickupApptCloseoutRequest](#)  
[ApptInductionCloseoutRequest](#)  
[ApptInductionCloseoutResponse](#)  
[ApptStatus](#)  
[ConsigneeGoodsReceipt](#)  
[ConsigneeGoodsReceiptDelivery](#)  
[ConsigneeGoodsReceiptNotification](#)  
[CustomerSupplierAgreementQueryRequest](#)  
[CustomerSupplierAgreementQueryResponse](#)  
[DeliveryApptCancelCreateRequest](#)  
[DeliveryApptCancelCreateResponse](#)  
[DeliveryApptCancelRequest](#)  
[DeliveryApptCancelResponse](#)  
[DeliveryApptContentRemoveRequest](#)  
[DeliveryApptContentRemoveResponse](#)  
[DeliveryApptCreateRequest](#)  
[DeliveryApptCreateResponse](#)  
[DeliveryApptMultiStopUpdateRequest](#)  
[DeliveryApptQueryRequest](#)  
[DeliveryApptQueryResponse](#)  
[DeliveryApptShellCancelRequest](#)  
[DeliveryApptShellCancelResponse](#)  
[DeliveryApptShellCreateRequest](#)  
[DeliveryApptShellCreateResponse](#)  
[DeliveryApptShellUpdateRequest](#)  
[DeliveryApptShellUpdateResponse](#)  
[DeliveryApptStatusQueryRequest](#)  
[DeliveryApptStatusQueryResponse](#)  
[DeliveryApptTransportationUpdateRequest](#)  
[DeliveryApptTransportationUpdateResponse](#)

Complex types

[actualBedloadType](#)  
[actualPalletType](#)  
[allDeliveryApptCloseoutAcceptType](#)  
[AppointmentInfoType](#)  
[apptBlockGoodsType](#)  
[apptBlockRequestType](#)  
[apptBlockUnscheduledGoodsType](#)  
[apptBlockUpdateType](#)  
[apptCloseoutDetailType](#)  
[apptCloseoutNotAvailableResponseType](#)  
[apptCloseoutResponseType](#)  
[apptInfoType](#)  
[availableApptType](#)  
[availableHourType](#)  
[availableSlotType](#)  
[bedloadHandlingUnitType](#)  
[bedloadUnitType](#)  
[carrierType](#)  
[containerInductionInfoType](#)  
[contentCancelType](#)  
[contentDetailInfoType](#)  
[contentDetailInfoUpdateType](#)  
[contentUspsSummaryType](#)  
[contentUspsSummaryUpdateType](#)  
[csaDispatchType](#)  
[csaInfoType](#)  
[deliveryApptAcceptType](#)  
[deliveryApptContentRemoveAcceptType](#)  
[deliveryApptContentRemoveRejectType](#)  
[deliveryApptRejectType](#)  
[deliveryApptShellAcceptType](#)  
[deliveryApptShellCancelRequestType](#)  
[deliveryApptShellCancelResponseType](#)  
[deliveryApptShellRejectType](#)  
[deliveryApptTransportationUpdateRequestType](#)  
[deliveryApptTransportationUpdateResponseType](#)  
[deliveryApptUpdateAcceptType](#)  
[deliveryApptUpdateRejectType](#)

Simple types

[appointmentNumberIdentifierType](#)  
[contentsBarcodeStatusType](#)  
[contentsBarcodeTypeType](#)  
[csaStatusType](#)  
[csaTemplateType](#)  
[IMcblInfoType](#)  
[locationStatusType](#)  
[packageServicesType](#)  
[processingCodeType](#)  
[scanEventType](#)  
[stopStatusType](#)  
[valueAddedServiceType](#)  
[verificationLocationType](#)

<a href="#">DeliveryApptUpdate</a>	<a href="#">deliveryContentAcceptType</a>
<a href="#">DeliveryApptUpdateRequest</a>	<a href="#">deliveryContentCancelRequestType</a>
<a href="#">DeliveryApptUpdateResponse</a>	<a href="#">deliveryContentCancelResponseType</a>
<a href="#">DeliveryContentCancelRequest</a>	<a href="#">deliveryContentRejectType</a>
<a href="#">DeliveryContentCancelResponse</a>	<a href="#">deliveryContentUpdateAcceptType</a>
<a href="#">DeliveryContentCreateRequest</a>	<a href="#">deliveryContentUpdatedType</a>
<a href="#">DeliveryContentCreateResponse</a>	<a href="#">deliveryContentUpdateRejectType</a>
<a href="#">DeliveryContentQueryRequest</a>	<a href="#">deliverySummaryType</a>
<a href="#">DeliveryContentQueryResponse</a>	<a href="#">detailInfoType</a>
<a href="#">DeliveryContentUpdateRequest</a>	<a href="#">eFileSamplingTimeType</a>
<a href="#">DeliveryContentUpdateResponse</a>	<a href="#">maildatSummaryType</a>
<a href="#">DeliveryReApptRequest</a>	<a href="#">oneTimeApptType</a>
<a href="#">DispatchContainerInfoNotification</a>	<a href="#">optionalApptType</a>
<a href="#">DispatchContainerInfoResponse</a>	<a href="#">optReturnInfoType</a>
<a href="#">GoodsReceiptResponse</a>	<a href="#">palletPresortType</a>
<a href="#">OpenApptQueryRequest</a>	<a href="#">palletUnitType</a>
<a href="#">OpenApptQueryResponse</a>	<a href="#">PartnerApptBlockType</a>
<a href="#">PartnerApptQueryRequest</a>	<a href="#">partnerContentAssignmentType</a>
<a href="#">PartnerApptQueryResponse</a>	<a href="#">pickupApptBlockRequestType</a>
<a href="#">PartnerContentAssignmentRequest</a>	<a href="#">presortType</a>
<a href="#">PartnerContentAssignmentResponse</a>	<a href="#">recurringApptBlockType</a>
<a href="#">PickupApptCancelRequest</a>	<a href="#">recurringApptType</a>
<a href="#">PickupApptCancelResponse</a>	<a href="#">slotAvailabilityType</a>
<a href="#">PickupApptCreateRequest</a>	<a href="#">staleContentNotificationElementType</a>
<a href="#">PickupApptCreateResponse</a>	<a href="#">trailerInfoType</a>
<a href="#">PickupApptUpdateRequest</a>	<a href="#">trailerType</a>
<a href="#">PickupApptUpdateResponse</a>	<a href="#">transportationContainerBlockType</a>
<a href="#">RecurringApptQueryRequest</a>	<a href="#">transportationContainerStatusBlockType</a>
<a href="#">RecurringApptQueryResponse</a>	<a href="#">transportationDetailBlockType</a>
<a href="#">ScheduledAppt</a>	<a href="#">transportationGeoDataBlockType</a>
<a href="#">StaleContentDelivery</a>	<a href="#">transportationSummaryBlockType</a>
<a href="#">StaleContentNotification</a>	<a href="#">trayHandlingUnitType</a>
<a href="#">StaleContentQueryRequest</a>	<a href="#">uspsClosedBySVType</a>
<a href="#">StaleContentQueryResponse</a>	<a href="#">uspsContainerInfoType</a>
<a href="#">UnscheduledConsigneeGoodsReceipt</a>	<a href="#">uspsDetailType</a>
<a href="#">UnscheduledConsigneeGoodsReceiptDeliver</a>	<a href="#">uspsSummaryType</a>
<a href="#">Y</a>	
<a href="#">UnscheduledConsigneeGoodsReceiptNotification</a>	
<a href="#">USPSDeliveryContentUpdatedDelivery</a>	
<a href="#">USPSDeliveryContentUpdatedNotification</a>	
<a href="#">USPSDeliveryContentUpdatedQueryRequest</a>	
<a href="#">USPSDeliveryContentUpdatedQueryResponse</a>	

## 2 Elements

### element ActualConsigneeFacility

diagram	<pre> classDiagram     class ActualConsigneeFacility     class mailxml_defs::CompanyName     class mailxml_defs::FacilityNumber     class mailxml_defs::FacilityAddress     class mailxml_defs::FacilityName     class mailxml_defs::FacilityType     class mailxml_defs::URL     class mailxml_defs::CommonContact      ActualConsigneeFacility &lt; -- mailxml_defs:consigneeFacilityType     mailxml_defs:consigneeFacilityType &lt; -- mailxml_defs:CompanyName     mailxml_defs:consigneeFacilityType &lt; -- mailxml_defs:FacilityNumber     mailxml_defs:consigneeFacilityType &lt; -- mailxml_defs:FacilityAddress     mailxml_defs:consigneeFacilityType &lt; -- mailxml_defs:FacilityName     mailxml_defs:consigneeFacilityType &lt; -- mailxml_defs:FacilityType     mailxml_defs:consigneeFacilityType &lt; -- mailxml_defs:URL     mailxml_defs:consigneeFacilityType &lt; -- mailxml_defs:CommonContact   </pre> <p>The diagram illustrates the structure of the <code>ActualConsigneeFacility</code> element. It is defined as a complex type (<code>mailxml_defs:consigneeFacilityType</code>) containing the following elements:</p> <ul style="list-style-type: none"> <li><code>mailxml_defs:CompanyName</code></li> <li><code>mailxml_defs:FacilityNumber</code></li> <li><code>mailxml_defs:FacilityAddress</code> (multiplicity 0..infinity)</li> <li><code>mailxml_defs:FacilityName</code></li> <li><code>mailxml_defs:FacilityType</code></li> <li><code>mailxml_defs:URL</code></li> <li><code>mailxml_defs:CommonContact</code></li> </ul>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<code>mailxml_defs:consigneeFacilityType</code>
properties	content complex
children	<code>mailxml_defs:CompanyName</code> <code>mailxml_defs:FacilityNumber</code> <code>mailxml_defs:FacilityAddress</code> <code>mailxml_defs:FacilityAddress</code> <code>mailxml_defs:FacilityName</code> <code>mailxml_defs:FacilityType</code> <code>mailxml_defs:URL</code> <code>mailxml_defs:CommonContact</code>
used by	complexTypes <a href="#">apptBlockGoodsType</a> <a href="#">apptBlockUnscheduledGoodsType</a>


### element ActualEndUnload

diagram	<pre> classDiagram     class ActualEndUnload     class xs::dateTime      ActualEndUnload &lt; -- xs:dateTime   </pre> <p>The diagram illustrates the structure of the <code>ActualEndUnload</code> element. It is defined as a simple type (<code>xs:dateTime</code>) with the following documentation:</p> <p>Actual date/time when unload is complete</p>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<code>xs:dateTime</code>
properties	content simple
used by	complexTypes <a href="#">apptBlockGoodsType</a> <a href="#">apptBlockUnscheduledGoodsType</a> <a href="#">apptInfoType</a>
annotation	documentation Actual date/time when unload is complete

**element ActualStartUnload**

diagram	 <b>ActualStartUnload</b>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>xs:dateTime</b>
properties	content simple
used by	complexTypes <a href="#">apptBlockGoodsType</a> <a href="#">apptBlockUnscheduledGoodsType</a> <a href="#">apptInfoType</a>

**element ActualTruckArrival**

diagram	 <b>ActualTruckArrival</b>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>xs:dateTime</b>
properties	content simple
used by	complexTypes <a href="#">apptBlockGoodsType</a> <a href="#">apptBlockUnscheduledGoodsType</a> <a href="#">apptInfoType</a>


## element AllApptCloseoutDelivery

diagram	<pre> classDiagram     class AllApptCloseoutDelivery {         grp mailxml_defs:LargeTrans...         mailxml_defs:MessageGroupID         mailxml_defs:TotalMessageCount         mailxml_defs:MessageSerialNumber         mailxml_defs:TransmittedRecordCount         mailxml_defs:TotalRecordsAcrossMessages         mailxml_defs&gt;LastMessage     }     class SubmittingParty     class SubmittingSoftware     class DataRecipient     class UserLicenseCode     class MaildatJobID     class CustomerGroupID     class MailingGroupID     class PushMessageID     class FullServiceAllApptCloseoutAccept      AllApptCloseoutDelivery "1..∞" --&gt; SubmittingParty     AllApptCloseoutDelivery "1..∞" --&gt; SubmittingSoftware     AllApptCloseoutDelivery "1..∞" --&gt; DataRecipient     AllApptCloseoutDelivery "1..∞" --&gt; UserLicenseCode     AllApptCloseoutDelivery "1..∞" --&gt; MaildatJobID     AllApptCloseoutDelivery "1..∞" --&gt; CustomerGroupID     AllApptCloseoutDelivery "1..∞" --&gt; MailingGroupID     AllApptCloseoutDelivery "1..∞" --&gt; PushMessageID     AllApptCloseoutDelivery "1..∞" --&gt; FullServiceAllApptCloseoutAccept   </pre>																																										
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																										
properties	content complex																																										
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_defs:DataRecipient</a> <a href="#">mailxml_tm:UserLicenseCode</a> <a href="#">mailxml_tm:MaildatJobID</a> <a href="#">mailxml_tm:CustomerGroupID</a> <a href="#">mailxml_tm:MailingGroupID</a> <a href="#">mailxml_tm:PushMessageID</a> <a href="#">mailxml_tm:FullServiceAllApptCloseoutAccept</a>																																										
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:MessageGroupID</td> <td><b>mailxml_base:s20</b></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:TotalMessageCount</td> <td><b>xs:positiveInteger</b></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MessageSerialNumber</td> <td><b>xs:positiveInteger</b></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:TransmittedRecordCount</td> <td><b>xs:positiveInteger</b></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:TotalRecordsAcrossMessages</td> <td><b>xs:positiveInteger</b></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs&gt;LastMessage</td> <td><b>mailxml_base:yesNo</b></td> <td>optional</td> <td>No</td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MessageGroupID	<b>mailxml_base:s20</b>	optional				mailxml_defs:TotalMessageCount	<b>xs:positiveInteger</b>	optional				mailxml_defs:MessageSerialNumber	<b>xs:positiveInteger</b>	optional				mailxml_defs:TransmittedRecordCount	<b>xs:positiveInteger</b>	optional				mailxml_defs:TotalRecordsAcrossMessages	<b>xs:positiveInteger</b>	optional				mailxml_defs>LastMessage	<b>mailxml_base:yesNo</b>	optional	No		
Name	Type	Use	Default	Fixed	annotation																																						
mailxml_defs:MessageGroupID	<b>mailxml_base:s20</b>	optional																																									
mailxml_defs:TotalMessageCount	<b>xs:positiveInteger</b>	optional																																									
mailxml_defs:MessageSerialNumber	<b>xs:positiveInteger</b>	optional																																									
mailxml_defs:TransmittedRecordCount	<b>xs:positiveInteger</b>	optional																																									
mailxml_defs:TotalRecordsAcrossMessages	<b>xs:positiveInteger</b>	optional																																									
mailxml_defs>LastMessage	<b>mailxml_base:yesNo</b>	optional	No																																								
annotation	documentation Delivery of full service closeout data of appointments from USPS.																																										

element **AllApptCloseoutDelivery/SubmittingParty**

diagram	<pre> classDiagram     class mailxml_tmSubmittingParty     class mailxml_defsParticipantIDType {         &lt;&lt;attributes&gt;&gt;         mailxml_defsMailerID6         mailxml_defsMailerID9         mailxml_defsCRID         mailxml_defsSchedulerID         mailxml_defsMaildatUserLicense         mailxml_defsShippingAgentID         mailxml_defsReceivingAgentID     }     mailxml_tmSubmittingParty "1" -- "1" mailxml_defsParticipantIDType   </pre>																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex																																								
isRef	0																																																
minOcc	0																																																
maxOcc	1																																																
content	complex																																																
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:MailerID6</td><td><b>mailxml_base:mailerID6Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MailerID9</td><td><b>mailxml_base:mailerID9Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:CRID</td><td><b>mailxml_base:CRIDType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatUserLicense</td><td><b>mailxml_base:userLicenseCodeType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShippingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ReceivingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

### element AllApptCloseoutDelivery/SubmittingSoftware

diagram																																					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																				
type	<b>mailxml_defs:submittingSoftwareType</b>																																				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex																												
isRef	0																																				
minOcc	0																																				
maxOcc	1																																				
content	complex																																				
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:SoftwareName</td><td><b>xs:string</b></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:Vendor</td><td><b>xs:string</b></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:Version</td><td><b>xs:string</b></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ApprovalDate</td><td><b>xs:date</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ApprovalKey</td><td><b>xs:string</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SoftwareName	<b>xs:string</b>	required				mailxml_defs:Vendor	<b>xs:string</b>	required				mailxml_defs:Version	<b>xs:string</b>	required				mailxml_defs:ApprovalDate	<b>xs:date</b>					mailxml_defs:ApprovalKey	<b>xs:string</b>				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_defs:SoftwareName	<b>xs:string</b>	required																																			
mailxml_defs:Vendor	<b>xs:string</b>	required																																			
mailxml_defs:Version	<b>xs:string</b>	required																																			
mailxml_defs:ApprovalDate	<b>xs:date</b>																																				
mailxml_defs:ApprovalKey	<b>xs:string</b>																																				

### element AllApptCloseoutDelivery/UserLicenseCode


diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:userLicenseCodeType</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	content	simple								
isRef	0												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>4</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	4		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	4												
whiteSpace	preserve												

### element AllApptCloseoutDelivery/MaildatJobID

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:jobIDType</b>

properties	isRef 0 content simple
facets	Kind Value annotation minLength 1 maxLength 8 whiteSpace preserve


#### element **AllApptCloseoutDelivery/CustomerGroupID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s25</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 25 whiteSpace preserve

#### element **AllApptCloseoutDelivery/MailingGroupID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:nonNegativeInteger</b>
properties	isRef 0 content simple

#### element **AllApptCloseoutDelivery/PushMessageID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s25</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 25 whiteSpace preserve

element **AllApptCloseoutDelivery/FullServiceAllApptCloseoutAccept**

diagram																															
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																														
type	<a href="#"><b>mailxml_tm:allDeliveryApptCloseoutAcceptType</b></a>																														
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>1</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	1	maxOcc	unbounded	content	complex																						
isRef	0																														
minOcc	1																														
maxOcc	unbounded																														
content	complex																														
children	<a href="#"><b>mailxml_tm:ConsigneeGoodsReceipt</b></a> <a href="#"><b>mailxml_tm:UnscheduledConsigneeGoodsReceipt</b></a>																														
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:CloseoutResponseID</td> <td><a href="#">mailxml_base:s12</a></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:CreatorSchedulerCorpID</td> <td><a href="#">mailxml_base:s12</a></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:CreatorSchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:CreatorSchedulerCRID</td> <td><a href="#">mailxml_base:CRIDType</a></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:CloseoutResponseID	<a href="#">mailxml_base:s12</a>	optional				mailxml_tm:CreatorSchedulerCorpID	<a href="#">mailxml_base:s12</a>	optional				mailxml_tm:CreatorSchedulerID	<a href="#">mailxml_base:s12</a>	optional				mailxml_tm:CreatorSchedulerCRID	<a href="#">mailxml_base:CRIDType</a>	optional			
Name	Type	Use	Default	Fixed	annotation																										
mailxml_tm:CloseoutResponseID	<a href="#">mailxml_base:s12</a>	optional																													
mailxml_tm:CreatorSchedulerCorpID	<a href="#">mailxml_base:s12</a>	optional																													
mailxml_tm:CreatorSchedulerID	<a href="#">mailxml_base:s12</a>	optional																													
mailxml_tm:CreatorSchedulerCRID	<a href="#">mailxml_base:CRIDType</a>	optional																													

## element AllApptCloseoutNotification


diagram	<pre> classDiagram     class AllApptCloseoutNotification {         mailxml_tm:SubmittingParty         mailxml_tm:SubmittingSoftware         mailxml_tm:CRID         mailxml_tm:PushMessageID         mailxml_tm:UserLicenseCode         mailxml_tm:MaildatJobID         mailxml_tm:CustomerGroupID         mailxml_tm:MailingGroupID         mailxml_tm:NotificationDate     }     class SubmittingParty     class SubmittingSoftware     class CRID     class PushMessageID     class UserLicenseCode     class MaildatJobID     class CustomerGroupID     class MailingGroupID     class NotificationDate      AllApptCloseoutNotification "1" --&gt; "1" SubmittingParty :      AllApptCloseoutNotification "1" --&gt; "1" SubmittingSoftware :      AllApptCloseoutNotification "1" --&gt; "1" CRID :      AllApptCloseoutNotification "1" --&gt; "1" PushMessageID :      AllApptCloseoutNotification "1" --&gt; "1" UserLicenseCode :      AllApptCloseoutNotification "1" --&gt; "1" MaildatJobID :      AllApptCloseoutNotification "1" --&gt; "1" CustomerGroupID :      AllApptCloseoutNotification "1" --&gt; "1" MailingGroupID :      AllApptCloseoutNotification "1" --&gt; "1" NotificationDate :   </pre> <p>Notification from UPS that full service closeout data is ready to be picked up.</p>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
properties	content complex
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:CRID</a> <a href="#">mailxml_tm:PushMessageID</a> <a href="#">mailxml_tm:UserLicenseCode</a> <a href="#">mailxml_tm:MaildatJobID</a> <a href="#">mailxml_tm:CustomerGroupID</a> <a href="#">mailxml_tm:MailingGroupID</a> <a href="#">mailxml_tm:NotificationDate</a>
annotation	documentation Notification from UPS that full service closeout data is ready to be picked up.

## element AllApptCloseoutNotification/SubmittingParty

diagram	<pre> classDiagram     class SubmittingParty     class participantIDType {         attributes             mailxml_defs:MailerID6             mailxml_defs:MailerID9             mailxml_defs:CRID             mailxml_defs:SchedulerID             mailxml_defs:MaildatUserLicense             mailxml_defs:ShippingAgentID             mailxml_defs:ReceivingAgentID     }     SubmittingParty "1" --&gt; "1" participantIDType :   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_defs:participantIDType</a>

properties	isRef 0 minOcc 0 maxOcc 1 content complex					
attributes	Name mailxml_defs:MailerID6 mailxml_defs:MailerID9 mailxml_defs:CRID mailxml_defs:SchedulerID mailxml_defs:MaildatUserLicense mailxml_defs:ShippingAgentID mailxml_defs:ReceivingAgentID	Type <b>mailxml_base:mailerID6Type</b> <b>mailxml_base:mailerID9Type</b> <b>mailxml_base:CRIDType</b> <b>mailxml_base:s12</b> <b>mailxml_base:userLicenseCodeType</b> <b>mailxml_base:s12</b> <b>mailxml_base:s12</b>	Use	Default	Fixed	annotation

### element AllApptCloseoutNotification/SubmittingSoftware

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_defs:submittingSoftwareType</b>
properties	isRef 0 minOcc 0 maxOcc 1 content complex
attributes	Name mailxml_defs:SoftwareName Type <b>xs:string</b> required mailxml_defs:Vendor Type <b>xs:string</b> required mailxml_defs:Version Type <b>xs:string</b> required mailxml_defs:ApprovalDate Type <b>xs:date</b> mailxml_defs:ApprovalKey Type <b>xs:string</b>

### element AllApptCloseoutNotification/CRID

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:CRIDType</b>

properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 15 pattern ([0-9])*

#### element AllApptCloseoutNotification/PushMessageID

diagram	mailxml_tm:PushMessageID
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	mailxml_base:s25
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 25 whiteSpace preserve

#### element AllApptCloseoutNotification/UserLicenseCode


diagram	mailxml_tm:UserLicenseCode
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	mailxml_base:userLicenseCodeType
properties	isRef 0 content simple
facets	Kind Value annotation minLength 1 maxLength 4 whiteSpace preserve

#### element AllApptCloseoutNotification/MaildatJobID

diagram	mailxml_tm:MaildatJobID
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	mailxml_base:jobIDType
properties	isRef 0 content simple
facets	Kind Value annotation minLength 1 maxLength 8

	whiteSpace preserve
--	---------------------

element **AllApptCloseoutNotification/CustomerGroupID**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s25</b>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>25</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	25		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	25												
whiteSpace	preserve												

element **AllApptCloseoutNotification/MailingGroupID**

diagram					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm				
type	<b>xs:nonNegativeInteger</b>				
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	content	simple
isRef	0				
content	simple				

element **AllApptCloseoutNotification/NotificationDate**

diagram					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm				
type	<b>xs:date</b>				
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	content	simple
isRef	0				
content	simple				

## element AllApptCloseoutResponse


diagram	<p><b>AllApptCloseoutResponse</b></p> <p>Response to the request to closeout all delivery appointments.</p> <p><b>attributes</b></p> <ul style="list-style-type: none"> <li>grp mailxml_defs:LargeTrans...</li> <li>mailxml_defs:MessageGroupID</li> <li>mailxml_defs:TotalMessageCou...</li> <li>mailxml_defs:Message SerialNu...</li> <li>mailxml_defs:TransmittedRecor...</li> <li>mailxml_defs:TotalRecordsAcro...</li> <li>mailxml_defs:LastMessage</li> </ul> <p><b>children</b></p> <ul style="list-style-type: none"> <li>mailxml_tm:TrackingID</li> <li>mailxml_tm:SubmitterTrackingID</li> <li>mailxml_tm:LargeTransactionDividerResult</li> <li>mailxml_tm:AllDeliveryApptCloseoutAccept</li> <li>mailxml_tm:AllDeliveryApptCloseoutReject</li> </ul> <p><b>notes</b></p> <ul style="list-style-type: none"> <li>Response indicating that all delivery appointments have been closed.</li> <li>Response indicating that all delivery appointments could not be closed and why.</li> </ul>																																										
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																										
properties	content complex																																										
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_defs:LargeTransactionDividerResult</a> <a href="#">mailxml_tm:AllDeliveryApptCloseoutAccept</a> <a href="#">mailxml_tm:AllDeliveryApptCloseoutReject</a>																																										
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:MessageGroupID</td> <td><a href="#">mailxml_base:s20</a></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:TotalMessageCount</td> <td><a href="#">xs:positiveInteger</a></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MessageSerialNumber</td> <td><a href="#">xs:positiveInteger</a></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:TransmittedRecordCount</td> <td><a href="#">xs:positiveInteger</a></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:TotalRecordsAcrossMessages</td> <td><a href="#">xs:positiveInteger</a></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:LastMessage</td> <td><a href="#">mailxml_base:yesNo</a></td> <td>optional</td> <td>No</td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MessageGroupID	<a href="#">mailxml_base:s20</a>	optional				mailxml_defs:TotalMessageCount	<a href="#">xs:positiveInteger</a>	optional				mailxml_defs:MessageSerialNumber	<a href="#">xs:positiveInteger</a>	optional				mailxml_defs:TransmittedRecordCount	<a href="#">xs:positiveInteger</a>	optional				mailxml_defs:TotalRecordsAcrossMessages	<a href="#">xs:positiveInteger</a>	optional				mailxml_defs:LastMessage	<a href="#">mailxml_base:yesNo</a>	optional	No		
Name	Type	Use	Default	Fixed	annotation																																						
mailxml_defs:MessageGroupID	<a href="#">mailxml_base:s20</a>	optional																																									
mailxml_defs:TotalMessageCount	<a href="#">xs:positiveInteger</a>	optional																																									
mailxml_defs:MessageSerialNumber	<a href="#">xs:positiveInteger</a>	optional																																									
mailxml_defs:TransmittedRecordCount	<a href="#">xs:positiveInteger</a>	optional																																									
mailxml_defs:TotalRecordsAcrossMessages	<a href="#">xs:positiveInteger</a>	optional																																									
mailxml_defs:LastMessage	<a href="#">mailxml_base:yesNo</a>	optional	No																																								
annotation	documentation Response to the request to closeout all delivery appointments.																																										

## element AllApptCloseoutResponse/TrackingID


diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>

type	<b>mailxml_base:s20</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

#### element AllApptCloseoutResponse/SubmitterTrackingID

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:s20</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

#### element AllApptCloseoutResponse/AllDeliveryApptCloseoutAccept

diagram	 <p>Response indicating that all delivery appointments have been closed.</p> <p>A report or message indicating delivery closeout status for a scheduled appointment.</p> <p>A report or message indicating delivery closeout status for an unscheduled delivery.</p>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>

properties	isRef 0 content complex						
children	<a href="#">mailxml_tm:ConsigneeGoodsReceipt</a> <a href="#">mailxml_tm:UnscheduledConsigneeGoodsReceipt</a>						
attributes	Name mailxml_tm:CloseoutResponseID mailxml_tm:CreatorSchedulerCorpID mailxml_tm:CreatorSchedulerID mailxml_tm:CreatorSchedulerCRID	Type <b>mailxml_base:s12</b> <b>mailxml_base:s12</b> <b>mailxml_base:s12</b> <b>mailxml_base:CRIDType</b>	Use optional optional optional optional	Default	Fixed	annotation	
annotation	documentation Response indicating that all delivery appointments have been closed.						

### element AllApptCloseoutResponse/AllDeliveryApptCloseoutReject

diagram	<pre> classDiagram     class mailxml_tm {         &lt;&lt;Attributes&gt;&gt;         &lt;&lt;Group&gt;&gt; mailxml_tm_StatusRequest         mailxml_tm_CloseoutResponseID         mailxml_tm_CreatorSchedulerCorpID         mailxml_tm_CreatorSchedulerID         mailxml_tm_CreatorSchedulerCRID     }     mailxml_tm "1" --&gt; "1" mailxml_tm_ReturnInfo     mailxml_tm_StatusRequest "1" --&gt; "1" mailxml_tm_CloseoutResponseID     mailxml_tm_StatusRequest "1" --&gt; "1" mailxml_tm_CreatorSchedulerCorpID     mailxml_tm_StatusRequest "1" --&gt; "1" mailxml_tm_CreatorSchedulerID     mailxml_tm_StatusRequest "1" --&gt; "1" mailxml_tm_CreatorSchedulerCRID   </pre> <p>Response indicating that all delivery appointments could not be closed and why.</p>						
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>						
properties	isRef 0 content complex						
children	<a href="#">mailxml_tm:ReturnInfo</a>						
attributes	Name mailxml_tm:CloseoutResponseID mailxml_tm:CreatorSchedulerCorpID mailxml_tm:CreatorSchedulerID mailxml_tm:CreatorSchedulerCRID	Type <b>mailxml_base:s12</b> <b>mailxml_base:s12</b> <b>mailxml_base:s12</b> <b>mailxml_base:CRIDType</b>	Use optional optional optional optional	Default	Fixed	annotation	
annotation	documentation Response indicating that all delivery appointments could not be closed and why.						

element **AllApptCloseoutResponse/AllDeliveryApptCloseoutReject/ReturnInfo**

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>mailxml_defs:basicReturnInfoType</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<b>mailxml_defs:ReturnCode</b> <b>mailxml_defs:ReturnDescription</b> <b>mailxml_defs:errorWarning</b> <b>mailxml_defs:ContainerErrorWarningBlock</b>								

element **AllDeliveryApptCloseoutRequest**

diagram	<p>Request to closeout all delivery appointments.</p>
---------	---

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
properties	content complex					
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a>					
attributes	Name mailxml_tm:SchedulerID mailxml_tm:SchedulerCRID mailxml_tm:SchedulerCorpID mailxml_tm:CreatorSchedulerCorpID mailxml_tm:CreatorSchedulerID mailxml_tm:CreatorSchedulerCRID mailxml_tm:Start mailxml_tm:End	Type <b>mailxml_base:s12</b> <b>mailxml_base:CRIDType</b> <b>mailxml_base:s12</b> <b>mailxml_base:s12</b> <b>mailxml_base:s12</b> <b>mailxml_base:CRIDType</b> <b>xs:dateTime</b> <b>xs:dateTime</b>	Use optional optional optional optional optional optional optional optional	Default	Fixed	annotation
annotation	documentation Request to closeout all delivery appointments.					

### element AllDeliveryApptCloseoutRequest/SubmittingParty

diagram	<pre> graph TD     participantIDType[mailxml_defs:participantIDType] --&gt; attributes[attributes]     attributes --&gt; mailerID6[mailerID6]     attributes --&gt; mailerID9[mailerID9]     attributes --&gt; crid[CRID]     attributes --&gt; schedulerID[SchedulerID]     attributes --&gt; maildatUserLicense[MaildatUserLicense]     attributes --&gt; shippingAgentID[ShippingAgentID]     attributes --&gt; receivingAgentID[ReceivingAgentID]   </pre>					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
type	<b>mailxml_defs:participantIDType</b>					
properties	isRef 0 content complex					
attributes	Name mailxml_defs:MailerID6 mailxml_defs:MailerID9 mailxml_defs:CRID mailxml_defs:SchedulerID mailxml_defs:MaildatUserLicense mailxml_defs:ShippingAgentID mailxml_defs:ReceivingAgentID	Type <b>mailxml_base:mailerID6Type</b> <b>mailxml_base:mailerID9Type</b> <b>mailxml_base:CRIDType</b> <b>mailxml_base:s12</b> <b>mailxml_base:userLicenseCodeType</b> <b>mailxml_base:s12</b> <b>mailxml_base:s12</b>	Use	Default	Fixed	annotation

element **AllDeliveryApptCloseoutRequest/SubmittingSoftware**

diagram	<pre> classDiagram     class SubmittingSoftware {         &lt;&lt;mailxml_tm&gt;&gt;     }     class submittingSoftwareType {         &lt;&lt;mailxml_defs&gt;&gt;         SoftwareName         Vendor         Version         ApprovalDate         ApprovalKey     }     SubmittingSoftware "1" -- "0..1" submittingSoftwareType   </pre>																																				
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																				
type	<b>mailxml_defs:submittingSoftwareType</b>																																				
properties	<table> <tr> <td>isRef</td><td>0</td> </tr> <tr> <td>content</td><td>complex</td> </tr> </table>	isRef	0	content	complex																																
isRef	0																																				
content	complex																																				
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:SoftwareName</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Vendor</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Version</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalDate</td> <td><b>xs:date</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalKey</td> <td><b>xs:string</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SoftwareName	<b>xs:string</b>	required				mailxml_defs:Vendor	<b>xs:string</b>	required				mailxml_defs:Version	<b>xs:string</b>	required				mailxml_defs:ApprovalDate	<b>xs:date</b>					mailxml_defs:ApprovalKey	<b>xs:string</b>				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_defs:SoftwareName	<b>xs:string</b>	required																																			
mailxml_defs:Vendor	<b>xs:string</b>	required																																			
mailxml_defs:Version	<b>xs:string</b>	required																																			
mailxml_defs:ApprovalDate	<b>xs:date</b>																																				
mailxml_defs:ApprovalKey	<b>xs:string</b>																																				

element **AllDeliveryApptCloseoutRequest/SubmitterTrackingID**

diagram	<pre> classDiagram     class SubmitterTrackingID {         &lt;&lt;mailxml_tm&gt;&gt;     }   </pre>												
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td><td>0</td> </tr> <tr> <td>minOcc</td><td>0</td> </tr> <tr> <td>maxOcc</td><td>1</td> </tr> <tr> <td>content</td><td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td> </tr> <tr> <td>minLength</td><td>1</td><td></td> </tr> <tr> <td>maxLength</td><td>20</td><td></td> </tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

## element AllPickupApptCloseoutRequest

diagram	<pre> classDiagram     class AllPickupApptCloseoutRequest {         mailxml_tm:ShipperID         mailxml_tm:ShipperCorpID         mailxml_tm:Start         mailxml_tm:End     }     class SubmittingParty     class SubmittingSoftware     class SubmitterTrackingID      AllPickupApptCloseoutRequest "1" -- "0..1" SubmittingParty :      AllPickupApptCloseoutRequest "1" -- "0..1" SubmittingSoftware :      AllPickupApptCloseoutRequest "1" -- "0..1" SubmitterTrackingID :   </pre> <p>Message sent from the Shipper to the Consignee to check the closeout status of all pickup appointments--scheduled and unscheduled.</p>																														
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																														
properties	content complex																														
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a>																														
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><a href="#">mailxml_tm:ShipperID</a></td> <td></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:ShipperCorpID</a></td> <td></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:Start</a></td> <td><a href="#">xs:dateTime</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:End</a></td> <td><a href="#">xs:dateTime</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:ShipperID</a>		required				<a href="#">mailxml_tm:ShipperCorpID</a>		required				<a href="#">mailxml_tm:Start</a>	<a href="#">xs:dateTime</a>	required				<a href="#">mailxml_tm:End</a>	<a href="#">xs:dateTime</a>	required			
Name	Type	Use	Default	Fixed	annotation																										
<a href="#">mailxml_tm:ShipperID</a>		required																													
<a href="#">mailxml_tm:ShipperCorpID</a>		required																													
<a href="#">mailxml_tm:Start</a>	<a href="#">xs:dateTime</a>	required																													
<a href="#">mailxml_tm:End</a>	<a href="#">xs:dateTime</a>	required																													
annotation	<p>documentation</p> <p>Message sent from the Shipper to the Consignee to check the closeout status of all pickup appointments--scheduled and unscheduled.</p>																														

### attribute AllPickupApptCloseoutRequest/@ShipperID

namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
properties	isRef 0 use required

### attribute AllPickupApptCloseoutRequest/@ShipperCorpID

namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
properties	isRef 0 use required

### attribute AllPickupApptCloseoutRequest/@Start

namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">xs:dateTime</a>
properties	isRef 0 use required

attribute **AllPickupApptCloseoutRequest/@End**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:dateTime</b>
properties	isRef 0 use required

element **AllPickupApptCloseoutRequest/SubmittingParty**

diagram	<pre> graph TD     participantIDType[mailxml_defs:participantIDType] --&gt; attributes[attributes]     attributes --&gt; MailerID6[mailxml_defs:MailerID6]     attributes --&gt; MailerID9[mailxml_defs:MailerID9]     attributes --&gt; CRID[mailxml_defs:CRID]     attributes --&gt; SchedulerID[mailxml_defs:SchedulerID]     attributes --&gt; MaildatUserLicense[mailxml_defs:MaildatUserLicense]     attributes --&gt; ShippingAgentID[mailxml_defs:ShippingAgentID]     attributes --&gt; ReceivingAgentID[mailxml_defs:ReceivingAgentID]   </pre>																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	isRef 0 content complex																																																
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:MailerID6</td> <td><b>mailxml_base:mailerID6Type</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MailerID9</td> <td><b>mailxml_base:mailerID9Type</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:CRID</td> <td><b>mailxml_base:CRIDType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MaildatUserLicense</td> <td><b>mailxml_base:userLicenseCodeType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ShippingAgentID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ReceivingAgentID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

element **AllPickupApptCloseoutRequest/SubmittingSoftware**

diagram	<pre> classDiagram     class mailxml_tm::SubmittingSoftware     class mailxml_defs::submittingSoftwareType {         SoftwareName         Vendor         Version         ApprovalDate         ApprovalKey     }     SubmittingSoftware "1" --&gt; "1" submittingSoftwareType   </pre>																																				
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																				
type	<b>mailxml_defs:submittingSoftwareType</b>																																				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																
isRef	0																																				
content	complex																																				
attributes	<table> <thead> <tr> <th>Name</th><th>Type</th><th>Use</th><th>Default</th><th>Fixed</th><th>annotation</th></tr> </thead> <tbody> <tr> <td>mailxml_defs:SoftwareName</td><td>xs:string</td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:Vendor</td><td>xs:string</td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:Version</td><td>xs:string</td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ApprovalDate</td><td>xs:date</td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ApprovalKey</td><td>xs:string</td><td></td><td></td><td></td><td></td></tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SoftwareName	xs:string	required				mailxml_defs:Vendor	xs:string	required				mailxml_defs:Version	xs:string	required				mailxml_defs:ApprovalDate	xs:date					mailxml_defs:ApprovalKey	xs:string				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_defs:SoftwareName	xs:string	required																																			
mailxml_defs:Vendor	xs:string	required																																			
mailxml_defs:Version	xs:string	required																																			
mailxml_defs:ApprovalDate	xs:date																																				
mailxml_defs:ApprovalKey	xs:string																																				

element **AllPickupApptCloseoutRequest/SubmitterTrackingID**

diagram	<pre> classDiagram     class mailxml_tm::SubmitterTrackingID   </pre>												
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <thead> <tr> <th>Kind</th><th>Value</th><th>annotation</th></tr> </thead> <tbody> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>20</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

## element ApptInductionCloseoutRequest

diagram																									
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																								
properties	content complex																								
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:ApptCloseout</a>																								
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:ConsigneeApptID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCorpID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>	required				mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>	optional				mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>	required			
Name	Type	Use	Default	Fixed	annotation																				
mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>	required																							
mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>	optional																							
mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>	required																							
annotation	<p>documentation</p> <p>Message sent by the Consigee to the Shipper to request induction closeouts.</p>																								

element **ApptInductionCloseoutRequest/SubmittingParty**

diagram	<pre> classDiagram     class mailxml_tmSubmittingParty     class mailxml_defsParticipantIDType {         &lt;&lt;attributes&gt;&gt;         mailxml_defsMailerID6         mailxml_defsMailerID9         mailxml_defsCRID         mailxml_defsSchedulerID         mailxml_defsMaildatUserLicense         mailxml_defsShippingAgentID         mailxml_defsReceivingAgentID     }     mailxml_tmSubmittingParty "1" -- "1" mailxml_defsParticipantIDType   </pre>																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:MailerID6</td><td><b>mailxml_base:mailerID6Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MailerID9</td><td><b>mailxml_base:mailerID9Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:CRID</td><td><b>mailxml_base:CRIDType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatUserLicense</td><td><b>mailxml_base:userLicenseCodeType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShippingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ReceivingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

element **ApptInductionCloseoutRequest/SubmittingSoftware**


diagram	<pre> classDiagram     class mailxml_tmSubmittingSoftware     class mailxml_defsSubmittingSoftwareType {         &lt;&lt;attributes&gt;&gt;         mailxml_defsSoftwareName         mailxml_defsVendor         mailxml_defsVersion         mailxml_defsApprovalDate         mailxml_defsApprovalKey     }     mailxml_tmSubmittingSoftware "1" -- "1" mailxml_defsSubmittingSoftwareType   </pre>
---------	--

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
type	<b>mailxml_defs:submittingSoftwareType</b>					
properties	isRef 0 content complex					
attributes	Name mailxml_defs:SoftwareName	Type <b>xs:string</b>	Use required	Default	Fixed	annotation
	mailxml_defs:Vendor	<b>xs:string</b>	required			
	mailxml_defs:Version	<b>xs:string</b>	required			
	mailxml_defs:ApprovalDate	<b>xs:date</b>				
	mailxml_defs:ApprovalKey	<b>xs:string</b>				

#### element ApptInductionCloseoutRequest/SubmitterTrackingID

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s20</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

#### element ApptInductionCloseoutRequest/ApptCloseout

diagram	 1..∞
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:dateTime</b>
properties	isRef 0 minOcc 1 maxOcc unbounded content simple

## element ApptInductionCloseoutResponse

diagram	<p>Response from the Shipper providing induction closeout information.</p>																																										
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																										
properties	content complex																																										
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:ApptInductionCloseoutAccept</a> <a href="#">mailxml_tm:ApptInductionCloseoutReject</a>																																										
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:MessageGroupID</td> <td><a href="#">mailxml_base:s20</a></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:TotalMessageCount</td> <td><a href="#">xs:positiveInteger</a></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MessageSerialNumber</td> <td><a href="#">xs:positiveInteger</a></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:TransmittedRecordCount</td> <td><a href="#">xs:positiveInteger</a></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:TotalRecordsAcrossMessages</td> <td><a href="#">xs:positiveInteger</a></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:LastMessage</td> <td><a href="#">mailxml_base:yesNo</a></td> <td>optional</td> <td>No</td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MessageGroupID	<a href="#">mailxml_base:s20</a>	optional				mailxml_defs:TotalMessageCount	<a href="#">xs:positiveInteger</a>	optional				mailxml_defs:MessageSerialNumber	<a href="#">xs:positiveInteger</a>	optional				mailxml_defs:TransmittedRecordCount	<a href="#">xs:positiveInteger</a>	optional				mailxml_defs:TotalRecordsAcrossMessages	<a href="#">xs:positiveInteger</a>	optional				mailxml_defs:LastMessage	<a href="#">mailxml_base:yesNo</a>	optional	No		
Name	Type	Use	Default	Fixed	annotation																																						
mailxml_defs:MessageGroupID	<a href="#">mailxml_base:s20</a>	optional																																									
mailxml_defs:TotalMessageCount	<a href="#">xs:positiveInteger</a>	optional																																									
mailxml_defs:MessageSerialNumber	<a href="#">xs:positiveInteger</a>	optional																																									
mailxml_defs:TransmittedRecordCount	<a href="#">xs:positiveInteger</a>	optional																																									
mailxml_defs:TotalRecordsAcrossMessages	<a href="#">xs:positiveInteger</a>	optional																																									
mailxml_defs:LastMessage	<a href="#">mailxml_base:yesNo</a>	optional	No																																								
annotation	documentation Response from the Shipper providing induction closeout information.																																										

## element ApptInductionCloseoutResponse/TrackingID

diagram									
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>								
type	<a href="#">mailxml_base:s20</a>								
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple
isRef	0								
minOcc	0								
maxOcc	1								
content	simple								
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> </table>	Kind	Value	annotation					
Kind	Value	annotation							

	<pre> minLength    1 maxLength    20 whiteSpace   preserve </pre>
--	---

### element ApptInductionCloseoutResponse/SubmitterTrackingID

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s20</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

### element ApptInductionCloseoutResponse/ApptInductionCloseoutAccept

diagram																									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																								
type	<b>mailxml_tm:apptCloseoutResponseType</b>																								
properties	isRef 0 content complex																								
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:ApptInfo</a> <a href="#">mailxml_tm:ContainerInductionInfo</a>																								
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:ConsigneeApptID</td> <td><b>mailxml_base:s12</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerID</td> <td><b>mailxml_base:s12</b></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCorpID</td> <td><b>mailxml_base:s12</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>	required				mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>	optional				mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>	required			
Name	Type	Use	Default	Fixed	annotation																				
mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>	required																							
mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>	optional																							
mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>	required																							

### element ApptInductionCloseoutResponse/ApptInductionCloseoutReject

diagram	<pre> classDiagram     class mailxml_tm::ApptInductionCloseoutNotAvailableResponseType {         mailxml_tm::ConsigneeApptID         mailxml_tm::SchedulerID         mailxml_tm::SchedulerCorpID         mailxml_tm::ReturnCode         mailxml_tm::ReturnDescription     }     mailxml_tm::ApptInductionCloseoutClos... &lt; -- mailxml_tm::ApptInductionCloseoutNotAvailableResponseType   </pre>																								
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																								
type	<a href="#">mailxml_tm:apptCloseoutNotAvailableResponseType</a>																								
properties	<table> <tr> <td>isRef</td><td>0</td> </tr> <tr> <td>content</td><td>complex</td> </tr> </table>	isRef	0	content	complex																				
isRef	0																								
content	complex																								
children	<a href="#">mailxml_tm:ReturnCode</a> <a href="#">mailxml_tm:ReturnDescription</a>																								
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td> </tr> <tr> <td>mailxml_tm:ConsigneeApptID</td><td><a href="#">mailxml_base:s12</a></td><td>required</td><td></td><td></td><td></td> </tr> <tr> <td>mailxml_tm:SchedulerID</td><td><a href="#">mailxml_base:s12</a></td><td>optional</td><td></td><td></td><td></td> </tr> <tr> <td>mailxml_tm:SchedulerCorpID</td><td><a href="#">mailxml_base:s12</a></td><td>required</td><td></td><td></td><td></td> </tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>	required				mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>	optional				mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>	required			
Name	Type	Use	Default	Fixed	annotation																				
mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>	required																							
mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>	optional																							
mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>	required																							

### element ApptStatus

diagram	<pre> classDiagram     class ApptStatus   </pre>																		
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																		
type	<a href="#">mailxml_base:apptStatusType</a>																		
properties	content simple																		
used by	<a href="#">apptBlockGoodsType</a> <a href="#">apptBlockUnscheduledGoodsType</a>																		
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td> </tr> <tr> <td>enumeration</td><td>Open</td><td></td> </tr> <tr> <td>enumeration</td><td>Closed</td><td></td> </tr> <tr> <td>enumeration</td><td>No Show</td><td></td> </tr> <tr> <td>enumeration</td><td>Unscheduled</td><td></td> </tr> <tr> <td>enumeration</td><td>Rejected</td><td></td> </tr> </table>	Kind	Value	annotation	enumeration	Open		enumeration	Closed		enumeration	No Show		enumeration	Unscheduled		enumeration	Rejected	
Kind	Value	annotation																	
enumeration	Open																		
enumeration	Closed																		
enumeration	No Show																		
enumeration	Unscheduled																		
enumeration	Rejected																		


## element ConsigneeGoodsReceipt

diagram	<p>The diagram illustrates the structure of the <code>ConsigneeGoodsReceipt</code> element. It consists of a main class box labeled <code>ConsigneeGoodsReceipt</code> with a description: "A report or message indicating delivery closeout status for a scheduled appointment." This class has a dashed line association to another class box labeled <code>mailxml_tm:ApptBlockGoodsR...</code>. This association is multiplicity 0..∞ and points to a connector node. From this connector node, three dashed line associations branch out to three separate class boxes: <code>mailxml_tm:DetailInfo</code>, <code>mailxml_tm:TrailerInfo</code>, and <code>mailxml_tm:ReturnInfo</code>. The <code>ConsigneeGoodsReceipt</code> class also contains a large box labeled <code>attributes</code> which lists several items under <code>grp mailxml_defs:ResponseM...</code>, including <code>mailxml_defs:ShipperApptRequ...</code>, <code>mailxml_defs:ConsigneeApptID</code>, <code>mailxml_defs:SchedulerID</code>, <code>mailxml_defs:SchedulerCorpID</code>, <code>mailxml_defs:SchedulerCRID</code>, <code>mailxml_defs:ShipperMultiStopID</code>, <code>mailxml_defs:ConsigneeMultiSt...</code>, <code>mailxml_defs:ShipperStopNumb...</code>, <code>mailxml_defs:ApptType</code>, <code>mailxml_defs:PickupOrDelivery</code>, <code>mailxml_defs:PalletPositionCount</code>, and <code>mailxml_defs:IncludesElectroni...</code>.</p>																																				
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																				
properties	content complex																																				
children	<a href="#">mailxml_tm:ApptBlockGoodsReceipt</a> <a href="#">mailxml_tm:DetailInfo</a> <a href="#">mailxml_tm:TrailerInfo</a> <a href="#">mailxml_tm:ReturnInfo</a>																																				
used by	elements <a href="#">AllApptCloseoutResponse</a> / <a href="#">AllDeliveryApptCloseoutAccept</a> <a href="#">DeliveryApptStatusQueryResponse</a> / <a href="#">QueryResults</a> complexType <a href="#">allDeliveryApptCloseoutAcceptType</a>																																				
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><code>mailxml_defs:ShipperApptRequestID</code></td> <td><code>mailxml_base:s12</code></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td><code>mailxml_defs:ConsigneeApptID</code></td> <td><code>mailxml_base:s12</code></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td><code>mailxml_defs:SchedulerID</code></td> <td><code>mailxml_base:s12</code></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><code>mailxml_defs:SchedulerCorpID</code></td> <td><code>mailxml_base:s12</code></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><code>mailxml_defs:SchedulerCRID</code></td> <td><code>mailxml_base:CRIDType</code></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<code>mailxml_defs:ShipperApptRequestID</code>	<code>mailxml_base:s12</code>	required				<code>mailxml_defs:ConsigneeApptID</code>	<code>mailxml_base:s12</code>	required				<code>mailxml_defs:SchedulerID</code>	<code>mailxml_base:s12</code>					<code>mailxml_defs:SchedulerCorpID</code>	<code>mailxml_base:s12</code>					<code>mailxml_defs:SchedulerCRID</code>	<code>mailxml_base:CRIDType</code>				
Name	Type	Use	Default	Fixed	annotation																																
<code>mailxml_defs:ShipperApptRequestID</code>	<code>mailxml_base:s12</code>	required																																			
<code>mailxml_defs:ConsigneeApptID</code>	<code>mailxml_base:s12</code>	required																																			
<code>mailxml_defs:SchedulerID</code>	<code>mailxml_base:s12</code>																																				
<code>mailxml_defs:SchedulerCorpID</code>	<code>mailxml_base:s12</code>																																				
<code>mailxml_defs:SchedulerCRID</code>	<code>mailxml_base:CRIDType</code>																																				

	mailxml_defs:ShipperMultiStopID <b>mailxml_base:s12</b> mailxml_defs:ConsigneeMultiStopID <b>mailxml_base:s12</b> mailxml_defs:ShipperStopNumber <b>mailxml_base:n06</b> mailxml_defs:ApptType <b>mailxml_base:apptTypeType</b> required mailxml_defs:PickupOrDelivery <b>mailxml_base:pickupOrDeliveryType</b> mailxml_defs:PalletPositionCount <b>mailxml_base:n02</b> mailxml_defs:IncludesElectronicLoad <b>mailxml_base:yesNo</b>
annotation	documentation A report or message indicating delivery closeout status for a scheduled appointment.

element **ConsigneeGoodsReceipt**/**ApptBlockGoodsReceipt**

diagram




namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:apptBlockGoodsType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:MailClass</a> <a href="#">mailxml_tm:ScheduledConsigneeFacility</a> <a href="#">mailxml_tm:ActualConsigneeFacility</a> <a href="#">mailxml_tm:ScheduledAppt</a> <a href="#">mailxml_tm:ActualTruckArrival</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ActualStartUnload</a> <a href="#">mailxml_tm:ActualEndUnload</a> <a href="#">mailxml_tm:ApptStatus</a> <a href="#">mailxml_tm:ContainerCount</a> <a href="#">mailxml_tm:ContainerErrorDescription</a> <a href="#">mailxml_tm:ContainerID</a> <a href="#">mailxml_tm:ContainerType</a> <a href="#">mailxml_tm:IMcb</a> <a href="#">mailxml_tm:IMtb</a> <a href="#">mailxml_tm:IMpb</a> <a href="#">mailxml_tm:ApptMethod</a> <a href="#">mailxml_tm:USPSDetail</a> <a href="#">mailxml_tm:VerificationLocation</a> <a href="#">mailxml_tm:TransportationMethod</a> <a href="#">mailxml_tm:ActualTotalPalletCount</a> <a href="#">mailxml_tm:ActualPalletCount</a> <a href="#">mailxml_tm:EvsSamplingTime</a> <a href="#">mailxml_tm:EFileSamplingTime</a> <a href="#">mailxml_tm:Irregularities</a> <a href="#">mailxml_tm:Resolution</a> <a href="#">mailxml_tm:ActualBedload</a> <a href="#">mailxml_tm:ExemptionCode</a> <a href="#">mailxml_tm:ValueAddedService</a>


### element ConsigneeGoodsReceipt/DetailInfo

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:detailInfoType</a>
properties	isRef 0 minOcc 0 maxOcc unbounded content complex
children	<a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:USPSSummary</a> <a href="#">mailxml_tm:ConsigneeContentID</a>

### element ConsigneeGoodsReceipt/TrailerInfo

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_tm:trailerInfoType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#">mailxml_tm:Trailer</a> <a href="#">mailxml_tm:Carrier</a> <a href="#">mailxml_tm:BillOfLadingNumber</a>								

### element ConsigneeGoodsReceipt/ReturnInfo

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_defs:returnInfoType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#">mailxml_defs:ConsigneeFacility</a> <a href="#">mailxml_defs:ErrorWarning</a> <a href="#">mailxml_defs:ContainerErrorWarningBlock</a>								

## element ConsigneeGoodsReceiptDelivery

diagram	<pre> classDiagram     class ConsigneeGoodsReceiptDelivery {         &lt;&lt;Delivery of a consignee goods receipt from the USPS&gt;&gt;     }     class SubmittingParty     class SubmittingSoftware     class DataRecipient     class UserLicenseCode     class MaildatJobID     class CustomerGroupID     class MailingGroupID     class PushMessageID     class ApptBlockGoodsReceipt     class DetailInfo     class TrailerInfo     class ReturnInfo      ConsigneeGoodsReceiptDelivery &lt; -- SubmittingParty     ConsigneeGoodsReceiptDelivery &lt; -- SubmittingSoftware     ConsigneeGoodsReceiptDelivery --&gt; DataRecipient     ConsigneeGoodsReceiptDelivery --&gt; UserLicenseCode     ConsigneeGoodsReceiptDelivery --&gt; MaildatJobID     ConsigneeGoodsReceiptDelivery --&gt; CustomerGroupID     ConsigneeGoodsReceiptDelivery --&gt; MailingGroupID     ConsigneeGoodsReceiptDelivery --&gt; PushMessageID     ConsigneeGoodsReceiptDelivery --&gt; ApptBlockGoodsReceipt     ConsigneeGoodsReceiptDelivery --&gt; DetailInfo     ConsigneeGoodsReceiptDelivery --&gt; TrailerInfo     ConsigneeGoodsReceiptDelivery --&gt; ReturnInfo   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
properties	content complex
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_defs:DataRecipient</a> <a href="#">mailxml_tm:UserLicenseCode</a> <a href="#">mailxml_tm:MaildatJobID</a> <a href="#">mailxml_tm:CustomerGroupID</a> <a href="#">mailxml_tm:MailingGroupID</a> <a href="#">mailxml_tm:PushMessageID</a> <a href="#">mailxml_tm:ApptBlockGoodsReceipt</a> <a href="#">mailxml_tm:DetailInfo</a> <sup>0..∞</sup> <a href="#">mailxml_tm:TrailerInfo</a> <a href="#">mailxml_tm:ReturnInfo</a>
annotation	documentation Delivery of a consignee goods receipt from the USPS

### element ConsigneeGoodsReceiptDelivery/SubmittingParty

diagram	<pre> classDiagram     class mailxml_tmSubmittingParty     class mailxml_defsParticipantIDType {         &lt;&lt;attributes&gt;&gt;         mailxml_defsMailerID6         mailxml_defsMailerID9         mailxml_defsCRID         mailxml_defsSchedulerID         mailxml_defsMaildatUserLicense         mailxml_defsShippingAgentID         mailxml_defsReceivingAgentID     }     mailxml_tmSubmittingParty "1" -- "1" mailxml_defsParticipantIDType   </pre>																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:MailerID6</td><td><b>mailxml_base:mailerID6Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MailerID9</td><td><b>mailxml_base:mailerID9Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:CRID</td><td><b>mailxml_base:CRIDType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatUserLicense</td><td><b>mailxml_base:userLicenseCodeType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShippingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ReceivingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

### element ConsigneeGoodsReceiptDelivery/SubmittingSoftware

diagram	<pre> classDiagram     class mailxml_tmSubmittingSoftware     class mailxml_defsSubmittingSoftwareType {         &lt;&lt;attributes&gt;&gt;         mailxml_defsSoftwareName         mailxml_defsVendor         mailxml_defsVersion         mailxml_defsApprovalDate         mailxml_defsApprovalKey     }     mailxml_tmSubmittingSoftware "1" -- "1" mailxml_defsSubmittingSoftwareType   </pre>
---------	--

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
type	<b>mailxml_defs:submittingSoftwareType</b>					
properties	isRef 0 content complex					
attributes	Name mailxml_defs:SoftwareName	Type <b>xs:string</b>	Use required	Default	Fixed	annotation
	mailxml_defs:Vendor	<b>xs:string</b>	required			
	mailxml_defs:Version	<b>xs:string</b>	required			
	mailxml_defs:ApprovalDate	<b>xs:date</b>				
	mailxml_defs:ApprovalKey	<b>xs:string</b>				


#### element ConsigneeGoodsReceiptDelivery/UserLicenseCode

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:userLicenseCodeType</b>
properties	isRef 0 content simple
facets	Kind Value annotation minLength 1 maxLength 4 whiteSpace preserve

#### element ConsigneeGoodsReceiptDelivery/MaildatJobID

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:jobIDType</b>
properties	isRef 0 content simple
facets	Kind Value annotation minLength 1 maxLength 8 whiteSpace preserve

#### element ConsigneeGoodsReceiptDelivery/CustomerGroupID


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s25</b>
properties	isRef 0 content simple
facets	Kind Value annotation

	minLength 1 maxLength 25 whiteSpace preserve
--	--

element **ConsigneeGoodsReceiptDelivery/MailingGroupID**


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:nonNegativeInteger</b>
properties	isRef 0 content simple

element **ConsigneeGoodsReceiptDelivery/PushMessageID**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s25</b>												
properties	isRef 0 minOcc 0 maxOcc 1 content simple												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>25</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	25		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	25												
whiteSpace	preserve												

element **ConsigneeGoodsReceiptDelivery/ApptBlockGoodsReceipt**

diagram




namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:apptBlockGoodsType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:MailClass</a> <a href="#">mailxml_tm:ScheduledConsigneeFacility</a> <a href="#">mailxml_tm:ActualConsigneeFacility</a> <a href="#">mailxml_tm:ScheduledAppt</a> <a href="#">mailxml_tm:ActualTruckArrival</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ActualStartUnload</a> <a href="#">mailxml_tm:ActualEndUnload</a> <a href="#">mailxml_tm:ApptStatus</a> <a href="#">mailxml_tm:ContainerCount</a> <a href="#">mailxml_tm:ContainerErrorDescription</a> <a href="#">mailxml_tm:ContainerID</a> <a href="#">mailxml_tm:ContainerType</a> <a href="#">mailxml_tm:IMcb</a> <a href="#">mailxml_tm:IMtb</a> <a href="#">mailxml_tm:IMpb</a> <a href="#">mailxml_tm:ApptMethod</a> <a href="#">mailxml_tm:USPSDetail</a> <a href="#">mailxml_tm:VerificationLocation</a> <a href="#">mailxml_tm:TransportationMethod</a> <a href="#">mailxml_tm:ActualTotalPalletCount</a> <a href="#">mailxml_tm:ActualPalletCount</a> <a href="#">mailxml_tm:EvsSamplingTime</a> <a href="#">mailxml_tm:EFileSamplingTime</a> <a href="#">mailxml_tm:Irregularities</a> <a href="#">mailxml_tm:Resolution</a> <a href="#">mailxml_tm:ActualBedload</a> <a href="#">mailxml_tm:ExemptionCode</a> <a href="#">mailxml_tm:ValueAddedService</a>


### element ConsigneeGoodsReceiptDelivery/DetailInfo

diagram	<pre> classDiagram     class DetailInfo     class DetailInfoType     class MaildatSummary     class USPSSummary     class ConsigneeContentID     class StartTheClockDate     class ShipperContainerGroupingID     class ConsigneeContainerGroupingID     class ShipperGroupingID      DetailInfo "0..∞" -- "1..∞" DetailInfoType     DetailInfoType "1..∞" -- "1..∞" MaildatSummary     DetailInfoType -- "1..∞" USPSSummary     DetailInfoType -- "1..∞" ConsigneeContentID     DetailInfoType -- "1..∞" StartTheClockDate     DetailInfoType -- "1..∞" ShipperContainerGroupingID     DetailInfoType -- "1..∞" ConsigneeContainerGroupingID     DetailInfoType -- "1..∞" ShipperGroupingID   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:detailInfoType</a>
properties	isRef 0 minOcc 0 maxOcc unbounded content complex
children	<a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ShipperGroupingID</a> <a href="#">mailxml_tm:Description</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:USPSSummary</a> <a href="#">mailxml_tm:ConsigneeContentID</a>

### element ConsigneeGoodsReceiptDelivery/TrailerInfo

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_tm:trailerInfoType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#">mailxml_tm:Trailer</a> <a href="#">mailxml_tm:Carrier</a> <a href="#">mailxml_tm:BillOfLadingNumber</a>								

### element ConsigneeGoodsReceiptDelivery/ReturnInfo

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_defs:returnInfoType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#">mailxml_defs:ConsigneeFacility</a> <a href="#">mailxml_defs:ErrorWarning</a> <a href="#">mailxml_defs:ContainerErrorWarningBlock</a>								

## element ConsigneeGoodsReceiptNotification

diagram	<pre> graph LR     CGRN[ConsigneeGoodsReceiptNotific...] --- SP[SubmittingParty]     CGRN --- SS[SubmittingSoftware]     CGRN --- CRID[CRID]     CGRN --- PMID[PushMessageID]     CGRN --- UL[UserLicenseCode]     CGRN --- MJID[MaildatJobID]     CGRN --- CGID[CustomerGroupID]     CGRN --- MGID[MailingGroupID]     CGRN --- ND[NotificationDate]      subgraph PushMessageIDAndNotificationDate [PushMessageID and NotificationDate]         PMID         ND     end     </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
properties	content complex
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:CRID</a> <a href="#">mailxml_tm:PushMessageID</a> <a href="#">mailxml_tm:UserLicenseCode</a> <a href="#">mailxml_tm:MaildatJobID</a> <a href="#">mailxml_tm:CustomerGroupID</a> <a href="#">mailxml_tm:MailingGroupID</a> <a href="#">mailxml_tm:NotificationDate</a>
annotation	<p>documentation</p> <p>Notification that a consignee goods receipt is ready for pickup from the USPS.</p>

## element ConsigneeGoodsReceiptNotification/SubmittingParty

diagram	<pre> graph LR     SP[mailxml_tm:SubmittingParty] --- PIDType[mailxml_defs:participantIDType]     subgraph PIDType [mailxml_defs:participantIDType]         attributes[attributes]         attributes --- M6[MailerID6]         attributes --- M9[MailerID9]         attributes --- CRID[CRID]         attributes --- SchedID[SchedulerID]         attributes --- MaildatUserLicense[MaildatUserLicense]         attributes --- SAID[ShippingAgentID]         attributes --- RAID[ReceivingAgentID]     end     </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_defs:participantIDType</a>
properties	isRef 0 content complex

			Use	Default	Fixed	annotation
attributes	Name mailxml_defs:MailerID6 mailxml_defs:MailerID9 mailxml_defs:CRID mailxml_defs:SchedulerID mailxml_defs:MaildatUserLicense mailxml_defs:ShippingAgentID mailxml_defs:ReceivingAgentID	Type <b>mailxml_base:mailerID6Type</b> <b>mailxml_base:mailerID9Type</b> <b>mailxml_base:CRIDType</b> <b>mailxml_base:s12</b> <b>mailxml_base:userLicenseCodeType</b> <b>mailxml_base:s12</b> <b>mailxml_base:s12</b>				

### element ConsigneeGoodsReceiptNotification/SubmittingSoftware


diagram	<pre> graph LR     A[mailxml_tm:Submitting Software] --&gt; B[mailxml_defs:submittingSoftwareType]     B --&gt; C[SoftwareName]     B --&gt; D[Vendor]     B --&gt; E[Version]     B --&gt; F[ApprovalDate]     B --&gt; G[ApprovalKey]   </pre>																																				
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																				
type	<b>mailxml_defs:submittingSoftwareType</b>																																				
properties	isRef 0 content complex																																				
attributes	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:SoftwareName</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Vendor</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Version</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalDate</td> <td><b>xs:date</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalKey</td> <td><b>xs:string</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SoftwareName	<b>xs:string</b>	required				mailxml_defs:Vendor	<b>xs:string</b>	required				mailxml_defs:Version	<b>xs:string</b>	required				mailxml_defs:ApprovalDate	<b>xs:date</b>					mailxml_defs:ApprovalKey	<b>xs:string</b>				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_defs:SoftwareName	<b>xs:string</b>	required																																			
mailxml_defs:Vendor	<b>xs:string</b>	required																																			
mailxml_defs:Version	<b>xs:string</b>	required																																			
mailxml_defs:ApprovalDate	<b>xs:date</b>																																				
mailxml_defs:ApprovalKey	<b>xs:string</b>																																				

### element ConsigneeGoodsReceiptNotification/CRID

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:CRIDType</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1

	maxLength 15 pattern ([0-9])*
--	----------------------------------

#### element ConsigneeGoodsReceiptNotification/PushMessageID

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s25</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 25 whiteSpace preserve

#### element ConsigneeGoodsReceiptNotification/UserLicenseCode

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:userLicenseCodeType</b>
properties	isRef 0 content simple
facets	Kind Value annotation minLength 1 maxLength 4 whiteSpace preserve

#### element ConsigneeGoodsReceiptNotification/MaildatJobID

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:jobIDType</b>
properties	isRef 0 content simple
facets	Kind Value annotation minLength 1 maxLength 8 whiteSpace preserve

#### element ConsigneeGoodsReceiptNotification/CustomerGroupID

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s25</b>
properties	isRef 0 content simple
facets	Kind Value annotation minLength 1 maxLength 25 whiteSpace preserve


#### element ConsigneeGoodsReceiptNotification/MailingGroupID

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:nonNegativeInteger</b>
properties	isRef 0 content simple

#### element ConsigneeGoodsReceiptNotification/NotificationDate

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:date</b>
properties	isRef 0 content simple

#### element CustomerSupplierAgreementQueryRequest



namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm						
properties	content complex						
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a>						
attributes	Name mailxml_tm:OwnerCRID	Type <b>mailxml_base:s10</b>	Use	Default	Fixed	annotation	
	mailxml_tm:CSAID	Type <b>mailxml_base:s10</b>					
annotation	documentation Query request for a Customer Supplier Agreement (CSA).						

### element CustomerSupplierAgreementQueryRequest/SubmittingParty

diagram	<pre> graph TD     participantIDType[mailxml_defs:participantIDType]     participantIDType --&gt; attributes[attributes]     attributes --&gt; MailerID6[mailerdefs:MailerID6]     attributes --&gt; MailerID9[mailerdefs:MailerID9]     attributes --&gt; CRID[mailerdefs:CRID]     attributes --&gt; SchedulerID[mailerdefs:ScheduledID]     attributes --&gt; MaildatUserLicense[mailerdefs:MaildatUserLicense]     attributes --&gt; ShippingAgentID[mailerdefs:ShippingAgentID]     attributes --&gt; ReceivingAgentID[mailerdefs:ReceivingAgentID]   </pre>																																										
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																										
type	<b>mailxml_defs:participantIDType</b>																																										
properties	isRef 0 content complex																																										
attributes	<table> <tr> <td>Name mailxml_defs:MailerID6</td><td>Type <b>mailxml_base:mailerID6Type</b></td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:MailerID9</td><td>Type <b>mailxml_base:mailerID9Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:CRID</td><td>Type <b>mailxml_base:CRIDType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ScheduledID</td><td>Type <b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatUserLicense</td><td>Type <b>mailxml_base:userLicenseCodeType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShippingAgentID</td><td>Type <b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ReceivingAgentID</td><td>Type <b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name mailxml_defs:MailerID6	Type <b>mailxml_base:mailerID6Type</b>	Use	Default	Fixed	annotation	mailxml_defs:MailerID9	Type <b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	Type <b>mailxml_base:CRIDType</b>					mailxml_defs:ScheduledID	Type <b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	Type <b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	Type <b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	Type <b>mailxml_base:s12</b>				
Name mailxml_defs:MailerID6	Type <b>mailxml_base:mailerID6Type</b>	Use	Default	Fixed	annotation																																						
mailxml_defs:MailerID9	Type <b>mailxml_base:mailerID9Type</b>																																										
mailxml_defs:CRID	Type <b>mailxml_base:CRIDType</b>																																										
mailxml_defs:ScheduledID	Type <b>mailxml_base:s12</b>																																										
mailxml_defs:MaildatUserLicense	Type <b>mailxml_base:userLicenseCodeType</b>																																										
mailxml_defs:ShippingAgentID	Type <b>mailxml_base:s12</b>																																										
mailxml_defs:ReceivingAgentID	Type <b>mailxml_base:s12</b>																																										

element **CustomerSupplierAgreementQueryRequest/SubmittingSoftware**

diagram	<pre> classDiagram     class mailxml_tm::SubmittingSoftware     class mailxml_defs::submittingSoftwareType {         SoftwareName         Vendor         Version         ApprovalDate         ApprovalKey     }     SubmittingSoftware "1" --&gt; "1" submittingSoftwareType   </pre>																																				
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																				
type	<b>mailxml_defs:submittingSoftwareType</b>																																				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																
isRef	0																																				
content	complex																																				
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:SoftwareName</td> <td>xs:string</td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Vendor</td> <td>xs:string</td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Version</td> <td>xs:string</td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalDate</td> <td>xs:date</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalKey</td> <td>xs:string</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SoftwareName	xs:string	required				mailxml_defs:Vendor	xs:string	required				mailxml_defs:Version	xs:string	required				mailxml_defs:ApprovalDate	xs:date					mailxml_defs:ApprovalKey	xs:string				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_defs:SoftwareName	xs:string	required																																			
mailxml_defs:Vendor	xs:string	required																																			
mailxml_defs:Version	xs:string	required																																			
mailxml_defs:ApprovalDate	xs:date																																				
mailxml_defs:ApprovalKey	xs:string																																				

element **CustomerSupplierAgreementQueryRequest/SubmitterTrackingID**

diagram	<pre> classDiagram     class mailxml_tm::SubmitterTrackingID   </pre>												
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

### element CustomerSupplierAgreementQueryResponse

diagram																			
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																		
properties	content complex																		
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:QueryResults</a> <a href="#">mailxml_tm:QueryError</a>																		
attributes	<table> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> <tr> <td>mailxml_tm:OwnerCRID</td> <td><a href="#">mailxml_base:s10</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:CSAID</td> <td><a href="#">mailxml_base:s10</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:OwnerCRID	<a href="#">mailxml_base:s10</a>					mailxml_tm:CSAID	<a href="#">mailxml_base:s10</a>				
Name	Type	Use	Default	Fixed	annotation														
mailxml_tm:OwnerCRID	<a href="#">mailxml_base:s10</a>																		
mailxml_tm:CSAID	<a href="#">mailxml_base:s10</a>																		
annotation	documentation Response to the Query request for for a Customer Supplier Agreement (CSA).																		

### element CustomerSupplierAgreementQueryResponse/TrackingID


diagram													
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>												
type	<a href="#">mailxml_base:s20</a>												
properties	<table> <tr> <td>isRef</td> <td>0</td> <td></td> </tr> <tr> <td>minOcc</td> <td>0</td> <td></td> </tr> <tr> <td>maxOcc</td> <td>1</td> <td></td> </tr> <tr> <td>content</td> <td>simple</td> <td></td> </tr> </table>	isRef	0		minOcc	0		maxOcc	1		content	simple	
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td><a href="#">minLength</a></td> <td>1</td> <td></td> </tr> <tr> <td><a href="#">maxLength</a></td> <td>20</td> <td></td> </tr> <tr> <td><a href="#">whiteSpace</a></td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	<a href="#">minLength</a>	1		<a href="#">maxLength</a>	20		<a href="#">whiteSpace</a>	preserve	
Kind	Value	annotation											
<a href="#">minLength</a>	1												
<a href="#">maxLength</a>	20												
<a href="#">whiteSpace</a>	preserve												

### element CustomerSupplierAgreementQueryResponse/SubmitterTrackingID


diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_base:s20</a>

properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve


### element CustomerSupplierAgreementQueryResponse/QueryResults

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:CSAInfo</a>

### element CustomerSupplierAgreementQueryResponse/QueryResults/CSAInfo

diagram																			
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																		
type	<a href="#">mailxml_tm:cSAInfoType</a>																		
properties	isRef 0 minOcc 0 maxOcc unbounded content complex																		
children	<a href="#">mailxml_tm:CSADispatch</a> <a href="#">mailxml_tm:ReturnInfo</a>																		
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><a href="#">mailxml_tm:CSAEffectiveDate</a></td> <td><a href="#">xs:date</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:CSAStatus</a></td> <td><a href="#">mailxml_tm:cSAStatusType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:CSAEffectiveDate</a>	<a href="#">xs:date</a>					<a href="#">mailxml_tm:CSAStatus</a>	<a href="#">mailxml_tm:cSAStatusType</a>				
Name	Type	Use	Default	Fixed	annotation														
<a href="#">mailxml_tm:CSAEffectiveDate</a>	<a href="#">xs:date</a>																		
<a href="#">mailxml_tm:CSAStatus</a>	<a href="#">mailxml_tm:cSAStatusType</a>																		

element **CustomerSupplierAgreementQueryResponse/QueryError**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_defs:queryErrorType</b>
properties	isRef 0 content complex
children	<b>mailxml_defs:ReturnInfo</b>

## element DeliveryApptCancelCreateRequest

diagram	<pre> graph TD     DA[DeliveryApptCancelCreateReq...]     DA --- Desc[Request to cancel a delivery appointment and create a new one.]     DA --- grp[grp mailxml_tm:CancelCreate...]     grp --- SA[mailxml_tm:ShipperApptReque...]     grp --- CA[mailxml_tm:ConsigneeApptID]     grp --- SC[mailxml_tm:SchedulerCorpID]     grp --- SI[mailxml_tm:SchedulerID]     grp --- CR[mailxml_tm:SchedulerCRID]     grp --- SM[mailxml_tm:ShipperMultiStopID]     grp --- CM[mailxml_tm:ConsigneeMultiStopID]     grp --- SSN[mailxml_tm:ShipperStopNumber]     grp --- AT[mailxml_tm:ApptType]     grp --- PUO[mailxml_tm:PickupOrDelivery]     grp --- PC[mailxml_tm:PalletPositionCount]     grp --- TA[mailxml_tm:TransferAllContent]          DA --- SP[mailxml_tm:SubmittingParty]     SP --- SS[mailxml_tm:SubmittingSoftware]     SS --- ST[mailxml_tm:SubmitterTrackingID]     ST --- DE[mailxml_tm:DestinationEntry]     DE --- AC[mailxml_tm:ApptCancel]     AC --- AB[mailxml_tm:ApptBlock]     AB --- DI[mailxml_tm:DetailInfo]     DI --- TI[mailxml_tm:TrailerInfo]   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
properties	content complex
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ApptCancel</a> <a href="#">mailxml_tm:ApptBlock</a> <a href="#">mailxml_tm:DetailInfo</a> <a href="#">mailxml_tm:TrailerInfo</a>

	Name	Type	Use	Default	Fixed	annotation
attributes	mailxml_tm:ShipperApptRequestID	<b>mailxml_base:s12</b>	required			
	mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>				
	mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>				
	mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>				
	mailxml_tm:SchedulerCRID	<b>mailxml_base:CRIDType</b>				
	mailxml_tm:ShipperMultiStopID	<b>mailxml_base:s12</b>				
	mailxml_tm:ConsigneeMultiStopID	<b>mailxml_base:s12</b>				
	mailxml_tm:ShipperStopNumber	<b>mailxml_base:n06</b>				
	mailxml_tm:ApptType	<b>mailxml_base:apptTypeType</b>	required			
	mailxml_tm:PickupOrDelivery	<b>mailxml_base:pickupOrDeliveryType</b>				
	mailxml_tm:PalletPositionCount	<b>mailxml_base:n02</b>				
	mailxml_tm:TransferAllContent	<b>mailxml_base:yesNo</b>	required			
annotation	documentation Request to cancel a delivery appointment and create a new one.					

### element **DeliveryApptCancelCreateRequest/SubmittingParty**

diagram	<pre> classDiagram     participantIDType &lt; -- submittingParty     participantIDType {         &lt;&lt;attributes&gt;&gt;         MailerID6         MailerID9         CRID         SchedulerID         MaildatUserLicense         ShippingAgentID         ReceivingAgentID     }   </pre>																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table border="1"> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table border="1"> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:MailerID6</td><td><b>mailxml_base:mailerID6Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MailerID9</td><td><b>mailxml_base:mailerID9Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:CRID</td><td><b>mailxml_base:CRIDType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatUserLicense</td><td><b>mailxml_base:userLicenseCodeType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShippingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ReceivingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

### element DeliveryApptCancelCreateRequest/SubmittingSoftware

diagram	<pre> classDiagram     class SubmittingSoftware {         &lt;&lt;mailxml_tm&gt;&gt;     }     class submittingSoftwareType {         &lt;&lt;mailxml_defs&gt;&gt;         SoftwareName         Vendor         Version         ApprovalDate         ApprovalKey     }     SubmittingSoftware "1" -- "0..1" submittingSoftwareType   </pre>																																				
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																				
type	<b>mailxml_defs:submittingSoftwareType</b>																																				
properties	<table> <tr> <td>isRef</td><td>0</td> </tr> <tr> <td>content</td><td>complex</td> </tr> </table>	isRef	0	content	complex																																
isRef	0																																				
content	complex																																				
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:SoftwareName</td> <td>xs:string</td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Vendor</td> <td>xs:string</td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Version</td> <td>xs:string</td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalDate</td> <td>xs:date</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalKey</td> <td>xs:string</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SoftwareName	xs:string	required				mailxml_defs:Vendor	xs:string	required				mailxml_defs:Version	xs:string	required				mailxml_defs:ApprovalDate	xs:date					mailxml_defs:ApprovalKey	xs:string				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_defs:SoftwareName	xs:string	required																																			
mailxml_defs:Vendor	xs:string	required																																			
mailxml_defs:Version	xs:string	required																																			
mailxml_defs:ApprovalDate	xs:date																																				
mailxml_defs:ApprovalKey	xs:string																																				

### element DeliveryApptCancelCreateRequest/SubmitterTrackingID


diagram	<pre> classDiagram     class SubmitterTrackingID {         &lt;&lt;mailxml_tm&gt;&gt;     }   </pre>												
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td><td>0</td> </tr> <tr> <td>minOcc</td><td>0</td> </tr> <tr> <td>maxOcc</td><td>1</td> </tr> <tr> <td>content</td><td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td> </tr> <tr> <td>minLength</td><td>1</td><td></td> </tr> <tr> <td>maxLength</td><td>20</td><td></td> </tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

### element DeliveryApptCancelCreateRequest/DestinationEntry

diagram	<pre> classDiagram     class DestinationEntry {         &lt;&lt;mailxml_tm&gt;&gt;     }   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>

type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No


#### element **DeliveryApptCancelCreateRequest/ApptCancel**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
properties	isRef 0 minOcc 1 maxOcc unbounded content complex
children	<a href="#">mailxml_tm:ReturnInfo</a>
attributes	Name <a href="#">mailxml_tm:ConsigneeApptID</a> Type <b>mailxml_base:s12</b> Use required Default Fixed annotation

#### attribute **DeliveryApptCancelCreateRequest/ApptCancel/@ConsigneeApptID**

namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:s12</b>
properties	isRef 0 use required
facets	Kind Value annotation minLength 1 maxLength 12 whiteSpace preserve

#### element **DeliveryApptCancelCreateRequest/ApptCancel/ReturnInfo**

diagram	
---------	--

namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_defs:returnInfoType</b>
properties	isRef 0 content complex
children	<a href="#">mailxml_defs:ConsigneeFacility</a> <a href="#">mailxml_defs:ErrorWarning</a> <a href="#">mailxml_defs:ContainerErrorWarningBlock</a>

#### element DeliveryApptCancelCreateRequest/ApptBlock

diagram	<pre> classDiagram     class mailxml_tm.apptBlockRequestType {         mailxml_tm.ApptBlock         mailxml_tm.ConsigneeFacility         mailxml_tm.PreferredAppt         mailxml_tm.OptionalAppt         mailxml_tm.Comment     }     mailxml_tm.ApptBlock --&gt; mailxml_tm.apptBlockRequestType     mailxml_tm.ConsigneeFacility --&gt; mailxml_tm.apptBlockRequestType     mailxml_tm.PreferredAppt --&gt; mailxml_tm.apptBlockRequestType     mailxml_tm.OptionalAppt --&gt; mailxml_tm.apptBlockRequestType     mailxml_tm.Comment --&gt; mailxml_tm.apptBlockRequestType   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:apptBlockRequestType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:PreferredAppt</a> <a href="#">mailxml_tm:OptionalAppt</a> <a href="#">mailxml_tm:Comment</a>

#### element DeliveryApptCancelCreateRequest/DetailInfo

diagram	<pre> classDiagram     class mailxml_tm.detailInfoType {         mailxml_tm.DetailInfo         mailxml_tm.ShipperContainerGroup         mailxml_tm.ConsigneeContainer         mailxml_tm.StartTheClockDate         mailxml_tm.ShipperGroupingID         mailxml_tm.MaildatSummary         mailxml_tm.USPSSummary         mailxml_tm.ConsigneeContentID     }     mailxml_tm.DetailInfo --&gt; mailxml_tm.detailInfoType     mailxml_tm.ShipperContainerGroup --&gt; mailxml_tm.detailInfoType     mailxml_tm.ConsigneeContainer --&gt; mailxml_tm.detailInfoType     mailxml_tm.StartTheClockDate --&gt; mailxml_tm.detailInfoType     mailxml_tm.ShipperGroupingID --&gt; mailxml_tm.detailInfoType     mailxml_tm.MaildatSummary --&gt; mailxml_tm.detailInfoType     mailxml_tm.USPSSummary --&gt; mailxml_tm.detailInfoType     mailxml_tm.ConsigneeContentID --&gt; mailxml_tm.detailInfoType   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:detailInfoType</a>

properties	isRef 0 minOcc 0 maxOcc unbounded content complex
children	<a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:USPSSummary</a> <a href="#">mailxml_tm:ConsigneeContentID</a>

### element DeliveryApptCancelCreateRequest/TrailerInfo

diagram	<pre> classDiagram     class trailerInfoType {         trailerInfo         +trailer         +carrier         +billOfLadingNumber     }     trailer &lt; -- trailerInfoType     trailer &lt; -- carrier     trailer &lt; -- billOfLadingNumber     trailer &lt; -- trailerInfo   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:trailerInfoType</a>
properties	isRef 0 minOcc 0 maxOcc 1 content complex
children	<a href="#">mailxml_tm:Trailer</a> <a href="#">mailxml_tm:Carrier</a> <a href="#">mailxml_tm:BillOfLadingNumber</a>


### element DeliveryApptCancelCreateResponse

diagram	<pre> classDiagram     class DeliveryApptCancelCreateRes... {         +TrackingID         +SubmitterTrackingID         +ReturnInfo         +ApptCancel         +DeliveryApptAccept         +DeliveryApptReject     }     TrackingID &lt; -- DeliveryApptCancelCreateRes...     SubmitterTrackingID &lt; -- DeliveryApptCancelCreateRes...     ReturnInfo &lt; -- DeliveryApptCancelCreateRes...     ApptCancel &lt; -- DeliveryApptCancelCreateRes...     DeliveryApptAccept &lt; -- DeliveryApptCancelCreateRes...     DeliveryApptReject &lt; -- DeliveryApptCancelCreateRes...   </pre> <p>Response to the request to cancel a delivery appointment and create a new one.</p>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
properties	content complex
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:ReturnInfo</a> <a href="#">mailxml_tm:ApptCancel</a> <a href="#">mailxml_tm:DeliveryApptAccept</a> <a href="#">mailxml_tm:DeliveryApptReject</a>
annotation	documentation Response to the request to cancel a delivery appointment and create a new one.


### element DeliveryApptCancelCreateResponse/TrackingID

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>20</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

### element DeliveryApptCancelCreateResponse/SubmitterTrackingID

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>20</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

### element DeliveryApptCancelCreateResponse/ReturnInfo

diagram					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm				
type	<b>mailxml_defs:returnInfoType</b>				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex
isRef	0				
content	complex				
children	<b>mailxml_defs:ConsigneeFacility</b> <b>mailxml_defs:ErrorWarning</b> <b>mailxml_defs:ContainerErrorWarningBlock</b>				

element **DeliveryApptCancelCreateResponse/ApptCancel**

diagram	<pre> classDiagram     class ApptCancel {         attribute ConsigneeApptID     } </pre>												
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
properties	isRef 0 content complex												
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><a href="#">mailxml_tm:ConsigneeApptID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:ConsigneeApptID</a>	<a href="#">mailxml_base:s12</a>	required			
Name	Type	Use	Default	Fixed	annotation								
<a href="#">mailxml_tm:ConsigneeApptID</a>	<a href="#">mailxml_base:s12</a>	required											

attribute **DeliveryApptCancelCreateResponse/ApptCancel/@ConsigneeApptID**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s12</b>												
properties	isRef 0 use required												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>12</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	12		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	12												
whiteSpace	preserve												

element **DeliveryApptCancelCreateResponse/DeliveryApptAccept**

diagram	<pre> classDiagram     class mailxml_tm {         deliveryApptAcceptType     }     class mailxml_tm {         DestinationEntry     }     class mailxml_tm {         RecurringAppt     }     class mailxml_tm {         OneTimeAppt     }     class mailxml_tm {         DetailInfo     }     class mailxml_tm {         TrailerInfo     }     class mailxml_tm {         ConsigneeFacility     }     class mailxml_tm {         Comment     }     class mailxml_tm {         ReturnInfo     }      mailxml_tm.deliveryApptAcceptType &lt; -- mailxml_tm.DestinationEntry     mailxml_tm.deliveryApptAcceptType &lt; -- mailxml_tm.RecurringAppt     mailxml_tm.deliveryApptAcceptType &lt; -- mailxml_tm.OneTimeAppt     mailxml_tm.deliveryApptAcceptType *-- mailxml_tm.DetailInfo     mailxml_tm.deliveryApptAcceptType &lt; -- mailxml_tm.TrailerInfo     mailxml_tm.deliveryApptAcceptType &lt; -- mailxml_tm.ConsigneeFacility     mailxml_tm.deliveryApptAcceptType &lt; -- mailxml_tm.Comment     mailxml_tm.deliveryApptAcceptType &lt; -- mailxml_tm.ReturnInfo   </pre>				
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm				
type	<a href="#">mailxml_tm:deliveryApptAcceptType</a>				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex
isRef	0				
content	complex				
children	<a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:RecurringAppt</a> <a href="#">mailxml_tm:OneTimeAppt</a> <a href="#">mailxml_tm:DetailInfo</a> <a href="#">mailxml_tm:TrailerInfo</a> <a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:Comment</a> <a href="#">mailxml_tm:ReturnInfo</a>				

	<a href="#">mailxml_tm:TrailerInfo</a> <a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:Comment</a> <a href="#">mailxml_tm:ReturnInfo</a>					
attributes	Name	Type	Use	Default	Fixed	annotation
	mailxml_defs:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required			
	mailxml_defs:ConsigneeApptID	<a href="#">mailxml_base:s12</a>	required			
	mailxml_defs:SchedulerID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:SchedulerCorpID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>				
	mailxml_defs:ShipperMultiStopID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:ConsigneeMultiStopID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:ShipperStopNumber	<a href="#">mailxml_base:n06</a>				
	mailxml_defs:ApptType	<a href="#">mailxml_base:apptTypeType</a>	required			
	mailxml_defs:PickupOrDelivery	<a href="#">mailxml_base:pickupOrDeliveryType</a>				
	mailxml_defs:PalletPositionCount	<a href="#">mailxml_base:n02</a>				
	mailxml_defs:IncludesElectronicLoad	<a href="#">mailxml_base:yesNo</a>				

### element **DeliveryApptCancelCreateResponse/DeliveryApptReject**

diagram	<pre> classDiagram     class DeliveryApptReject {         &lt;&lt;mailxml_tm:DeliveryApptReject&gt;&gt;     }     class deliveryApptRejectType {         &lt;&lt;mailxml_tm:deliveryApptRejectType&gt;&gt;         attribute mailxml_defs:ShipperApptRequestID         attribute mailxml_defs:ConsigneeApptID         attribute mailxml_defs:SchedulerID         attribute mailxml_defs:SchedulerCorpID         attribute mailxml_defs:SchedulerCRID         attribute mailxml_defs:ShipperMultiStopID         attribute mailxml_defs:ConsigneeMultiStopID         attribute mailxml_defs:ShipperStopNumber         attribute mailxml_defs:ApptType         attribute mailxml_defs:PickupOrDelivery         attribute mailxml_defs:PalletPositionCount         attribute mailxml_defs:IncludesElectronicLoad     }     DeliveryApptReject "1" -- "*" deliveryApptRejectType   </pre>
namespac	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>

e							
type	<a href="#">mailxml_tm:deliveryApptRejectType</a>						
properties	isRef content	0 complex					
children	<a href="#">mailxml_tm:ReturnInfo</a>						
attributes	Name	Type	Use	Default	Fixed	annotation	
	mailxml_defs:ShipperApptRequestID	<b>mailxml_base:s12</b>	required				
	mailxml_defs:ConsigneeApptID	<b>mailxml_base:s12</b>					
	mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					
	mailxml_defs:SchedulerCorpID	<b>mailxml_base:s12</b>					
	mailxml_defs:SchedulerCRID	<b>mailxml_base:CRIDType</b>					
	mailxml_defs:ShipperMultiStopID	<b>mailxml_base:s12</b>					
	mailxml_defs:ConsigneeMultiStopID	<b>mailxml_base:s12</b>					
	mailxml_defs:ShipperStopNumber	<b>mailxml_base:n06</b>					
	mailxml_defs:ApptType	<b>mailxml_base:apptTypeType</b>	required				
	mailxml_defs:PickupOrDelivery	<b>mailxml_base:pickupOrDeliveryType</b>					
	mailxml_defs:PalletPositionCount	<b>mailxml_base:n02</b>					
	mailxml_defs:IncludesElectronicLoad	<b>mailxml_base:yesNo</b>					

## element DeliveryApptCancelRequest


diagram	<p><b>DeliveryApptCancelRequest</b></p> <p>Request to cancel a delivery appointment.</p>																																										
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																										
properties	content complex																																										
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ReturnInfo</a>																																										
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:ShipperApptRequestID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ConsigneeApptID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerCorpID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerCRID</td> <td><a href="#">mailxml_base:CRIDType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ShipperMultiStopID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	Annotation	mailxml_defs:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required				mailxml_defs:ConsigneeApptID	<a href="#">mailxml_base:s12</a>	required				mailxml_defs:SchedulerID	<a href="#">mailxml_base:s12</a>					mailxml_defs:SchedulerCorpID	<a href="#">mailxml_base:s12</a>					mailxml_defs:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>					mailxml_defs:ShipperMultiStopID	<a href="#">mailxml_base:s12</a>				
Name	Type	Use	Default	Fixed	Annotation																																						
mailxml_defs:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required																																									
mailxml_defs:ConsigneeApptID	<a href="#">mailxml_base:s12</a>	required																																									
mailxml_defs:SchedulerID	<a href="#">mailxml_base:s12</a>																																										
mailxml_defs:SchedulerCorpID	<a href="#">mailxml_base:s12</a>																																										
mailxml_defs:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>																																										
mailxml_defs:ShipperMultiStopID	<a href="#">mailxml_base:s12</a>																																										

	<p>mailxml_defs:ConsigneeMultiStopID      <b>mailxml_base:s12</b></p> <p>mailxml_defs:ShipperStopNumber      <b>mailxml_base:n06</b></p> <p>mailxml_defs:ApptType      <b>mailxml_base:apptTypeType</b> required</p> <p>mailxml_defs:PickupOrDelivery      <b>mailxml_base:pickupOrDeliveryType</b></p> <p>mailxml_defs:PalletPositionCount      <b>mailxml_base:n02</b></p> <p>mailxml_defs:IncludesElectronicLoad      <b>mailxml_base:yesNo</b></p>
annotation	documentation Request to cancel a delivery appointment.

### element **DeliveryApptCancelRequest/SubmittingParty**

diagram	<pre> <b>mailxml_tm:SubmittingParty</b> [complexType]   attributes     mailxml_defs:MailerID6     mailxml_defs:MailerID9     mailxml_defs:CRID     mailxml_defs:SchedulerID     mailxml_defs:MaildatUserLicense     mailxml_defs:ShippingAgentID     mailxml_defs:ReceivingAgentID   </pre>																																																
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td><td>0</td> </tr> <tr> <td>content</td><td>complex</td> </tr> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:MailerID6</td><td><b>mailxml_base:mailerID6Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MailerID9</td><td><b>mailxml_base:mailerID9Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:CRID</td><td><b>mailxml_base:CRIDType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatUserLicense</td><td><b>mailxml_base:userLicenseCodeType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShippingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ReceivingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

### element DeliveryApptCancelRequest/SubmittingSoftware

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_defs:submittingSoftwareType</b>
properties	isRef 0 content complex
attributes	Name                    Type mailxml_defs:SoftwareName      xs:string      required mailxml_defs:Vendor              xs:string      required mailxml_defs:Version            xs:string      required mailxml_defs:ApprovalDate      xs:date mailxml_defs:ApprovalKey        xs:string

### element DeliveryApptCancelRequest/SubmitterTrackingID

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s20</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind            Value            annotation minLength      1 maxLength      20 whiteSpace     preserve

### element DeliveryApptCancelRequest/DestinationEntry

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>

properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

#### element DeliveryApptCancelRequest/ReturnInfo

diagram	<pre> classDiagram     class mailxml_tm::optReturnInfoType {         mailxml_tm::ConsigneeFacility         mailxml_tm::ReturnCode "0..∞"         mailxml_tm::ReturnDescription     }     mailxml_tm::ReturnInfo --&gt; optReturnInfoType   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:optReturnInfoType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:ReturnCode</a> <a href="#">mailxml_tm:ReturnDescription</a>

#### element DeliveryApptCancelResponse


diagram	<pre> classDiagram     class DeliveryApptCancelResponse {         mailxml_tm::TrackingID         mailxml_tm::SubmitterTrackingID     }     note over DeliveryApptCancelResponse: Response to the request to cancel a delivery appointment.   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
properties	content complex
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:DeliveryApptCancelAccept</a> <a href="#">mailxml_tm:DeliveryApptCancelReject</a>
annotation	documentation Response to the request to cancel a delivery appointment.

#### element DeliveryApptCancelResponse/TrackingID

diagram	<pre> classDiagram     class mailxml_tm::TrackingID   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_base:s20</a>
properties	isRef 0

	minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

element **DeliveryApptCancelResponse/SubmitterTrackingID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s20</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

element **DeliveryApptCancelResponse/DeliveryApptCancelAccept**

diagram	The diagram shows the <code>DeliveryApptCancelAccept</code> element on the left, connected to a box labeled "attributes". Inside the "attributes" box, there is a group box labeled "grp <code>mailxml_defs:ResponseM...</code> ". Below it, several individual attributes are listed: <code>mailxml_defs:ShipperApptRequ...</code> , <code>mailxml_defs:ConsigneeApptID</code> , <code>mailxml_defs:SchedulerID</code> , <code>mailxml_defs:SchedulerCorpID</code> , <code>mailxml_defs:SchedulerCRID</code> , <code>mailxml_defs:ShipperMultiStopID</code> , <code>mailxml_defs:ConsigneeMultiSt...</code> , <code>mailxml_defs:ShipperStopNumb...</code> , <code>mailxml_defs:ApptType</code> , <code>mailxml_defs:PickupOrDelivery</code> , <code>mailxml_defs:PalletPositionCount</code> , and <code>mailxml_defs:IncludesElectroni...</code> . Most of these attributes have dashed borders around them.
---------	--

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm						
properties	isRef content	0 complex					
attributes	Name	Type	Use	Default	Fixed	annotation	
	mailxml_defs:ShipperApptRequestID	<b>mailxml_base:s12</b>	required				
	mailxml_defs:ConsigneeApptID	<b>mailxml_base:s12</b>	required				
	mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					
	mailxml_defs:SchedulerCorpID	<b>mailxml_base:s12</b>					
	mailxml_defs:SchedulerCRID	<b>mailxml_base:CRIDType</b>					
	mailxml_defs:ShipperMultiStopID	<b>mailxml_base:s12</b>					
	mailxml_defs:ConsigneeMultiStopID	<b>mailxml_base:s12</b>					
	mailxml_defs:ShipperStopNumber	<b>mailxml_base:n06</b>					
	mailxml_defs:ApptType	<b>mailxml_base:apptTypeType</b>	required				

## element DeliveryApptCancelResponse/DeliveryApptCancelReject

diagram																																																																															
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																																														
properties	isRef 0 content complex																																																																														
children	<a href="#">mailxml_tm:ReturnInfo</a>																																																																														
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:ShipperApptRequestID</td> <td><b>mailxml_base:s12</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ConsigneeApptID</td> <td><b>mailxml_base:s12</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerCorpID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerCRID</td> <td><b>mailxml_base:CRIDType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ShipperMultiStopID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ConsigneeMultiStopID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ShipperStopNumber</td> <td><b>mailxml_base:n06</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApptType</td> <td><b>mailxml_base:apptTypeType</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:PickupOrDelivery</td> <td><b>mailxml_base:pickupOrDeliveryType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:PalletPositionCount</td> <td><b>mailxml_base:n02</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:IncludesElectronicLoad</td> <td><b>mailxml_base:yesNo</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:ShipperApptRequestID	<b>mailxml_base:s12</b>	required				mailxml_defs:ConsigneeApptID	<b>mailxml_base:s12</b>	required				mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:SchedulerCorpID	<b>mailxml_base:s12</b>					mailxml_defs:SchedulerCRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:ShipperMultiStopID	<b>mailxml_base:s12</b>					mailxml_defs:ConsigneeMultiStopID	<b>mailxml_base:s12</b>					mailxml_defs:ShipperStopNumber	<b>mailxml_base:n06</b>					mailxml_defs:ApptType	<b>mailxml_base:apptTypeType</b>	required				mailxml_defs:PickupOrDelivery	<b>mailxml_base:pickupOrDeliveryType</b>					mailxml_defs:PalletPositionCount	<b>mailxml_base:n02</b>					mailxml_defs:IncludesElectronicLoad	<b>mailxml_base:yesNo</b>				
Name	Type	Use	Default	Fixed	annotation																																																																										
mailxml_defs:ShipperApptRequestID	<b>mailxml_base:s12</b>	required																																																																													
mailxml_defs:ConsigneeApptID	<b>mailxml_base:s12</b>	required																																																																													
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																																														
mailxml_defs:SchedulerCorpID	<b>mailxml_base:s12</b>																																																																														
mailxml_defs:SchedulerCRID	<b>mailxml_base:CRIDType</b>																																																																														
mailxml_defs:ShipperMultiStopID	<b>mailxml_base:s12</b>																																																																														
mailxml_defs:ConsigneeMultiStopID	<b>mailxml_base:s12</b>																																																																														
mailxml_defs:ShipperStopNumber	<b>mailxml_base:n06</b>																																																																														
mailxml_defs:ApptType	<b>mailxml_base:apptTypeType</b>	required																																																																													
mailxml_defs:PickupOrDelivery	<b>mailxml_base:pickupOrDeliveryType</b>																																																																														
mailxml_defs:PalletPositionCount	<b>mailxml_base:n02</b>																																																																														
mailxml_defs:IncludesElectronicLoad	<b>mailxml_base:yesNo</b>																																																																														

element **DeliveryApptCancelResponse/DeliveryApptCancelReject/ReturnInfo**

diagram	<pre> classDiagram     class mailxml_tm::ReturnInfo     class mailxml_defs::returnInfoType {         &lt;&lt;mailxml_tm::ReturnInfo&gt;&gt;         * mailxml_tm::ConsigneeFacility         * mailxml_tm::ErrorWarning         * mailxml_tm::ContainerErrorW...     }     mailxml_tm::ReturnInfo --&gt; mailxml_defs::returnInfoType   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_defs:returnInfoType</b>
properties	isRef 0 content complex
children	<b>mailxml_defs:ConsigneeFacility</b> <b>mailxml_tm:ErrorWarning</b> <b>mailxml_tm:ContainerErrorWarningBlock</b>

element **DeliveryApptContentRemoveRequest**


diagram	<pre> classDiagram     class DeliveryApptContentRemoveR...     class mailxml_tm::ContentRemo...     class mailxml_tm::SubmittingParty     class mailxml_tm::SubmittingSoftware     class mailxml_tm::SubmitterTrackingID     class mailxml_tm::ContentID     DeliveryApptContentRemoveR... --&gt; mailxml_tm::ContentRemo...     mailxml_tm::ContentRemo... "1..∞" --&gt; mailxml_tm::SubmittingParty     mailxml_tm::SubmittingParty --&gt; mailxml_tm::SubmittingSoftware     mailxml_tm::SubmittingSoftware --&gt; mailxml_tm::SubmitterTrackingID     mailxml_tm::SubmitterTrackingID --&gt; mailxml_tm::ContentID   </pre>																		
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																		
properties	content complex																		
children	<b>mailxml_tm:SubmittingParty</b> <b>mailxml_tm:SubmittingSoftware</b> <b>mailxml_tm:SubmitterTrackingID</b> <b>mailxml_tm:ContentID</b>																		
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:ConsigneeApptID</td> <td><b>mailxml_base:s12</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerID</td> <td><b>mailxml_base:s12</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>	required				mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>	required			
Name	Type	Use	Default	Fixed	annotation														
mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>	required																	
mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>	required																	

	mailxml_tm:SchedulerCorpID <b>mailxml_base:s12</b> required
annotation	documentation Request to remove content from a delivery appointment.

### element DeliveryApptContentRemoveRequest/SubmittingParty

diagram	<p>The diagram illustrates the structure of the <b>mailxml_defs:participantIDType</b> element. It is represented by a yellow dashed box containing a list of attributes. Inside this box, there is a reference to the <b>mailxml_tm:SubmittingParty</b> element, which is shown as a blue box with a small icon indicating it is a reference. The attributes listed are: <b>mailerID6</b>, <b>mailerID9</b>, <b>CRID</b>, <b>SchedulerID</b>, <b>MaildatUserLicense</b>, <b>ShippingAgentID</b>, and <b>ReceivingAgentID</b>. Each attribute is enclosed in a dashed box.</p>																																																
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>content</td> <td>complex</td> </tr> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:MailerID6</td> <td><b>mailxml_base:mailerID6Type</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MailerID9</td> <td><b>mailxml_base:mailerID9Type</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:CRID</td> <td><b>mailxml_base:CRIDType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MaildatUserLicense</td> <td><b>mailxml_base:userLicenseCodeType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ShippingAgentID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ReceivingAgentID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																


### element DeliveryApptContentRemoveRequest/SubmittingSoftware

diagram																																					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																				
type	<b>mailxml_defs:submittingSoftwareType</b>																																				
properties	isRef 0 content complex																																				
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:SoftwareName</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Vendor</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Version</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalDate</td> <td><b>xs:date</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalKey</td> <td><b>xs:string</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SoftwareName	<b>xs:string</b>	required				mailxml_defs:Vendor	<b>xs:string</b>	required				mailxml_defs:Version	<b>xs:string</b>	required				mailxml_defs:ApprovalDate	<b>xs:date</b>					mailxml_defs:ApprovalKey	<b>xs:string</b>				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_defs:SoftwareName	<b>xs:string</b>	required																																			
mailxml_defs:Vendor	<b>xs:string</b>	required																																			
mailxml_defs:Version	<b>xs:string</b>	required																																			
mailxml_defs:ApprovalDate	<b>xs:date</b>																																				
mailxml_defs:ApprovalKey	<b>xs:string</b>																																				


### element DeliveryApptContentRemoveRequest/SubmitterTrackingID

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	isRef 0 minOcc 0 maxOcc 1 content simple												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

### element DeliveryApptContentRemoveRequest/ContentID

diagram																			
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																		
type	<b>mailxml_defs:contentIDType</b>																		
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>1</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	1	maxOcc	unbounded	content	complex										
isRef	0																		
minOcc	1																		
maxOcc	unbounded																		
content	complex																		
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:ConsigneeContentID</td><td><b>mailxml_base:s12</b></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerContentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:ConsigneeContentID	<b>mailxml_base:s12</b>	required				mailxml_defs:SchedulerContentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation														
mailxml_defs:ConsigneeContentID	<b>mailxml_base:s12</b>	required																	
mailxml_defs:SchedulerContentID	<b>mailxml_base:s12</b>																		

### element DeliveryApptContentRemoveResponse


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
properties	content complex
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:DeliveryApptContentRemoveAccept</a> <a href="#">mailxml_tm:DeliveryApptContentRemoveReject</a>
annotation	documentation Response to the request to remove content from a delivery appointment.

### element DeliveryApptContentRemoveResponse/TrackingID


diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>mailxml_base:s20</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple
isRef	0								
minOcc	0								
maxOcc	1								
content	simple								
facets	Kind Value annotation								

	<pre>minLength    1 maxLength    20 whiteSpace   preserve</pre>
--	---


#### element **DeliveryApptContentRemoveResponse/SubmitterTrackingID**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<pre>isRef 0 minOcc 0 maxOcc 1 content simple</pre>												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

#### element **DeliveryApptContentRemoveResponse/DeliveryApptContentRemoveAccept**


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_tm:deliveryApptContentRemoveAcceptType</b>
properties	<pre>isRef 0 content complex</pre>
children	<a href="#">mailxml_tm:ContentID</a> <a href="#">mailxml_tm:ReturnInfo</a>

#### element **DeliveryApptContentRemoveResponse/DeliveryApptContentRemoveReject**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_tm:deliveryApptContentRemoveRejectType</b>
properties	<pre>isRef 0 content complex</pre>
children	<a href="#">mailxml_tm:ContentID</a> <a href="#">mailxml_tm:ReturnInfo</a>



element **DeliveryApptCreateRequest**



e						
properties	content complex					
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:RecurringAppt</a> <a href="#">mailxml_tm:OneTimeAppt</a> <a href="#">mailxml_tm:DetailInfo</a> <a href="#">mailxml_tm:TrailerInfo</a> <a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:Comment</a> <a href="#">mailxml_tm:ValueAddedService</a>					
attributes	Name	Type	Use	Default	Fixed	annotation
	mailxml_defs:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required			
	mailxml_defs:ConsigneeApptID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:SchedulerID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:SchedulerCorpID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>				
	mailxml_defs:ShipperMultiStopID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:ConsigneeMultiStopID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:ShipperStopNumber	<a href="#">mailxml_base:n06</a>				
	mailxml_defs:ApptType	<a href="#">mailxml_base:apptTypeType</a>	required			
	mailxml_defs:PickupOrDelivery	<a href="#">mailxml_base:pickupOrDeliveryType</a>				
	mailxml_defs:PalletPositionCount	<a href="#">mailxml_base:n02</a>				
	mailxml_defs:IncludesElectronicLoad	<a href="#">mailxml_base:yesNo</a>				
annotation	documentation Request to create a delivery appointment.					

### element DeliveryApptCreateRequest/SubmittingParty

diagram	<pre> classDiagram     class SubmittingParty {         &lt;&lt;mailxml_tm:SubmittingParty&gt;&gt;         &lt;&lt;mailxml_defs:participantIDType&gt;&gt;             &lt;&lt;attributes&gt;&gt;                 MailerID6                 MailerID9                 CRID                 SchedulerID                 MaildatUserLicense                 ShippingAgentID                 ReceivingAgentID             &lt;/&gt;         &lt;/&gt;     } </pre>					
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>					
type	<a href="#">mailxml_defs:participantIDType</a>					
properties	isRef 0 content complex					
attributes	Name mailxml_defs:MailerID6	Type <a href="#">mailxml_base:mailerID6Type</a>	Use	Default	Fixed	annotation

	mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>
	mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>
	mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>
	mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>
	mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>
	mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>

#### element **DeliveryApptCreateRequest/SubmittingSoftware**

diagram	<pre> classDiagram     class mailxml_tmSubmittingSoftware     class mailxml_defsSubmittingSoftwareType {         SoftwareName : xs:string         Vendor : xs:string         Version : xs:string         ApprovalDate : xs:date         ApprovalKey : xs:string     }     mailxml_tmSubmittingSoftware "2" --&gt; mailxml_defsSubmittingSoftwareType   </pre>																																				
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																				
type	<b>mailxml_defs:submittingSoftwareType</b>																																				
properties	<table> <tr> <td>isRef</td><td>0</td> </tr> <tr> <td>content</td><td>complex</td> </tr> </table>	isRef	0	content	complex																																
isRef	0																																				
content	complex																																				
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td> </tr> <tr> <td>mailxml_defs:SoftwareName</td><td><b>xs:string</b></td><td>required</td><td></td><td></td><td></td> </tr> <tr> <td>mailxml_defs:Vendor</td><td><b>xs:string</b></td><td>required</td><td></td><td></td><td></td> </tr> <tr> <td>mailxml_defs:Version</td><td><b>xs:string</b></td><td>required</td><td></td><td></td><td></td> </tr> <tr> <td>mailxml_defs:ApprovalDate</td><td><b>xs:date</b></td><td></td><td></td><td></td><td></td> </tr> <tr> <td>mailxml_defs:ApprovalKey</td><td><b>xs:string</b></td><td></td><td></td><td></td><td></td> </tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SoftwareName	<b>xs:string</b>	required				mailxml_defs:Vendor	<b>xs:string</b>	required				mailxml_defs:Version	<b>xs:string</b>	required				mailxml_defs:ApprovalDate	<b>xs:date</b>					mailxml_defs:ApprovalKey	<b>xs:string</b>				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_defs:SoftwareName	<b>xs:string</b>	required																																			
mailxml_defs:Vendor	<b>xs:string</b>	required																																			
mailxml_defs:Version	<b>xs:string</b>	required																																			
mailxml_defs:ApprovalDate	<b>xs:date</b>																																				
mailxml_defs:ApprovalKey	<b>xs:string</b>																																				

#### element **DeliveryApptCreateRequest/SubmitterTrackingID**


diagram	<pre> classDiagram     class mailxml_tmSubmitterTrackingID     class mailxml_baseS20     mailxml_tmSubmitterTrackingID "2" --&gt; mailxml_baseS20   </pre>									
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>									
type	<b>mailxml_base:s20</b>									
properties	<table> <tr> <td>isRef</td><td>0</td> </tr> <tr> <td>minOcc</td><td>0</td> </tr> <tr> <td>maxOcc</td><td>1</td> </tr> <tr> <td>content</td><td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple	
isRef	0									
minOcc	0									
maxOcc	1									
content	simple									
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td> </tr> <tr> <td>minLength</td><td>1</td><td></td> </tr> <tr> <td>maxLength</td><td>20</td><td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20	
Kind	Value	annotation								
minLength	1									
maxLength	20									

	whiteSpace preserve
--	---------------------


element **DeliveryApptCreateRequest/DestinationEntry**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

element **DeliveryApptCreateRequest/RecurringAppt**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_tm:recurringApptType</b>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:EffectiveStartDate</a> <a href="#">mailxml_tm:EffectiveEndDate</a> <a href="#">mailxml_tm:ApptTime</a> <a href="#">mailxml_tm:DayFrequency</a> <a href="#">mailxml_tm:WeekFrequency</a>

element **DeliveryApptCreateRequest/OneTimeAppt**

diagram	
---------	--

namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:oneTimeApptType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:PreferredAppt</a> <a href="#">mailxml_tm:OptionalAppt</a>

### element DeliveryApptCreateRequest/DetailInfo

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:DetailInfoType</a>
properties	isRef 0 minOcc 1 maxOcc unbounded content complex
children	<a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:USPSSummary</a> <a href="#">mailxml_tm:ConsigneeContentID</a>

### element DeliveryApptCreateRequest/TrailerInfo

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>

type	<a href="#">mailxml_tm:trailerInfoType</a>
properties	isRef 0 minOcc 0 maxOcc 1 content complex
children	<a href="#">mailxml_tm:Trailer</a> <a href="#">mailxml_tm:Carrier</a> <a href="#">mailxml_tm:BillOfLadingNumber</a>


### element DeliveryApptCreateRequest/ConsigneeFacility

diagram	<pre> classDiagram     class mailxml_tm_ConsigneeFacility     class mailxml_defs_ConsigneeFacilityType {         mailxml_defs_CompanyName         mailxml_defs_FacilityNumber         mailxml_defs_FacilityAddress "0.."         mailxml_defs_FacilityName         mailxml_defs_FacilityType         mailxml_defs_URL         mailxml_defs_CommonContact     }     mailxml_tm_ConsigneeFacility --&gt; mailxml_defs_ConsigneeFacilityType   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_defs:consigneeFacilityType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_defs:CompanyName</a> <a href="#">mailxml_defs:FacilityNumber</a> <a href="#">mailxml_defs:FacilityAddress</a> <a href="#">mailxml_defs:FacilityAddress</a> <a href="#">mailxml_defs:FacilityName</a> <a href="#">mailxml_defs:FacilityType</a> <a href="#">mailxml_defs:URL</a> <a href="#">mailxml_defs:CommonContact</a>


### element DeliveryApptCreateRequest/Comment

diagram	<pre> classDiagram     class mailxml_tm_Comment   </pre>												
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>												
type	<a href="#">mailxml_base:s256</a>												
properties	isRef 0 minOcc 0 maxOcc 1 content simple												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>256</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	256		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	256												
whiteSpace	preserve												

element **DeliveryApptCreateRequest/ValueAddedService**


diagram																																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																															
type	<a href="#">mailxml_tm:valueAddedServiceType</a>																																																															
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple																																																							
isRef	0																																																															
minOcc	0																																																															
maxOcc	1																																																															
content	simple																																																															
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>D1</td><td></td></tr> <tr> <td>enumeration</td><td>D2</td><td></td></tr> <tr> <td>enumeration</td><td>D3</td><td></td></tr> <tr> <td>enumeration</td><td>D4</td><td></td></tr> <tr> <td>enumeration</td><td>D5</td><td></td></tr> <tr> <td>enumeration</td><td>D6</td><td></td></tr> <tr> <td>enumeration</td><td>D7</td><td></td></tr> <tr> <td>enumeration</td><td>D8</td><td></td></tr> <tr> <td>enumeration</td><td>D9</td><td></td></tr> <tr> <td>enumeration</td><td>D10</td><td></td></tr> <tr> <td>enumeration</td><td>D11</td><td></td></tr> <tr> <td>enumeration</td><td>D12</td><td></td></tr> <tr> <td>enumeration</td><td>D13</td><td></td></tr> <tr> <td>enumeration</td><td>D14</td><td></td></tr> <tr> <td>enumeration</td><td>D15</td><td></td></tr> <tr> <td>enumeration</td><td>D16</td><td></td></tr> <tr> <td>enumeration</td><td>D17</td><td></td></tr> <tr> <td>enumeration</td><td>D18</td><td></td></tr> <tr> <td>enumeration</td><td>D19</td><td></td></tr> <tr> <td>enumeration</td><td>D20</td><td></td></tr> </tbody> </table>	Kind	Value	annotation	enumeration	D1		enumeration	D2		enumeration	D3		enumeration	D4		enumeration	D5		enumeration	D6		enumeration	D7		enumeration	D8		enumeration	D9		enumeration	D10		enumeration	D11		enumeration	D12		enumeration	D13		enumeration	D14		enumeration	D15		enumeration	D16		enumeration	D17		enumeration	D18		enumeration	D19		enumeration	D20	
Kind	Value	annotation																																																														
enumeration	D1																																																															
enumeration	D2																																																															
enumeration	D3																																																															
enumeration	D4																																																															
enumeration	D5																																																															
enumeration	D6																																																															
enumeration	D7																																																															
enumeration	D8																																																															
enumeration	D9																																																															
enumeration	D10																																																															
enumeration	D11																																																															
enumeration	D12																																																															
enumeration	D13																																																															
enumeration	D14																																																															
enumeration	D15																																																															
enumeration	D16																																																															
enumeration	D17																																																															
enumeration	D18																																																															
enumeration	D19																																																															
enumeration	D20																																																															

element **DeliveryApptCreateResponse**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
properties	content complex
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:DeliveryApptCreateAccept</a>

	<a href="#"><b>mailxml_tm:DeliveryApptCreateReject</b></a>
annotation	documentation Response to the request to create a delivery appointment.

**element [DeliveryApptCreateResponse/TrackingID](#)**

diagram	 <a href="#"><b>mailxml_tm:TrackingID</b></a>												
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

**element [DeliveryApptCreateResponse/SubmitterTrackingID](#)**

diagram	 <a href="#"><b>mailxml_tm:SubmitterTrackingID</b></a>												
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

element **DeliveryApptCreateResponse/DeliveryApptCreateAccept**

diagram	<pre> classDiagram     class mailxml_tm:deliveryApptAcceptType {         attributes             mailxml_defs:ShipperApptReqID             mailxml_defs:ConsigneeApptID             mailxml_defs:SchedulerID             mailxml_defs:SchedulerCorpID             mailxml_defs:SchedulerCRID             mailxml_defs:ShipperMultiStopID             mailxml_defs:ConsigneeMultiStopID             mailxml_defs:ShipperStopNumber             mailxml_defs:ApptType             mailxml_defs:PickupOrDelivery             mailxml_defs:PalletPositionCount             mailxml_defs:IncludesElectronic         }         "1..&gt;" -- "1..&gt;" mailxml_tm:DestinationEntry {             mailxml_tm:RecurringAppt             mailxml_tm:OneTimeAppt         }         "1..&gt;" -- "1..&gt;" mailxml_tm:DetailInfo {             mailxml_tm:TrailerInfo             mailxml_tm:ConsigneeFacility             mailxml_tm:Comment             mailxml_tm:ReturnInfo         }     } </pre>				
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm				
type	<a href="#">mailxml_tm:deliveryApptAcceptType</a>				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex
isRef	0				
content	complex				
children	<a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:RecurringAppt</a> <a href="#">mailxml_tm:OneTimeAppt</a> <a href="#">mailxml_tm:DetailInfo</a>				

	<u><a href="#">mailxml_tm:TrailerInfo</a></u> <u><a href="#">mailxml_tm:ConsigneeFacility</a></u> <u><a href="#">mailxml_tm:Comment</a></u> <u><a href="#">mailxml_tm:ReturnInfo</a></u>					
attributes	Name	Type	Use	Default	Fixed	annotation
	mailxml_defs:ShipperApptRequestID	<b>mailxml_base:s12</b>	required			
	mailxml_defs:ConsigneeApptID	<b>mailxml_base:s12</b>	required			
	mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>				
	mailxml_defs:SchedulerCorpID	<b>mailxml_base:s12</b>				
	mailxml_defs:SchedulerCRID	<b>mailxml_base:CRIDType</b>				
	mailxml_defs:ShipperMultiStopID	<b>mailxml_base:s12</b>				
	mailxml_defs:ConsigneeMultiStopID	<b>mailxml_base:s12</b>				
	mailxml_defs:ShipperStopNumber	<b>mailxml_base:n06</b>				
	mailxml_defs:ApptType	<b>mailxml_base:apptTypeType</b>	required			
	mailxml_defs:PickupOrDelivery	<b>mailxml_base:pickupOrDeliveryType</b>				
	mailxml_defs:PalletPositionCount	<b>mailxml_base:n02</b>				
	mailxml_defs:IncludesElectronicLoad	<b>mailxml_base:yesNo</b>				

### element **DeliveryApptCreateResponse/DeliveryApptCreateReject**

diagram	<pre> classDiagram     class mailxml_tm:deliveryApptRejectType {         mailxml_defs:ShipperApptRequestID         mailxml_defs:ConsigneeApptID         mailxml_defs:SchedulerID         mailxml_defs:SchedulerCorpID         mailxml_defs:SchedulerCRID         mailxml_defs:ShipperMultiStopID         mailxml_defs:ConsigneeMultiStopID         mailxml_defs:ShipperStopNumber         mailxml_defs:ApptType         mailxml_defs:PickupOrDelivery         mailxml_defs:PalletPositionCount         mailxml_defs:IncludesElectronicLoad     }     class mailxml_tm:DeliveryApptCreate...     class mailxml_tm:ReturnInfo     mailxml_tm:DeliveryApptCreate... --&gt; mailxml_tm:ReturnInfo   </pre>
namespac	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>

e						
type	<a href="#">mailxml_tm:deliveryApptRejectType</a>					
properties	isRef 0 content complex					
children	<a href="#">mailxml_tm:ReturnInfo</a>					
attributes	Name	Type	Use	Default	Fixed	annotation
	mailxml_defs:ShipperApptRequestID	<b>mailxml_base:s12</b>	required			
	mailxml_defs:ConsigneeApptID	<b>mailxml_base:s12</b>				
	mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>				
	mailxml_defs:SchedulerCorpID	<b>mailxml_base:s12</b>				
	mailxml_defs:SchedulerCRID	<b>mailxml_base:CRIDType</b>				
	mailxml_defs:ShipperMultiStopID	<b>mailxml_base:s12</b>				
	mailxml_defs:ConsigneeMultiStopID	<b>mailxml_base:s12</b>				
	mailxml_defs:ShipperStopNumber	<b>mailxml_base:n06</b>				
	mailxml_defs:ApptType	<b>mailxml_base:apptTypeType</b>	required			
	mailxml_defs:PickupOrDelivery	<b>mailxml_base:pickupOrDeliveryType</b>				
	mailxml_defs:PalletPositionCount	<b>mailxml_base:n02</b>				
	mailxml_defs:IncludesElectronicLoad	<b>mailxml_base:yesNo</b>				

## element DeliveryApptMultiStopUpdateRequest

diagram																																																							
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																						
properties	content complex																																																						
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:ReturnInfo</a>																																																						
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:ShipperApptRequestID</td> <td><b>mailxml_base:s12</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:ConsigneeApptID</td> <td><b>mailxml_base:s12</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerID</td> <td><b>mailxml_base:s12</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCorpID</td> <td><b>mailxml_base:s12</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:ShipperMultiStopID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:ConsigneeMultiStopID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:PickupOrDelivery</td> <td><b>mailxml_base:pickupOrDeliveryType</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:ShipperStopNumber</td> <td><b>mailxml_base:n06</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ShipperApptRequestID	<b>mailxml_base:s12</b>	required				mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>	required				mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>	required				mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>	required				mailxml_tm:ShipperMultiStopID	<b>mailxml_base:s12</b>					mailxml_tm:ConsigneeMultiStopID	<b>mailxml_base:s12</b>					mailxml_tm:PickupOrDelivery	<b>mailxml_base:pickupOrDeliveryType</b>	required				mailxml_tm:ShipperStopNumber	<b>mailxml_base:n06</b>				
Name	Type	Use	Default	Fixed	annotation																																																		
mailxml_tm:ShipperApptRequestID	<b>mailxml_base:s12</b>	required																																																					
mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>	required																																																					
mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>	required																																																					
mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>	required																																																					
mailxml_tm:ShipperMultiStopID	<b>mailxml_base:s12</b>																																																						
mailxml_tm:ConsigneeMultiStopID	<b>mailxml_base:s12</b>																																																						
mailxml_tm:PickupOrDelivery	<b>mailxml_base:pickupOrDeliveryType</b>	required																																																					
mailxml_tm:ShipperStopNumber	<b>mailxml_base:n06</b>																																																						
annotation	documentation Request to update a multistop delivery appointment.																																																						

element **DeliveryApptMultiStopUpdateRequest/SubmittingParty**

diagram	<pre> graph LR     SP[mailxml_tm:SubmittingParty] --- PID[mailxml_defs:participantIDType]     PID --- A[attributes]     A --- M6[mailxml_defs:MailerID6]     A --- M9[mailxml_defs:MailerID9]     A --- CRID[mailxml_defs:CRID]     A --- SCHED[mailxml_defs:SchedulerID]     A --- MAILDAT[mailxml_defs:MaildatUserLicense]     A --- SHIPAG[mailxml_defs:ShippingAgentID]     A --- RECAG[mailxml_defs:ReceivingAgentID]   </pre>																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:MailerID6</td><td><b>mailxml_base:mailerID6Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MailerID9</td><td><b>mailxml_base:mailerID9Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:CRID</td><td><b>mailxml_base:CRIDType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatUserLicense</td><td><b>mailxml_base:userLicenseCodeType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShippingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ReceivingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

element **DeliveryApptMultiStopUpdateRequest/SubmittingSoftware**


diagram	<pre> graph LR     SS[mailxml_tm:SubmittingSoftware] --- SST[mailxml_defs:submittingSoftwareType]     SST --- A[attributes]     A --- SN[mailxml_defs:SoftwareName]     A --- V[mailxml_defs:Vendor]     A --- VER[mailxml_defs:Version]     A --- AD[mailxml_defs:ApprovalDate]     A --- AK[mailxml_defs:ApprovalKey]   </pre>
---------	--

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
type	<b>mailxml_defs:submittingSoftwareType</b>					
properties	isRef 0 content complex					
attributes	Name mailxml_defs:SoftwareName mailxml_defs:Vendor mailxml_defs:Version mailxml_defs:ApprovalDate mailxml_defs:ApprovalKey	Type <b>xs:string</b> <b>xs:string</b> <b>xs:string</b> <b>xs:date</b> <b>xs:string</b>	Use required required required	Default	Fixed	annotation


#### element **DeliveryApptMultiStopUpdateRequest/SubmitterTrackingID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s20</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

#### element **DeliveryApptMultiStopUpdateRequest/ReturnInfo**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_defs:returnInfoType</b>
properties	isRef 0 minOcc 0 maxOcc 1 content complex
children	<b>mailxml_defs:ConsigneeFacility</b> <b>mailxml_defs:ErrorWarning</b> <b>mailxml_defs:ContainerErrorWarningBlock</b>

element **DeliveryApptQueryRequest**



e						
properties	content complex					
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:RecurringAppt</a> <a href="#">mailxml_tm:OneTimeAppt</a> <a href="#">mailxml_tm:SlotAvailability</a> <a href="#">mailxml_tm:DetailInfo</a> <a href="#">mailxml_tm:TrailerInfo</a> <a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:Comment</a>					
attributes	Name	Type	Use	Default	Fixed	annotation
	mailxml_defs:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required			
	mailxml_defs:ConsigneeApptID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:SchedulerID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:SchedulerCorpID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>				
	mailxml_defs:ShipperMultiStopID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:ConsigneeMultiStopID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:ShipperStopNumber	<a href="#">mailxml_base:n06</a>				
	mailxml_defs:ApptType	<a href="#">mailxml_base:apptTypeType</a>	required			
	mailxml_defs:PickupOrDelivery	<a href="#">mailxml_base:pickupOrDeliveryType</a>				
	mailxml_defs:PalletPositionCount	<a href="#">mailxml_base:n02</a>				
	mailxml_defs:IncludesElectronicLoad	<a href="#">mailxml_base:yesNo</a>				
annotation	documentation Query request for availability of a particular appointment.					

### element DeliveryApptQueryRequest/SubmittingParty

diagram	<pre> classDiagram     class SubmittingParty {         &lt;&lt;mailxml_tm:SubmittingParty&gt;&gt;         &lt;&lt;mailxml_defs:participantIDType&gt;&gt;         &lt;&lt;attributes&gt;&gt;             MailerID6             MailerID9             CRID             SchedulerID             MaildatUserLicense             ShippingAgentID             ReceivingAgentID         &lt;/&gt;     }   </pre>					
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>					
type	<a href="#">mailxml_defs:participantIDType</a>					
properties	isRef 0 content complex					
attributes	Name mailxml_defs:MailerID6	Type <a href="#">mailxml_base:mailerID6Type</a>	Use	Default	Fixed	annotation

	mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>
	mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>
	mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>
	mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>
	mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>
	mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>

### element **DeliveryApptQueryRequest/SubmittingSoftware**

diagram	<pre> classDiagram     class mailxml_tm::SubmittingSoftware     class mailxml_defs::submittingSoftwareType {         SoftwareName : xs:string         Vendor : xs:string         Version : xs:string         ApprovalDate : xs:date         ApprovalKey : xs:string     }     SubmittingSoftware &lt; -- submittingSoftwareType   </pre>																																				
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																				
type	<b>mailxml_defs:submittingSoftwareType</b>																																				
properties	<table> <tr> <td>isRef</td><td>0</td> </tr> <tr> <td>content</td><td>complex</td> </tr> </table>	isRef	0	content	complex																																
isRef	0																																				
content	complex																																				
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:SoftwareName</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Vendor</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Version</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalDate</td> <td><b>xs:date</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalKey</td> <td><b>xs:string</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SoftwareName	<b>xs:string</b>	required				mailxml_defs:Vendor	<b>xs:string</b>	required				mailxml_defs:Version	<b>xs:string</b>	required				mailxml_defs:ApprovalDate	<b>xs:date</b>					mailxml_defs:ApprovalKey	<b>xs:string</b>				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_defs:SoftwareName	<b>xs:string</b>	required																																			
mailxml_defs:Vendor	<b>xs:string</b>	required																																			
mailxml_defs:Version	<b>xs:string</b>	required																																			
mailxml_defs:ApprovalDate	<b>xs:date</b>																																				
mailxml_defs:ApprovalKey	<b>xs:string</b>																																				

### element **DeliveryApptQueryRequest/SubmitterTrackingID**

diagram	<pre> classDiagram     class mailxml_tm::SubmitterTrackingID   </pre>									
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>									
type	<b>mailxml_base:s20</b>									
properties	<table> <tr> <td>isRef</td><td>0</td> </tr> <tr> <td>minOcc</td><td>0</td> </tr> <tr> <td>maxOcc</td><td>1</td> </tr> <tr> <td>content</td><td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple	
isRef	0									
minOcc	0									
maxOcc	1									
content	simple									
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>20</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20	
Kind	Value	annotation								
minLength	1									
maxLength	20									

	whiteSpace preserve
--	---------------------

element **DeliveryApptQueryRequest/DestinationEntry**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_base:yesNo</a>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

element **DeliveryApptQueryRequest/RecurringAppt**

diagram	<pre>sequenceDiagram     participant RA as mailxml_tm:RecurringAppt     participant ESD as mailxml_tm:EffectiveStartDate     participant EED as mailxml_tm:EffectiveEndDate     participant AT as mailxml_tm:ApptTime     participant DF as mailxml_tm:DayFrequency     participant WF as mailxml_tm:WeekFrequency      RA --&gt;&gt; ESD     RA --&gt;&gt; EED     RA --&gt;&gt; AT     RA --&gt;&gt; DF     RA --&gt;&gt; WF</pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:recurringApptType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:EffectiveStartDate</a> <a href="#">mailxml_tm:EffectiveEndDate</a> <a href="#">mailxml_tm:ApptTime</a> <a href="#">mailxml_tm:DayFrequency</a> <a href="#">mailxml_tm:WeekFrequency</a>

element **DeliveryApptQueryRequest/OneTimeAppt**


diagram	<pre>sequenceDiagram     participant OA as mailxml_tm:OneTimeAppt     participant PA as mailxml_tm:PreferredAppt     participant OA as mailxml_tm:OptionalAppt      OA --&gt;&gt; PA     OA --&gt;&gt; OA</pre>
---------	---

namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#"><b>mailxml_tm:oneTimeApptType</b></a>
properties	isRef 0 content complex
children	<a href="#"><b>mailxml_tm:PreferredAppt</b></a> <a href="#"><b>mailxml_tm:OptionalAppt</b></a>


### element **DeliveryApptQueryRequest/SlotAvailability**

diagram	<pre> classDiagram     class mailxml_tm::SlotAvailability     class mailxml_tm::slotAvailabilityType {         ApptType         MailClass         Perishable         ApptStartTime         ApptEndTime         ApplyTiers     }     SlotAvailability --&gt; slotAvailabilityType   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#"><b>mailxml_tm:slotAvailabilityType</b></a>
properties	isRef 0 content complex
children	<a href="#"><b>mailxml_tm:ApptType</b></a> <a href="#"><b>mailxml_tm:MailClass</b></a> <a href="#"><b>mailxml_tm:Perishable</b></a> <a href="#"><b>mailxml_tm:ApptStartTime</b></a> <a href="#"><b>mailxml_tm:ApptEndTime</b></a> <a href="#"><b>mailxml_tm:ApplyTiers</b></a>

element **DeliveryApptQueryRequest/DetailInfo**

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_tm:detailInfoType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	unbounded	content	complex
isRef	0								
minOcc	0								
maxOcc	unbounded								
content	complex								
children	<a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:USPSSummary</a> <a href="#">mailxml_tm:ConsigneeContentID</a>								

element **DeliveryApptQueryRequest/TrailerInfo**

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_tm:trailerInfoType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#">mailxml_tm:Trailer</a> <a href="#">mailxml_tm:Carrier</a> <a href="#">mailxml_tm:BillOfLadingNumber</a>								

### element DeliveryApptQueryRequest/ConsigneeFacility

diagram	<pre> classDiagram     class mailxml_tm {         ConsigneeFacility     }     class mailxml_defs {         consigneeFacilityType {             CompanyName             FacilityNumber             FacilityAddress             FacilityName             FacilityType             URL             CommonContact         }     }     mailxml_tm::ConsigneeFacility --&gt; mailxml_defs::consigneeFacilityType   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_defs:consigneeFacilityType</b>
properties	isRef 0 content complex
children	<b>mailxml_defs:CompanyName</b> <b>mailxml_defs:FacilityNumber</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityName</b> <b>mailxml_defs:FacilityType</b> <b>mailxml_defs:URL</b> <b>mailxml_defs:CommonContact</b>

### element DeliveryApptQueryRequest/Comment

diagram	<pre> classDiagram     class mailxml_tm {         Comment     }     class mailxml_base {         s256     }     mailxml_tm::Comment &lt; -- mailxml_base::s256   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s256</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 256 whiteSpace preserve

## element DeliveryApptQueryResponse

diagram	<p>The diagram illustrates the structure of the <code>DeliveryApptQueryResponse</code> element. It features a main class box labeled <code>DeliveryApptQueryResponse</code> with a description: "Response to the Query request for availability of a particular appointment." Below this, a large box labeled <code>attributes</code> contains a group named <code>grp mailxml_defs:RequestMs...</code>. This group includes several attributes: <code>mailxml_defs:ShipperApptReq...</code>, <code>mailxml_defs:ConsigneeApptID</code>, <code>mailxml_defs:SchedulerID</code>, <code>mailxml_defs:SchedulerCorpID</code>, <code>mailxml_defs:SchedulerCRID</code>, <code>mailxml_defs:ShipperMultiStopID</code>, <code>mailxml_defs:ConsigneeMultiSt...</code>, <code>mailxml_defs:ShipperStopNumb...</code>, <code>mailxml_defs:ApptType</code>, <code>mailxml_defs:PickupOrDelivery</code>, <code>mailxml_defs:PalletPositionCount</code>, and <code>mailxml_defs:IncludesElectroni...</code>. Below these attributes, there are two association points connected to a dashed box containing <code>mailxml_tm:TrackingID</code> and <code>mailxml_tm:SubmitterTrackingID</code>. From these points, arrows point to another dashed box containing <code>mailxml_tm:QueryResults</code> and <code>mailxml_tm:QueryError</code>.</p>																																																						
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																																						
properties	content complex																																																						
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:QueryResults</a> <a href="#">mailxml_tm:QueryError</a>																																																						
attributes	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td><code>mailxml_defs:ShipperApptRequestID</code></td> <td><code>mailxml_base:s12</code></td> <td></td> <td></td> <td>required</td> <td></td> </tr> <tr> <td><code>mailxml_defs:ConsigneeApptID</code></td> <td><code>mailxml_base:s12</code></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><code>mailxml_defs:SchedulerID</code></td> <td><code>mailxml_base:s12</code></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><code>mailxml_defs:SchedulerCorpID</code></td> <td><code>mailxml_base:s12</code></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><code>mailxml_defs:SchedulerCRID</code></td> <td><code>mailxml_base:CRIDType</code></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><code>mailxml_defs:ShipperMultiStopID</code></td> <td><code>mailxml_base:s12</code></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><code>mailxml_defs:ConsigneeMultiStopID</code></td> <td><code>mailxml_base:s12</code></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><code>mailxml_defs:ShipperStopNumber</code></td> <td><code>mailxml_base:n06</code></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	Annotation	<code>mailxml_defs:ShipperApptRequestID</code>	<code>mailxml_base:s12</code>			required		<code>mailxml_defs:ConsigneeApptID</code>	<code>mailxml_base:s12</code>					<code>mailxml_defs:SchedulerID</code>	<code>mailxml_base:s12</code>					<code>mailxml_defs:SchedulerCorpID</code>	<code>mailxml_base:s12</code>					<code>mailxml_defs:SchedulerCRID</code>	<code>mailxml_base:CRIDType</code>					<code>mailxml_defs:ShipperMultiStopID</code>	<code>mailxml_base:s12</code>					<code>mailxml_defs:ConsigneeMultiStopID</code>	<code>mailxml_base:s12</code>					<code>mailxml_defs:ShipperStopNumber</code>	<code>mailxml_base:n06</code>				
Name	Type	Use	Default	Fixed	Annotation																																																		
<code>mailxml_defs:ShipperApptRequestID</code>	<code>mailxml_base:s12</code>			required																																																			
<code>mailxml_defs:ConsigneeApptID</code>	<code>mailxml_base:s12</code>																																																						
<code>mailxml_defs:SchedulerID</code>	<code>mailxml_base:s12</code>																																																						
<code>mailxml_defs:SchedulerCorpID</code>	<code>mailxml_base:s12</code>																																																						
<code>mailxml_defs:SchedulerCRID</code>	<code>mailxml_base:CRIDType</code>																																																						
<code>mailxml_defs:ShipperMultiStopID</code>	<code>mailxml_base:s12</code>																																																						
<code>mailxml_defs:ConsigneeMultiStopID</code>	<code>mailxml_base:s12</code>																																																						
<code>mailxml_defs:ShipperStopNumber</code>	<code>mailxml_base:n06</code>																																																						

	mailxml_defs:ApptType mailxml_defs:PickupOrDelivery mailxml_defs:PalletPositionCount mailxml_defs:IncludesElectronicLoad	<b>mailxml_base:apptTypeType</b> <b>mailxml_base:pickupOrDeliveryType</b> <b>mailxml_base:n02</b> <b>mailxml_base:yesNo</b>	required
annotation	documentation Response to the Query request for availability of a particular appointment.		

#### element **DeliveryApptQueryResponse/TrackingID**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	isRef 0 minOcc 0 maxOcc 1 content simple												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

#### element **DeliveryApptQueryResponse/SubmitterTrackingID**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	isRef 0 minOcc 0 maxOcc 1 content simple												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

### element DeliveryApptQueryResponse/QueryResults

diagram	<pre> graph LR     QR[mailxml_tm:QueryResults] --&gt; DE[mailxml_tm:DestinationEntry]     DE --- RA[mailxml_tm:RecurringAppt]     DE --- OA[mailxml_tm:OneTimeAppt]     DE --- SA[mailxml_tm:SlotAvailability]     DE --- DI[mailxml_tm:DetailInfo]     DE --- TI[mailxml_tm:TrailerInfo]     DE --- CF[mailxml_tm:ConsigneeFacility]     DE --- C[mailxml_tm:Comment]     DE --- AS[mailxml_tm:AvailableSlots]     DE --- RI[mailxml_tm:ReturnInfo]     style DI fill:none,stroke:none   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:RecurringAppt</a> <a href="#">mailxml_tm:OneTimeAppt</a> <a href="#">mailxml_tm:SlotAvailability</a> <a href="#">mailxml_tm:DetailInfo</a> <a href="#">mailxml_tm:TrailerInfo</a> <a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:Comment</a> <a href="#">mailxml_tm:AvailableSlots</a> <a href="#">mailxml_tm:ReturnInfo</a>

### element DeliveryApptQueryResponse/QueryResults/DestinationEntry

diagram	<pre> graph LR     DE[mailxml_tm:DestinationEntry]   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

element **DeliveryApptQueryResponse/QueryResults/RecurringAppt**

diagram	<pre> classDiagram     class RecurringAppt {         *--&gt; recurringApptType     }     class recurringApptType {         mailxml_tm:EffectiveStartDate         mailxml_tm:EffectiveEndDate         mailxml_tm:ApptTime         mailxml_tm:DayFrequency         mailxml_tm:WeekFrequency     }     RecurringAppt "*" --&gt; "1..∞" recurringApptType     DayFrequency "*" --&gt; "1..∞" WeekFrequency   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:recurringApptType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:EffectiveStartDate</a> <a href="#">mailxml_tm:EffectiveEndDate</a> <a href="#">mailxml_tm:ApptTime</a> <a href="#">mailxml_tm:DayFrequency</a> <a href="#">mailxml_tm:WeekFrequency</a>

element **DeliveryApptQueryResponse/QueryResults/OneTimeAppt**

diagram	<pre> classDiagram     class OneTimeAppt {         *--&gt; oneTimeApptType     }     class oneTimeApptType {         mailxml_tm:PreferredAppt         mailxml_tm:OptionalAppt     }     OneTimeAppt "*" --&gt; "0..∞" oneTimeApptType   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:oneTimeApptType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:PreferredAppt</a> <a href="#">mailxml_tm:OptionalAppt</a>

element **DeliveryApptQueryResponse/QueryResults/SlotAvailability**

diagram	<pre> classDiagram     class mailxml_tm::SlotAvailability     class mailxml_tm::slotAvailabilityType {         mailxml_tm::ApptType         mailxml_tm::MailClass         mailxml_tm::Perishable         mailxml_tm::ApptStartTime         mailxml_tm::ApptEndTime         mailxml_tm::ApplyTiers     }     SlotAvailability "0..1" --&gt; slotAvailabilityType   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:slotAvailabilityType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:ApptType</a> <a href="#">mailxml_tm:MailClass</a> <a href="#">mailxml_tm:Perishable</a> <a href="#">mailxml_tm:ApptStartTime</a> <a href="#">mailxml_tm:ApptEndTime</a> <a href="#">mailxml_tm:ApplyTiers</a>

element **DeliveryApptQueryResponse/QueryResults/DetailInfo**

diagram	<pre> classDiagram     class mailxml_tm::DetailInfo     class mailxml_tm::detailInfoType {         mailxml_tm::ShipperContainerGr...         mailxml_tm::ConsigneeContain...         mailxml_tm::StartTheClockDate         mailxml_tm::ShipperGroupingID...         mailxml_tm::MaildatSummary         mailxml_tm::USPSSummary         mailxml_tm::ConsigneeContentID     }     DetailInfo "0..∞" --&gt; detailInfoType     MaildatSummary "1..∞" --&gt; MaildatSummaryType {         USPSSummary         ConsigneeContentID     }   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:detailInfoType</a>
properties	isRef 0 minOcc 0 maxOcc unbounded content complex

children	<a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ShipperGroupingID</a> <a href="#">Description</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:USPSSummary</a> <a href="#">mailxml_tm:ConsigneeContentID</a>
----------	--

#### element DeliveryApptQueryResponse/QueryResults/TrailerInfo

diagram	<pre> classDiagram     class trailerInfoType {         trailerInfo         +Trailer         +Carrier         +BillOfLadingNumber     }     trailerInfo &lt; -- trailerInfoType     trailerInfo "0..2" --&gt; trailer     trailerInfo "1..2" --&gt; carrier     trailerInfo "1..2" --&gt; BillOfLadingNumber   </pre>								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_tm:trailerInfoType</a>								
properties	<table border="1"> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#">mailxml_tm:Trailer</a> <a href="#">mailxml_tm:Carrier</a> <a href="#">mailxml_tm:BillOfLadingNumber</a>								

#### element DeliveryApptQueryResponse/QueryResults/ConsigneeFacility


diagram	<pre> classDiagram     class consigneeFacilityType {         companyName         facilityNumber         facilityAddress         facilityName         facilityType         URL         commonContact     }     consigneeFacility &lt; -- consigneeFacilityType     consigneeFacility "0..2" --&gt; companyName     consigneeFacility "0..2" --&gt; facilityNumber     facilityAddress "1..2" --&gt; facilityAddress     facilityAddress "0..infinity" --&gt; facilityAddress     consigneeFacility "0..2" --&gt; facilityName     consigneeFacility "0..2" --&gt; facilityType     consigneeFacility "0..2" --&gt; URL     consigneeFacility "0..infinity" --&gt; commonContact   </pre>				
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm				
type	<a href="#">mailxml_defs:consigneeFacilityType</a>				
properties	<table border="1"> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex
isRef	0				
content	complex				

children	<a href="#">mailxml_defs:CompanyName</a> <a href="#">mailxml_defs:FacilityNumber</a> <a href="#">mailxml_defs:FacilityAddress</a> <a href="#">mailxml_defs:FacilityAddress</a> <a href="#">mailxml_defs:FacilityName</a> <a href="#">mailxml_defs:FacilityType</a> <a href="#">mailxml_defs:URL</a> <a href="#">mailxml_defs:CommonContact</a>
----------	--


element **DeliveryApptQueryResponse/QueryResults/Comment**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<a href="#">mailxml_base:s256</a>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>256</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	256		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	256												
whiteSpace	preserve												


element **DeliveryApptQueryResponse/QueryResults/AvailableSlots**

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_tm:availableSlotType</a>								
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>complex</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#">mailxml_tm:MailClass</a> <a href="#">mailxml_tm:Perishable</a> <a href="#">mailxml_tm:AvailableHours</a>								

element **DeliveryApptQueryResponse/QueryResults/ReturnInfo**

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>mailxml_defs:returnInfoType</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<b>mailxml_defs:ConsigneeFacility</b> <b>mailxml_defs:ErrorWarning</b> <b>mailxml_defs:ContainerErrorWarningBlock</b>								

element **DeliveryApptQueryResponse/QueryError**

diagram					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm				
type	<b>mailxml_defs:queryErrorType</b>				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex
isRef	0				
content	complex				
children	<b>mailxml_defs:ReturnInfo</b>				

## element DeliveryApptShellCancelRequest


diagram	<pre> classDiagram     class DeliveryApptShellCancelRequest {         &lt;&lt;Request to cancel a delivery appointment shell to which content will be added later.&gt;&gt;     }     class mailxml_tm.deliveryApptShellCancelRequestType {         &lt;&lt;mailxml_tm:deliveryApptShellCancelRequestType&gt;&gt;         attributes:              mailxml_defs:ShipperApptReq...             mailxml_defs:ConsigneeApptID             mailxml_defs:SchedulerID             mailxml_defs:SchedulerCorpID             mailxml_defs:SchedulerCRID             mailxml_defs:ShipperMultiStopID             mailxml_defs:ConsigneeMultiSt...             mailxml_defs:ShipperStopNumb...             mailxml_defs:ApptType             mailxml_defs:PickupOrDelivery             mailxml_defs:PalletPositionCount             mailxml_defs:IncludesElectroni...         children:              mailxml_tm:SubmittingParty             mailxml_tm:SubmittingSoftware             mailxml_tm:SubmitterTrackingID             mailxml_tm:DestinationEntry             mailxml_tm:ReturnInfo     }     DeliveryApptShellCancelRequest --&gt; mailxml_tm.deliveryApptShellCancelRequestType   </pre>																														
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																														
type	<a href="#">mailxml_tm:deliveryApptShellCancelRequestType</a>																														
properties	content complex																														
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ReturnInfo</a>																														
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:ShipperApptRequestID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td>required</td> <td></td> </tr> <tr> <td>mailxml_defs:ConsigneeApptID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerCorpID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	Annotation	mailxml_defs:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>			required		mailxml_defs:ConsigneeApptID	<a href="#">mailxml_base:s12</a>					mailxml_defs:SchedulerID	<a href="#">mailxml_base:s12</a>					mailxml_defs:SchedulerCorpID	<a href="#">mailxml_base:s12</a>				
Name	Type	Use	Default	Fixed	Annotation																										
mailxml_defs:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>			required																											
mailxml_defs:ConsigneeApptID	<a href="#">mailxml_base:s12</a>																														
mailxml_defs:SchedulerID	<a href="#">mailxml_base:s12</a>																														
mailxml_defs:SchedulerCorpID	<a href="#">mailxml_base:s12</a>																														

	mailxml_defs:SchedulerCRID mailxml_defs:ShipperMultiStopID mailxml_defs:ConsigneeMultiStopID mailxml_defs:ShipperStopNumber mailxml_defs:ApptType mailxml_defs:PickupOrDelivery mailxml_defs:PalletPositionCount mailxml_defs:IncludesElectronicLoad	<b>mailxml_base:CRIDType</b> <b>mailxml_base:s12</b> <b>mailxml_base:s12</b> <b>mailxml_base:n06</b> <b>mailxml_base:apptTypeType</b> <b>mailxml_base:pickupOrDeliveryType</b> <b>mailxml_base:n02</b> <b>mailxml_base:yesNo</b>	required
annotation	documentation Request to cancel a delivery appointment shell to which content will be added later.		

### element **DeliveryApptShellCancelResponse**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:deliveryApptShellCancelResponseType</a>
properties	content complex
children	<a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:DeliveryApptCancelAccept</a> <a href="#">mailxml_tm:DeliveryApptCancelReject</a>
annotation	documentation Response to a request to cancel a delivery appointment shell to which content will be added later.

element **DeliveryApptShellCreateRequest**



e						
properties	content complex					
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:MailClass</a> <a href="#">mailxml_tm:RecurringAppt</a> <a href="#">mailxml_tm:OneTimeAppt</a> <a href="#">mailxml_tm:TrailerInfo</a> <a href="#">mailxml_tm:Comment</a> <a href="#">mailxml_tm:ValueAddedService</a>					
attributes	Name	Type	Use	Default	Fixed	annotation
	mailxml_defs:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required			
	mailxml_defs:ConsigneeApptID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:SchedulerID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:SchedulerCorpID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>				
	mailxml_defs:ShipperMultiStopID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:ConsigneeMultiStopID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:ShipperStopNumber	<a href="#">mailxml_base:n06</a>				
	mailxml_defs:ApptType	<a href="#">mailxml_base:apptTypeType</a>	required			
	mailxml_defs:PickupOrDelivery	<a href="#">mailxml_base:pickupOrDeliveryType</a>				
	mailxml_defs:PalletPositionCount	<a href="#">mailxml_base:n02</a>				
	mailxml_defs:IncludesElectronicLoad	<a href="#">mailxml_base:yesNo</a>				
annotation	documentation Request to create a delivery appointment shell to which content will be added later.					

### element DeliveryApptShellCreateRequest/SubmittingParty

diagram	<pre> classDiagram     class participantIDType {         &lt;&lt;mailxml_defs:participantIDType&gt;&gt;         &lt;&lt;attributes&gt;&gt;             MailerID6             MailerID9             CRID             SchedulerID             MaildatUserLicense             ShippingAgentID             ReceivingAgentID     }     class SubmittingParty {         &lt;&lt;mailxml_tm:SubmittingParty&gt;&gt;     }     SubmittingParty "2" --&gt; participantIDType   </pre>					
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>					
type	<a href="#">mailxml_defs:participantIDType</a>					
properties	isRef 0 content complex					
attributes	Name mailxml_defs:MailerID6	Type <a href="#">mailxml_base:mailerID6Type</a>	Use	Default	Fixed	annotation

	mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>
	mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>
	mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>
	mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>
	mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>
	mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>

### element **DeliveryApptShellCreateRequest/SubmittingSoftware**

diagram	<pre> classDiagram     class mailxml_tmSubmittingSoftware     class mailxml_defsSubmittingSoftwareType {         SoftwareName         Vendor         Version         ApprovalDate         ApprovalKey     }     mailxml_tmSubmittingSoftware "2" --&gt; mailxml_defsSubmittingSoftwareType   </pre>																																				
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																				
type	<b>mailxml_defs:submittingSoftwareType</b>																																				
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>content</td> <td>complex</td> </tr> </table>	isRef	0	content	complex																																
isRef	0																																				
content	complex																																				
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:SoftwareName</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Vendor</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Version</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalDate</td> <td><b>xs:date</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalKey</td> <td><b>xs:string</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SoftwareName	<b>xs:string</b>	required				mailxml_defs:Vendor	<b>xs:string</b>	required				mailxml_defs:Version	<b>xs:string</b>	required				mailxml_defs:ApprovalDate	<b>xs:date</b>					mailxml_defs:ApprovalKey	<b>xs:string</b>				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_defs:SoftwareName	<b>xs:string</b>	required																																			
mailxml_defs:Vendor	<b>xs:string</b>	required																																			
mailxml_defs:Version	<b>xs:string</b>	required																																			
mailxml_defs:ApprovalDate	<b>xs:date</b>																																				
mailxml_defs:ApprovalKey	<b>xs:string</b>																																				

### element **DeliveryApptShellCreateRequest/SubmitterTrackingID**

diagram	<pre> classDiagram     class mailxml_tmSubmitterTrackingID     class mailxml_baseS20     mailxml_tmSubmitterTrackingID "2" --&gt; mailxml_baseS20   </pre>									
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>									
type	<b>mailxml_base:s20</b>									
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple	
isRef	0									
minOcc	0									
maxOcc	1									
content	simple									
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	20	
Kind	Value	annotation								
minLength	1									
maxLength	20									

	whiteSpace preserve
--	---------------------

#### element DeliveryApptShellCreateRequest/ConsigneeFacility

diagram	<pre> classDiagram     class mailxml_tm_ConsigneeFacility     class mailxml_defs_ConsigneeFacilityType {         mailxml_defs_CompanyName         mailxml_defs_FacilityNumber         mailxml_defs_FacilityAddress         mailxml_defs_FacilityName         mailxml_defs_FacilityType         mailxml_defs_URL         mailxml_defs_CommonContact     }     mailxml_tm_ConsigneeFacility "0..1" --&gt; "1..1" mailxml_defs_ConsigneeFacilityType   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_defs:consigneeFacilityType</b>
properties	isRef 0 content complex
children	mailxml_defs:CompanyName mailxml_defs:FacilityNumber mailxml_defs:FacilityAddress mailxml_defs:FacilityAddress mailxml_defs:FacilityName mailxml_defs:FacilityType mailxml_defs:URL mailxml_defs:CommonContact

#### element DeliveryApptShellCreateRequest/DestinationEntry

diagram	<pre> classDiagram     class mailxml_tm_DestinationEntry   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

#### element DeliveryApptShellCreateRequest/MailClass

diagram	<pre> classDiagram     class mailxml_tm_MailClass   </pre>
---------	--

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:mailClassType</b>
properties	isRef 0 minOcc 1 maxOcc unbounded content simple
facets	Kind Value annotation enumeration 1 enumeration 2 enumeration 3 enumeration 4 enumeration 6

#### element DeliveryApptShellCreateRequest/RecurringAppt


diagram	<pre> classDiagram     class RecurringAppt {         &lt;&lt;mailxml_tm:RecurringAppt&gt;&gt;     }     class EffectiveStartDate {         &lt;&lt;mailxml_tm:EffectiveStartDate&gt;&gt;     }     class EffectiveEndDate {         &lt;&lt;mailxml_tm:EffectiveEndDate&gt;&gt;     }     class ApptTime {         &lt;&lt;mailxml_tm:ApptTime&gt;&gt;     }     class DayFrequency {         &lt;&lt;mailxml_tm:DayFrequency&gt;&gt;     }     class WeekFrequency {         &lt;&lt;mailxml_tm:WeekFrequency&gt;&gt;     }      RecurringAppt "3..3" *-- "*" EffectiveStartDate     RecurringAppt "3..3" *-- "*" EffectiveEndDate     RecurringAppt "3..3" *-- "*" ApptTime     RecurringAppt "3..3" *-- "*" DayFrequency     RecurringAppt "3..3" *-- "*" WeekFrequency   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#"><b>mailxml_tm:recurringApptType</b></a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:EffectiveStartDate</a> <a href="#">mailxml_tm:EffectiveEndDate</a> <a href="#">mailxml_tm:ApptTime</a> <a href="#">mailxml_tm:DayFrequency</a> <a href="#">mailxml_tm:WeekFrequency</a>

#### element DeliveryApptShellCreateRequest/OneTimeAppt

diagram	<pre> classDiagram     class OneTimeAppt {         &lt;&lt;mailxml_tm:OneTimeAppt&gt;&gt;     }     class PreferredAppt {         &lt;&lt;mailxml_tm:PreferredAppt&gt;&gt;     }     class OptionalAppt {         &lt;&lt;mailxml_tm:OptionalAppt&gt;&gt;     }      OneTimeAppt "3..3" *-- "*" PreferredAppt     OneTimeAppt "3..3" *-- "*" OptionalAppt   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm

type	<a href="#">mailxml_tm:oneTimeApptType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:PreferredAppt</a> <a href="#">mailxml_tm:OptionalAppt</a>


#### element **DeliveryApptShellCreateRequest/TrailerInfo**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:trailerInfoType</a>
properties	isRef 0 minOcc 0 maxOcc 1 content complex
children	<a href="#">mailxml_tm:Trailer</a> <a href="#">mailxml_tm:Carrier</a> <a href="#">mailxml_tm:BillOfLadingNumber</a>

#### element **DeliveryApptShellCreateRequest/Comment**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_base:s256</a>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 256 whiteSpace preserve

#### element **DeliveryApptShellCreateRequest/ValueAddedService**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:valueAddedServiceType</a>

properties	isRef 0 minOcc 0 maxOcc 1 content simple																																																															
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr><td>enumeration</td><td>D1</td><td></td></tr> <tr><td>enumeration</td><td>D2</td><td></td></tr> <tr><td>enumeration</td><td>D3</td><td></td></tr> <tr><td>enumeration</td><td>D4</td><td></td></tr> <tr><td>enumeration</td><td>D5</td><td></td></tr> <tr><td>enumeration</td><td>D6</td><td></td></tr> <tr><td>enumeration</td><td>D7</td><td></td></tr> <tr><td>enumeration</td><td>D8</td><td></td></tr> <tr><td>enumeration</td><td>D9</td><td></td></tr> <tr><td>enumeration</td><td>D10</td><td></td></tr> <tr><td>enumeration</td><td>D11</td><td></td></tr> <tr><td>enumeration</td><td>D12</td><td></td></tr> <tr><td>enumeration</td><td>D13</td><td></td></tr> <tr><td>enumeration</td><td>D14</td><td></td></tr> <tr><td>enumeration</td><td>D15</td><td></td></tr> <tr><td>enumeration</td><td>D16</td><td></td></tr> <tr><td>enumeration</td><td>D17</td><td></td></tr> <tr><td>enumeration</td><td>D18</td><td></td></tr> <tr><td>enumeration</td><td>D19</td><td></td></tr> <tr><td>enumeration</td><td>D20</td><td></td></tr> </tbody> </table>	Kind	Value	annotation	enumeration	D1		enumeration	D2		enumeration	D3		enumeration	D4		enumeration	D5		enumeration	D6		enumeration	D7		enumeration	D8		enumeration	D9		enumeration	D10		enumeration	D11		enumeration	D12		enumeration	D13		enumeration	D14		enumeration	D15		enumeration	D16		enumeration	D17		enumeration	D18		enumeration	D19		enumeration	D20	
Kind	Value	annotation																																																														
enumeration	D1																																																															
enumeration	D2																																																															
enumeration	D3																																																															
enumeration	D4																																																															
enumeration	D5																																																															
enumeration	D6																																																															
enumeration	D7																																																															
enumeration	D8																																																															
enumeration	D9																																																															
enumeration	D10																																																															
enumeration	D11																																																															
enumeration	D12																																																															
enumeration	D13																																																															
enumeration	D14																																																															
enumeration	D15																																																															
enumeration	D16																																																															
enumeration	D17																																																															
enumeration	D18																																																															
enumeration	D19																																																															
enumeration	D20																																																															

### element DeliveryApptShellCreateResponse

diagram	<p>The diagram illustrates the structure of the <code>DeliveryApptShellCreateResponse</code> element. It is a complex type derived from <code>DeliveryApptShellCreateRespo...</code>. It has two associations: one with <code>mailxml_tm:TrackingID</code> and another with <code>mailxml_tm:SubmitterTrackingID</code>. The <code>mailxml_tm:TrackingID</code> association is marked with a multiplicity of 1..* and has a target node labeled <code>mailxml_tm:DeliveryApptShellC...</code>. The <code>mailxml_tm:SubmitterTrackingID</code> association is marked with a multiplicity of 0..1 and has a target node labeled <code>mailxml_tm:DeliveryApptShellC...</code>.</p>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
properties	content complex
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:DeliveryApptShellCreateAccept</a> <a href="#">mailxml_tm:DeliveryApptShellCreateReject</a>
annotation	documentation Response to the request to create a delivery appointment shell to which content will be added later.

### element DeliveryApptShellCreateResponse/TrackingID

diagram	<p>The diagram shows a dashed box containing the label <code>mailxml_tm:TrackingID</code>, indicating that this is a reference type within the context of the <code>DeliveryApptShellCreateResponse</code> element.</p>
---------	---

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm		
type	<b>mailxml_base:s20</b>		
properties	isRef	0	
	minOcc	0	
	maxOcc	1	
	content	simple	
facets	Kind	Value	annotation
	minLength	1	
	maxLength	20	
	whiteSpace	preserve	

**element DeliveryApptShellCreateResponse/SubmitterTrackingID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s20</b>
properties	isRef 0
	minOcc 0
	maxOcc 1
	content simple
facets	Kind Value annotation
	minLength 1
	maxLength 20
	whiteSpace preserve

element **DeliveryApptShellCreateResponse/DeliveryApptShellCreateAccept**

diagram	<pre> classDiagram     class mailxml_tm {         deliveryApptShellAcceptType {             attributes: ShipperApptReqID, ConsigneeApptID, SchedulerID, SchedulerCorpID, SchedulerCRID, ShipperMultiStopID, ConsigneeMultiSt..., ApptType, PickupOrDelivery, PalletPositionCount, IncludesElectronic             children: ConsigneeFacility, TrailerInfo, DestinationEntry, MailClass[1..∞], ReturnInfo         }     } </pre>						
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm						
type	<a href="#">mailxml_tm:deliveryApptShellAcceptType</a>						
properties	isRef 0 content complex						
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:RecurringAppt</a> <a href="#">mailxml_tm:OneTimeAppt</a> <a href="#">mailxml_tm:TrailerInfo</a> <a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:MailClass</a> <a href="#">mailxml_tm:ReturnInfo</a>						
attributes	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>Annotation</th> </tr> </thead> </table>	Name	Type	Use	Default	Fixed	Annotation
Name	Type	Use	Default	Fixed	Annotation		

	mailxml_defs:ShipperApptRequestID	<b>mailxml_base:s12</b>	require d
	mailxml_defs:ConsigneeApptID	<b>mailxml_base:s12</b>	
	mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>	
	mailxml_defs:SchedulerCorpID	<b>mailxml_base:s12</b>	
	mailxml_defs:SchedulerCRID	<b>mailxml_base:CRIDType</b>	
	mailxml_defs:ShipperMultiStopID	<b>mailxml_base:s12</b>	
	mailxml_defs:ConsigneeMultiStopID	<b>mailxml_base:s12</b>	
	mailxml_defs:ShipperStopNumber	<b>mailxml_base:n06</b>	
	mailxml_defs:ApptType	<b>mailxml_base:apptTypeType</b>	require d
	mailxml_defs:PickupOrDelivery	<b>mailxml_base:pickupOrDeliveryTyp e</b>	
	mailxml_defs:PalletPositionCount	<b>mailxml_base:n02</b>	
	mailxml_defs:IncludesElectronicLoa d	<b>mailxml_base:yesNo</b>	

element **DeliveryApptShellCreateResponse/DeliveryApptShellCreateReject**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>

type	<a href="#"><b>mailxml_tm:deliveryApptShellRejectType</b></a>					
properties	isRef content	0 complex				
children	<a href="#"><b>mailxml_tm:DestinationEntry</b></a> <a href="#"><b>mailxml_tm:ReturnInfo</b></a>					
attributes	Name	Type	Use	Default	Fixed	annotation
	mailxml_defs:ShipperApptRequestID	<b>mailxml_base:s12</b>	required			
	mailxml_defs:ConsigneeApptID	<b>mailxml_base:s12</b>				
	mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>				
	mailxml_defs:SchedulerCorpID	<b>mailxml_base:s12</b>				
	mailxml_defs:SchedulerCRID	<b>mailxml_base:CRIDType</b>				
	mailxml_defs:ShipperMultiStopID	<b>mailxml_base:s12</b>				
	mailxml_defs:ConsigneeMultiStopID	<b>mailxml_base:s12</b>				
	mailxml_defs:ShipperStopNumber	<b>mailxml_base:n06</b>				
	mailxml_defs:ApptType	<b>mailxml_base:apptTypeType</b>	required			
	mailxml_defs:PickupOrDelivery	<b>mailxml_base:pickupOrDeliveryType</b>				
	mailxml_defs:PalletPositionCount	<b>mailxml_base:n02</b>				
	mailxml_defs:IncludesElectronicLoad	<b>mailxml_base:yesNo</b>				

## element DeliveryApptShellUpdateRequest

diagram	<p>The diagram illustrates the structure of the <code>DeliveryApptShellUpdateRequest</code> element. It features a main class <code>DeliveryApptShellUpdateRequest</code> with the following details:</p> <ul style="list-style-type: none"> <li><b>Attributes:</b> <ul style="list-style-type: none"> <li><code>grp mailxml_defs:RequestMs...</code></li> <li><code>mailxml_defs:ShipperApptRequ...</code></li> <li><code>mailxml_defs:ConsigneeApptID</code></li> <li><code>mailxml_defs:SchedulerID</code></li> <li><code>mailxml_defs:SchedulerCorpID</code></li> <li><code>mailxml_defs:SchedulerCRID</code></li> <li><code>mailxml_defs:ShipperMultiStopID</code></li> <li><code>mailxml_defs:ConsigneeMultiSto...</code></li> <li><code>mailxml_defs:ShipperStopNumb...</code></li> <li><code>mailxml_defs:ApptType</code></li> <li><code>mailxml_defs:PickupOrDelivery</code></li> <li><code>mailxml_defs:PalletPositionCount</code></li> <li><code>mailxml_defs:IncludesElectroni...</code></li> </ul> </li> <li><b>Associations:</b> <ul style="list-style-type: none"> <li>An association with <code>mailxml_tm:SubmittingParty</code>.</li> <li>An association with <code>mailxml_tm:SubmittingSoftware</code>.</li> <li>An association with <code>mailxml_tm:SubmitterTrackingID</code>.</li> <li>An association with <code>mailxml_tm:ConsigneeFacility</code>.</li> <li>An association with <code>mailxml_tm:DestinationEntry</code>.</li> <li>An association with <code>mailxml_tm:MailClass</code>, which has a multiplicity of <code>1..∞</code>.</li> <li>An association with <code>mailxml_tm:RecurringAppt</code>.</li> <li>An association with <code>mailxml_tm:OneTimeAppt</code>.</li> <li>An association with <code>mailxml_tm:TrailerInfo</code>.</li> <li>An association with <code>mailxml_tm:Comment</code>.</li> <li>An association with <code>mailxml_tm:ValueAddedService</code>.</li> </ul> </li> </ul> <p><b>Description:</b> Request to update a delivery appointment shell to which content will be added later.</p>
namespac	<code>http://idealliance.org/Specs/mailxml23.0/mailxml_tm</code>

e						
properties	content complex					
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:MailClass</a> <a href="#">mailxml_tm:RecurringAppt</a> <a href="#">mailxml_tm:OneTimeAppt</a> <a href="#">mailxml_tm:TrailerInfo</a> <a href="#">mailxml_tm:Comment</a> <a href="#">mailxml_tm:ValueAddedService</a>					
attributes	Name	Type	Use	Default	Fixed	annotation
	mailxml_defs:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required			
	mailxml_defs:ConsigneeApptID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:SchedulerID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:SchedulerCorpID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>				
	mailxml_defs:ShipperMultiStopID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:ConsigneeMultiStopID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:ShipperStopNumber	<a href="#">mailxml_base:n06</a>				
	mailxml_defs:ApptType	<a href="#">mailxml_base:apptTypeType</a>	required			
	mailxml_defs:PickupOrDelivery	<a href="#">mailxml_base:pickupOrDeliveryType</a>				
	mailxml_defs:PalletPositionCount	<a href="#">mailxml_base:n02</a>				
	mailxml_defs:IncludesElectronicLoad	<a href="#">mailxml_base:yesNo</a>				
annotation	documentation Request to update a delivery appointment shell to which content will be added later.					

### element DeliveryApptShellUpdateRequest/SubmittingParty

diagram	<pre> classDiagram     class participantIDType {         &lt;&lt;mailxml_defs:participantIDType&gt;&gt;         &lt;&lt;attributes&gt;&gt;             MailerID6             MailerID9             CRID             SchedulerID             MaildatUserLicense             ShippingAgentID             ReceivingAgentID     }     class SubmittingParty {         &lt;&lt;mailxml_tm:SubmittingParty&gt;&gt;     }     SubmittingParty "2" --&gt; participantIDType   </pre>					
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>					
type	<a href="#">mailxml_defs:participantIDType</a>					
properties	isRef 0 content complex					
attributes	Name mailxml_defs:MailerID6	Type <a href="#">mailxml_base:mailerID6Type</a>	Use	Default	Fixed	annotation

	mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>
	mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>
	mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>
	mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>
	mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>
	mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>

#### element **DeliveryApptShellUpdateRequest/SubmittingSoftware**

diagram	<pre> classDiagram     class mailxml_tm::SubmittingSoftware     class mailxml_defs::submittingSoftwareType {         SoftwareName : xs:string         Vendor : xs:string         Version : xs:string         ApprovalDate : xs:date         ApprovalKey : xs:string     }     SubmittingSoftware &lt; -- submittingSoftwareType   </pre>																																				
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																				
type	<b>mailxml_defs:submittingSoftwareType</b>																																				
properties	<table> <tr> <td>isRef</td><td>0</td> </tr> <tr> <td>content</td><td>complex</td> </tr> </table>	isRef	0	content	complex																																
isRef	0																																				
content	complex																																				
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:SoftwareName</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Vendor</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Version</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalDate</td> <td><b>xs:date</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalKey</td> <td><b>xs:string</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SoftwareName	<b>xs:string</b>	required				mailxml_defs:Vendor	<b>xs:string</b>	required				mailxml_defs:Version	<b>xs:string</b>	required				mailxml_defs:ApprovalDate	<b>xs:date</b>					mailxml_defs:ApprovalKey	<b>xs:string</b>				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_defs:SoftwareName	<b>xs:string</b>	required																																			
mailxml_defs:Vendor	<b>xs:string</b>	required																																			
mailxml_defs:Version	<b>xs:string</b>	required																																			
mailxml_defs:ApprovalDate	<b>xs:date</b>																																				
mailxml_defs:ApprovalKey	<b>xs:string</b>																																				

#### element **DeliveryApptShellUpdateRequest/SubmitterTrackingID**

diagram	<pre> classDiagram     class mailxml_tm::SubmitterTrackingID   </pre>									
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>									
type	<b>mailxml_base:s20</b>									
properties	<table> <tr> <td>isRef</td><td>0</td> </tr> <tr> <td>minOcc</td><td>0</td> </tr> <tr> <td>maxOcc</td><td>1</td> </tr> <tr> <td>content</td><td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple	
isRef	0									
minOcc	0									
maxOcc	1									
content	simple									
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td><td>1</td><td></td> </tr> <tr> <td>maxLength</td><td>20</td><td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	20	
Kind	Value	annotation								
minLength	1									
maxLength	20									

	whiteSpace preserve
--	---------------------

#### element DeliveryApptShellUpdateRequest/ConsigneeFacility

diagram	<pre> classDiagram     class mailxml_tm_ConsigneeFacility     class mailxml_defs_ConsigneeFacilityType     class mailxml_defs_CompanyName     class mailxml_defs_FacilityNumber     class mailxml_defs_FacilityAddress     class mailxml_defs_FacilityName     class mailxml_defs_FacilityType     class mailxml_defs_URL     class mailxml_defs_CommonContact      mailxml_tm_ConsigneeFacility "0..1" --&gt; mailxml_defs_ConsigneeFacilityType     mailxml_tm_ConsigneeFacility "0..1" --&gt; mailxml_defs_CompanyName     mailxml_tm_ConsigneeFacility "0..1" --&gt; mailxml_defs_FacilityNumber     mailxml_tm_ConsigneeFacility "0..infinity" --&gt; mailxml_defs_FacilityAddress     mailxml_tm_ConsigneeFacility "0..1" --&gt; mailxml_defs_FacilityName     mailxml_tm_ConsigneeFacility "0..1" --&gt; mailxml_defs_FacilityType     mailxml_tm_ConsigneeFacility "0..1" --&gt; mailxml_defs_URL     mailxml_tm_ConsigneeFacility "0..1" --&gt; mailxml_defs_CommonContact   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_defs:consigneeFacilityType</b>
properties	isRef 0 content complex
children	mailxml_defs:CompanyName mailxml_defs:FacilityNumber mailxml_defs:FacilityAddress mailxml_defs:FacilityAddress mailxml_defs:FacilityName mailxml_defs:FacilityType mailxml_defs:URL mailxml_defs:CommonContact

#### element DeliveryApptShellUpdateRequest/DestinationEntry

diagram	<pre> classDiagram     class mailxml_tm_DestinationEntry   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

#### element DeliveryApptShellUpdateRequest/MailClass

diagram	<pre> classDiagram     class mailxml_tm_MailClass   </pre>
---------	--

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:mailClassType</b>
properties	isRef 0 minOcc 1 maxOcc unbounded content simple
facets	Kind Value annotation enumeration 1 enumeration 2 enumeration 3 enumeration 4 enumeration 6

#### element DeliveryApptShellUpdateRequest/RecurringAppt


diagram	<pre> classDiagram     class RecurringAppt     class EffectiveStartDate     class EffectiveEndDate     class ApptTime     class DayFrequency     class WeekFrequency      RecurringAppt "3..3" -- "*" EffectiveStartDate     RecurringAppt "3..3" -- "*" EffectiveEndDate     RecurringAppt "3..3" -- "*" ApptTime     RecurringAppt "3..3" -- "*" DayFrequency     RecurringAppt "3..3" -- "*" WeekFrequency   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_tm:recurringApptType</b>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:EffectiveStartDate</a> <a href="#">mailxml_tm:EffectiveEndDate</a> <a href="#">mailxml_tm:ApptTime</a> <a href="#">mailxml_tm:DayFrequency</a> <a href="#">mailxml_tm:WeekFrequency</a>

#### element DeliveryApptShellUpdateRequest/OneTimeAppt

diagram	<pre> classDiagram     class OneTimeAppt     class PreferredAppt     class OptionalAppt      OneTimeAppt "3..3" -- "*" PreferredAppt     OneTimeAppt "3..3" -- "*" OptionalAppt   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm

type	<a href="#">mailxml_tm:oneTimeApptType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:PreferredAppt</a> <a href="#">mailxml_tm:OptionalAppt</a>


#### element DeliveryApptShellUpdateRequest/TrailerInfo

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:trailerInfoType</a>
properties	isRef 0 minOcc 0 maxOcc 1 content complex
children	<a href="#">mailxml_tm:Trailer</a> <a href="#">mailxml_tm:Carrier</a> <a href="#">mailxml_tm:BillOfLadingNumber</a>

#### element DeliveryApptShellUpdateRequest/Comment

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_base:s256</a>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 256 whiteSpace preserve

#### element DeliveryApptShellUpdateRequest/ValueAddedService

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:valueAddedServiceType</a>

properties	isRef 0 minOcc 0 maxOcc 1 content simple																																																															
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr><td>enumeration</td><td>D1</td><td></td></tr> <tr><td>enumeration</td><td>D2</td><td></td></tr> <tr><td>enumeration</td><td>D3</td><td></td></tr> <tr><td>enumeration</td><td>D4</td><td></td></tr> <tr><td>enumeration</td><td>D5</td><td></td></tr> <tr><td>enumeration</td><td>D6</td><td></td></tr> <tr><td>enumeration</td><td>D7</td><td></td></tr> <tr><td>enumeration</td><td>D8</td><td></td></tr> <tr><td>enumeration</td><td>D9</td><td></td></tr> <tr><td>enumeration</td><td>D10</td><td></td></tr> <tr><td>enumeration</td><td>D11</td><td></td></tr> <tr><td>enumeration</td><td>D12</td><td></td></tr> <tr><td>enumeration</td><td>D13</td><td></td></tr> <tr><td>enumeration</td><td>D14</td><td></td></tr> <tr><td>enumeration</td><td>D15</td><td></td></tr> <tr><td>enumeration</td><td>D16</td><td></td></tr> <tr><td>enumeration</td><td>D17</td><td></td></tr> <tr><td>enumeration</td><td>D18</td><td></td></tr> <tr><td>enumeration</td><td>D19</td><td></td></tr> <tr><td>enumeration</td><td>D20</td><td></td></tr> </tbody> </table>	Kind	Value	annotation	enumeration	D1		enumeration	D2		enumeration	D3		enumeration	D4		enumeration	D5		enumeration	D6		enumeration	D7		enumeration	D8		enumeration	D9		enumeration	D10		enumeration	D11		enumeration	D12		enumeration	D13		enumeration	D14		enumeration	D15		enumeration	D16		enumeration	D17		enumeration	D18		enumeration	D19		enumeration	D20	
Kind	Value	annotation																																																														
enumeration	D1																																																															
enumeration	D2																																																															
enumeration	D3																																																															
enumeration	D4																																																															
enumeration	D5																																																															
enumeration	D6																																																															
enumeration	D7																																																															
enumeration	D8																																																															
enumeration	D9																																																															
enumeration	D10																																																															
enumeration	D11																																																															
enumeration	D12																																																															
enumeration	D13																																																															
enumeration	D14																																																															
enumeration	D15																																																															
enumeration	D16																																																															
enumeration	D17																																																															
enumeration	D18																																																															
enumeration	D19																																																															
enumeration	D20																																																															

### element DeliveryApptShellUpdateResponse

diagram	<pre> classDiagram     class DeliveryApptShellUpdateResponse {         &lt;&lt;Response to the request to update a delivery appointment shell to which content will be added later.&gt;&gt;     }     class TrackingID     class SubmitterTrackingID     class DeliveryApptShellAccept     class DeliveryApptShellReject      DeliveryApptShellUpdateResponse &lt; -- TrackingID     DeliveryApptShellUpdateResponse &lt; -- SubmitterTrackingID     DeliveryApptShellUpdateResponse --&gt;  TrackingID : &lt;&lt;mailxml_tm&gt;&gt;     DeliveryApptShellUpdateResponse --&gt;  SubmitterTrackingID : &lt;&lt;mailxml_tm&gt;&gt;     DeliveryApptShellUpdateResponse --&gt;  DeliveryApptShellAccept : &lt;&lt;mailxml_tm&gt;&gt;     DeliveryApptShellUpdateResponse --&gt;  DeliveryApptShellReject : &lt;&lt;mailxml_tm&gt;&gt;   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
properties	content complex
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:DeliveryApptShellAccept</a> <a href="#">mailxml_tm:DeliveryApptShellReject</a>
annotation	documentation Response to the request to update a delivery appointment shell to which content will be added later.

### element DeliveryApptShellUpdateResponse/TrackingID

diagram	<pre> classDiagram     class TrackingID {         &lt;&lt;mailxml_tm&gt;&gt;     }   </pre>
---------	---

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm		
type	<b>mailxml_base:s20</b>		
properties	isRef	0	
	minOcc	0	
	maxOcc	1	
	content	simple	
facets	Kind	Value	annotation
	minLength	1	
	maxLength	20	
	whiteSpace	preserve	

**element DeliveryApptShellUpdateResponse/SubmitterTrackingID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s20</b>
properties	isRef 0
	minOcc 0
	maxOcc 1
	content simple
facets	Kind Value annotation
	minLength 1
	maxLength 20
	whiteSpace preserve

element **DeliveryApptShellUpdateResponse/DeliveryApptShellAccept**

diagram	<pre> classDiagram     class mailxml_tm {         deliveryApptShellAcceptType     }     class mailxml_tm {         DeliveryApptShellAcceptType     }     class mailxml_tm {         attributes     }     class mailxml_tm {         ShipperApptReq     }     class mailxml_tm {         ConsigneeApptID     }     class mailxml_tm {         SchedulerID     }     class mailxml_tm {         SchedulerCorpID     }     class mailxml_tm {         SchedulerCRID     }     class mailxml_tm {         ShipperMultiStopID     }     class mailxml_tm {         ConsigneeMultiSt...     }     class mailxml_tm {         ShipperStopNumb...     }     class mailxml_tm {         ApptType     }     class mailxml_tm {         PickupOrDelivery     }     class mailxml_tm {         PalletPositionCount     }     class mailxml_tm {         IncludesElectroni...     }     class mailxml_tm {         ConsigneeFacility     }     class mailxml_tm {         RecurringAppt     }     class mailxml_tm {         OneTimeAppt     }     class mailxml_tm {         TrailerInfo     }     class mailxml_tm {         DestinationEntry     }     class mailxml_tm {         MailClass     }     class mailxml_tm {         ReturnInfo     }      mailxml_tm(DeliveryApptShellAcceptType) --&gt; mailxml_tm(attributes)     mailxml_tm(DeliveryApptShellAcceptType) --&gt; mailxml_tm(ShipperApptReq)     mailxml_tm(DeliveryApptShellAcceptType) --&gt; mailxml_tm(ConsigneeApptID)     mailxml_tm(DeliveryApptShellAcceptType) --&gt; mailxml_tm(SchedulerID)     mailxml_tm(DeliveryApptShellAcceptType) --&gt; mailxml_tm(SchedulerCorpID)     mailxml_tm(DeliveryApptShellAcceptType) --&gt; mailxml_tm(SchedulerCRID)     mailxml_tm(DeliveryApptShellAcceptType) --&gt; mailxml_tm(ShipperMultiStopID)     mailxml_tm(DeliveryApptShellAcceptType) --&gt; mailxml_tm(ConsigneeMultiSt...)     mailxml_tm(DeliveryApptShellAcceptType) --&gt; mailxml_tm(ShipperStopNumb...)     mailxml_tm(DeliveryApptShellAcceptType) --&gt; mailxml_tm(ApptType)     mailxml_tm(DeliveryApptShellAcceptType) --&gt; mailxml_tm(PickupOrDelivery)     mailxml_tm(DeliveryApptShellAcceptType) --&gt; mailxml_tm(PalletPositionCount)     mailxml_tm(DeliveryApptShellAcceptType) --&gt; mailxml_tm(IncludesElectroni...)     mailxml_tm(DeliveryApptShellAcceptType) --&gt; mailxml_tm(ConsigneeFacility)     mailxml_tm(DeliveryApptShellAcceptType) --&gt; mailxml_tm(RecurringAppt)     mailxml_tm(DeliveryApptShellAcceptType) --&gt; mailxml_tm(OneTimeAppt)     mailxml_tm(DeliveryApptShellAcceptType) --&gt; mailxml_tm(TrailerInfo)     mailxml_tm(DeliveryApptShellAcceptType) --&gt; mailxml_tm(DestinationEntry)     mailxml_tm(DeliveryApptShellAcceptType) --&gt; mailxml_tm(MailClass)     mailxml_tm(DeliveryApptShellAcceptType) --&gt; mailxml_tm(ReturnInfo)   </pre>						
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm						
type	<a href="#">mailxml_tm:deliveryApptShellAcceptType</a>						
properties	isRef 0 content complex						
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:RecurringAppt</a> <a href="#">mailxml_tm:OneTimeAppt</a> <a href="#">mailxml_tm:TrailerInfo</a> <a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:MailClass</a> <a href="#">mailxml_tm:ReturnInfo</a>						
attributes	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> </table>	Name	Type	Use	Default	Fixed	annotation
Name	Type	Use	Default	Fixed	annotation		

	mailxml_defs:ShipperApptRequestID	<b>mailxml_base:s12</b>	require d
	mailxml_defs:ConsigneeApptID	<b>mailxml_base:s12</b>	
	mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>	
	mailxml_defs:SchedulerCorpID	<b>mailxml_base:s12</b>	
	mailxml_defs:SchedulerCRID	<b>mailxml_base:CRIDType</b>	
	mailxml_defs:ShipperMultiStopID	<b>mailxml_base:s12</b>	
	mailxml_defs:ConsigneeMultiStopID	<b>mailxml_base:s12</b>	
	mailxml_defs:ShipperStopNumber	<b>mailxml_base:n06</b>	
	mailxml_defs:ApptType	<b>mailxml_base:apptTypeType</b>	require d
	mailxml_defs:PickupOrDelivery	<b>mailxml_base:pickupOrDeliveryTyp e</b>	
	mailxml_defs:PalletPositionCount	<b>mailxml_base:n02</b>	
	mailxml_defs:IncludesElectronicLoa d	<b>mailxml_base:yesNo</b>	

element **DeliveryApptShellUpdateResponse/DeliveryApptShellReject**

diagram	<pre> classDiagram     class mailxml_tm.deliveryApptShellRejectType {         &lt;&lt;attributes&gt;&gt;         mailxml_defs:ShipperApptRequestID         mailxml_defs:ConsigneeApptID         mailxml_defs:SchedulerID         mailxml_defs:SchedulerCorpID         mailxml_defs:SchedulerCRID         mailxml_defs:ShipperMultiStopID         mailxml_defs:ConsigneeMultiStopID         mailxml_defs:ShipperStopNumber         mailxml_defs:ApptType         mailxml_defs:PickupOrDelivery         mailxml_defs:PalletPositionCount         mailxml_defs:IncludesElectronicLoad     }     mailxml_tm.deliveryApptShellRejectType "1" -- "1" mailxml_tm.DestinationEntry     mailxml_tm.deliveryApptShellRejectType "1" -- "1" mailxml_tm.ReturnInfo     class mailxml_tm.DeliveryApptShellR...   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>

type	<a href="#">mailxml_tm:deliveryApptShellRejectType</a>					
properties	isRef 0 content complex					
children	<a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ReturnInfo</a>					
attributes	Name	Type	Use	Default	Fixed	annotation
	mailxml_defs:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required			
	mailxml_defs:ConsigneeApptID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:SchedulerID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:SchedulerCorpID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>				
	mailxml_defs:ShipperMultiStopID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:ConsigneeMultiStopID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:ShipperStopNumber	<a href="#">mailxml_base:n06</a>				
	mailxml_defs:ApptType	<a href="#">mailxml_base:apptTypeType</a>	required			
	mailxml_defs:PickupOrDelivery	<a href="#">mailxml_base:pickupOrDeliveryType</a>				
	mailxml_defs:PalletPositionCount	<a href="#">mailxml_base:n02</a>				
	mailxml_defs:IncludesElectronicLoad	<a href="#">mailxml_base:yesNo</a>				

### element DeliveryApptStatusQueryRequest

diagram																			
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																		
properties	content complex																		
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a>																		
attributes	<table> <tr> <td>Name</td> <td>Type</td> <td>Use</td> <td>Default</td> <td>Fixed</td> <td>annotation</td> </tr> <tr> <td>mailxml_tm:ShipperApptRequestID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:ConsigneeApptID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required				mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>	required			
Name	Type	Use	Default	Fixed	annotation														
mailxml_tm:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required																	
mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>	required																	
annotation	documentation Query request for the status of a delivery appointment.																		

### element DeliveryApptStatusQueryRequest/SubmittingParty

diagram	<pre> classDiagram     class mailxml_tmSubmittingParty     class mailxml_defsParticipantIDType {         &lt;&lt;attributes&gt;&gt;         mailxml_defsMailerID6         mailxml_defsMailerID9         mailxml_defsCRID         mailxml_defsSchedulerID         mailxml_defsMaildatUserLicense         mailxml_defsShippingAgentID         mailxml_defsReceivingAgentID     }     mailxml_tmSubmittingParty "1" -- "1" mailxml_defsParticipantIDType   </pre>																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:MailerID6</td><td><b>mailxml_base:mailerID6Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MailerID9</td><td><b>mailxml_base:mailerID9Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:CRID</td><td><b>mailxml_base:CRIDType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatUserLicense</td><td><b>mailxml_base:userLicenseCodeType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShippingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ReceivingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

### element DeliveryApptStatusQueryRequest/SubmittingSoftware


diagram	<pre> classDiagram     class mailxml_tmSubmittingSoftware     class mailxml_defsSubmittingSoftwareType {         &lt;&lt;attributes&gt;&gt;         mailxml_defsSoftwareName         mailxml_defsVendor         mailxml_defsVersion         mailxml_defsApprovalDate         mailxml_defsApprovalKey     }     mailxml_tmSubmittingSoftware "1" -- "1" mailxml_defsSubmittingSoftwareType   </pre>
---------	--

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
type	<b>mailxml_defs:submittingSoftwareType</b>					
properties	isRef 0 content complex					
attributes	Name mailxml_defs:SoftwareName	Type <b>xs:string</b>	Use required	Default	Fixed	annotation
	mailxml_defs:Vendor	<b>xs:string</b>	required			
	mailxml_defs:Version	<b>xs:string</b>	required			
	mailxml_defs:ApprovalDate	<b>xs:date</b>				
	mailxml_defs:ApprovalKey	<b>xs:string</b>				

#### element **DeliveryApptStatusQueryRequest/SubmitterTrackingID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s20</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

#### element **DeliveryApptStatusQueryResponse**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
properties	content complex
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:QueryResults</a> <a href="#">mailxml_defs:QueryError</a>
annotation	documentation Response to the Query request for the status of a delivery appointment.


**element DeliveryApptStatusQueryResponse/TrackingID**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>20</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

**element DeliveryApptStatusQueryResponse/SubmitterTrackingID**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>20</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

**element DeliveryApptStatusQueryResponse/QueryResults**

diagram					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex
isRef	0				
content	complex				
children	<a href="#">mailxml_tm:DeliveryApptUpdate</a> <a href="#">mailxml_tm:ConsigneeGoodsReceipt</a> <a href="#">mailxml_tm:ReturnInfo</a>				

**element DeliveryApptStatusQueryResponse/QueryResults/ReturnInfo**

diagram	<pre> classDiagram     class mailxml_tm::ReturnInfo     class mailxml_tm::ConsigneeFacility     class mailxml_tm::ErrorWarning     class mailxml_tm::ContainerErrorWarningBlock      mailxml_tm::ReturnInfo "0..1" --&gt; mailxml_tm::ConsigneeFacility     mailxml_tm::ReturnInfo "0..1" --&gt; mailxml_tm::ErrorWarning     mailxml_tm::ReturnInfo "0..1" --&gt; mailxml_tm::ContainerErrorWarningBlock   </pre>								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_defs:returnInfoType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#">mailxml_defs:ConsigneeFacility</a> <a href="#">mailxml_tm:ErrorWarning</a> <a href="#">mailxml_tm:ContainerErrorWarningBlock</a>								

**element DeliveryApptTransportationUpdateRequest**

diagram	<pre> classDiagram     class DeliveryApptTransportationUpd...     class mailxml_tm::ShipperApptRequestID     class mailxml_tm::ConsigneeApptID     class mailxml_tm::SchedulerContentID     class mailxml_tm::SchedulerID      DeliveryApptTransportationUpd... "0..1" --&gt; mailxml_tm::ShipperApptRequestID     DeliveryApptTransportationUpd... "0..1" --&gt; mailxml_tm::ConsigneeApptID     DeliveryApptTransportationUpd... "0..1" --&gt; mailxml_tm::SchedulerContentID     DeliveryApptTransportationUpd... "0..1" --&gt; mailxml_tm::SchedulerID      DeliveryApptTransportationUpd... "0..1" --&gt; mailxml_tm::SubmittingParty     DeliveryApptTransportationUpd... "0..1" --&gt; mailxml_tm::SubmittingSoftware     DeliveryApptTransportationUpd... "0..1" --&gt; mailxml_tm::SubmitterTrackingID     DeliveryApptTransportationUpd... "0..1" --&gt; mailxml_tm::TrailerInfo   </pre> <p>Request to update the transportation for a delivery appointment.</p>									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm									
type	<a href="#">mailxml_tm:deliveryApptTransportationUpdateRequestType</a>									
properties	content complex									
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:TrailerInfo</a>									
attributes	<table> <tr> <td>Name</td><td>mailxml_tm:ShipperApptRequestID</td> <td>Type</td><td><a href="#">mailxml_base:s12</a></td> <td>Use</td><td>required</td> <td>Default</td><td>Fixed</td> <td>annotation</td> </tr> </table>	Name	mailxml_tm:ShipperApptRequestID	Type	<a href="#">mailxml_base:s12</a>	Use	required	Default	Fixed	annotation
Name	mailxml_tm:ShipperApptRequestID	Type	<a href="#">mailxml_base:s12</a>	Use	required	Default	Fixed	annotation		

	mailxml_tm:ConsigneeApptID mailxml_tm:SchedulerContentID mailxml_tm:SchedulerID	<b>mailxml_base:s12</b> required <b>mailxml_base:s12</b> required <b>mailxml_base:s12</b> required
annotation	documentation Request to update the transportation for a delivery appointment.	

### element DeliveryApptTransportationUpdateResponse

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:deliveryApptTransportationUpdateResponseType</a>
properties	content complex
children	<a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:DeliveryApptTransportationAccept</a> <a href="#">mailxml_tm:DeliveryApptTransportationReject</a>
annotation	documentation Response to the request to update the transportation for a delivery appointment.

## element DeliveryApptUpdate

diagram	<p>The diagram illustrates the structure of the <code>DeliveryApptUpdate</code> element. It consists of a main class box labeled <code>DeliveryApptUpdate</code> containing several attributes. A dashed association line connects <code>DeliveryApptUpdate</code> to another class box labeled <code>ApptBlockUpdate</code>, which in turn has a multiplicity of <code>1..∞</code> at its end, indicating it can appear multiple times. This association line also passes through a connector node.</p>																																																												
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																																												
properties	content complex																																																												
children	<a href="#">mailxml_tm:ApptBlockUpdate</a> <a href="#">mailxml_tm:DetailInfo</a> <a href="#">mailxml_tm:TrailerInfo</a> <a href="#">mailxml_tm:ReturnInfo</a>																																																												
used by	element <a href="#">DeliveryApptStatusQueryResponse/QueryResults</a>																																																												
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><code>mailxml_tm:ShipperApptRequestID</code></td> <td><code>mailxml_base:s12</code></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td><code>mailxml_tm:ConsigneeApptID</code></td> <td><code>mailxml_base:s12</code></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><code>mailxml_tm:SchedulerID</code></td> <td><code>mailxml_base:s12</code></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><code>mailxml_tm:SchedulerCorpID</code></td> <td><code>mailxml_base:s12</code></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><code>mailxml_tm:SchedulerCRID</code></td> <td><code>mailxml_base:CRIDType</code></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><code>mailxml_tm:ApptType</code></td> <td><code>mailxml_base:apptTypeType</code></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td><code>mailxml_tm:PickupOrDelivery</code></td> <td><code>mailxml_base:pickupOrDeliveryType</code></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><code>mailxml_tm:PalletPositionCount</code></td> <td><code>mailxml_base:n02</code></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><code>mailxml_tm:IncludesElectronicLoad</code></td> <td><code>mailxml_base:yesNo</code></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<code>mailxml_tm:ShipperApptRequestID</code>	<code>mailxml_base:s12</code>	required				<code>mailxml_tm:ConsigneeApptID</code>	<code>mailxml_base:s12</code>					<code>mailxml_tm:SchedulerID</code>	<code>mailxml_base:s12</code>					<code>mailxml_tm:SchedulerCorpID</code>	<code>mailxml_base:s12</code>					<code>mailxml_tm:SchedulerCRID</code>	<code>mailxml_base:CRIDType</code>					<code>mailxml_tm:ApptType</code>	<code>mailxml_base:apptTypeType</code>	required				<code>mailxml_tm:PickupOrDelivery</code>	<code>mailxml_base:pickupOrDeliveryType</code>					<code>mailxml_tm:PalletPositionCount</code>	<code>mailxml_base:n02</code>					<code>mailxml_tm:IncludesElectronicLoad</code>	<code>mailxml_base:yesNo</code>				
Name	Type	Use	Default	Fixed	annotation																																																								
<code>mailxml_tm:ShipperApptRequestID</code>	<code>mailxml_base:s12</code>	required																																																											
<code>mailxml_tm:ConsigneeApptID</code>	<code>mailxml_base:s12</code>																																																												
<code>mailxml_tm:SchedulerID</code>	<code>mailxml_base:s12</code>																																																												
<code>mailxml_tm:SchedulerCorpID</code>	<code>mailxml_base:s12</code>																																																												
<code>mailxml_tm:SchedulerCRID</code>	<code>mailxml_base:CRIDType</code>																																																												
<code>mailxml_tm:ApptType</code>	<code>mailxml_base:apptTypeType</code>	required																																																											
<code>mailxml_tm:PickupOrDelivery</code>	<code>mailxml_base:pickupOrDeliveryType</code>																																																												
<code>mailxml_tm:PalletPositionCount</code>	<code>mailxml_base:n02</code>																																																												
<code>mailxml_tm:IncludesElectronicLoad</code>	<code>mailxml_base:yesNo</code>																																																												

element **DeliveryApptUpdate/ApptBlockUpdate**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:apptBlockUpdateType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:PreferredAppt</a> <a href="#">mailxml_tm:OptionalAppt</a> <a href="#">mailxml_tm:ETA</a> <a href="#">mailxml_tm:Comment</a>

element **DeliveryApptUpdate/DetailInfo**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:detailInfoType</a>
properties	isRef 0 minOcc 1 maxOcc unbounded content complex
children	<a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:USPSSummary</a> <a href="#">mailxml_tm:ConsigneeContentID</a>


### element DeliveryApptUpdate/TrailerInfo

diagram	<pre> classDiagram     class mailxml_tm::trailerInfoType {         mailxml_tm::Trailer         mailxml_tm::Carrier         mailxml_tm::BillOfLadingNumber     }     mailxml_tm::TrailerInfo &lt; -- mailxml_tm::trailerInfoType     mailxml_tm::TrailerInfo --&gt; mailxml_tm::Trailer : 0..2     mailxml_tm::TrailerInfo --&gt; mailxml_tm::Carrier : 0..1     mailxml_tm::TrailerInfo --&gt; mailxml_tm::BillOfLadingNumber : 1..2   </pre>								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_tm:trailerInfoType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#">mailxml_tm:Trailer</a> <a href="#">mailxml_tm:Carrier</a> <a href="#">mailxml_tm:BillOfLadingNumber</a>								

### element DeliveryApptUpdate/ReturnInfo

diagram	<pre> classDiagram     class mailxml_defs::returnInfoType {         mailxml_defs::ConsigneeFacility         mailxml_defs::ErrorWarning     }     mailxml_tm::ReturnInfo &lt; -- mailxml_defs::returnInfoType     mailxml_tm::ReturnInfo --&gt; mailxml_defs::ConsigneeFacility : 0..infinity     mailxml_tm::ReturnInfo --&gt; mailxml_defs::ErrorWarning : 0..infinity   </pre>								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_defs:returnInfoType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#">mailxml_defs:ConsigneeFacility</a> <a href="#">mailxml_defs:ErrorWarning</a> <a href="#">mailxml_defs:ContainerErrorWarningBlock</a>								

element **DeliveryApptUpdateRequest**



properties	content complex					
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:RecurringAppt</a> <a href="#">mailxml_tm:OneTimeAppt</a> <a href="#">mailxml_tm:DetailInfo</a> <a href="#">mailxml_tm:TrailerInfo</a> <a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:Comment</a> <a href="#">mailxml_tm:ETA</a> <a href="#">mailxml_tm:ValueAddedService</a> <a href="#">mailxml_tm:ReturnInfo</a>					
attributes	Name mailxml_tm:ShipperApptRequestID mailxml_tm:ConsigneeApptID mailxml_tm:SchedulerID mailxml_tm:SchedulerCorpID mailxml_tm:SchedulerCRID mailxml_tm:ApptType mailxml_tm:PickupOrDelivery mailxml_tm:PalletPositionCount mailxml_tm:IncludesElectronicLoad	Type <b>mailxml_base:s12</b> <b>mailxml_base:s12</b> <b>mailxml_base:s12</b> <b>mailxml_base:s12</b> <b>mailxml_base:CRIDType</b> <b>mailxml_base:apptTypeType</b> <b>mailxml_base:pickupOrDeliveryType</b> <b>mailxml_base:n02</b> <b>mailxml_base:yesNo</b>	Use required required	Default	Fixed	annotation
annotation	documentation Request to update a deliver appointment.					

### element DeliveryApptUpdateRequest/SubmittingParty

diagram						
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>					
type	<b>mailxml_defs:participantIDType</b>					
properties	isRef 0 content complex					
attributes	Name mailxml_defs:MailerID6 mailxml_defs:MailerID9 mailxml_defs:CRID mailxml_defs:SchedulerID mailxml_defs:MaildatUserLicense mailxml_defs:ShippingAgentID mailxml_defs:ReceivingAgentID	Type <b>mailxml_base:mailerID6Type</b> <b>mailxml_base:mailerID9Type</b> <b>mailxml_base:CRIDType</b> <b>mailxml_base:s12</b> <b>mailxml_base:userLicenseCodeType</b> <b>mailxml_base:s12</b>	Use	Default	Fixed	annotation

	mailxml_defs:ReceivingAgentID	mailxml_base:s12
--	-------------------------------	------------------

element **DeliveryApptUpdateRequest/SubmittingSoftware**

diagram	<pre> classDiagram     class mailxml_tmSubmittingSoftware     class mailxml_defsSubmittingSoftwareType {         SoftwareName         Vendor         Version         ApprovalDate         ApprovalKey     }     mailxml_tmSubmittingSoftware "1" --&gt; "1" mailxml_defsSubmittingSoftwareType   </pre>																																				
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																				
type	<b>mailxml_defs:submittingSoftwareType</b>																																				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																
isRef	0																																				
content	complex																																				
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:SoftwareName</td> <td>xs:string</td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Vendor</td> <td>xs:string</td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Version</td> <td>xs:string</td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalDate</td> <td>xs:date</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalKey</td> <td>xs:string</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SoftwareName	xs:string	required				mailxml_defs:Vendor	xs:string	required				mailxml_defs:Version	xs:string	required				mailxml_defs:ApprovalDate	xs:date					mailxml_defs:ApprovalKey	xs:string				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_defs:SoftwareName	xs:string	required																																			
mailxml_defs:Vendor	xs:string	required																																			
mailxml_defs:Version	xs:string	required																																			
mailxml_defs:ApprovalDate	xs:date																																				
mailxml_defs:ApprovalKey	xs:string																																				

element **DeliveryApptUpdateRequest/SubmitterTrackingID**

diagram	<pre> classDiagram     class mailxml_tmSubmitterTrackingID   </pre>												
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

element **DeliveryApptUpdateRequest/DestinationEntry**

diagram										
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm									
type	<a href="#">mailxml_base:yesNo</a>									
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	content	simple					
isRef	0									
content	simple									
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>enumeration</td><td>Yes</td><td></td></tr> <tr> <td>enumeration</td><td>No</td><td></td></tr> </table>	Kind	Value	annotation	enumeration	Yes		enumeration	No	
Kind	Value	annotation								
enumeration	Yes									
enumeration	No									

element **DeliveryApptUpdateRequest/RecurringAppt**

diagram					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm				
type	<a href="#">mailxml_tm:recurringApptType</a>				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex
isRef	0				
content	complex				
children	<a href="#">mailxml_tm:EffectiveStartDate</a> <a href="#">mailxml_tm:EffectiveEndDate</a> <a href="#">mailxml_tm:ApptTime</a> <a href="#">mailxml_tm:DayFrequency</a> <a href="#">mailxml_tm:WeekFrequency</a>				

element **DeliveryApptUpdateRequest/OneTimeAppt**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:oneTimeApptType</a>

properties	isRef 0 content complex
children	<a href="#">mailxml_tm:PreferredAppt</a> <a href="#">mailxml_tm:OptionalAppt</a>

#### element DeliveryApptUpdateRequest/DetailInfo

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:detailInfoType</a>
properties	isRef 0 minOcc 1 maxOcc unbounded content complex
children	<a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:USPSSummary</a> <a href="#">mailxml_tm:ConsigneeContentID</a>

#### element DeliveryApptUpdateRequest/TrailerInfo

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:trailerInfoType</a>
properties	isRef 0 minOcc 0

	maxOcc 1 content complex
children	<a href="#">mailxml_tm:Trailer</a> <a href="#">mailxml_tm:Carrier</a> <a href="#">mailxml_tm:BillOfLadingNumber</a>

### element DeliveryApptUpdateRequest/ConsigneeFacility

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_defs:consigneeFacilityType</b>
properties	isRef 0 content complex
children	<a href="#">mailxml_defs:CompanyName</a> <a href="#">mailxml_defs:FacilityNumber</a> <a href="#">mailxml_defs:FacilityAddress</a> <a href="#">mailxml_defs:FacilityAddress</a> <a href="#">mailxml_defs:FacilityName</a> <a href="#">mailxml_defs:FacilityType</a> <a href="#">mailxml_defs:URL</a> <a href="#">mailxml_defs:CommonContact</a>

### element DeliveryApptUpdateRequest/Comment

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:s256</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 256 whiteSpace preserve

**element DeliveryApptUpdateRequest/ETA**

diagram	mailxml_tm:ETA								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>xs:dateTime</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple
isRef	0								
minOcc	0								
maxOcc	1								
content	simple								

**element DeliveryApptUpdateRequest/ValueAddedService**

diagram	mailxml_tm:ValueAddedService																																																															
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																															
type	<b>mailxml_tm:valueAddedServiceType</b>																																																															
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple																																																							
isRef	0																																																															
minOcc	0																																																															
maxOcc	1																																																															
content	simple																																																															
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>D1</td><td></td></tr> <tr> <td>enumeration</td><td>D2</td><td></td></tr> <tr> <td>enumeration</td><td>D3</td><td></td></tr> <tr> <td>enumeration</td><td>D4</td><td></td></tr> <tr> <td>enumeration</td><td>D5</td><td></td></tr> <tr> <td>enumeration</td><td>D6</td><td></td></tr> <tr> <td>enumeration</td><td>D7</td><td></td></tr> <tr> <td>enumeration</td><td>D8</td><td></td></tr> <tr> <td>enumeration</td><td>D9</td><td></td></tr> <tr> <td>enumeration</td><td>D10</td><td></td></tr> <tr> <td>enumeration</td><td>D11</td><td></td></tr> <tr> <td>enumeration</td><td>D12</td><td></td></tr> <tr> <td>enumeration</td><td>D13</td><td></td></tr> <tr> <td>enumeration</td><td>D14</td><td></td></tr> <tr> <td>enumeration</td><td>D15</td><td></td></tr> <tr> <td>enumeration</td><td>D16</td><td></td></tr> <tr> <td>enumeration</td><td>D17</td><td></td></tr> <tr> <td>enumeration</td><td>D18</td><td></td></tr> <tr> <td>enumeration</td><td>D19</td><td></td></tr> <tr> <td>enumeration</td><td>D20</td><td></td></tr> </tbody> </table>	Kind	Value	annotation	enumeration	D1		enumeration	D2		enumeration	D3		enumeration	D4		enumeration	D5		enumeration	D6		enumeration	D7		enumeration	D8		enumeration	D9		enumeration	D10		enumeration	D11		enumeration	D12		enumeration	D13		enumeration	D14		enumeration	D15		enumeration	D16		enumeration	D17		enumeration	D18		enumeration	D19		enumeration	D20	
Kind	Value	annotation																																																														
enumeration	D1																																																															
enumeration	D2																																																															
enumeration	D3																																																															
enumeration	D4																																																															
enumeration	D5																																																															
enumeration	D6																																																															
enumeration	D7																																																															
enumeration	D8																																																															
enumeration	D9																																																															
enumeration	D10																																																															
enumeration	D11																																																															
enumeration	D12																																																															
enumeration	D13																																																															
enumeration	D14																																																															
enumeration	D15																																																															
enumeration	D16																																																															
enumeration	D17																																																															
enumeration	D18																																																															
enumeration	D19																																																															
enumeration	D20																																																															

### element DeliveryApptUpdateRequest/ReturnInfo

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>mailxml_defs:returnInfoType</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#">mailxml_defs:ConsigneeFacility</a> <a href="#">mailxml_defs:ErrorWarning</a> <a href="#">mailxml_defs:ContainerErrorWarningBlock</a>								

### element DeliveryApptUpdateResponse


diagram	<p>Response to the request to update a deliver appointment.</p>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
properties	content complex
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:DeliveryApptUpdateAccept</a> <a href="#">mailxml_tm:DeliveryApptUpdateReject</a>
annotation	documentation Response to the request to update a deliver appointment.

### element DeliveryApptUpdateResponse/TrackingID

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>mailxml_base:s20</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple
isRef	0								
minOcc	0								
maxOcc	1								
content	simple								
facets	Kind Value annotation								

	minLength 1 maxLength 20 whiteSpace preserve
--	--

element **DeliveryApptUpdateResponse/SubmitterTrackingID**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	isRef 0 minOcc 0 maxOcc 1 content simple												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

element **DeliveryApptUpdateResponse/DeliveryApptUpdateAccept**

diagram	<pre> classDiagram     class mailxml_tm {         deliveryApptUpdateAcceptType     }     class mailxml_tm {         DestinationEntry     }     class mailxml_tm {         RecurringAppt     }     class mailxml_tm {         OneTimeAppt     }     class mailxml_tm {         DetailInfo     }     class mailxml_tm {         TrailerInfo     }     class mailxml_tm {         ConsigneeFacility     }     class mailxml_tm {         Comment     }     class mailxml_tm {         ReturnInfo     }      mailxml_tm.deliveryApptUpdateAcceptType {         attributes             mailxml_defs:ShipperApptReqID             mailxml_defs:ConsigneeApptID             mailxml_defs:SchedulerID             mailxml_defs:SchedulerCorpID             mailxml_defs:SchedulerCRID             mailxml_defs:ShipperMultiStopID             mailxml_defs:ConsigneeMultiStopID             mailxml_defs:ShipperStopNum...             mailxml_defs:ApptType             mailxml_defs:PickupOrDelivery             mailxml_defs:PalletPositionCount             mailxml_defs:IncludesElectroni...     }     mailxml_tm.deliveryApptUpdateAcceptType {         children             mailxml_tm.DestinationEntry             mailxml_tm.DestinationEntry {                 mailxml_tm.RecurringAppt                 mailxml_tm.OneTimeAppt             }             mailxml_tm.DetailInfo             mailxml_tm.DetailInfo {                 mailxml_tm.TrailerInfo                 mailxml_tm.ConsigneeFacility                 mailxml_tm.Comment                 mailxml_tm.ReturnInfo             }     } </pre>				
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm				
type	<a href="#">mailxml_tm:deliveryApptUpdateAcceptType</a>				
properties	<table border="1"> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex
isRef	0				
content	complex				
children	<a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:RecurringAppt</a> <a href="#">mailxml_tm:OneTimeAppt</a> <a href="#">mailxml_tm:DetailInfo</a>				

	<u><a href="#">mailxml_tm:TrailerInfo</a></u> <u><a href="#">mailxml_tm:ConsigneeFacility</a></u> <u><a href="#">mailxml_tm:Comment</a></u> <u><a href="#">mailxml_tm:ReturnInfo</a></u>					
attributes	Name	Type	Use	Default	Fixed	annotation
	mailxml_defs:ShipperApptRequestID	<b>mailxml_base:s12</b>	required			
	mailxml_defs:ConsigneeApptID	<b>mailxml_base:s12</b>	required			
	mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>				
	mailxml_defs:SchedulerCorpID	<b>mailxml_base:s12</b>				
	mailxml_defs:SchedulerCRID	<b>mailxml_base:CRIDType</b>				
	mailxml_defs:ShipperMultiStopID	<b>mailxml_base:s12</b>				
	mailxml_defs:ConsigneeMultiStopID	<b>mailxml_base:s12</b>				
	mailxml_defs:ShipperStopNumber	<b>mailxml_base:n06</b>				
	mailxml_defs:ApptType	<b>mailxml_base:apptTypeType</b>	required			
	mailxml_defs:PickupOrDelivery	<b>mailxml_base:pickupOrDeliveryType</b>				
	mailxml_defs:PalletPositionCount	<b>mailxml_base:n02</b>				
	mailxml_defs:IncludesElectronicLoad	<b>mailxml_base:yesNo</b>				

### element **DeliveryApptUpdateResponse/DeliveryApptUpdateReject**

diagram	<pre> classDiagram     class mailxml_tm.deliveryApptUpdateRejectType {         &lt;&lt;attributes&gt;&gt;             mailxml_defs:ShipperApptRequestID             mailxml_defs:ConsigneeApptID             mailxml_defs:SchedulerID             mailxml_defs:SchedulerCorpID             mailxml_defs:SchedulerCRID             mailxml_defs:ShipperMultiStopID             mailxml_defs:ConsigneeMultiStopID             mailxml_defs:ShipperStopNumber             mailxml_defs:ApptType             mailxml_defs:PickupOrDelivery     }     mailxml_tm.DeliveryApptUpdate... &lt; -- mailxml_tm.ReturnInfo   </pre>
namespac	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>

e						
type	<a href="#">mailxml_tm:deliveryApptUpdateRejectType</a>					
properties	isRef 0 content complex					
children	<a href="#">mailxml_tm:ReturnInfo</a>					
attributes	Name	Type	Use	Default	Fixed	annotation
	mailxml_defs:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required			
	mailxml_defs:ConsigneeApptID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:SchedulerID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:SchedulerCorpID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>				
	mailxml_defs:ShipperMultiStopID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:ConsigneeMultiStopID	<a href="#">mailxml_base:s12</a>				
	mailxml_defs:ShipperStopNumber	<a href="#">mailxml_base:n06</a>				
	mailxml_defs:ApptType	<a href="#">mailxml_base:apptTypeType</a>	required			
	mailxml_defs:PickupOrDelivery	<a href="#">mailxml_base:pickupOrDeliveryType</a>				
	mailxml_defs:PalletPositionCount	<a href="#">mailxml_base:n02</a>				
	mailxml_defs:IncludesElectronicLoad	<a href="#">mailxml_base:yesNo</a>				

### element **DeliveryContentCancelRequest**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:deliveryContentCancelRequestType</a>
properties	content complex

children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ContentCancel</a>				
attributes	Name mailxml_tm:SchedulerID mailxml_tm:SchedulerCorpID mailxml_tm:SchedulerCRID	Type <b>mailxml_base:s12</b> <b>mailxml_base:s12</b> <b>mailxml_base:CRIDType</b>	Use	Default	Fixed annotation
annotation	documentation Request to cancel delivery content.				

### element **DeliveryContentCancelResponse**

diagram	<pre> classDiagram     class DeliveryContentCancelResponse {         * --&gt; mailxml_tm:TrackingID         mailxml_tm:TrackingID --&gt; mailxml_tm:SubmitterTrackingID         mailxml_tm:SubmitterTrackingID --&gt; mailxml_tm:DeliveryContentCancelAccept         mailxml_tm:SubmitterTrackingID --&gt; mailxml_tm:DeliveryContentCancelReject     }   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:deliveryContentCancelResponseType</a>
properties	content complex
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:DeliveryContentCancelAccept</a> <a href="#">mailxml_tm:DeliveryContentCancelReject</a>
annotation	documentation Response to the request to cancel delivery content.

## element DeliveryContentCreateRequest

diagram	<p>The diagram illustrates the structure of the <b>DeliveryContentCreateRequest</b> element. It features a main class box labeled <b>DeliveryContentCreateRequest</b> with a brief description: "Request from the Shipper to the Consignee to create content for delivery." A dashed line connects this class to a larger box representing its attributes. Inside this attributes box, there is a group named <b>grp mailxml_tm:DeliveryConte...</b> containing four attributes: <b>mailxml_tm:ConsigneeApptID</b>, <b>mailxml_tm:SchedulerID</b>, <b>mailxml_tm:SchedulerCorpID</b>, and <b>mailxml_tm:SchedulerCRID</b>. Below this group is another dashed line leading to a sequence of elements: <b>mailxml_tm:SubmittingParty</b>, <b>mailxml_tm:SubmittingSoftware</b>, <b>mailxml_tm:SubmitterTrackingID</b>, <b>mailxml_tm:ConsigneeFacility</b>, <b>mailxml_tm:DestinationEntry</b>, and <b>mailxml_tm:ContentDetailInfo</b>. A multiplicity of <b>1..∞</b> is shown at the end of this sequence.</p>																														
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																														
properties	content complex																														
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ContentDetailInfo</a>																														
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><b>mailxml_tm:ConsigneeApptID</b></td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><b>mailxml_tm:SchedulerID</b></td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><b>mailxml_tm:SchedulerCorpID</b></td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><b>mailxml_tm:SchedulerCRID</b></td> <td><b>mailxml_base:CRIDType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<b>mailxml_tm:ConsigneeApptID</b>	<b>mailxml_base:s12</b>					<b>mailxml_tm:SchedulerID</b>	<b>mailxml_base:s12</b>					<b>mailxml_tm:SchedulerCorpID</b>	<b>mailxml_base:s12</b>					<b>mailxml_tm:SchedulerCRID</b>	<b>mailxml_base:CRIDType</b>				
Name	Type	Use	Default	Fixed	annotation																										
<b>mailxml_tm:ConsigneeApptID</b>	<b>mailxml_base:s12</b>																														
<b>mailxml_tm:SchedulerID</b>	<b>mailxml_base:s12</b>																														
<b>mailxml_tm:SchedulerCorpID</b>	<b>mailxml_base:s12</b>																														
<b>mailxml_tm:SchedulerCRID</b>	<b>mailxml_base:CRIDType</b>																														
annotation	documentation Request from the Shipper to the Consignee to create content for delivery.																														

### element DeliveryContentCreateRequest/SubmittingParty

diagram	<pre> classDiagram     class mailxml_tmSubmittingParty     class mailxml_defsParticipantIDType {         &lt;&lt;attributes&gt;&gt;         mailxml_defsMailerID6         mailxml_defsMailerID9         mailxml_defsCRID         mailxml_defsSchedulerID         mailxml_defsMaildatUserLicense         mailxml_defsShippingAgentID         mailxml_defsReceivingAgentID     }     mailxml_tmSubmittingParty "1" -- "1" mailxml_defsParticipantIDType   </pre>																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:MailerID6</td><td><b>mailxml_base:mailerID6Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MailerID9</td><td><b>mailxml_base:mailerID9Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:CRID</td><td><b>mailxml_base:CRIDType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatUserLicense</td><td><b>mailxml_base:userLicenseCodeType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShippingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ReceivingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

### element DeliveryContentCreateRequest/SubmittingSoftware


diagram	<pre> classDiagram     class mailxml_tmSubmittingSoftware     class mailxml_defsSubmittingSoftwareType {         &lt;&lt;attributes&gt;&gt;         mailxml_defsSoftwareName         mailxml_defsVendor         mailxml_defsVersion         mailxml_defsApprovalDate         mailxml_defsApprovalKey     }     mailxml_tmSubmittingSoftware "1" -- "1" mailxml_defsSubmittingSoftwareType   </pre>
---------	--

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
type	<b>mailxml_defs:submittingSoftwareType</b>					
properties	isRef 0 content complex					
attributes	Name mailxml_defs:SoftwareName	Type <b>xs:string</b>	Use required	Default	Fixed	annotation
	mailxml_defs:Vendor	<b>xs:string</b>	required			
	mailxml_defs:Version	<b>xs:string</b>	required			
	mailxml_defs:ApprovalDate	<b>xs:date</b>				
	mailxml_defs:ApprovalKey	<b>xs:string</b>				

#### element **DeliveryContentCreateRequest/SubmitterTrackingID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s20</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

#### element **DeliveryContentCreateRequest/ConsigneeFacility**


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_defs:consigneeFacilityType</b>

properties	isRef 0 minOcc 0 maxOcc 1 content complex
children	<b>mailxml_defs:CompanyName</b> <b>mailxml_defs:FacilityNumber</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityName</b> <b>mailxml_defs:FacilityType</b> <b>mailxml_defs:URL</b> <b>mailxml_defs:CommonContact</b>

#### element **DeliveryContentCreateRequest/DestinationEntry**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

#### element **DeliveryContentCreateRequest/ContentDetailInfo**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>

type	<a href="#">mailxml_tm:contentDetailInfoType</a>					
properties	isRef 0 minOcc 1 maxOcc unbounded content complex					
children	<a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:ScheduledInductionDate</a> <a href="#">mailxml_tm:NumberOfDaysStale</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:ContentUSPSSummary</a>					
attributes	Name <a href="#">mailxml_tm:LogisticsSchedulerID</a> <a href="#">mailxml_tm:LogisticsCorpID</a> <a href="#">mailxml_tm:LogisticsSchedulerCRID</a>	Type <a href="#">mailxml_base:s12</a> <a href="#">mailxml_base:s12</a> <a href="#">mailxml_base:CRIDType</a>	Use	Default	Fixed	annotation


#### element DeliveryContentCreateResponse

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
properties	content complex
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:DeliveryContentAccept</a> <a href="#">mailxml_tm:DeliveryContentReject</a>
annotation	documentation Response to the request to create content for delivery.


#### element DeliveryContentCreateResponse/TrackingID

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_base:s20</a>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

element **DeliveryContentCreateResponse/SubmitterTrackingID**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>20</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

element **DeliveryContentCreateResponse/DeliveryContentAccept**

diagram																															
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																														
type	<b>mailxml_tm:deliveryContentAcceptType</b>																														
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																										
isRef	0																														
content	complex																														
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ContentDetailInfo</a> <a href="#">mailxml_tm:ReturnInfo</a>																														
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:ConsigneeApptID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td></tr> <tr> <td>mailxml_tm:SchedulerID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td></tr> <tr> <td>mailxml_tm:SchedularCorpID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td></tr> <tr> <td>mailxml_tm:SchedularCRID</td> <td><b>mailxml_base:CRIDType</b></td> <td></td> <td></td> <td></td> <td></td></tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>					mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>					mailxml_tm:SchedularCorpID	<b>mailxml_base:s12</b>					mailxml_tm:SchedularCRID	<b>mailxml_base:CRIDType</b>				
Name	Type	Use	Default	Fixed	annotation																										
mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>																														
mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>																														
mailxml_tm:SchedularCorpID	<b>mailxml_base:s12</b>																														
mailxml_tm:SchedularCRID	<b>mailxml_base:CRIDType</b>																														

element **DeliveryContentCreateResponse/DeliveryContentReject**

diagram	<pre> classDiagram     class mailxml_tm:deliveryContentRejectType {         mailxml_tm:ConsigneeApptID         mailxml_tm:SchedulerID         mailxml_tm:SchedulerCorpID         mailxml_tm:SchedulerCRID         mailxml_tm:DestinationEntry         mailxml_tm:ReturnInfo     }     mailxml_tm:DeliveryContentRej... &lt; -- mailxml_tm:deliveryContentRejectType     mailxml_tm:DeliveryContentRej... --&gt; mailxml_tm:DestinationEntry     mailxml_tm:DeliveryContentRej... --&gt; mailxml_tm:ReturnInfo   </pre>																														
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																														
type	<a href="#">mailxml_tm:deliveryContentRejectType</a>																														
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																										
isRef	0																														
content	complex																														
children	<a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ReturnInfo</a>																														
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_tm:ConsigneeApptID</td><td><a href="#">mailxml_base:s12</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:SchedulerID</td><td><a href="#">mailxml_base:s12</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:SchedulerCorpID</td><td><a href="#">mailxml_base:s12</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:SchedulerCRID</td><td><a href="#">mailxml_base:CRIDType</a></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>				
Name	Type	Use	Default	Fixed	annotation																										
mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>																														
mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>																														
mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>																														
mailxml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>																														

## element DeliveryContentQueryRequest

diagram	<p><b>DeliveryContentQueryRequest</b></p> <p>Query request for delivery content.</p>																																																						
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																																						
properties	content complex																																																						
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:DestinationEntry</a>																																																						
attributes	<table> <tbody> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_tm:ConsigneeApptID</td><td><a href="#">mailxml_base:s12</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:SchedulerID</td><td><a href="#">mailxml_base:s12</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:SchedulerCorpID</td><td><a href="#">mailxml_base:s12</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:SchedulerCRID</td><td><a href="#">mailxml_base:CRIDType</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:SchedulerContentID</td><td><a href="#">mailxml_base:s12</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:ConsigneeContentID</td><td><a href="#">mailxml_base:s12</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:RetrieveContentUpdatedStartDate</td><td><a href="#">xs:date</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:RetrieveContentUpdatedEndDate</td><td><a href="#">xs:date</a></td><td></td><td></td><td></td><td></td></tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>					mailxml_tm:SchedulerContentID	<a href="#">mailxml_base:s12</a>					mailxml_tm:ConsigneeContentID	<a href="#">mailxml_base:s12</a>					mailxml_tm:RetrieveContentUpdatedStartDate	<a href="#">xs:date</a>					mailxml_tm:RetrieveContentUpdatedEndDate	<a href="#">xs:date</a>				
Name	Type	Use	Default	Fixed	annotation																																																		
mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>																																																						
mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>																																																						
mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>																																																						
mailxml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>																																																						
mailxml_tm:SchedulerContentID	<a href="#">mailxml_base:s12</a>																																																						
mailxml_tm:ConsigneeContentID	<a href="#">mailxml_base:s12</a>																																																						
mailxml_tm:RetrieveContentUpdatedStartDate	<a href="#">xs:date</a>																																																						
mailxml_tm:RetrieveContentUpdatedEndDate	<a href="#">xs:date</a>																																																						
annotation	documentation Query request for delivery content.																																																						

### element DeliveryContentQueryRequest/SubmittingParty

diagram	<pre> classDiagram     class mailxml_tmSubmittingParty     class mailxml_defsParticipantIDType {         &lt;&lt;attributes&gt;&gt;         mailxml_defsMailerID6         mailxml_defsMailerID9         mailxml_defsCRID         mailxml_defsSchedulerID         mailxml_defsMaildatUserLicense         mailxml_defsShippingAgentID         mailxml_defsReceivingAgentID     }     mailxml_tmSubmittingParty "1" -- "1" mailxml_defsParticipantIDType   </pre>																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:MailerID6</td><td><b>mailxml_base:mailerID6Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MailerID9</td><td><b>mailxml_base:mailerID9Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:CRID</td><td><b>mailxml_base:CRIDType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatUserLicense</td><td><b>mailxml_base:userLicenseCodeType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShippingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ReceivingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

### element DeliveryContentQueryRequest/SubmittingSoftware


diagram	<pre> classDiagram     class mailxml_tmSubmittingSoftware     class mailxml_defsSubmittingSoftwareType {         &lt;&lt;attributes&gt;&gt;         mailxml_defsSoftwareName         mailxml_defsVendor         mailxml_defsVersion         mailxml_defsApprovalDate         mailxml_defsApprovalKey     }     mailxml_tmSubmittingSoftware "1" -- "1" mailxml_defsSubmittingSoftwareType   </pre>
---------	--

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
type	<b>mailxml_defs:submittingSoftwareType</b>					
properties	isRef 0 content complex					
attributes	Name mailxml_defs:SoftwareName	Type <b>xs:string</b>	Use required	Default	Fixed	annotation
	mailxml_defs:Vendor	<b>xs:string</b>	required			
	mailxml_defs:Version	<b>xs:string</b>	required			
	mailxml_defs:ApprovalDate	<b>xs:date</b>				
	mailxml_defs:ApprovalKey	<b>xs:string</b>				

### element **DeliveryContentQueryRequest/SubmitterTrackingID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s20</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

### element **DeliveryContentQueryRequest/ConsigneeFacility**


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_defs:consigneeFacilityType</b>

properties	isRef 0 minOcc 0 maxOcc 1 content complex
children	<b>mailxml_defs:CompanyName</b> <b>mailxml_defs:FacilityNumber</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityName</b> <b>mailxml_defs:FacilityType</b> <b>mailxml_defs:URL</b> <b>mailxml_defs:CommonContact</b>

### element **DeliveryContentQueryRequest/DestinationEntry**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

### element **DeliveryContentQueryResponse**


diagram	 <p><b>DeliveryContentQueryResponse</b> Response to the Query request for delivery content.</p>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>

properties	content complex					
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:QueryResults</a> <a href="#">mailxml_tm:QueryError</a>					
attributes	Name mailxml_tm:ConsigneeApptID mailxml_tm:SchedulerID mailxml_tm:SchedulerCorpID mailxml_tm:SchedulerCRID mailxml_tm:SchedulerContentID mailxml_tm:ConsigneeContentID mailxml_tm:RetrieveContentUpdatedStartDate mailxml_tm:RetrieveContentUpdatedEndDate	Type <b>mailxml_base:s12</b> <b>mailxml_base:s12</b> <b>mailxml_base:s12</b> <b>mailxml_base:CRIDType</b> <b>mailxml_base:s12</b> <b>mailxml_base:s12</b> <b>xs:date</b> <b>xs:date</b>	Use	Default	Fixed	annotation
annotation	documentation Response to the Query request for delivery content.					

#### element **DeliveryContentQueryResponse/TrackingID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s20</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

#### element **DeliveryContentQueryResponse/SubmitterTrackingID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s20</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve


### element DeliveryContentQueryResponse/QueryResults

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ContentDetailInfoUpdate</a> <a href="#">mailxml_tm:ReturnInfo</a>


### element DeliveryContentQueryResponse/QueryResults/ConsigneeFacility

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_defs:consigneeFacilityType</b>
properties	isRef 0 minOcc 0 maxOcc 1 content complex
children	<a href="#">mailxml_defs:CompanyName</a> <a href="#">mailxml_defs:FacilityNumber</a> <a href="#">mailxml_defs:FacilityAddress</a> <a href="#">mailxml_defs:FacilityAddress</a> <a href="#">mailxml_defs:FacilityName</a> <a href="#">mailxml_defs:FacilityType</a> <a href="#">mailxml_defs:URL</a> <a href="#">mailxml_defs:CommonContact</a>


element **DeliveryContentQueryResponse/QueryResults/DestinationEntry**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No


element **DeliveryContentQueryResponse/QueryResults/ContentDetailInfoUpdate**

diagram																									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																								
type	<b>mailxml_tm:contentDetailInfoUpdateType</b>																								
properties	isRef 0 minOcc 0 maxOcc unbounded content complex																								
children	<a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:ScheduledInductionDate</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:ContentUSPSSummary</a>																								
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><a href="#">mailxml_tm:LogisticsSchedulerID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:LogisticsCorpID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:LogisticsSchedulerCRID</a></td> <td><a href="#">mailxml_base:CRIDType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:LogisticsSchedulerID</a>	<a href="#">mailxml_base:s12</a>					<a href="#">mailxml_tm:LogisticsCorpID</a>	<a href="#">mailxml_base:s12</a>					<a href="#">mailxml_tm:LogisticsSchedulerCRID</a>	<a href="#">mailxml_base:CRIDType</a>				
Name	Type	Use	Default	Fixed	annotation																				
<a href="#">mailxml_tm:LogisticsSchedulerID</a>	<a href="#">mailxml_base:s12</a>																								
<a href="#">mailxml_tm:LogisticsCorpID</a>	<a href="#">mailxml_base:s12</a>																								
<a href="#">mailxml_tm:LogisticsSchedulerCRID</a>	<a href="#">mailxml_base:CRIDType</a>																								

element **DeliveryContentQueryResponse/QueryResults/ReturnInfo**

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>mailxml_defs:returnInfoType</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<b>mailxml_defs:ConsigneeFacility</b> <b>mailxml_defs:ErrorWarning</b> <b>mailxml_defs:ContainerErrorWarningBlock</b>								

element **DeliveryContentQueryResponse/QueryError**

diagram					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm				
type	<b>mailxml_defs:queryErrorType</b>				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex
isRef	0				
content	complex				
children	<b>mailxml_defs:ReturnInfo</b>				

## element DeliveryContentUpdateRequest

diagram	<p><b>DeliveryContentUpdateRequest</b></p> <p>Request from the Shipper to the Consignee to update the content for delivery.</p>																																				
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																				
properties	content complex																																				
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ContentDetailInfoUpdate</a>																																				
attributes	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:ConsigneeApptID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCorpID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCRID</td> <td><b>mailxml_base:CRIDType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:FullContentReplacement</td> <td><b>mailxml_base:yesNo</b></td> <td></td> <td>No</td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>					mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>					mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>					mailxml_tm:SchedulerCRID	<b>mailxml_base:CRIDType</b>					mailxml_tm:FullContentReplacement	<b>mailxml_base:yesNo</b>		No		
Name	Type	Use	Default	Fixed	annotation																																
mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>																																				
mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>																																				
mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>																																				
mailxml_tm:SchedulerCRID	<b>mailxml_base:CRIDType</b>																																				
mailxml_tm:FullContentReplacement	<b>mailxml_base:yesNo</b>		No																																		
annotation	documentation Request from the Shipper to the Consignee to update the content for delivery.																																				

### element DeliveryContentUpdateRequest/SubmittingParty

diagram	<pre> classDiagram     class mailxml_tmSubmittingParty     class mailxml_defsParticipantIDType {         -mailxml_defsMailerID6         -mailxml_defsMailerID9         -mailxml_defsCRID         -mailxml_defsSchedulerID         -mailxml_defsMaildatUserLicense         -mailxml_defsShippingAgentID         -mailxml_defsReceivingAgentID     }     mailxml_tmSubmittingParty "1" -- "1" mailxml_defsParticipantIDType   </pre>																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:MailerID6</td><td><b>mailxml_base:mailerID6Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MailerID9</td><td><b>mailxml_base:mailerID9Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:CRID</td><td><b>mailxml_base:CRIDType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatUserLicense</td><td><b>mailxml_base:userLicenseCodeType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShippingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ReceivingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

### element DeliveryContentUpdateRequest/SubmittingSoftware


diagram	<pre> classDiagram     class mailxml_tmSubmittingSoftware     class mailxml_defsSubmittingSoftwareType {         -mailxml_defsSoftwareName         -mailxml_defsVendor         -mailxml_defsVersion         -mailxml_defsApprovalDate         -mailxml_defsApprovalKey     }     mailxml_tmSubmittingSoftware "1" -- "1" mailxml_defsSubmittingSoftwareType   </pre>
---------	--

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
type	<b>mailxml_defs:submittingSoftwareType</b>					
properties	isRef 0 content complex					
attributes	Name mailxml_defs:SoftwareName	Type <b>xs:string</b>	Use required	Default	Fixed	annotation
	mailxml_defs:Vendor	<b>xs:string</b>	required			
	mailxml_defs:Version	<b>xs:string</b>	required			
	mailxml_defs:ApprovalDate	<b>xs:date</b>				
	mailxml_defs:ApprovalKey	<b>xs:string</b>				

#### element **DeliveryContentUpdateRequest/SubmitterTrackingID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s20</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

#### element **DeliveryContentUpdateRequest/ConsigneeFacility**


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_defs:consigneeFacilityType</b>

properties	isRef 0 minOcc 0 maxOcc 1 content complex
children	<b>mailxml_defs:CompanyName</b> <b>mailxml_defs:FacilityNumber</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityName</b> <b>mailxml_defs:FacilityType</b> <b>mailxml_defs:URL</b> <b>mailxml_defs:CommonContact</b>

### element **DeliveryContentUpdateRequest/DestinationEntry**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

### element **DeliveryContentUpdateRequest/ContentDetailInfoUpdate**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_tm:ContentDetailInfoUpdateType</b>
properties	isRef 0 minOcc 1 maxOcc unbounded content complex
children	<b>mailxml_tm:ShipperContainerGroupingID</b> <b>mailxml_tm:ConsigneeContainerGroupingID</b>

	<a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:ScheduledInductionDate</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:ContentUSPSSummary</a>					
attributes	Name <a href="#">mailxml_tm:LogisticsSchedulerID</a> <a href="#">mailxml_tm:LogisticsCorpID</a> <a href="#">mailxml_tm:LogisticsSchedulerCRID</a>	Type <a href="#">mailxml_base:s12</a> <a href="#">mailxml_base:s12</a> <a href="#">mailxml_base:CRIDType</a>	Use	Default	Fixed	annotation


### element **DeliveryContentUpdateResponse**

diagram	<p>Response to the request from the Shipper to the Consignee to update the content for delivery.</p>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
properties	content complex
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:DeliveryContentUpdateAccept</a> <a href="#">mailxml_tm:DeliveryContentUpdateReject</a>
annotation	documentation Response to the request from the Shipper to the Consignee to update the content for delivery.

### element **DeliveryContentUpdateResponse/TrackingID**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_base:s20</a>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

### element **DeliveryContentUpdateResponse/SubmitterTrackingID**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_base:s20</a>
properties	isRef 0 minOcc 0 maxOcc 1

	content	simple
facets	Kind	Value
	minLength	1
	maxLength	20
	whiteSpace	preserve

### element DeliveryContentUpdateResponse/DeliveryContentUpdateAccept

diagram																																					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																				
type	<a href="#">mailxml_tm:deliveryContentUpdateAcceptType</a>																																				
properties	isRef 0 content complex																																				
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ContentDetailInfoUpdate</a> <a href="#">mailxml_tm:ReturnInfo</a>																																				
attributes	<table> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> <tr> <td>mailxml_tm:ConsigneeApptID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCorpID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCRID</td> <td><a href="#">mailxml_base:CRIDType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:FullContentReplacement</td> <td><a href="#">mailxml_base:yesNo</a></td> <td></td> <td>No</td> <td></td> <td></td> </tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>					mailxml_tm:FullContentReplacement	<a href="#">mailxml_base:yesNo</a>		No		
Name	Type	Use	Default	Fixed	annotation																																
mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>																																				
mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>																																				
mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>																																				
mailxml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>																																				
mailxml_tm:FullContentReplacement	<a href="#">mailxml_base:yesNo</a>		No																																		

element **DeliveryContentUpdateResponse/DeliveryContentUpdateReject**

diagram	<pre> classDiagram     class mailxml_tm:deliveryContentUpdateRejectType {         mailxml_tm:ConsigneeApptID         mailxml_tm:SchedulerID         mailxml_tm:SchedulerCorpID         mailxml_tm:SchedulerCRID         mailxml_tm:FullContentReplace...         mailxml_tm:DestinationEntry         mailxml_tm:ReturnInfo     }     mailxml_tm:DeliveryContentUp... --&gt; mailxml_tm:deliveryContentUpdateRejectType   </pre>																																				
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																				
type	<a href="#">mailxml_tm:deliveryContentUpdateRejectType</a>																																				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																
isRef	0																																				
content	complex																																				
children	<a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ReturnInfo</a>																																				
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:ConsigneeApptID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCorpID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCRID</td> <td><b>mailxml_base:CRIDType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:FullContentReplacement</td> <td><b>mailxml_base:yesNo</b></td> <td>No</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>					mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>					mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>					mailxml_tm:SchedulerCRID	<b>mailxml_base:CRIDType</b>					mailxml_tm:FullContentReplacement	<b>mailxml_base:yesNo</b>	No			
Name	Type	Use	Default	Fixed	annotation																																
mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>																																				
mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>																																				
mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>																																				
mailxml_tm:SchedulerCRID	<b>mailxml_base:CRIDType</b>																																				
mailxml_tm:FullContentReplacement	<b>mailxml_base:yesNo</b>	No																																			

## element DeliveryReApptRequest

diagram	<p>The diagram illustrates the structure of the <code>DeliveryReApptRequest</code> element. It features a main class box labeled <code>DeliveryReApptRequest</code> with a note below it: "Request is sent from the Shipper to the Consignee if an appointment is cancelled and the Shipper wants to rebook the delivery using the same Consignee Appointment ID". A large bracket on the right side groups several attributes and child elements. The grouped items include:</p> <ul style="list-style-type: none"> <li><code>grp mailxml_defs:ResponseM...</code></li> <li><code>mailxml_defs:ShipperApptRequ...</code></li> <li><code>mailxml_defs:ConsigneeApptID</code></li> <li><code>mailxml_defs:SchedulerID</code></li> <li><code>mailxml_defs:SchedulerCorpID</code></li> <li><code>mailxml_defs:SchedulerCRID</code></li> <li><code>mailxml_defs:ShipperMultiStopID</code></li> <li><code>mailxml_defs:ConsigneeMultiSt...</code></li> <li><code>mailxml_defs:ShipperStopNumb...</code></li> <li><code>mailxml_defs:ApptType</code></li> <li><code>mailxml_defs:PickupOrDelivery</code></li> <li><code>mailxml_defs:PalletPositionCount</code></li> <li><code>mailxml_defs:IncludesElectroni...</code></li> </ul> <p>Below this group is a multiplicity node (a small circle with three dots) connected to a sequence of child elements:</p> <ul style="list-style-type: none"> <li><code>mailxml_tm:SubmittingParty</code></li> <li><code>mailxml_tm:SubmittingSoftware</code></li> <li><code>mailxml_tm:SubmitterTrackingID</code></li> <li><code>mailxml_tm:ApptBlock</code></li> <li><code>mailxml_tm:DetailInfo</code> (with a multiplicity of <code>1..∞</code>)</li> <li><code>mailxml_tm:TrailerInfo</code></li> <li><code>mailxml_tm:ValueAddedService</code></li> </ul>												
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>												
properties	content complex												
children	<code>mailxml_tm:SubmittingParty</code> <code>mailxml_tm:SubmittingSoftware</code> <code>mailxml_tm:SubmitterTrackingID</code> <code>mailxml_tm:ApptBlock</code> <code>mailxml_tm:DetailInfo</code> <code>mailxml_tm:TrailerInfo</code> <code>mailxml_tm:ValueAddedService</code>												
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td><code>mailxml_defs:ShipperApptRequestID</code></td> <td><code>mailxml_base:s12</code></td> <td>required</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	Annotation	<code>mailxml_defs:ShipperApptRequestID</code>	<code>mailxml_base:s12</code>	required			
Name	Type	Use	Default	Fixed	Annotation								
<code>mailxml_defs:ShipperApptRequestID</code>	<code>mailxml_base:s12</code>	required											

	mailxml_defs:ConsigneeApptID mailxml_defs:SchedulerID mailxml_defs:SchedulerCorpID mailxml_defs:SchedulerCRID mailxml_defs:ShipperMultiStopID mailxml_defs:ConsigneeMultiStopID mailxml_defs:ShipperStopNumber mailxml_defs:ApptType mailxml_defs:PickupOrDelivery mailxml_defs:PalletPositionCount mailxml_defs:IncludesElectronicLoad	<b>mailxml_base:s12</b> <b>mailxml_base:s12</b> <b>mailxml_base:s12</b> <b>mailxml_base:CRIDType</b> <b>mailxml_base:s12</b> <b>mailxml_base:s12</b> <b>mailxml_base:n06</b> <b>mailxml_base:apptTypeType</b> <b>mailxml_base:pickupOrDeliveryType</b> <b>mailxml_base:n02</b> <b>mailxml_base:yesNo</b>	required
annotation	documentation Request is sent from the Shipper to the Consignee if an appointment is cancelled and the Shipper wants to rebook the delivery using the same Consignee Appointment ID		

### element **DeliveryReApptRequest/SubmittingParty**

diagram	<pre> classDiagram     class SubmittingParty {         &lt;&lt;mailxml_tm&gt;&gt;     }     class participantIDType {         &lt;&lt;mailxml_defs&gt;&gt;         &lt;&lt;attributes&gt;&gt;             MailerID6             MailerID9             CRID             SchedulerID             MaildatUserLicense             ShippingAgentID             ReceivingAgentID         end     }     SubmittingParty "1" -- "0..1" participantIDType   </pre>																																																
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	isRef 0 content complex																																																
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:MailerID6</td> <td><b>mailxml_base:mailerID6Type</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MailerID9</td> <td><b>mailxml_base:mailerID9Type</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:CRID</td> <td><b>mailxml_base:CRIDType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MaildatUserLicense</td> <td><b>mailxml_base:userLicenseCodeType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ShippingAgentID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ReceivingAgentID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

element **DeliveryReApptRequest/SubmittingSoftware**

diagram	<pre> classDiagram     mailxml_tm::SubmittingSoftware &lt; -- mailxml_defs::submittingSoftwareType     mailxml_defs::submittingSoftwareType {         SoftwareName         Vendor         Version         ApprovalDate         ApprovalKey     }   </pre>																																				
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																				
type	<b>mailxml_defs:submittingSoftwareType</b>																																				
properties	<table> <tr> <td>isRef</td><td>0</td> </tr> <tr> <td>content</td><td>complex</td> </tr> </table>	isRef	0	content	complex																																
isRef	0																																				
content	complex																																				
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:SoftwareName</td><td><b>xs:string</b></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:Vendor</td><td><b>xs:string</b></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:Version</td><td><b>xs:string</b></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ApprovalDate</td><td><b>xs:date</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ApprovalKey</td><td><b>xs:string</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SoftwareName	<b>xs:string</b>	required				mailxml_defs:Vendor	<b>xs:string</b>	required				mailxml_defs:Version	<b>xs:string</b>	required				mailxml_defs:ApprovalDate	<b>xs:date</b>					mailxml_defs:ApprovalKey	<b>xs:string</b>				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_defs:SoftwareName	<b>xs:string</b>	required																																			
mailxml_defs:Vendor	<b>xs:string</b>	required																																			
mailxml_defs:Version	<b>xs:string</b>	required																																			
mailxml_defs:ApprovalDate	<b>xs:date</b>																																				
mailxml_defs:ApprovalKey	<b>xs:string</b>																																				

element **DeliveryReApptRequest/SubmitterTrackingID**

diagram	<pre> classDiagram     mailxml_tm::SubmitterTrackingID   </pre>												
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td><td>0</td> </tr> <tr> <td>minOcc</td><td>0</td> </tr> <tr> <td>maxOcc</td><td>1</td> </tr> <tr> <td>content</td><td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>20</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												


element **DeliveryReApptRequest/ApptBlock**

diagram	<pre> classDiagram     class mailxml_tm::apptBlockRequestType {         mailxml_tm::ConsigneeFacility         mailxml_tm::PreferredAppt         mailxml_tm::OptionalAppt         mailxml_tm::Comment     }     class mailxml_tm::ApptBlock     mailxml_tm::ApptBlock "1" --&gt; "1..∞" mailxml_tm::apptBlockRequestType   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:apptBlockRequestType</a>
properties	isRef 0 minOcc 0 maxOcc unbounded content complex
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:PreferredAppt</a> <a href="#">mailxml_tm:OptionalAppt</a> <a href="#">mailxml_tm:Comment</a>


element **DeliveryReApptRequest/DetailInfo**

diagram	<pre> classDiagram     class mailxml_tm::detailInfoType {         mailxml_tm::ShipperContainerGr...         mailxml_tm::ConsigneeContain...         mailxml_tm::StartTheClockDate         mailxml_tm::ShipperGroupingID...         mailxml_tm::MaildatSummary         mailxml_tm::USPSSummary         mailxml_tm::ConsigneeContentID     }     class mailxml_tm::DetailInfo     mailxml_tm::DetailInfo "1..∞" --&gt; "1..∞" mailxml_tm::detailInfoType     mailxml_tm::detailInfoType "1..∞" --&gt; "1..∞" mailxml_tm::MaildatSummary     mailxml_tm::detailInfoType "1..∞" --&gt; "1..∞" mailxml_tm::USPSSummary     mailxml_tm::detailInfoType "1..∞" --&gt; "1..∞" mailxml_tm::ConsigneeContentID   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:detailInfoType</a>
properties	isRef 0 minOcc 1 maxOcc unbounded content complex
children	<a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:USPSSummary</a> <a href="#">mailxml_tm:ConsigneeContentID</a>

### element DeliveryReApptRequest/TrailerInfo

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_tm:trailerInfoType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#">mailxml_tm:Trailer</a> <a href="#">mailxml_tm:Carrier</a> <a href="#">mailxml_tm:BillOfLadingNumber</a>								

### element DeliveryReApptRequest/ValueAddedService

diagram																																																							
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																						
type	<a href="#">mailxml_tm:valueAddedServiceType</a>																																																						
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple																																														
isRef	0																																																						
minOcc	0																																																						
maxOcc	1																																																						
content	simple																																																						
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>enumeration</td><td>D1</td><td></td></tr> <tr> <td>enumeration</td><td>D2</td><td></td></tr> <tr> <td>enumeration</td><td>D3</td><td></td></tr> <tr> <td>enumeration</td><td>D4</td><td></td></tr> <tr> <td>enumeration</td><td>D5</td><td></td></tr> <tr> <td>enumeration</td><td>D6</td><td></td></tr> <tr> <td>enumeration</td><td>D7</td><td></td></tr> <tr> <td>enumeration</td><td>D8</td><td></td></tr> <tr> <td>enumeration</td><td>D9</td><td></td></tr> <tr> <td>enumeration</td><td>D10</td><td></td></tr> <tr> <td>enumeration</td><td>D11</td><td></td></tr> <tr> <td>enumeration</td><td>D12</td><td></td></tr> <tr> <td>enumeration</td><td>D13</td><td></td></tr> <tr> <td>enumeration</td><td>D14</td><td></td></tr> <tr> <td>enumeration</td><td>D15</td><td></td></tr> <tr> <td>enumeration</td><td>D16</td><td></td></tr> <tr> <td>enumeration</td><td>D17</td><td></td></tr> </table>	Kind	Value	annotation	enumeration	D1		enumeration	D2		enumeration	D3		enumeration	D4		enumeration	D5		enumeration	D6		enumeration	D7		enumeration	D8		enumeration	D9		enumeration	D10		enumeration	D11		enumeration	D12		enumeration	D13		enumeration	D14		enumeration	D15		enumeration	D16		enumeration	D17	
Kind	Value	annotation																																																					
enumeration	D1																																																						
enumeration	D2																																																						
enumeration	D3																																																						
enumeration	D4																																																						
enumeration	D5																																																						
enumeration	D6																																																						
enumeration	D7																																																						
enumeration	D8																																																						
enumeration	D9																																																						
enumeration	D10																																																						
enumeration	D11																																																						
enumeration	D12																																																						
enumeration	D13																																																						
enumeration	D14																																																						
enumeration	D15																																																						
enumeration	D16																																																						
enumeration	D17																																																						

	enumeration D18
	enumeration D19
	enumeration D20

### element DispatchContainerInfoNotification

diagram	<pre> graph TD     DCIN[DispatchContainerInfoNotification] --&gt; ATTR(attributes)     ATTR --&gt; CG[mailxml_tm:CustomerGroupID]     ATTR --&gt; MG[mailxml_tm:MailingGroupID]     DCIN --&gt; SP[SubmittingParty]     SP --&gt; SS[SubmittingSoftware]     SP --&gt; ST[SubmitterTrackingID]     SP --&gt; TS[TransportationSummaryBlock]     SP --&gt; TG[TransportationGeoDataBlock]     SP --&gt; TC[TransportationContainerStatusBlock]   </pre>																		
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																		
properties	content complex																		
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:TransportationSummaryBlock</a> <a href="#">mailxml_tm:TransportationGeoDataBlock</a> <a href="#">mailxml_tm:TransportationContainerStatusBlock</a>																		
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:CustomerGroupID</td> <td><a href="#">mailxml_base:s25</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:MailingGroupID</td> <td><a href="#">xs:nonNegativeInteger</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:CustomerGroupID	<a href="#">mailxml_base:s25</a>	required				mailxml_tm:MailingGroupID	<a href="#">xs:nonNegativeInteger</a>	required			
Name	Type	Use	Default	Fixed	annotation														
mailxml_tm:CustomerGroupID	<a href="#">mailxml_base:s25</a>	required																	
mailxml_tm:MailingGroupID	<a href="#">xs:nonNegativeInteger</a>	required																	
annotation	documentation Transportation messaging																		

### element DispatchContainerInfoNotification/SubmittingParty

diagram	<pre> classDiagram     class mailxml_tmSubmittingParty     class mailxml_defsparticipantIDType {         &lt;&lt;attributes&gt;&gt;         mailxml_defsMailerID6         mailxml_defsMailerID9         mailxml_defsCRID         mailxml_defsSchedulerID         mailxml_defsMaildatUserLicense         mailxml_defsShippingAgentID         mailxml_defsReceivingAgentID     }     mailxml_tmSubmittingParty "1" -- "1" mailxml_defsparticipantIDType   </pre>																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:MailerID6</td><td><b>mailxml_base:mailerID6Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MailerID9</td><td><b>mailxml_base:mailerID9Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:CRID</td><td><b>mailxml_base:CRIDType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatUserLicense</td><td><b>mailxml_base:userLicenseCodeType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShippingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ReceivingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

### element DispatchContainerInfoNotification/SubmittingSoftware


diagram	<pre> classDiagram     class mailxml_tmSubmittingSoftware     class mailxml_defssubmittingSoftwareType {         &lt;&lt;attributes&gt;&gt;         mailxml_defsSoftwareName         mailxml_defsVendor         mailxml_defsVersion         mailxml_defsApprovalDate         mailxml_defsApprovalKey     }     mailxml_tmSubmittingSoftware "1" -- "1" mailxml_defssubmittingSoftwareType   </pre>
---------	--

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
type	<b>mailxml_defs:submittingSoftwareType</b>					
properties	isRef 0 content complex					
attributes	Name mailxml_defs:SoftwareName mailxml_defs:Vendor mailxml_defs:Version mailxml_defs:ApprovalDate mailxml_defs:ApprovalKey	Type <b>xs:string</b> <b>xs:string</b> <b>xs:string</b> <b>xs:date</b> <b>xs:string</b>	Use required required required	Default	Fixed	annotation

#### element **DispatchContainerInfoNotification/SubmitterTrackingID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s20</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

#### element **DispatchContainerInfoNotification/TransportationSummaryBlock**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_tm:transportationSummaryBlockType</b>
properties	isRef 0 minOcc 0 maxOcc 1 content complex
children	<a href="#">mailxml_tm:TransportationID</a> <a href="#">mailxml_tm:LoadTruckDispatchNumber</a> <a href="#">mailxml_tm:TargetShipDateTime</a> <a href="#">mailxml_tm:Stops</a>

element DispatchContainerInfoNotification/TransportationGeoDataBlock

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_tm:transportationGeoDataBlockType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#">mailxml_tm:TransportationID</a> <a href="#">mailxml_tm:LocationDateTime</a> <a href="#">mailxml_tm:Latitude</a> <a href="#">mailxml_tm:Longitude</a> <a href="#">mailxml_tm:City</a> <a href="#">mailxml_tm:State</a> <a href="#">mailxml_tm:ZIP</a> <a href="#">mailxml_tm:LocationStatus</a> <a href="#">mailxml_tm:Containers</a>								

## element DispatchContainerInfoNotification/TransportationContainerStatusBlock


diagram	<pre> classDiagram     class mailxml_tm::transportationContainerStatusBlockType {         mailxml_tm::ContentsBarcode         mailxml_tm::ScanDateTime         mailxml_tm::Latitude         mailxml_tm::Longitude         mailxml_tm::LocationDescription         mailxml_tm::City         mailxml_tm::State         mailxml_tm::ZIP         mailxml_tm::ScanEvent         mailxml_tm::UserOptionField         mailxml_tm::AppointmentNumber         mailxml_tm::AppointmentNumberIdentifier     }     class mailxml_tm::TransportationCon...     mailxml_tm::TransportationCon... --&gt; mailxml_tm::transportationContainerStatusBlockType   </pre>								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_tm:transportationContainerStatusBlockType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#">mailxml_tm:ContentsBarcode</a> <a href="#">mailxml_tm:ScanDateTime</a> <a href="#">mailxml_tm:Latitude</a> <a href="#">mailxml_tm:Longitude</a> <a href="#">mailxml_tm:LocationDescription</a> <a href="#">mailxml_tm:City</a> <a href="#">mailxml_tm:State</a> <a href="#">mailxml_tm:ZIP</a> <a href="#">mailxml_tm:ScanEvent</a> <a href="#">mailxml_tm:UserOptionField</a> <a href="#">mailxml_tm:AppointmentNumber</a> <a href="#">mailxml_tm:AppointmentNumberIdentifier</a>								

## element DispatchContainerInfoResponse


diagram	<pre> classDiagram     class DispatchContainerInfoResponse {         mailxml_tm::TrackingID         mailxml_tm::SubmitterTrackingID         mailxml_tm::DispatchContainerInfoList         mailxml_tm::DispatchContainerInfoList     }     note over DispatchContainerInfoResponse: Response to the notification for dispatch container information.   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm

properties	content complex
children	<a href="#"><u>mailxml_tm:TrackingID</u></a> <a href="#"><u>mailxml_tm:SubmitterTrackingID</u></a> <a href="#"><u>mailxml_tm:DispatchContainerInfoAccept</u></a> <a href="#"><u>mailxml_tm:DispatchContainerInfoReject</u></a>
annotation	documentation Response to the notification for dispatch container information.

#### element DispatchContainerInfoResponse/TrackingID

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

#### element DispatchContainerInfoResponse/SubmitterTrackingID

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

element **DispatchContainerInfoResponse/DispatchContainerInfoAccept**

diagram	<pre> classDiagram     class mailxml_tm {         &lt;&lt;DispatchContainerInfoAccept&gt;&gt;     }     class mailxml_tm {         &lt;&lt;ReturnInfo&gt;&gt;     }     mailxml_tm::DispatchContainerInfoAccept "1..∞" --&gt; mailxml_tm::ReturnInfo     mailxml_tm::ReturnInfo {         &lt;&lt;attributes&gt;&gt;         grp mailxml_defs:MailXMLHe...         mailxml_defs:CustomerGroupID         mailxml_defs:MailingGroupID         mailxml_defs:MaildatJobID         mailxml_defs:UserLicenseCode     }   </pre>																														
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																														
properties	<table> <tr> <td>isRef</td><td>0</td> </tr> <tr> <td>content</td><td>complex</td> </tr> </table>	isRef	0	content	complex																										
isRef	0																														
content	complex																														
children	<a href="#">mailxml_tm:ReturnInfo</a>																														
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:CustomerGroupID</td><td><a href="#">mailxml_base:s25</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MailingGroupID</td><td><a href="#">xs:nonNegativeInteger</a></td><td></td><td>required</td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatJobID</td><td><a href="#">mailxml_base:jobIDType</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:UserLicenseCode</td><td><a href="#">mailxml_base:userLicenseCodeType</a></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:CustomerGroupID	<a href="#">mailxml_base:s25</a>					mailxml_defs:MailingGroupID	<a href="#">xs:nonNegativeInteger</a>		required			mailxml_defs:MaildatJobID	<a href="#">mailxml_base:jobIDType</a>					mailxml_defs:UserLicenseCode	<a href="#">mailxml_base:userLicenseCodeType</a>				
Name	Type	Use	Default	Fixed	annotation																										
mailxml_defs:CustomerGroupID	<a href="#">mailxml_base:s25</a>																														
mailxml_defs:MailingGroupID	<a href="#">xs:nonNegativeInteger</a>		required																												
mailxml_defs:MaildatJobID	<a href="#">mailxml_base:jobIDType</a>																														
mailxml_defs:UserLicenseCode	<a href="#">mailxml_base:userLicenseCodeType</a>																														

element **DispatchContainerInfoResponse/DispatchContainerInfoAccept/ReturnInfo**

diagram	<pre> classDiagram     class mailxml_tm {         &lt;&lt;ReturnInfo&gt;&gt;     }     class mailxml_tm {         &lt;&lt;basicReturnInfoType&gt;&gt;     }     mailxml_tm::ReturnInfo "0..∞" --&gt; mailxml_tm::basicReturnInfoType     mailxml_tm::basicReturnInfoType {         &lt;&lt;attributes&gt;&gt;         mailxml_defs:ReturnCode         mailxml_defs:ReturnDescription         mailxml_defs:errorWarning "0..∞"         mailxml_defs:ContainerErrorWarningBlock "0..∞"     }   </pre>								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_defs:basicReturnInfoType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td> </tr> <tr> <td>minOcc</td><td>0</td> </tr> <tr> <td>maxOcc</td><td>1</td> </tr> <tr> <td>content</td><td>complex</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#">mailxml_defs:ReturnCode</a> <a href="#">mailxml_defs:ReturnDescription</a> <a href="#">mailxml_defs:errorWarning</a> <a href="#">mailxml_defs:ContainerErrorWarningBlock</a>								

element **DispatchContainerInfoResponse/DispatchContainerInfoReject**

diagram	<pre> classDiagram     class DispatchContainerInfo {         &lt;&lt;grp mailxml_defs:MailXMLHe...&gt;&gt;         CustomerGroupID         MailingGroupID         MaildatJobID         UserLicenseCode     }     class ReturnInfo     DispatchContainerInfo "0..1" --&gt; ReturnInfo   </pre>																														
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																														
properties	isRef 0 content complex																														
children	<a href="#">mailxml_tm:ReturnInfo</a>																														
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:CustomerGroupID</td><td><b>mailxml_base:s25</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MailingGroupID</td><td><b>xs:nonNegativeInteger</b></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatJobID</td><td><b>mailxml_base:jobIDType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:UserLicenseCode</td><td><b>mailxml_base:userLicenseCodeType</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:CustomerGroupID	<b>mailxml_base:s25</b>					mailxml_defs:MailingGroupID	<b>xs:nonNegativeInteger</b>	required				mailxml_defs:MaildatJobID	<b>mailxml_base:jobIDType</b>					mailxml_defs:UserLicenseCode	<b>mailxml_base:userLicenseCodeType</b>				
Name	Type	Use	Default	Fixed	annotation																										
mailxml_defs:CustomerGroupID	<b>mailxml_base:s25</b>																														
mailxml_defs:MailingGroupID	<b>xs:nonNegativeInteger</b>	required																													
mailxml_defs:MaildatJobID	<b>mailxml_base:jobIDType</b>																														
mailxml_defs:UserLicenseCode	<b>mailxml_base:userLicenseCodeType</b>																														

element **DispatchContainerInfoResponse/DispatchContainerInfoReject/ReturnInfo**

diagram	<pre> classDiagram     class ReturnInfo     class basicReturnInfoType {         ReturnCode         ReturnDescription         errorWarning         ContainerErrorW...     }     ReturnInfo "0..1" --&gt; basicReturnInfoType   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_defs:basicReturnInfoType</b>
properties	isRef 0 content complex
children	<b>mailxml_defs:ReturnCode</b> <b>mailxml_defs:ReturnDescription</b> <b>mailxml_defs:errorWarning</b> <b>mailxml_defs:ContainerErrorW...</b>

## element GoodsReceiptResponse

diagram	<pre> sequenceDiagram     participant GoodsReceiptResponse     participant TrackingID     participant SubmitterTrackingID     participant OK     participant ReturnInfo     GoodsReceiptResponse-&gt;&gt;TrackingID:      activate TrackingID     TrackingID--&gt;&gt;SubmitterTrackingID:      activate SubmitterTrackingID     TrackingID--&gt;&gt;OK:      activate OK     TrackingID--&gt;&gt;ReturnInfo:      activate ReturnInfo   </pre> <p>Response to the consignee goods response message.</p>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
properties	content complex
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:OK</a> <a href="#">mailxml_tm:ReturnInfo</a>
annotation	documentation Response to the consignee goods response message.

## element GoodsReceiptResponse/TrackingID

diagram	<pre> classDiagram     class TrackingID   </pre>												
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>												
type	<a href="#">mailxml_base:s20</a>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												


## element GoodsReceiptResponse/SubmitterTrackingID

diagram	<pre> classDiagram     class SubmitterTrackingID   </pre>												
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>												
type	<a href="#">mailxml_base:s20</a>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

element **GoodsReceiptResponse/OK**

diagram					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm				
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>content</td> <td>complex</td> </tr> </table>	isRef	0	content	complex
isRef	0				
content	complex				

element **GoodsReceiptResponse/ReturnInfo**

diagram					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm				
type	<b>mailxml_defs:returnInfoType</b>				
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>content</td> <td>complex</td> </tr> </table>	isRef	0	content	complex
isRef	0				
content	complex				
children	<b>mailxml_defs:ConsigneeFacility</b> <b>mailxml_defs:ErrorWarning</b> <b>mailxml_defs:ContainerErrorWarningBlock</b>				

element **OpenApptQueryRequest**

diagram	<pre> classDiagram     class OpenApptQueryRequest {         grp mailxml_defs:QueryMsgH...         mailxml_defs:SchedulerID         mailxml_defs:SchedulerCorpID         mailxml_defs:ApptType     }     class mailxml_tm:SubmittingParty     class mailxml_tm:SubmittingSoftware     class mailxml_tm:SubmitterTrackingID     class mailxml_tm:ConsigneeFacility     class mailxml_tm:OptionalAppt      OpenApptQueryRequest "1..∞" --&gt; mailxml_tm:SubmittingParty     OpenApptQueryRequest "1..∞" --&gt; mailxml_tm:SubmittingSoftware     OpenApptQueryRequest "1..∞" --&gt; mailxml_tm:SubmitterTrackingID     OpenApptQueryRequest "1..∞" --&gt; mailxml_tm:ConsigneeFacility     OpenApptQueryRequest "1..∞" --&gt; mailxml_tm:OptionalAppt   </pre>																								
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																								
properties	content complex																								
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:OptionalAppt</a>																								
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:SchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerCorpID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApptType</td> <td><a href="#">mailxml_base:apptTypeType</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SchedulerID	<a href="#">mailxml_base:s12</a>	required				mailxml_defs:SchedulerCorpID	<a href="#">mailxml_base:s12</a>	required				mailxml_defs:ApptType	<a href="#">mailxml_base:apptTypeType</a>	required			
Name	Type	Use	Default	Fixed	annotation																				
mailxml_defs:SchedulerID	<a href="#">mailxml_base:s12</a>	required																							
mailxml_defs:SchedulerCorpID	<a href="#">mailxml_base:s12</a>	required																							
mailxml_defs:ApptType	<a href="#">mailxml_base:apptTypeType</a>	required																							
annotation	<p>documentation</p> <p>Query request for available delivery appointments.</p>																								

element **OpenApptQueryRequest/SubmittingParty**

diagram	<pre> graph LR     SP[mailxml_tm:SubmittingParty] --- PID[mailxml_defs:participantIDType]     PID --- A[attributes]     A --- M6[mailxml_defs:MailerID6]     A --- M9[mailxml_defs:MailerID9]     A --- CRID[mailxml_defs:CRID]     A --- SCHED[mailxml_defs:SchedulerID]     A --- ML[mailxml_defs:MaildatUserLicense]     A --- SAID[mailxml_defs:ShippingAgentID]     A --- RAID[mailxml_defs:ReceivingAgentID]   </pre>																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:MailerID6</td><td><b>mailxml_base:mailerID6Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MailerID9</td><td><b>mailxml_base:mailerID9Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:CRID</td><td><b>mailxml_base:CRIDType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatUserLicense</td><td><b>mailxml_base:userLicenseCodeType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShippingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ReceivingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

element **OpenApptQueryRequest/SubmittingSoftware**


diagram	<pre> graph LR     SS[mailxml_tm:SubmittingSoftware] --- SST[mailxml_defs:submittingSoftwareType]     SST --- A[attributes]     A --- SN[mailxml_defs:SoftwareName]     A --- V[mailxml_defs:Vendor]     A --- V2[mailxml_defs:Version]     A --- AD[mailxml_defs:ApprovalDate]     A --- AK[mailxml_defs:ApprovalKey]   </pre>
---------	---

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
type	<b>mailxml_defs:submittingSoftwareType</b>					
properties	isRef 0 content complex					
attributes	Name mailxml_defs:SoftwareName	Type <b>xs:string</b>	Use required	Default	Fixed	annotation
	mailxml_defs:Vendor	<b>xs:string</b>	required			
	mailxml_defs:Version	<b>xs:string</b>	required			
	mailxml_defs:ApprovalDate	<b>xs:date</b>				
	mailxml_defs:ApprovalKey	<b>xs:string</b>				

#### element OpenApptQueryRequest/SubmitterTrackingID


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s20</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

#### element OpenApptQueryRequest/ConsigneeFacility

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_defs:consigneeFacilityType</b>

properties	isRef 0 content complex
children	mailxml_defs:CompanyName mailxml_defs:FacilityNumber mailxml_defs:FacilityAddress mailxml_defs:FacilityAddress mailxml_defs:FacilityName mailxml_defs:FacilityType mailxml_defs:URL mailxml_defs:CommonContact

### element OpenApptQueryRequest/OptionalAppt


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:optionalApptType</a>
properties	isRef 0 minOcc 1 maxOcc unbounded content complex
children	<a href="#">mailxml_tm:Start</a> <a href="#">mailxml_tm:End</a>

### element OpenApptQueryResponse


diagram	<p>Response to the query request for available delivery appointments.</p> <p>Error issued when the query data cannot be provided.</p>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
properties	content complex
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:QueryResults</a> <a href="#">mailxml_defs:QueryError</a>
attributes	Name Type Use Default Fixed annotation

	mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>	required
	mailxml_defs:SchedulerCorpID	<b>mailxml_base:s12</b>	required
	mailxml_defs:ApptType	<b>mailxml_base:apptTypeType</b>	required
annotation	documentation Response to the query request for available delivery appointments.		


#### element OpenApptQueryResponse/TrackingID

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

#### element OpenApptQueryResponse/SubmitterTrackingID

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

#### element OpenApptQueryResponse/QueryResults

diagram					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm				
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>content</td> <td>complex</td> </tr> </table>	isRef	0	content	complex
isRef	0				
content	complex				
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:AvailableAppt</a>				

element **OpenApptQueryResponse/QueryResults/ConsigneeFacility**

diagram	<pre> classDiagram     class mailxml_tm_ConsigneeFacility {         &lt;&lt;mailxml_tm&gt;&gt;     }     class mailxml_tm_availableApptType {         &lt;&lt;mailxml_tm&gt;&gt;     }     class mailxml_defs_ConsigneeFacilityType {         &lt;&lt;mailxml_defs&gt;&gt;     }      mailxml_tm_ConsigneeFacility &lt; -- mailxml_tm_availableApptType     mailxml_tm_availableApptType &lt; -- mailxml_defs_ConsigneeFacilityType      mailxml_tm_ConsigneeFacility --&gt; mailxml_tm_Start     mailxml_tm_ConsigneeFacility --&gt; mailxml_tm_End     mailxml_tm_ConsigneeFacility --&gt; mailxml_tm_Units     mailxml_tm_ConsigneeFacility --&gt; mailxml_tm_ReturnInfo   </pre> <p>The diagram shows the UML class structure for the element. It consists of four classes: <code>mailxml_tm:ConsigneeFacility</code>, <code>mailxml_tm:availableApptType</code>, <code>mailxml_defs:consigneeFacilityType</code>, and <code>mailxml_tm:Start</code>. <code>mailxml_tm:ConsigneeFacility</code> inherits from <code>mailxml_tm:availableApptType</code>, which in turn inherits from <code>mailxml_defs:consigneeFacilityType</code>. <code>mailxml_tm:ConsigneeFacility</code> has four associations: one to <code>mailxml_tm:Start</code>, one to <code>mailxml_tm:End</code>, one to <code>mailxml_tm:Units</code>, and one to <code>mailxml_tm:ReturnInfo</code>.</p>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#"><code>mailxml_defs:consigneeFacilityType</code></a>
properties	isRef 0 content complex
children	<a href="#"><code>mailxml_defs:CompanyName</code></a> <a href="#"><code>mailxml_defs:FacilityNumber</code></a> <a href="#"><code>mailxml_defs:FacilityAddress</code></a> <a href="#"><code>mailxml_defs:FacilityName</code></a> <a href="#"><code>mailxml_defs:FacilityType</code></a> <a href="#"><code>mailxml_defs:URL</code></a> <a href="#"><code>mailxml_defs:CommonContact</code></a>

element **OpenApptQueryResponse/QueryResults/AvailableAppt**

diagram	<pre> classDiagram     class mailxml_tm_AvailableAppt {         &lt;&lt;mailxml_tm&gt;&gt;     }     class mailxml_tm_availableApptType {         &lt;&lt;mailxml_tm&gt;&gt;     }      mailxml_tm_AvailableAppt &lt; -- mailxml_tm_availableApptType      mailxml_tm_AvailableAppt --&gt; mailxml_tm_Start     mailxml_tm_AvailableAppt --&gt; mailxml_tm_End     mailxml_tm_AvailableAppt --&gt; mailxml_tm_Units     mailxml_tm_AvailableAppt --&gt; mailxml_tm_ReturnInfo   </pre> <p>The diagram shows the UML class structure for the element. It consists of two classes: <code>mailxml_tm:AvailableAppt</code> and <code>mailxml_tm:availableApptType</code>. <code>mailxml_tm:AvailableAppt</code> inherits from <code>mailxml_tm:availableApptType</code>. <code>mailxml_tm:AvailableAppt</code> has four associations: one to <code>mailxml_tm:Start</code>, one to <code>mailxml_tm:End</code>, one to <code>mailxml_tm:Units</code>, and one to <code>mailxml_tm:ReturnInfo</code>.</p>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#"><code>mailxml_tm:availableApptType</code></a>
properties	isRef 0 minOcc 0 maxOcc unbounded content complex
children	<a href="#"><code>mailxml_tm:Start</code></a> <a href="#"><code>mailxml_tm:End</code></a> <a href="#"><code>mailxml_tm:Units</code></a> <a href="#"><code>mailxml_tm:ReturnInfo</code></a>

## element PartnerApptQueryRequest

diagram																																																																			
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																																																		
properties	content complex																																																																		
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:ConsigneeFacility</a>																																																																		
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:ConsigneeApptID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCorpID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCRID</td> <td><a href="#">mailxml_base:CRIDType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerContentID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:ConsigneeContentID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:Start</td> <td><a href="#">xs:dateTime</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:End</td> <td><a href="#">xs:dateTime</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:RetrieveContentUpdatedStartDate</td> <td><a href="#">xs:date</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:RetrieveContentUpdatedEndDate</td> <td><a href="#">xs:date</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>					mailxml_tm:SchedulerContentID	<a href="#">mailxml_base:s12</a>					mailxml_tm:ConsigneeContentID	<a href="#">mailxml_base:s12</a>					mailxml_tm:Start	<a href="#">xs:dateTime</a>					mailxml_tm:End	<a href="#">xs:dateTime</a>					mailxml_tm:RetrieveContentUpdatedStartDate	<a href="#">xs:date</a>					mailxml_tm:RetrieveContentUpdatedEndDate	<a href="#">xs:date</a>				
Name	Type	Use	Default	Fixed	annotation																																																														
mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>																																																																		
mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>																																																																		
mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>																																																																		
mailxml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>																																																																		
mailxml_tm:SchedulerContentID	<a href="#">mailxml_base:s12</a>																																																																		
mailxml_tm:ConsigneeContentID	<a href="#">mailxml_base:s12</a>																																																																		
mailxml_tm:Start	<a href="#">xs:dateTime</a>																																																																		
mailxml_tm:End	<a href="#">xs:dateTime</a>																																																																		
mailxml_tm:RetrieveContentUpdatedStartDate	<a href="#">xs:date</a>																																																																		
mailxml_tm:RetrieveContentUpdatedEndDate	<a href="#">xs:date</a>																																																																		
annotation	<p>documentation</p> <p>Request from a company such as a printer or logistics company to query appointments on behalf of their business</p>																																																																		

	partner such as the mail owner.
--	---------------------------------

### element PartnerApptQueryRequest/SubmittingParty

diagram	<pre> classDiagram     participantIDType {         &lt;&lt;mailxml_defs:participantIDType&gt;&gt;         &lt;&lt;attributes&gt;&gt;         mailxml_defs:MailerID6         mailxml_defs:MailerID9         mailxml_defs:CRID         mailxml_defs:SchedulerID         mailxml_defs:MaildatUserLicense         mailxml_defs:ShippingAgentID         mailxml_defs:ReceivingAgentID     }     SubmittingParty {         &lt;&lt;mailxml_tm:SubmittingParty&gt;&gt;     }     SubmittingParty --&gt; participantIDType   </pre>																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td><td>0</td> </tr> <tr> <td>content</td><td>complex</td> </tr> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:MailerID6</td><td><b>mailxml_base:mailerID6Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MailerID9</td><td><b>mailxml_base:mailerID9Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:CRID</td><td><b>mailxml_base:CRIDType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatUserLicense</td><td><b>mailxml_base:userLicenseCodeType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShippingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ReceivingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

**element PartnerApptQueryRequest/SubmittingSoftware**

diagram	<pre> classDiagram     class mailxml_tmSubmittingSoftware     class mailxml_defsSubmittingSoftwareType {         SoftwareName         Vendor         Version         ApprovalDate         ApprovalKey     }     mailxml_tmSubmittingSoftware "1" --&gt; "1" mailxml_defsSubmittingSoftwareType   </pre>																																				
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																				
type	<b>mailxml_defs:submittingSoftwareType</b>																																				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																
isRef	0																																				
content	complex																																				
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:SoftwareName</td> <td>xs:string</td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Vendor</td> <td>xs:string</td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Version</td> <td>xs:string</td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalDate</td> <td>xs:date</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalKey</td> <td>xs:string</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SoftwareName	xs:string	required				mailxml_defs:Vendor	xs:string	required				mailxml_defs:Version	xs:string	required				mailxml_defs:ApprovalDate	xs:date					mailxml_defs:ApprovalKey	xs:string				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_defs:SoftwareName	xs:string	required																																			
mailxml_defs:Vendor	xs:string	required																																			
mailxml_defs:Version	xs:string	required																																			
mailxml_defs:ApprovalDate	xs:date																																				
mailxml_defs:ApprovalKey	xs:string																																				

**element PartnerApptQueryRequest/SubmitterTrackingID**

diagram	<pre> classDiagram     class mailxml_tmSubmitterTrackingID   </pre>												
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

element **PartnerApptQueryRequest/ConsigneeFacility**

diagram	<pre> sequenceDiagram     participant CF as mailxml_tm:ConsigneeFacility     participant CNT as mailxml_defs:CompanyName     participant FN as mailxml_defs:FacilityNumber     participant FA1 as mailxml_defs:FacilityAddress     participant FA2 as mailxml_defs:FacilityAddress     participant FN2 as mailxml_defs:FacilityName     participant FT as mailxml_defs:FacilityType     participant URL as mailxml_defs:URL     participant CC as mailxml_defs:CommonContact      CF-&gt;&gt;CNT:      CNT--&gt;&gt;FN     FN--&gt;&gt;FA1     FN--&gt;&gt;FA2     FA1--&gt;&gt;FN2     FA1--&gt;&gt;FT     FA1--&gt;&gt;URL     FA1--&gt;&gt;CC   </pre>								
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>								
type	<b>mailxml_defs:consigneeFacilityType</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<b>mailxml_defs:CompanyName</b> <b>mailxml_defs:FacilityNumber</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityName</b> <b>mailxml_defs:FacilityType</b> <b>mailxml_defs:URL</b> <b>mailxml_defs:CommonContact</b>								

## element PartnerApptQueryResponse


diagram	<p>The diagram illustrates the structure of the <b>PartnerApptQueryResponse</b> element. It features a main class box labeled <b>PartnerApptQueryResponse</b> with a description: "Response to the request from a company such as a printer or logistics company to query appointments on behalf of their business partner such as the mail owner." Below the class box is a detailed view of its attributes, grouped under <b>attributes</b>. The attributes listed are: <b>mailxml_tm:ConsigneeApptID</b>, <b>mailxml_tm:SchedulerID</b>, <b>mailxml_tm:SchedulerCorpID</b>, <b>mailxml_tm:SchedulerCRID</b>, <b>mailxml_tm:SchedulerContentID</b>, <b>mailxml_tm:ConsigneeContentID</b>, <b>mailxml_tm:Start</b>, <b>mailxml_tm:End</b>, <b>mailxml_tm:RetrieveContentUp...</b>, and <b>mailxml_tm:RetrieveContentUp...</b>. Below these attributes is a dashed box containing <b>mailxml_tm:TrackingID</b> and <b>mailxml_tm:SubmitterTrackingID</b>. A line connects this dashed box to another dashed box containing <b>mailxml_tm:QueryResults</b> and <b>mailxml_tm:QueryError</b>. Ellipsis symbols (three dots) are placed between the dashed boxes to indicate they are part of a larger structure.</p>																																																																		
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																																																		
properties	content complex																																																																		
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:QueryResults</a> <a href="#">mailxml_tm:QueryError</a>																																																																		
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><b>mailxml_tm:ConsigneeApptID</b></td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><b>mailxml_tm:SchedulerID</b></td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><b>mailxml_tm:SchedulerCorpID</b></td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><b>mailxml_tm:SchedulerCRID</b></td> <td><b>mailxml_base:CRIDType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><b>mailxml_tm:SchedulerContentID</b></td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><b>mailxml_tm:ConsigneeContentID</b></td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><b>mailxml_tm:Start</b></td> <td><b>xs:dateTime</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><b>mailxml_tm:End</b></td> <td><b>xs:dateTime</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><b>mailxml_tm:RetrieveContentUpdatedStartDate</b></td> <td><b>xs:date</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><b>mailxml_tm:RetrieveContentUpdatedEndDate</b></td> <td><b>xs:date</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<b>mailxml_tm:ConsigneeApptID</b>	<b>mailxml_base:s12</b>					<b>mailxml_tm:SchedulerID</b>	<b>mailxml_base:s12</b>					<b>mailxml_tm:SchedulerCorpID</b>	<b>mailxml_base:s12</b>					<b>mailxml_tm:SchedulerCRID</b>	<b>mailxml_base:CRIDType</b>					<b>mailxml_tm:SchedulerContentID</b>	<b>mailxml_base:s12</b>					<b>mailxml_tm:ConsigneeContentID</b>	<b>mailxml_base:s12</b>					<b>mailxml_tm:Start</b>	<b>xs:dateTime</b>					<b>mailxml_tm:End</b>	<b>xs:dateTime</b>					<b>mailxml_tm:RetrieveContentUpdatedStartDate</b>	<b>xs:date</b>					<b>mailxml_tm:RetrieveContentUpdatedEndDate</b>	<b>xs:date</b>				
Name	Type	Use	Default	Fixed	annotation																																																														
<b>mailxml_tm:ConsigneeApptID</b>	<b>mailxml_base:s12</b>																																																																		
<b>mailxml_tm:SchedulerID</b>	<b>mailxml_base:s12</b>																																																																		
<b>mailxml_tm:SchedulerCorpID</b>	<b>mailxml_base:s12</b>																																																																		
<b>mailxml_tm:SchedulerCRID</b>	<b>mailxml_base:CRIDType</b>																																																																		
<b>mailxml_tm:SchedulerContentID</b>	<b>mailxml_base:s12</b>																																																																		
<b>mailxml_tm:ConsigneeContentID</b>	<b>mailxml_base:s12</b>																																																																		
<b>mailxml_tm:Start</b>	<b>xs:dateTime</b>																																																																		
<b>mailxml_tm:End</b>	<b>xs:dateTime</b>																																																																		
<b>mailxml_tm:RetrieveContentUpdatedStartDate</b>	<b>xs:date</b>																																																																		
<b>mailxml_tm:RetrieveContentUpdatedEndDate</b>	<b>xs:date</b>																																																																		
annotation	documentation Response to the request from a company such as a printer or logistics company to query appointments on behalf of their business partner such as the mail owner.																																																																		

	business partner such as the mail owner.
--	--


#### element PartnerApptQueryResponse/TrackingID

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												


#### element PartnerApptQueryResponse/SubmitterTrackingID

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												


#### element PartnerApptQueryResponse/QueryResults

diagram					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm				
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>content</td> <td>complex</td> </tr> </table>	isRef	0	content	complex
isRef	0				
content	complex				
children	<a href="#">mailxml_tm:ApptBlock</a> <a href="#">mailxml_tm:ReturnInfo</a>				
annotation	documentation				


element **PartnerApptQueryResponse/QueryResults/ApptBlock**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:PartnerApptBlockType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:ConsigneeApptID</a> <a href="#">mailxml_tm:ScheduledAppt</a> <a href="#">mailxml_tm:Comment</a> <a href="#">mailxml_tm:MailClass</a> <a href="#">mailxml_tm:TrailerInfo</a> <a href="#">mailxml_tm:ContentDetailInfoUpdate</a>


element **PartnerApptQueryResponse/QueryResults/ReturnInfo**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_defs:returnInfoType</a>
properties	isRef 0 minOcc 0 maxOcc 1 content complex
children	<a href="#">mailxml_defs:ConsigneeFacility</a> <a href="#">mailxml_defs:ErrorWarning</a> <a href="#">mailxml_defs:ContainerErrorWarningBlock</a>

element **PartnerApptQueryResponse/QueryError**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_defs:queryErrorType</b>
properties	isRef 0 content complex
children	<b>mailxml_defs:ReturnInfo</b>

element **PartnerContentAssignmentRequest**

diagram																															
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																														
properties	content complex																														
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:CurrentPartnerOwner</a> <a href="#">mailxml_tm:PartnerContentAssignedTo</a>																														
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:SchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCorpID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCRID</td> <td><a href="#">mailxml_base:CRIDType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:MailerID6</td> <td><a href="#">mailxml_base:mailerID6Type</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>					mailxml_tm:MailerID6	<a href="#">mailxml_base:mailerID6Type</a>				
Name	Type	Use	Default	Fixed	annotation																										
mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>																														
mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>																														
mailxml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>																														
mailxml_tm:MailerID6	<a href="#">mailxml_base:mailerID6Type</a>																														

	mailxml_tm:MailerID9	<b>mailxml_base:mailerID9Type</b>
annotation	documentation	Request from a users such as owner, preparer, consolidator, scheduler to assign the content to another user

### element PartnerContentAssignmentRequest/SubmittingParty

diagram	<pre> classDiagram     participant IDType     participant SubmittingParty      IDType &lt; -- SubmittingParty     IDType {         &lt;&lt;attributes&gt;&gt;         MailerID6         MailerID9         CRID         SchedulerID         MaildatUserLicense         ShippingAgentID         ReceivingAgentID     }   </pre>																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td><td>0</td> </tr> <tr> <td>content</td><td>complex</td> </tr> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:MailerID6</td> <td><b>mailxml_base:mailerID6Type</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MailerID9</td> <td><b>mailxml_base:mailerID9Type</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:CRID</td> <td><b>mailxml_base:CRIDType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MaildatUserLicense</td> <td><b>mailxml_base:userLicenseCodeType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ShippingAgentID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ReceivingAgentID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

**element PartnerContentAssignmentRequest/SubmittingSoftware**

diagram	<pre> classDiagram     class mailxml_tmSubmittingSoftware     class mailxml_defsSubmittingSoftwareType {         SoftwareName         Vendor         Version         ApprovalDate         ApprovalKey     }     mailxml_tmSubmittingSoftware "1" --&gt; "1" mailxml_defsSubmittingSoftwareType   </pre>																																				
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																				
type	<b>mailxml_defs:submittingSoftwareType</b>																																				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																
isRef	0																																				
content	complex																																				
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:SoftwareName</td> <td>xs:string</td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Vendor</td> <td>xs:string</td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Version</td> <td>xs:string</td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalDate</td> <td>xs:date</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalKey</td> <td>xs:string</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SoftwareName	xs:string	required				mailxml_defs:Vendor	xs:string	required				mailxml_defs:Version	xs:string	required				mailxml_defs:ApprovalDate	xs:date					mailxml_defs:ApprovalKey	xs:string				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_defs:SoftwareName	xs:string	required																																			
mailxml_defs:Vendor	xs:string	required																																			
mailxml_defs:Version	xs:string	required																																			
mailxml_defs:ApprovalDate	xs:date																																				
mailxml_defs:ApprovalKey	xs:string																																				

**element PartnerContentAssignmentRequest/SubmitterTrackingID**

diagram	<pre> classDiagram     class mailxml_tmSubmitterTrackingID   </pre>												
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

element **PartnerContentAssignmentRequest/CurrentPartnerOwner**

diagram	<pre> classDiagram     participant CurrentPartnerOwner     participant participantIDType     CurrentPartnerOwner --&gt; participantIDType     participantIDType &lt;&lt;mailxml_defs:participantIDType&gt;&gt;     participantIDType &lt;&lt;attributes&gt;&gt;         MailerID6         MailerID9         CRID         SchedulerID         MaildatUserLicense         ShippingAgentID         ReceivingAgentID     end   </pre>																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:MailerID6</td> <td><b>mailxml_base:mailerID6Type</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MailerID9</td> <td><b>mailxml_base:mailerID9Type</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:CRID</td> <td><b>mailxml_base:CRIDType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MaildatUserLicense</td> <td><b>mailxml_base:userLicenseCodeType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ShippingAgentID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ReceivingAgentID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

element **PartnerContentAssignmentRequest/PartnerContentAssignedTo**

diagram	<pre> classDiagram     participant PartnerContentAssignedTo     participant partnerContentAssignmentType     PartnerContentAssignedTo --&gt; partnerContentAssignmentType     partnerContentAssignmentType &lt;&lt;mailxml_tm:partnerContentAssignmentType&gt;&gt;     partnerContentAssignmentType &lt;&lt;attributes&gt;&gt;         PartnerIdentifier         ConsigneeContentID         DestinationEntry     end     PartnerIdentifier &lt; -- multiplicity: 1..∞     ConsigneeContentID &lt; -- multiplicity: 1..∞     DestinationEntry &lt; -- multiplicity: 1..∞   </pre>						
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm						
type	<b>mailxml_tm:partnerContentAssignmentType</b>						
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>1</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> </table>	isRef	0	minOcc	1	maxOcc	unbounded
isRef	0						
minOcc	1						
maxOcc	unbounded						

	content complex
children	<a href="#">mailxml_tm:PartnerIdentifier</a> <a href="#">mailxml_tm:ConsigneeContentID</a> <a href="#">mailxml_tm:DestinationEntry</a>

### element PartnerContentAssignmentResponse

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
properties	content complex
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:PartnerContentAssignmentAccepted</a> <a href="#">mailxml_tm:PartnerContentAssignmentRejected</a>
annotation	documentation Response to the request from a user for assignment of content to other user

### element PartnerContentAssignmentResponse/TrackingID

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:s20</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

### element PartnerContentAssignmentResponse/SubmitterTrackingID

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:s20</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1

	<pre>maxLength    20 whiteSpace   preserve</pre>
--	--

element **PartnerContentAssignmentResponse/PartnerContentAssignmentAccepted**

diagram	<pre>mailxml_tm:partnerContentAssignmentType   mailxml_tm:PartnerIdentifier [0..1]   mailxml_tm:ConsigneeContentID [1..∞]   mailxml_tm:DestinationEntry [0..1]</pre>								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_tm:partnerContentAssignmentType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>1</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	1	maxOcc	unbounded	content	complex
isRef	0								
minOcc	1								
maxOcc	unbounded								
content	complex								
children	<a href="#">mailxml_tm:PartnerIdentifier</a> <a href="#">mailxml_tm:ConsigneeContentID</a> <a href="#">mailxml_tm:DestinationEntry</a>								

element **PartnerContentAssignmentResponse/PartnerContentAssignmentRejected**

diagram	<pre>mailxml_defs:returnInfoType   mailxml_defs:ConsigneeFacility [0..∞]   mailxml_defs:ErrorWarning [0..∞]   mailxml_defs:ContainerErrorWarningBlock [0..∞]</pre>				
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm				
type	<a href="#">mailxml_defs:returnInfoType</a>				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex
isRef	0				
content	complex				
children	<a href="#">mailxml_defs:ConsigneeFacility</a> <a href="#">mailxml_defs:ErrorWarning</a> <a href="#">mailxml_defs:ContainerErrorWarningBlock</a>				

## element PickupApptCancelRequest

diagram	<pre> classDiagram     class PickupApptCancelRequest {         grp mailxml_tm:PickupRespo...         mailxml_tm:ShipperApptReque...         mailxml_tm:ConsigneeApptID         mailxml_tm:SchedulerCorpID         mailxml_tm:SchedulerID         mailxml_tm:ApptType     }     class SubmittingParty     class SubmittingSoftware     class SubmitterTrackingID     class ReturnInfo      PickupApptCancelRequest "1" -- "0..1" SubmittingParty : mailxml_tm:SubmittingParty     PickupApptCancelRequest "1" -- "0..1" SubmittingSoftware : mailxml_tm:SubmittingSoftware     PickupApptCancelRequest "1" -- "0..1" SubmitterTrackingID : mailxml_tm:SubmitterTrackingID     PickupApptCancelRequest "1" -- "0..1" ReturnInfo : mailxml_tm:ReturnInfo   </pre> <p>Request to cancel a pickup delivery appointment.</p>																																				
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																				
properties	content complex																																				
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:ReturnInfo</a>																																				
attributes	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:ShipperApptRequestID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:ConsigneeApptID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCorpID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:ApptType</td> <td><a href="#">mailxml_base:apptTypeType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required				mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>	required				mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>	required				mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>	required				mailxml_tm:ApptType	<a href="#">mailxml_base:apptTypeType</a>				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_tm:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required																																			
mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>	required																																			
mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>	required																																			
mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>	required																																			
mailxml_tm:ApptType	<a href="#">mailxml_base:apptTypeType</a>																																				
annotation	documentation Request to cancel a pickup delivery appointment.																																				

### element PickupApptCancelRequest/SubmittingParty

diagram	<pre> classDiagram     class mailxml_tmSubmittingParty     class mailxml_defsparticipantIDType {         -mailxml_defsMailerID6         -mailxml_defsMailerID9         -mailxml_defsCRID         -mailxml_defsSchedulerID         -mailxml_defsMaildatUserLicense         -mailxml_defsShippingAgentID         -mailxml_defsReceivingAgentID     }     mailxml_tmSubmittingParty "1" -- "1" mailxml_defsparticipantIDType   </pre>																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:MailerID6</td><td><b>mailxml_base:mailerID6Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MailerID9</td><td><b>mailxml_base:mailerID9Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:CRID</td><td><b>mailxml_base:CRIDType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatUserLicense</td><td><b>mailxml_base:userLicenseCodeType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShippingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ReceivingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

### element PickupApptCancelRequest/SubmittingSoftware


diagram	<pre> classDiagram     class mailxml_tmSubmittingSoftware     class mailxml_defssubmittingSoftwareType {         -mailxml_defsSoftwareName         -mailxml_defsVendor         -mailxml_defsVersion         -mailxml_defsApprovalDate         -mailxml_defsApprovalKey     }     mailxml_tmSubmittingSoftware "1" -- "1" mailxml_defssubmittingSoftwareType   </pre>
---------	--

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
type	<b>mailxml_defs:submittingSoftwareType</b>					
properties	isRef 0 content complex					
attributes	Name mailxml_defs:SoftwareName mailxml_defs:Vendor mailxml_defs:Version mailxml_defs:ApprovalDate mailxml_defs:ApprovalKey	Type <b>xs:string</b> <b>xs:string</b> <b>xs:string</b> <b>xs:date</b> <b>xs:string</b>	Use required required required	Default	Fixed	annotation

#### element PickupApptCancelRequest/SubmitterTrackingID

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s20</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

#### element PickupApptCancelRequest/ReturnInfo

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_defs:basicReturnInfoType</b>
properties	isRef 0 minOcc 0 maxOcc 1 content complex
children	<b>mailxml_defs:ReturnCode</b> <b>mailxml_defs:ReturnDescription</b> <b>mailxml_defs:errorWarning</b> <b>mailxml_defs:ContainerErrorWarningBlock</b>

### element PickupApptCancelResponse

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
properties	content complex
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:DeliveryApptCancelAccept</a> <a href="#">mailxml_tm:DeliveryApptCancelReject</a>
annotation	documentation Response to a request to cancel a pickup delivery appointment.


### element PickupApptCancelResponse/TrackingID

diagram													
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												


### element PickupApptCancelResponse/SubmitterTrackingID

diagram													
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

element PickupApptCancelResponse/DeliveryApptCancelAccept

diagram																																					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																				
properties	<table> <tr> <td>isRef</td><td>0</td> </tr> <tr> <td>content</td><td>complex</td> </tr> </table>	isRef	0	content	complex																																
isRef	0																																				
content	complex																																				
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_tm:ShipperApptRequestID</td><td><b>mailxml_base:s12</b></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:ConsigneeApptID</td><td><b>mailxml_base:s12</b></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:SchedulerCorpID</td><td><b>mailxml_base:s12</b></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:SchedulerID</td><td><b>mailxml_base:s12</b></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:ApptType</td><td><b>mailxml_base:apptTypeType</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ShipperApptRequestID	<b>mailxml_base:s12</b>	required				mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>	required				mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>	required				mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>	required				mailxml_tm:ApptType	<b>mailxml_base:apptTypeType</b>				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_tm:ShipperApptRequestID	<b>mailxml_base:s12</b>	required																																			
mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>	required																																			
mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>	required																																			
mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>	required																																			
mailxml_tm:ApptType	<b>mailxml_base:apptTypeType</b>																																				

element PickupApptCancelResponse/DeliveryApptCancelReject


diagram					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm				
properties	<table> <tr> <td>isRef</td><td>0</td> </tr> <tr> <td>content</td><td>complex</td> </tr> </table>	isRef	0	content	complex
isRef	0				
content	complex				
children	<a href="#">mailxml_tm:ReturnInfo</a>				

	Name	Type	Use	Default	Fixed	annotation
	mailxml_tm:ShipperApptRequestID	<b>mailxml_base:s12</b>	required			
	mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>	required			
	mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>	required			
	mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>	required			
	mailxml_tm:ApptType	<b>mailxml_base:apptTypeType</b>				

element **PickupApptCancelResponse/DeliveryApptCancelReject/ReturnInfo**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_defs:returnInfoType</b>
properties	isRef 0 content complex
children	<b>mailxml_defs:ConsigneeFacility</b> <b>mailxml_defs:ErrorWarning</b> <b>mailxml_defs:ContainerErrorWarningBlock</b>

## element PickupApptCreateRequest

diagram	 <p>PickupApptCreateRequest Request to create a pickup delivery appointment.</p>																																										
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																										
properties	content complex																																										
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:ApptBlock</a> <a href="#">mailxml_tm:DetailInfo</a>																																										
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:ShipperApptRequestID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:ConsigneeApptID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCorpID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:ApptType</td> <td><a href="#">mailxml_base:apptTypeType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:IncludesElectronicLoad</td> <td><a href="#">mailxml_base:yesNo</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required				mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>	required				mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>	required				mailxml_tm:ApptType	<a href="#">mailxml_base:apptTypeType</a>					mailxml_tm:IncludesElectronicLoad	<a href="#">mailxml_base:yesNo</a>				
Name	Type	Use	Default	Fixed	annotation																																						
mailxml_tm:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required																																									
mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>																																										
mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>	required																																									
mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>	required																																									
mailxml_tm:ApptType	<a href="#">mailxml_base:apptTypeType</a>																																										
mailxml_tm:IncludesElectronicLoad	<a href="#">mailxml_base:yesNo</a>																																										
annotation	documentation Request to create a pickup delivery appointment.																																										

### element PickupApptCreateRequest/SubmittingParty

diagram	<pre> classDiagram     class mailxml_tmSubmittingParty     class mailxml_defsParticipantIDType {         -mailxml_defsMailerID6         -mailxml_defsMailerID9         -mailxml_defsCRID         -mailxml_defsSchedulerID         -mailxml_defsMaildatUserLicense         -mailxml_defsShippingAgentID         -mailxml_defsReceivingAgentID     }     mailxml_tmSubmittingParty "1" -- "1" mailxml_defsParticipantIDType   </pre>																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:MailerID6</td><td><b>mailxml_base:mailerID6Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MailerID9</td><td><b>mailxml_base:mailerID9Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:CRID</td><td><b>mailxml_base:CRIDType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatUserLicense</td><td><b>mailxml_base:userLicenseCodeType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShippingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ReceivingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

### element PickupApptCreateRequest/SubmittingSoftware


diagram	<pre> classDiagram     class mailxml_tmSubmittingSoftware     class mailxml_defsSubmittingSoftwareType {         -mailxml_defsSoftwareName         -mailxml_defsVendor         -mailxml_defsVersion         -mailxml_defsApprovalDate         -mailxml_defsApprovalKey     }     mailxml_tmSubmittingSoftware "1" -- "1" mailxml_defsSubmittingSoftwareType   </pre>
---------	--

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
type	<b>mailxml_defs:submittingSoftwareType</b>					
properties	isRef 0 content complex					
attributes	Name mailxml_defs:SoftwareName	Type <b>xs:string</b>	Use required	Default	Fixed	annotation
	mailxml_defs:Vendor	<b>xs:string</b>	required			
	mailxml_defs:Version	<b>xs:string</b>	required			
	mailxml_defs:ApprovalDate	<b>xs:date</b>				
	mailxml_defs:ApprovalKey	<b>xs:string</b>				

#### element PickupApptCreateRequest/SubmitterTrackingID

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s20</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

#### element PickupApptCreateRequest/ApptBlock

diagram	
---------	--

namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:pickupApptBlockRequestType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:PickupLocation</a> <a href="#">mailxml_tm:PreferredAppt</a> <a href="#">mailxml_tm:OptionalAppt</a> <a href="#">mailxml_tm:Comment</a> <a href="#">mailxml_tm:TransportationResponsibility</a>

### element PickupApptCreateRequest/DetailInfo


diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:detailInfoType</a>
properties	isRef 0 minOcc 1 maxOcc unbounded content complex
children	<a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:USPSSummary</a> <a href="#">mailxml_tm:ConsigneeContentID</a>

### element PickupApptCreateResponse

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
properties	content complex

children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:PickupApptCreateAccept</a> <a href="#">mailxml_tm:PickupApptCreateReject</a>
annotation	documentation Response to a request to create a pickup delivery appointment.

#### element PickupApptCreateResponse/TrackingID

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

#### element PickupApptCreateResponse/SubmitterTrackingID

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

element **PickupApptCreateResponse/PickupApptCreateAccept**

diagram	<pre> classDiagram     class PickupApptCreateResponse {         grp mailxml_tm:PickupRespo...         mailxml_tm:ShipperApptReque...         mailxml_tm:ConsigneeApptID         mailxml_tm:SchedulerCorpID         mailxml_tm:SchedulerID         mailxml_tm:ApptType     }     class ApptInfo     class DetailInfo     class ReturnInfo      PickupApptCreateResponse "1" --&gt; "1" ApptInfo     PickupApptCreateResponse "1" --&gt; "1" DetailInfo     PickupApptCreateResponse "1" --&gt; "1" ReturnInfo   </pre>																																				
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																				
properties	<table border="1"> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																
isRef	0																																				
content	complex																																				
children	<a href="#">mailxml_tm:ApptInfo</a> <a href="#">mailxml_tm:DetailInfo</a> <a href="#">mailxml_tm:ReturnInfo</a>																																				
attributes	<table border="1"> <thead> <tr> <th>Name</th><th>Type</th><th>Use</th><th>Default</th><th>Fixed</th><th>annotation</th></tr> </thead> <tbody> <tr> <td>mailxml_tm:ShipperApptRequestID</td><td><b>mailxml_base:s12</b></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:ConsigneeApptID</td><td><b>mailxml_base:s12</b></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:SchedulerCorpID</td><td><b>mailxml_base:s12</b></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:SchedulerID</td><td><b>mailxml_base:s12</b></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:ApptType</td><td><b>mailxml_base:apptTypeType</b></td><td></td><td></td><td></td><td></td></tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ShipperApptRequestID	<b>mailxml_base:s12</b>	required				mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>	required				mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>	required				mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>	required				mailxml_tm:ApptType	<b>mailxml_base:apptTypeType</b>				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_tm:ShipperApptRequestID	<b>mailxml_base:s12</b>	required																																			
mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>	required																																			
mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>	required																																			
mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>	required																																			
mailxml_tm:ApptType	<b>mailxml_base:apptTypeType</b>																																				

element **PickupApptCreateResponse/PickupApptCreateAccept/ApptInfo**

diagram	<pre> classDiagram     pickupApptBlockResponseType "mailxml_defs:pickupApptBlockResponseType"     ApptInfo "mailxml_tm:ApptInfo"     TrackingID "mailxml_defs:TrackingID"     ConsigneeApptID "mailxml_defs:ConsigneeApptID"     ConsigneeFacility "mailxml_defs:ConsigneeFacility"     PickupLocation "mailxml_defs:PickupLocation"     ScheduledAppt "mailxml_defs:ScheduledAppt"     Comment "mailxml_defs:Comment"     TransportationResponsibility "mailxml_defs:TransportationRe..."      pickupApptBlockResponseType &lt; -- ApptInfo     ApptInfo &lt; -- TrackingID     ApptInfo &lt; -- ConsigneeApptID     ApptInfo &lt; -- ConsigneeFacility     ApptInfo &lt; -- PickupLocation     ApptInfo &lt; -- ScheduledAppt     ApptInfo &lt; -- Comment     ApptInfo &lt; -- TransportationResponsibility   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_defs:pickupApptBlockResponseType</b>
properties	isRef 0 content complex
children	mailxml_defs:TrackingID mailxml_defs:ConsigneeApptID mailxml_defs:ConsigneeFacility mailxml_defs:PickupLocation mailxml_defs:ScheduledAppt mailxml_defs:Comment mailxml_defs:TransportationResponsibility

element **PickupApptCreateResponse/PickupApptCreateAccept/DetailInfo**

diagram	<pre> classDiagram     detailInfoType "mailxml_tm:detailInfoType"     DetailInfo "mailxml_tm:DetailInfo"     ShipperContainerGroup "mailxml_tm:ShipperContainerGr..."     ConsigneeContainer "mailxml_tm:ConsigneeContain..."     StartTheClockDate "mailxml_tm:StartTheClockDate"     ShipperGroupingID "mailxml_tm:ShipperGroupingID..."     MaildatSummary "mailxml_tm:MaildatSummary"     USPSSummary "mailxml_tm:USPSSummary"     ConsigneeContentID "mailxml_tm:ConsigneeContentID"      detailInfoType &lt; -- DetailInfo     DetailInfo &lt; -- ShipperContainerGroup     DetailInfo &lt; -- ConsigneeContainer     DetailInfo &lt; -- StartTheClockDate     DetailInfo &lt; -- ShipperGroupingID     DetailInfo &lt; -- MaildatSummary     DetailInfo &lt; -- "1..oo" *--&gt; USPSSummary     DetailInfo &lt; -- ConsigneeContentID   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_tm:detailInfoType</b>
properties	isRef 0 content complex

children	<a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:USPSSummary</a> <a href="#">mailxml_tm:ConsigneeContentID</a>
----------	---

element **PickupApptCreateResponse/PickupApptCreateAccept/ReturnInfo**

diagram									
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>								
type	<b>mailxml_defs:basicReturnInfoType</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#">mailxml_defs:ReturnCode</a> <a href="#">mailxml_defs:ReturnDescription</a> <a href="#">mailxml_defs:errorWarning</a> <a href="#">mailxml_defs:ContainerErrorW...</a>								

element **PickupApptCreateResponse/PickupApptCreateReject**

diagram																																											
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																										
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																						
isRef	0																																										
content	complex																																										
children	<a href="#">mailxml_tm:ApptInfo</a> <a href="#">mailxml_tm:DetailInfo</a> <a href="#">mailxml_tm:ReturnInfo</a>																																										
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:ShipperApptRequestID</td> <td><b>mailxml_base:s12</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:ConsigneeApptID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCorpID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:ApptType</td> <td><b>mailxml_base:apptTypeType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:IncludesElectronicLoad</td> <td><b>mailxml_base:yesNo</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ShipperApptRequestID	<b>mailxml_base:s12</b>	required				mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>					mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>					mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>					mailxml_tm:ApptType	<b>mailxml_base:apptTypeType</b>					mailxml_tm:IncludesElectronicLoad	<b>mailxml_base:yesNo</b>				
Name	Type	Use	Default	Fixed	annotation																																						
mailxml_tm:ShipperApptRequestID	<b>mailxml_base:s12</b>	required																																									
mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>																																										
mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>																																										
mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>																																										
mailxml_tm:ApptType	<b>mailxml_base:apptTypeType</b>																																										
mailxml_tm:IncludesElectronicLoad	<b>mailxml_base:yesNo</b>																																										

element PickupApptCreateResponse/PickupApptCreateReject/ApptInfo

diagram	<pre> classDiagram     class mailxml_tm.pickupApptBlockRequestType {         SubmittingParty         SubmittingSoftware         ConsigneeFacility         PickupLocation         PreferredAppt         &lt;&lt;OptionalAppt&gt;&gt;         Comment         TransportationResponsibility     }     ApptInfo --&gt; mailxml_tm.pickupApptBlockRequestType     ApptInfo &lt; -- mailxml_tm.pickupApptBlockRequestType     </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:pickupApptBlockRequestType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:PickupLocation</a> <a href="#">mailxml_tm:PreferredAppt</a> <a href="#">mailxml_tm:OptionalAppt</a> <a href="#">mailxml_tm:Comment</a> <a href="#">mailxml_tm:TransportationResponsibility</a>

element PickupApptCreateResponse/PickupApptCreateReject/DetailInfo

diagram	<pre> classDiagram     class mailxml_tm.detailInfoType {         ShipperContainerGr...         ConsigneeContain...         StartTheClockDate         ShipperGroupingID...         MaildatSummary         USPSSummary         ConsigneeContentID     }     DetailInfo --&gt; mailxml_tm.detailInfoType     DetailInfo &lt; -- mailxml_tm.detailInfoType     </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm

type	<a href="#">mailxml_tm:detailInfoType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:USPSSummary</a> <a href="#">mailxml_tm:ConsigneeContentID</a>

### element PickupApptCreateResponse/PickupApptCreateReject/ReturnInfo

diagram	<pre> classDiagram     class mailxml_tm::ReturnInfo     class mailxml_defs::basicReturnInfoType {         mailxml_defs::ReturnCode         mailxml_defs::ReturnDescription         mailxml_defs::errorWarning         mailxml_defs::ContainerErrorW...     }     mailxml_tm::ReturnInfo --&gt; basicReturnInfoType   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_defs:basicReturnInfoType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_defs:ReturnCode</a> <a href="#">mailxml_defs:ReturnDescription</a> <a href="#">mailxml_defs:errorWarning</a> <a href="#">mailxml_defs:ContainerErrorWarningBlock</a>

## element PickupApptUpdateRequest

diagram	<pre> classDiagram     class PickupApptUpdateRequest {         grp mailxml_tm:PickupRespo...         mailxml_tm:ShipperApptReque...         mailxml_tm:ConsigneeApptID         mailxml_tm:SchedulerCorpID         mailxml_tm:SchedulerID         mailxml_tm:ApptType     }     PickupApptUpdateRequest "Request to update a pickup delivery appointment."     PickupApptUpdateRequest &lt; --&gt; mailxml_tm:SubmittingParty     PickupApptUpdateRequest &lt; --&gt; mailxml_tm:SubmittingSoftware     PickupApptUpdateRequest &lt; --&gt; mailxml_tm:SubmitterTrackingID     PickupApptUpdateRequest &lt; --&gt; mailxml_tm:ApptBlock     PickupApptUpdateRequest &lt; --&gt; mailxml_tm:DetailInfo   </pre>																																				
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																				
properties	content complex																																				
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:ApptBlock</a> <a href="#">mailxml_tm:DetailInfo</a>																																				
attributes	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:ShipperApptRequestID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:ConsigneeApptID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCorpID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:ApptType</td> <td><a href="#">mailxml_base:apptTypeType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required				mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>	required				mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>	required				mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>	required				mailxml_tm:ApptType	<a href="#">mailxml_base:apptTypeType</a>				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_tm:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required																																			
mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>	required																																			
mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>	required																																			
mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>	required																																			
mailxml_tm:ApptType	<a href="#">mailxml_base:apptTypeType</a>																																				
annotation	documentation Request to update a pickup delivery appointment.																																				

### element PickupApptUpdateRequest/SubmittingParty

diagram	<pre> classDiagram     class mailxml_tmSubmittingParty     class mailxml_defsParticipantIDType {         &lt;&lt;attributes&gt;&gt;         mailxml_defsMailerID6         mailxml_defsMailerID9         mailxml_defsCRID         mailxml_defsSchedulerID         mailxml_defsMaildatUserLicense         mailxml_defsShippingAgentID         mailxml_defsReceivingAgentID     }     mailxml_tmSubmittingParty "1" -- "1" mailxml_defsParticipantIDType   </pre>																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:MailerID6</td><td><b>mailxml_base:mailerID6Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MailerID9</td><td><b>mailxml_base:mailerID9Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:CRID</td><td><b>mailxml_base:CRIDType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatUserLicense</td><td><b>mailxml_base:userLicenseCodeType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShippingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ReceivingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

### element PickupApptUpdateRequest/SubmittingSoftware


diagram	<pre> classDiagram     class mailxml_tmSubmittingSoftware     class mailxml_defsSubmittingSoftwareType {         &lt;&lt;attributes&gt;&gt;         mailxml_defsSoftwareName         mailxml_defsVendor         mailxml_defsVersion         mailxml_defsApprovalDate         mailxml_defsApprovalKey     }     mailxml_tmSubmittingSoftware "1" -- "1" mailxml_defsSubmittingSoftwareType   </pre>
---------	--

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
type	<b>mailxml_defs:submittingSoftwareType</b>					
properties	isRef 0 content complex					
attributes	Name mailxml_defs:SoftwareName	Type <b>xs:string</b>	Use required	Default	Fixed	annotation
	mailxml_defs:Vendor	<b>xs:string</b>	required			
	mailxml_defs:Version	<b>xs:string</b>	required			
	mailxml_defs:ApprovalDate	<b>xs:date</b>				
	mailxml_defs:ApprovalKey	<b>xs:string</b>				

#### element **PickupApptUpdateRequest/SubmitterTrackingID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s20</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

#### element **PickupApptUpdateRequest/ApptBlock**

diagram	
---------	--

namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:pickupApptBlockRequestType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:PickupLocation</a> <a href="#">mailxml_tm:PreferredAppt</a> <a href="#">mailxml_tm:OptionalAppt</a> <a href="#">mailxml_tm:Comment</a> <a href="#">mailxml_tm:TransportationResponsibility</a>

### element PickupApptUpdateRequest/DetailInfo

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:detailInfoType</a>
properties	isRef 0 minOcc 1 maxOcc unbounded content complex
children	<a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:USPSSummary</a> <a href="#">mailxml_tm:ConsigneeContentID</a>

### element PickupApptUpdateResponse

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
properties	content complex

children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:PickupApptUpdateAccept</a> <a href="#">mailxml_tm:PickupApptUpdateReject</a>
annotation	documentation Response to a request to update a pickup delivery appointment.

#### element PickupApptUpdateResponse/TrackingID

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

#### element PickupApptUpdateResponse/SubmitterTrackingID

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

element **PickupApptUpdateResponse/PickupApptUpdateAccept**

diagram	<pre> classDiagram     class PickupApptUpdate {         grp mailxml_tm:PickupRespo...         mailxml_tm:ShipperApptReque...         mailxml_tm:ConsigneeApptID         mailxml_tm:SchedulerCorpID         mailxml_tm:SchedulerID         mailxml_tm:ApptType     }     class ApptInfo     class DetailInfo     class ReturnInfo      PickupApptUpdate "1" --&gt; "3..1" ApptInfo     PickupApptUpdate "1" --&gt; "3..1" DetailInfo     PickupApptUpdate "1" --&gt; "3..1" ReturnInfo </pre>																																				
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																				
properties	<table border="1"> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																
isRef	0																																				
content	complex																																				
children	<a href="#">mailxml_tm:ApptInfo</a> <a href="#">mailxml_tm:DetailInfo</a> <a href="#">mailxml_tm:ReturnInfo</a>																																				
attributes	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:ShipperApptRequestID</td> <td><b>mailxml_base:s12</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:ConsigneeApptID</td> <td><b>mailxml_base:s12</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCorpID</td> <td><b>mailxml_base:s12</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerID</td> <td><b>mailxml_base:s12</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:ApptType</td> <td><b>mailxml_base:apptTypeType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ShipperApptRequestID	<b>mailxml_base:s12</b>	required				mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>	required				mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>	required				mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>	required				mailxml_tm:ApptType	<b>mailxml_base:apptTypeType</b>				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_tm:ShipperApptRequestID	<b>mailxml_base:s12</b>	required																																			
mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>	required																																			
mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>	required																																			
mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>	required																																			
mailxml_tm:ApptType	<b>mailxml_base:apptTypeType</b>																																				

element **PickupApptUpdateResponse/PickupApptUpdateAccept/ApptInfo**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_defs:pickupApptBlockResponseType</b>
properties	isRef 0 content complex
children	<b>mailxml_defs:TrackingID</b> <b>mailxml_defs:ConsigneeApptID</b> <b>mailxml_defs:ConsigneeFacility</b> <b>mailxml_defs:PickupLocation</b> <b>mailxml_defs:ScheduledAppt</b> <b>mailxml_defs:Comment</b> <b>mailxml_defs:TransportationResponsibility</b>

element **PickupApptUpdateResponse/PickupApptUpdateAccept/DetailInfo**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_tm:detailInfoType</b>
properties	isRef 0 content complex

children	<a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:USPSSummary</a> <a href="#">mailxml_tm:ConsigneeContentID</a>
----------	---

element **PickupApptUpdateResponse/PickupApptUpdateAccept/ReturnInfo**

diagram	<pre> classDiagram     class ReturnInfo {         &lt;&lt;mailxml_tm&gt;&gt;         &lt;&lt;0..∞&gt;&gt;     }     class ReturnCode {         &lt;&lt;mailxml_defs&gt;&gt;     }     class ReturnDescription {         &lt;&lt;mailxml_defs&gt;&gt;     }     class errorWarning {         &lt;&lt;mailxml_defs&gt;&gt;     }     class ContainerErrorW... {         &lt;&lt;mailxml_defs&gt;&gt;     }      ReturnInfo "0..∞" *--&gt; ReturnCode     ReturnInfo "0..∞" *--&gt; ReturnDescription     ReturnInfo "0..∞" *--&gt; errorWarning     ReturnInfo "0..∞" *--&gt; ContainerErrorW...   </pre>								
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>								
type	<b>mailxml_defs:basicReturnInfoType</b>								
properties	<table border="1"> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#">mailxml_defs:ReturnCode</a> <a href="#">mailxml_defs:ReturnDescription</a> <a href="#">mailxml_defs:errorWarning</a> <a href="#">mailxml_defs:ContainerErrorWarningBlock</a>								

element **PickupApptUpdateResponse/PickupApptUpdateReject**

diagram	<pre> classDiagram     class PickupApptUpdate... {         &lt;&lt;0..∞&gt;&gt;     }     class grp {         mailxml_tm:PickupRespo...         mailxml_tm:ShipperApptReque...         mailxml_tm:ConsigneeApptID         mailxml_tm:SchedulerCorpID         mailxml_tm:SchedulerID         mailxml_tm:ApptType     }     class ApptInfo     class DetailInfo     class ReturnInfo      PickupApptUpdate... "0..∞" *--&gt; grp     classDiagram         class ApptInfo         class DetailInfo         class ReturnInfo          ApptInfo &lt; -- DetailInfo         DetailInfo "0..∞" *--&gt; ReturnInfo   </pre>
---------	---

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
properties	isRef 0 content complex					
children	<a href="#">mailxml_tm:ApptInfo</a> <a href="#">mailxml_tm:DetailInfo</a> <a href="#">mailxml_tm:ReturnInfo</a>					
attributes	Name	Type	Use	Default	Fixed	annotation
	mailxml_tm:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required			
	mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>	required			
	mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>	required			
	mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>	required			
	mailxml_tm:ApptType	<a href="#">mailxml_base:apptTypeType</a>				

### element PickupApptUpdateResponse/PickupApptUpdateReject/ApptInfo

diagram	<pre> classDiagram     class mailxml_tm.pickupApptBlockRequestType {         mailxml_tm.SubmittingParty         mailxml_tm.SubmittingSoftware         mailxml_tm.CongnneeFacility         mailxml_tm.PickupLocation         mailxml_tm.PreferredAppt         mailxml_tm.OptionalAppt         mailxml_tm.Comment         mailxml_tm.TransportationResponsibility     }     mailxml_tm.ApptInfo --&gt; mailxml_tm.pickupApptBlockRequestType     mailxml_tm.SubmittingParty &lt; -- mailxml_tm.ConsigneeFacility     mailxml_tm.OptionalAppt *--&gt; mailxml_tm.ConsigneeFacility   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:pickupApptBlockRequestType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:PickupLocation</a> <a href="#">mailxml_tm:PreferredAppt</a> <a href="#">mailxml_tm:OptionalAppt</a> <a href="#">mailxml_tm:Comment</a> <a href="#">mailxml_tm:TransportationResponsibility</a>

element PickupApptUpdateResponse/PickupApptUpdateReject/DetailInfo

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:detailInfoType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:USPSSummary</a> <a href="#">mailxml_tm:ConsigneeContentID</a>

element PickupApptUpdateResponse/PickupApptUpdateReject/ReturnInfo

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_defs:basicReturnInfoType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_defs:ReturnCode</a> <a href="#">mailxml_defs:ReturnDescription</a> <a href="#">mailxml_defs:errorWarning</a> <a href="#">mailxml_defs:ContainerErrorW...</a>

## element RecurringApptQueryRequest

diagram	<pre> classDiagram     class RecurringApptQueryRequest {         grp mailxml_tm:RecurringApp...         mailxml_tm:CreatorSchedulerID         mailxml_tm:CreatorSchedulerC...         mailxml_tm:CreatorSchedulerC...         mailxml_tm:RecurringApptStatus         mailxml_tm:RecurringApptID         mailxml_tm:RetrieveContentUp...         mailxml_tm:RetrieveContentUp...     }     class SubmittingParty     class SubmittingSoftware     class SubmitterTrackingID     class ConsigneeFacility      RecurringApptQueryRequest "1" --&gt; "0..∞" SubmittingParty     RecurringApptQueryRequest "1" --&gt; "0..∞" SubmittingSoftware     RecurringApptQueryRequest "1" --&gt; "0..∞" SubmitterTrackingID     RecurringApptQueryRequest "1" --&gt; "0..∞" ConsigneeFacility   </pre>																																																
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																																
properties	content complex																																																
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:ConsigneeFacility</a>																																																
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:CreatorSchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:CreatorSchedulerCorpID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:CreatorSchedulerCRID</td> <td><a href="#">mailxml_base:CRIDType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:RecurringApptStatus</td> <td><a href="#">mailxml_base:recurringStatusType</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:RecurringApptID</td> <td><a href="#">mailxml_base:s08</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:RetrieveContentUpdatedStartDate</td> <td><a href="#">xs:date</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:RetrieveContentUpdatedEndDate</td> <td><a href="#">xs:date</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:CreatorSchedulerID	<a href="#">mailxml_base:s12</a>					mailxml_tm:CreatorSchedulerCorpID	<a href="#">mailxml_base:s12</a>					mailxml_tm:CreatorSchedulerCRID	<a href="#">mailxml_base:CRIDType</a>					mailxml_tm:RecurringApptStatus	<a href="#">mailxml_base:recurringStatusType</a>	required				mailxml_tm:RecurringApptID	<a href="#">mailxml_base:s08</a>					mailxml_tm:RetrieveContentUpdatedStartDate	<a href="#">xs:date</a>					mailxml_tm:RetrieveContentUpdatedEndDate	<a href="#">xs:date</a>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_tm:CreatorSchedulerID	<a href="#">mailxml_base:s12</a>																																																
mailxml_tm:CreatorSchedulerCorpID	<a href="#">mailxml_base:s12</a>																																																
mailxml_tm:CreatorSchedulerCRID	<a href="#">mailxml_base:CRIDType</a>																																																
mailxml_tm:RecurringApptStatus	<a href="#">mailxml_base:recurringStatusType</a>	required																																															
mailxml_tm:RecurringApptID	<a href="#">mailxml_base:s08</a>																																																
mailxml_tm:RetrieveContentUpdatedStartDate	<a href="#">xs:date</a>																																																
mailxml_tm:RetrieveContentUpdatedEndDate	<a href="#">xs:date</a>																																																
annotation	documentation Query request for recurring appointment information.																																																

### element RecurringApptQueryRequest/SubmittingParty

diagram	<pre> classDiagram     class mailxml_tmSubmittingParty     class mailxml_defsParticipantIDType {         &lt;&lt;attributes&gt;&gt;         mailxml_defsMailerID6         mailxml_defsMailerID9         mailxml_defsCRID         mailxml_defsSchedulerID         mailxml_defsMaildatUserLicense         mailxml_defsShippingAgentID         mailxml_defsReceivingAgentID     }     mailxml_tmSubmittingParty "1" -- "1" mailxml_defsParticipantIDType   </pre>																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:MailerID6</td><td><b>mailxml_base:mailerID6Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MailerID9</td><td><b>mailxml_base:mailerID9Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:CRID</td><td><b>mailxml_base:CRIDType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatUserLicense</td><td><b>mailxml_base:userLicenseCodeType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShippingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ReceivingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

### element RecurringApptQueryRequest/SubmittingSoftware


diagram	<pre> classDiagram     class mailxml_tmSubmittingSoftware     class mailxml_defsSubmittingSoftwareType {         &lt;&lt;attributes&gt;&gt;         mailxml_defsSoftwareName         mailxml_defsVendor         mailxml_defsVersion         mailxml_defsApprovalDate         mailxml_defsApprovalKey     }     mailxml_tmSubmittingSoftware "1" -- "1" mailxml_defsSubmittingSoftwareType   </pre>
---------	--

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
type	<b>mailxml_defs:submittingSoftwareType</b>					
properties	isRef 0 content complex					
attributes	Name mailxml_defs:SoftwareName	Type <b>xs:string</b>	Use required	Default	Fixed	annotation
	mailxml_defs:Vendor	<b>xs:string</b>	required			
	mailxml_defs:Version	<b>xs:string</b>	required			
	mailxml_defs:ApprovalDate	<b>xs:date</b>				
	mailxml_defs:ApprovalKey	<b>xs:string</b>				

#### element RecurringApptQueryRequest/SubmitterTrackingID

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s20</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

#### element RecurringApptQueryRequest/ConsigneeFacility

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_defs:consigneeFacilityType</b>

properties	isRef 0 minOcc 0 maxOcc unbounded content complex
children	<a href="#">mailxml_defs:CompanyName</a> <a href="#">mailxml_defs:FacilityNumber</a> <a href="#">mailxml_defs:FacilityAddress</a> <a href="#">mailxml_defs:FacilityAddress</a> <a href="#">mailxml_defs:FacilityName</a> <a href="#">mailxml_defs:FacilityType</a> <a href="#">mailxml_defs:URL</a> <a href="#">mailxml_defs:CommonContact</a>

### element RecurringApptQueryResponse

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
properties	content complex
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:QueryResults</a> <a href="#">mailxml_tm:QueryError</a>
annotation	documentation Response to the query for recurring appointment information.

### element RecurringApptQueryResponse/TrackingID


diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_base:s20</a>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

### element RecurringApptQueryResponse/SubmitterTrackingID

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_base:s20</a>
properties	isRef 0 minOcc 0 maxOcc 1 content simple

facets	Kind minLength maxLength whiteSpace	Value 1 20 preserve	annotation
--------	--	------------------------------	------------

element RecurringApptQueryResponse/QueryResults


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:RecurringApptBlock</a> <a href="#">mailxml_tm:ReturnInfo</a>

element RecurringApptQueryResponse/QueryResults/RecurringApptBlock


diagram	<pre> classDiagram     class mailxml_tm:recurringApptBlockType {         mailxml_tm:CreatorSchedulerID         mailxml_tm:CreatorSchedulerC...         mailxml_tm:CreatorSchedulerC...         mailxml_tm:RecurringApptID         mailxml_tm:ApptType         mailxml_tm:RecurringApptStatus         mailxml_tm:RetrieveContentUp...         mailxml_tm:RetrieveContentUp...     }     class mailxml_tm:RecurringApptBlock     class mailxml_tm:ConsigneeFacility     class mailxml_tm:RecurringData     class mailxml_tm:RecurringApptStatus     class mailxml_tm:USPSSummary     class mailxml_tm:PostalClass     class mailxml_tm:ReturnInfo      mailxml_tm:RecurringApptBlock "1..∞" --&gt; mailxml_tm:recurringApptBlockType     mailxml_tm:recurringApptBlockType "0..∞" --&gt; mailxml_tm:USPSSummary     mailxml_tm:recurringApptBlockType "1..∞" --&gt; mailxml_tm:PostalClass     mailxml_tm:recurringApptBlockType "0..∞" --&gt; mailxml_tm:ReturnInfo   </pre>																																				
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																				
type	<a href="#">mailxml_tm:recurringApptBlockType</a>																																				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>1</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	1	maxOcc	unbounded	content	complex																												
isRef	0																																				
minOcc	1																																				
maxOcc	unbounded																																				
content	complex																																				
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:RecurringData</a> <a href="#">mailxml_tm:RecurringApptStatus</a> <a href="#">mailxml_tm:USPSSummary</a> <a href="#">mailxml_tm:PostalClass</a> <a href="#">mailxml_tm:ReturnInfo</a>																																				
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:CreatorSchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:CreatorSchedulerCorpID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:CreatorSchedulerCRID</td> <td><a href="#">mailxml_base:CRIDType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:RecurringApptID</td> <td><a href="#">mailxml_base:s08</a></td> <td></td> <td></td> <td>required</td> <td></td> </tr> <tr> <td>mailxml_tm:ApptType</td> <td><a href="#">mailxml_base:apptTypeType</a></td> <td></td> <td></td> <td>required</td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:CreatorSchedulerID	<a href="#">mailxml_base:s12</a>					mailxml_tm:CreatorSchedulerCorpID	<a href="#">mailxml_base:s12</a>					mailxml_tm:CreatorSchedulerCRID	<a href="#">mailxml_base:CRIDType</a>					mailxml_tm:RecurringApptID	<a href="#">mailxml_base:s08</a>			required		mailxml_tm:ApptType	<a href="#">mailxml_base:apptTypeType</a>			required	
Name	Type	Use	Default	Fixed	annotation																																
mailxml_tm:CreatorSchedulerID	<a href="#">mailxml_base:s12</a>																																				
mailxml_tm:CreatorSchedulerCorpID	<a href="#">mailxml_base:s12</a>																																				
mailxml_tm:CreatorSchedulerCRID	<a href="#">mailxml_base:CRIDType</a>																																				
mailxml_tm:RecurringApptID	<a href="#">mailxml_base:s08</a>			required																																	
mailxml_tm:ApptType	<a href="#">mailxml_base:apptTypeType</a>			required																																	

	mailxml_tm:RecurringApptStatus mailxml_tm:RetrieveContentUpdatedStartD ate mailxml_tm:RetrieveContentUpdatedEndD ate	<b>mailxml_base:recurringStatusTy pe</b> <b>xs:date</b> <b>xs:date</b>	d require d
--	--	--	-------------------


#### element RecurringApptQueryResponse/QueryResults/ReturnInfo

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>mailxml_defs:basicReturnInfoType</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<b>mailxml_defs:ReturnCode</b> <b>mailxml_defs:ReturnDescription</b> <b>mailxml_defs:errorWarning</b> <b>mailxml_defs:ContainerErrorWarningBlock</b>								

#### element RecurringApptQueryResponse/QueryError

diagram					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm				
type	<b>mailxml_defs:queryErrorType</b>				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex
isRef	0				
content	complex				
children	<b>mailxml_defs:ReturnInfo</b>				

#### element ScheduledAppt

diagram	
---------	---


namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>xs:dateTime</b>
properties	content simple
used by	complexTypes <a href="#">apptBlockGoodsType</a> <a href="#">apptInfoType</a>

### element **StaleContentDelivery**


diagram	<pre> graph TD     SD[StaleContentDelivery] --&gt; Attr[attributes]     SD --&gt; LargeTrans[grp mailxml_defs:LargeTrans...]     SD --&gt; SP[mailxml_tm:SubmittingParty]     SD --&gt; SS[mailxml_tm:SubmittingSoftware]     SD --&gt; DR[mailxml_defs:DataRecipient]     SD --&gt; PMI[mailxml_tm:PushMessageID]     SD --&gt; DS[mailxml_tm:DeliverySummary]      Attr --&gt; C1[grp mailxml_tm:DeliveryConte...]     Attr --&gt; C2[grp mailxml_tm:DeliveryConte...]     Attr --&gt; C3[grp mailxml_tm:DeliveryConte...]     Attr --&gt; C4[grp mailxml_tm:DeliveryConte...]      C1 --&gt; CA1[mailxml_tm:ConsigneeApptID]     C1 --&gt; CS1[mailxml_tm:SchedulerID]     C1 --&gt; CS2[mailxml_tm:SchedulerCorpID]     C1 --&gt; CS3[mailxml_tm:SchedulerCRID]      C2 --&gt; CMG[mailxml_defs:MessageGroupID]     C2 --&gt; TMC[mailxml_defs:TotalMessageCou...]     C2 --&gt; MSMN[mailxml_defs:MessageSerialNu...]     C2 --&gt; TRR[mailxml_defs:TransmittedRecor...]     C2 --&gt; TRA[mailxml_defs:TotalRecordsAcro...]     C2 --&gt; LM[mailxml_defs:LastMessage]      C3 --&gt; SP     C3 --&gt; SS     C3 --&gt; DR     C3 --&gt; PMI     C3 --&gt; DS   </pre> <p>Push from USPS to Customer with the Stale Content Data.</p>												
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>												
properties	content complex												
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_defs:DataRecipient</a> <a href="#">mailxml_tm:PushMessageID</a> <a href="#">mailxml_tm:DeliverySummary</a>												
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:ConsigneeApptID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>				
Name	Type	Use	Default	Fixed	annotation								
mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>												

	mailxml_tm:SchedulerID mailxml_tm:SchedulerCorpID mailxml_tm:SchedulerCRID mailxml_defs:MessageGroupID mailxml_defs:TotalMessageCount mailxml_defs:MessageSerialNumber mailxml_defs:TransmittedRecordCount mailxml_defs:TotalRecordsAcrossMessages mailxml_defs:LastMessage	<b>mailxml_base:s12</b> <b>mailxml_base:s12</b> <b>mailxml_base:CRIDType</b> <b>mailxml_base:s20</b> optional <b>xs:positiveInteger</b> optional <b>xs:positiveInteger</b> optional <b>xs:positiveInteger</b> optional <b>xs:positiveInteger</b> optional <b>mailxml_base:yesNo</b> optional No
annotation	documentation Push from USPS to Customer with the Stale Content Data.	

### element **StaleContentDelivery/SubmittingParty**

diagram																																																	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	isRef 0 minOcc 0 maxOcc 1 content complex																																																
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:MailerID6</td> <td><b>mailxml_base:mailerID6Type</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MailerID9</td> <td><b>mailxml_base:mailerID9Type</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:CRID</td> <td><b>mailxml_base:CRIDType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MaildatUserLicense</td> <td><b>mailxml_base:userLicenseCodeType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ShippingAgentID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ReceivingAgentID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																


element **StaleContentDelivery/SubmittingSoftware**

diagram																																					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																				
type	<b>mailxml_defs:submittingSoftwareType</b>																																				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex																												
isRef	0																																				
minOcc	0																																				
maxOcc	1																																				
content	complex																																				
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:SoftwareName</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td></tr> <tr> <td>mailxml_defs:Vendor</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td></tr> <tr> <td>mailxml_defs:Version</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td></tr> <tr> <td>mailxml_defs:ApprovalDate</td> <td><b>xs:date</b></td> <td></td> <td></td> <td></td> <td></td></tr> <tr> <td>mailxml_defs:ApprovalKey</td> <td><b>xs:string</b></td> <td></td> <td></td> <td></td> <td></td></tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SoftwareName	<b>xs:string</b>	required				mailxml_defs:Vendor	<b>xs:string</b>	required				mailxml_defs:Version	<b>xs:string</b>	required				mailxml_defs:ApprovalDate	<b>xs:date</b>					mailxml_defs:ApprovalKey	<b>xs:string</b>				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_defs:SoftwareName	<b>xs:string</b>	required																																			
mailxml_defs:Vendor	<b>xs:string</b>	required																																			
mailxml_defs:Version	<b>xs:string</b>	required																																			
mailxml_defs:ApprovalDate	<b>xs:date</b>																																				
mailxml_defs:ApprovalKey	<b>xs:string</b>																																				


element **StaleContentDelivery/PushMessageID**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s25</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td></tr> <tr> <td>maxLength</td> <td>25</td> <td></td></tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td></tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	25		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	25												
whiteSpace	preserve												

### element StaleContentDelivery/DeliverySummary


diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_tm:deliverySummaryType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>1</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	1	maxOcc	unbounded	content	complex
isRef	0								
minOcc	1								
maxOcc	unbounded								
content	complex								
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ContentDetailInfo</a>								

### element StaleContentNotification


diagram							
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm						
properties	content complex						
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:PushMessageID</a> <a href="#">mailxml_tm:NotificationDate</a> <a href="#">mailxml_tm:StaleContentNotificationElement</a>						
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> </table>	Name	Type	Use	Default	Fixed	annotation
Name	Type	Use	Default	Fixed	annotation		

	mailxml_tm:ConsigneeApptID <b>mailxml_base:s12</b> mailxml_tm:SchedulerID <b>mailxml_base:s12</b> mailxml_tm:SchedulerCorpID <b>mailxml_base:s12</b> mailxml_tm:SchedulerCRID <b>mailxml_base:CRIDType</b>
annotation	documentation Notification from USPS to customer informing that stale content exist which will be deleted in 90 days.


### element **StaleContentNotification/SubmittingParty**

diagram																																																	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex																																								
isRef	0																																																
minOcc	0																																																
maxOcc	1																																																
content	complex																																																
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:MailerID6</td> <td><b>mailxml_base:mailerID6Type</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MailerID9</td> <td><b>mailxml_base:mailerID9Type</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:CRID</td> <td><b>mailxml_base:CRIDType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MaildatUserLicense</td> <td><b>mailxml_base:userLicenseCodeType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ShippingAgentID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ReceivingAgentID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

### element StaleContentNotification/SubmittingSoftware

diagram																																					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																				
type	<b>mailxml_defs:submittingSoftwareType</b>																																				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex																												
isRef	0																																				
minOcc	0																																				
maxOcc	1																																				
content	complex																																				
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:SoftwareName</td><td><b>xs:string</b></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:Vendor</td><td><b>xs:string</b></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:Version</td><td><b>xs:string</b></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ApprovalDate</td><td><b>xs:date</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ApprovalKey</td><td><b>xs:string</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SoftwareName	<b>xs:string</b>	required				mailxml_defs:Vendor	<b>xs:string</b>	required				mailxml_defs:Version	<b>xs:string</b>	required				mailxml_defs:ApprovalDate	<b>xs:date</b>					mailxml_defs:ApprovalKey	<b>xs:string</b>				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_defs:SoftwareName	<b>xs:string</b>	required																																			
mailxml_defs:Vendor	<b>xs:string</b>	required																																			
mailxml_defs:Version	<b>xs:string</b>	required																																			
mailxml_defs:ApprovalDate	<b>xs:date</b>																																				
mailxml_defs:ApprovalKey	<b>xs:string</b>																																				

### element StaleContentNotification/PushMessageID

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s25</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>25</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	25		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	25												
whiteSpace	preserve												

### element StaleContentNotification/NotificationDate

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm

type	<b>xs:date</b>
properties	isRef 0 content simple

**element StaleContentNotification/StaleContentNotificationElement**

diagram	<pre> classDiagram     class mailxml_tm::StaleContentNotificationElement {         &lt;&lt;StaleContentNotification&gt;&gt;     }     class mailxml_tm::staleContentNotificationElementType {         &lt;&lt;staleContentNotificationElement&gt;&gt;     }     mailxml_tm::StaleContentNotificationElement "1..∞" --&gt; mailxml_tm::staleContentNotificationElementType     mailxml_tm::staleContentNotificationElementType "mailxml_tm::ConsigneeFacility"     mailxml_tm::staleContentNotificationElementType "mailxml_tm::ConsigneeContentID"     mailxml_tm::staleContentNotificationElementType "mailxml_tm::NumberOfDaysStale"     mailxml_tm::staleContentNotificationElementType "mailxml_tm::DestinationEntry"   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#"><b>mailxml_tm:staleContentNotificationElementType</b></a>
properties	isRef 0 minOcc 1 maxOcc unbounded content complex
children	<a href="#"><b>mailxml_tm:ConsigneeFacility</b></a> <a href="#"><b>mailxml_tm:ConsigneeContentID</b></a> <a href="#"><b>mailxml_tm:NumberOfDaysStale</b></a> <a href="#"><b>mailxml_tm:DestinationEntry</b></a>


element **StaleContentQueryRequest**

diagram	<pre> classDiagram     class StaleContentQueryRequest {         &lt;&lt;Query request for stale delivery content.&gt;&gt;         mailxml_tm:DeliveryContentID         mailxml_tm:ConsigneeApptID         mailxml_tm:SchedulerID         mailxml_tm:SchedulerCorpID         mailxml_tm:SchedulerCRID         mailxml_tm:SchedulerContentID         mailxml_tm:ConsigneeContentID         mailxml_tm:RetrieveContentUpdatedStartDate         mailxml_tm:RetrieveContentUpdatedEndDate         mailxml_tm:SubmittingParty         mailxml_tm:SubmittingSoftware         mailxml_tm:SubmitterTrackingID         mailxml_tm:ConsigneeFacility         mailxml_tm:DestinationEntry         mailxml_tm:NumberOfDaysStale         mailxml_tm:RequestContentIDOnly     }     StaleContentQueryRequest "1" -- "*" :&gt; "mailxml_tm:SubmittingParty"     StaleContentQueryRequest "1" -- "*" :&gt; "mailxml_tm:SubmittingSoftware"     StaleContentQueryRequest "1" -- "*" :&gt; "mailxml_tm:SubmitterTrackingID"     StaleContentQueryRequest "1" -- "*" :&gt; "mailxml_tm:ConsigneeFacility"     StaleContentQueryRequest "1" -- "*" :&gt; "mailxml_tm:DestinationEntry"     StaleContentQueryRequest "1" -- "*" :&gt; "mailxml_tm:NumberOfDaysStale"     StaleContentQueryRequest "1" -- "*" :&gt; "mailxml_tm:RequestContentIDOnly" </pre>																																																						
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																																						
properties	content complex																																																						
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:NumberOfDaysStale</a> <a href="#">mailxml_tm:RequestContentIDOnly</a>																																																						
attributes	<table> <thead> <tr> <th>Name</th><th>Type</th><th>Use</th><th>Default</th><th>Fixed</th><th>annotation</th></tr> </thead> <tbody> <tr> <td>mailxml_tm:ConsigneeApptID</td><td><a href="#">mailxml_base:s12</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:SchedulerID</td><td><a href="#">mailxml_base:s12</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:SchedulerCorpID</td><td><a href="#">mailxml_base:s12</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:SchedulerCRID</td><td><a href="#">mailxml_base:CRIDType</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:SchedulerContentID</td><td><a href="#">mailxml_base:s12</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:ConsigneeContentID</td><td><a href="#">mailxml_base:s12</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:RetrieveContentUpdatedStartDate</td><td><a href="#">xs:date</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:RetrieveContentUpdatedEndDate</td><td><a href="#">xs:date</a></td><td></td><td></td><td></td><td></td></tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>					mailxml_tm:SchedulerContentID	<a href="#">mailxml_base:s12</a>					mailxml_tm:ConsigneeContentID	<a href="#">mailxml_base:s12</a>					mailxml_tm:RetrieveContentUpdatedStartDate	<a href="#">xs:date</a>					mailxml_tm:RetrieveContentUpdatedEndDate	<a href="#">xs:date</a>				
Name	Type	Use	Default	Fixed	annotation																																																		
mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>																																																						
mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>																																																						
mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>																																																						
mailxml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>																																																						
mailxml_tm:SchedulerContentID	<a href="#">mailxml_base:s12</a>																																																						
mailxml_tm:ConsigneeContentID	<a href="#">mailxml_base:s12</a>																																																						
mailxml_tm:RetrieveContentUpdatedStartDate	<a href="#">xs:date</a>																																																						
mailxml_tm:RetrieveContentUpdatedEndDate	<a href="#">xs:date</a>																																																						
annotation	documentation Query request for stale delivery content.																																																						

element **StaleContentQueryRequest/SubmittingParty**

diagram	<pre> classDiagram     participantIDType "7" as mailxml_defs:participantIDType     submittingParty "4" as mailxml_tm:SubmittingParty     mailerID6     mailerID9     CRID     SchedulerID     MaildatUserLicense     ShippingAgentID     ReceivingAgentID      mailxml_tm:SubmittingParty "4" --&gt; "7" mailxml_defs:participantIDType     participantIDType "7" &lt; -- mailerID6     participantIDType "7" &lt; -- mailerID9     participantIDType "7" &lt; -- CRID     participantIDType "7" &lt; -- SchedulerID     participantIDType "7" &lt; -- MaildatUserLicense     participantIDType "7" &lt; -- ShippingAgentID     participantIDType "7" &lt; -- ReceivingAgentID   </pre>																																																
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td><td>0</td> </tr> <tr> <td>content</td><td>complex</td> </tr> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailerID6</td> <td><b>mailxml_base:mailerID6Type</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailerID9</td> <td><b>mailxml_base:mailerID9Type</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>CRID</td> <td><b>mailxml_base:CRIDType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>SchedulerID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>MaildatUserLicense</td> <td><b>mailxml_base:userLicenseCodeType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>ShippingAgentID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>ReceivingAgentID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailerID6	<b>mailxml_base:mailerID6Type</b>					mailerID9	<b>mailxml_base:mailerID9Type</b>					CRID	<b>mailxml_base:CRIDType</b>					SchedulerID	<b>mailxml_base:s12</b>					MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					ShippingAgentID	<b>mailxml_base:s12</b>					ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailerID9	<b>mailxml_base:mailerID9Type</b>																																																
CRID	<b>mailxml_base:CRIDType</b>																																																
SchedulerID	<b>mailxml_base:s12</b>																																																
MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
ShippingAgentID	<b>mailxml_base:s12</b>																																																
ReceivingAgentID	<b>mailxml_base:s12</b>																																																

element **StaleContentQueryRequest/SubmittingSoftware**

diagram																																					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																				
type	<b>mailxml_defs:submittingSoftwareType</b>																																				
properties	isRef 0 content complex																																				
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:SoftwareName</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Vendor</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Version</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalDate</td> <td><b>xs:date</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalKey</td> <td><b>xs:string</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SoftwareName	<b>xs:string</b>	required				mailxml_defs:Vendor	<b>xs:string</b>	required				mailxml_defs:Version	<b>xs:string</b>	required				mailxml_defs:ApprovalDate	<b>xs:date</b>					mailxml_defs:ApprovalKey	<b>xs:string</b>				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_defs:SoftwareName	<b>xs:string</b>	required																																			
mailxml_defs:Vendor	<b>xs:string</b>	required																																			
mailxml_defs:Version	<b>xs:string</b>	required																																			
mailxml_defs:ApprovalDate	<b>xs:date</b>																																				
mailxml_defs:ApprovalKey	<b>xs:string</b>																																				

element **StaleContentQueryRequest/SubmitterTrackingID**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	isRef 0 minOcc 0 maxOcc 1 content simple												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

### element StaleContentQueryRequest/ConsigneeFacility

diagram	<pre> classDiagram     class mailxml_tm_ConsigneeFacility     class mailxml_defs_CompanyName     class mailxml_defs_FacilityNumber     class mailxml_defs_FacilityAddress     class mailxml_defs_FacilityName     class mailxml_defs_FacilityType     class mailxml_defs_URL     class mailxml_defs_CommonContact      mailxml_tm_ConsigneeFacility --&gt; mailxml_defs_CompanyName     mailxml_tm_ConsigneeFacility --&gt; mailxml_defs_FacilityNumber     mailxml_tm_ConsigneeFacility --&gt; mailxml_defs_FacilityAddress     mailxml_tm_ConsigneeFacility --&gt; mailxml_defs_FacilityName     mailxml_tm_ConsigneeFacility --&gt; mailxml_defs_FacilityType     mailxml_tm_ConsigneeFacility --&gt; mailxml_defs_URL     mailxml_tm_ConsigneeFacility --&gt; mailxml_defs_CommonContact   </pre>								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>mailxml_defs:consigneeFacilityType</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<b>mailxml_defs:CompanyName</b> <b>mailxml_defs:FacilityNumber</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityName</b> <b>mailxml_defs:FacilityType</b> <b>mailxml_defs:URL</b> <b>mailxml_defs:CommonContact</b>								

### element StaleContentQueryRequest/DestinationEntry


diagram	<pre> classDiagram     class mailxml_tm_DestinationEntry   </pre>									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm									
type	<b>mailxml_base:yesNo</b>									
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	content	simple					
isRef	0									
content	simple									
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>enumeration</td><td>Yes</td><td></td></tr> <tr> <td>enumeration</td><td>No</td><td></td></tr> </table>	Kind	Value	annotation	enumeration	Yes		enumeration	No	
Kind	Value	annotation								
enumeration	Yes									
enumeration	No									

### element StaleContentQueryRequest/NumberOfDaysStale

diagram	<pre> classDiagram     class mailxml_tm_NumberOfDaysStale   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:ns02</b>
properties	isRef 0

	minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation pattern [0-9]{2}

element **StaleContentQueryRequest/RequestContentIDOnly**


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple default Yes
facets	Kind Value annotation enumeration Yes enumeration No

element **StaleContentQueryResponse**

diagram	<pre> classDiagram     class StaleContentQueryResponse {         &lt;&lt;Response to the Query request for stale delivery content.&gt;&gt;         mailxml_tm:DeliveryContentID         mailxml_tm:ConsigneeApptID         mailxml_tm:SchedulerID         mailxml_tm:SchedulerCorpID         mailxml_tm:SchedulerCRID         mailxml_tm:SchedulerContentID         mailxml_tm:ConsigneeContentID         mailxml_tm:RetrieveContentUp...         mailxml_tm:RetrieveContentUp...         mailxml_tm:MessageGroupID         mailxml_tm:TotalMessageCount         mailxml_tm:MessageSerialNumber         mailxml_tm:TransmittedRecords         mailxml_tm&gt;TotalRecordsAcrossAll         mailxml_tm&gt;LastMessage         mailxml_tm:TrackingID         mailxml_tm:SubmitterTrackingID         mailxml_tm:QueryResults         mailxml_tm:QueryError     } </pre>																																				
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																				
properties	content complex																																				
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:QueryResults</a> <a href="#">mailxml_tm:QueryError</a>																																				
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:ConsigneeApptID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCorpID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCRID</td> <td><a href="#">mailxml_base:CRIDType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerContentID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>					mailxml_tm:SchedulerContentID	<a href="#">mailxml_base:s12</a>				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>																																				
mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>																																				
mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>																																				
mailxml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>																																				
mailxml_tm:SchedulerContentID	<a href="#">mailxml_base:s12</a>																																				

	mailxml_tm:ConsigneeContentID	<b>mailxml_base:s12</b>		
	mailxml_tm:RetrieveContentUpdatedStartDate	<b>xs:date</b>		
	mailxml_tm:RetrieveContentUpdatedEndDate	<b>xs:date</b>		
	mailxml_defs:MessageGroupID	<b>mailxml_base:s20</b>	optional	
	mailxml_defs:TotalMessageCount	<b>xs:positiveInteger</b>	optional	
	mailxml_defs:MessageSerialNumber	<b>xs:positiveInteger</b>	optional	
	mailxml_defs:TransmittedRecordCount	<b>xs:positiveInteger</b>	optional	
	mailxml_defs:TotalRecordsAcrossMessages	<b>xs:positiveInteger</b>	optional	
	mailxml_defs>LastMessage	<b>mailxml_base:yesNo</b>	optional	No
annotation	documentation Response to the Query request for stale delivery content.			


#### element **StaleContentQueryResponse/TrackingID**

diagram	 mailxml_tm:TrackingID												
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>20</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												


#### element **StaleContentQueryResponse/SubmitterTrackingID**

diagram	 mailxml_tm:SubmitterTrackingID												
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>20</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

element **StaleContentQueryResponse/QueryResults**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
properties	isRef 0 content complex
children	<a href="#">mailxml_defs:LargeTransactionDividerResult</a> <a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:ReturnInfo</a> <a href="#">mailxml_tm:ContentDetailInfo</a> <a href="#">mailxml_tm:ConsigneeContentID</a>

element **StaleContentQueryResponse/QueryResults/ConsigneeFacility**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_defs:consigneeFacilityType</b>
properties	isRef 0 minOcc 0 maxOcc 1 content complex
children	<a href="#">mailxml_defs:CompanyName</a> <a href="#">mailxml_defs:FacilityNumber</a> <a href="#">mailxml_defs:FacilityAddress</a> <a href="#">mailxml_defs:FacilityAddress</a> <a href="#">mailxml_defs:FacilityName</a> <a href="#">mailxml_defs:FacilityType</a> <a href="#">mailxml_defs:URL</a> <a href="#">mailxml_defs:CommonContact</a>

element **StaleContentQueryResponse/QueryResults/ReturnInfo**


diagram	<pre> classDiagram     class mailxml_tm::ReturnInfo     class mailxml_tm::DestinationEntry     class mailxml_tm::ErrorWarning     class mailxml_tm::ContainerErrorWarningBlock     class mailxml_defs::ConsigneeFacility      mailxml_tm::ReturnInfo "0..∞" *-- "0..∞" mailxml_tm::DestinationEntry     mailxml_tm::ReturnInfo "0..∞" *-- "0..∞" mailxml_tm::ErrorWarning     mailxml_tm::ReturnInfo "0..∞" *-- "0..∞" mailxml_tm::ContainerErrorWarningBlock     mailxml_tm::ReturnInfo "0..∞" *-- "0..∞" mailxml_defs::ConsigneeFacility   </pre>								
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>								
type	<b>mailxml_defs:returnInfoType</b>								
properties	<table border="1"> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<b>mailxml_defs:ConsigneeFacility</b> <b>mailxml_tm:ErrorWarning</b> <b>mailxml_tm:ContainerErrorWarningBlock</b>								

element **StaleContentQueryResponse/QueryResults/ContentDetailInfo**


diagram	<pre> classDiagram     class mailxml_tm::ContentDetailInfo     class mailxml_tm::LogisticsSchedulerID     class mailxml_tm::DestinationEntry     class mailxml_tm::ShipperContainerGroup     class mailxml_tm::ConsigneeContainerGroup     class mailxml_tm::ShipperGroupingID     class mailxml_tm::ScheduledInductionDate     class mailxml_tm::NumberOfDaysStale     class mailxml_tm::MaildatSummary     class mailxml_tm::ContentUSPSSummary      mailxml_tm::ContentDetailInfo "1..∞" *-- "1..∞" mailxml_tm::LogisticsSchedulerID     mailxml_tm::ContentDetailInfo "1..∞" *-- "1..∞" mailxml_tm::DestinationEntry     mailxml_tm::DestinationEntry "1..∞" *-- "1..∞" mailxml_tm::ShipperContainerGroup     mailxml_tm::DestinationEntry "1..∞" *-- "1..∞" mailxml_tm::ConsigneeContainerGroup     mailxml_tm::DestinationEntry "1..∞" *-- "1..∞" mailxml_tm::ShipperGroupingID     mailxml_tm::DestinationEntry "1..∞" *-- "1..∞" mailxml_tm::ScheduledInductionDate     mailxml_tm::DestinationEntry "1..∞" *-- "1..∞" mailxml_tm::NumberOfDaysStale     mailxml_tm::ContentDetailInfo "1..∞" *-- "1..∞" mailxml_tm::MaildatSummary     mailxml_tm::ContentDetailInfo "1..∞" *-- "1..∞" mailxml_tm::ContentUSPSSummary   </pre>
---------	---

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
type	<a href="#">mailxml_tm:contentDetailInfoType</a>					
properties	isRef 0 minOcc 1 maxOcc unbounded content complex					
children	<a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:ScheduledInductionDate</a> <a href="#">mailxml_tm:NumberOfDaysStale</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:ContentUSPSSummary</a>					
attributes	Name <a href="#">mailxml_tm:LogisticsSchedulerID</a> <a href="#">mailxml_tm:LogisticsCorpID</a> <a href="#">mailxml_tm:LogisticsSchedulerCRID</a>	Type <a href="#">mailxml_base:s12</a> <a href="#">mailxml_base:s12</a> <a href="#">mailxml_base:CRIDType</a>	Use	Default	Fixed	annotation

#### element StaleContentQueryResponse/QueryResults/ConsigneeContentID

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_base:s12</a>
properties	isRef 0 minOcc 1 maxOcc unbounded content simple
facets	Kind Value annotation minLength 1 maxLength 12 whiteSpace preserve

#### element StaleContentQueryResponse/QueryError

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_defs:queryErrorType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_defs:ReturnInfo</a>

## element UnscheduledConsigneeGoodsReceipt

diagram	<pre> classDiagram     class UnscheduledConsigneeGoodsReceipt {         mailxml_tm:ConsigneeApptID         mailxml_tm:SchedulerID         mailxml_tm:SchedulerCorpID         mailxml_tm:SchedulerCRID         mailxml_tm:ApptType     }     UnscheduledConsigneeGoodsReceipt "0..∞" --&gt; ApptBlockUnscheduledGoodsReceipt     UnscheduledConsigneeGoodsReceipt "0..∞" --&gt; DetailInfo     UnscheduledConsigneeGoodsReceipt --&gt; TrailerInfo     UnscheduledConsigneeGoodsReceipt --&gt; ReturnInfo     note over UnscheduledConsigneeGoodsReceipt: A report or message indicating delivery closeout status for an unscheduled delivery.   </pre>																																				
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																				
properties	content complex																																				
children	<a href="#">mailxml_tm:ApptBlockUnscheduledGoodsReceipt</a> <a href="#">mailxml_tm:DetailInfo</a> <a href="#">mailxml_tm:TrailerInfo</a> <a href="#">mailxml_tm:ReturnInfo</a>																																				
used by	element <a href="#">AllApptCloseoutResponse/AllDeliveryApptCloseoutAccept</a> complexType <a href="#">allDeliveryApptCloseoutAcceptType</a>																																				
attributes	<table border="0"> <tr> <td>Name</td> <td>Type</td> <td>Use</td> <td>Default</td> <td>Fixed</td> <td>annotation</td> </tr> <tr> <td>mailxml_tm:ConsigneeApptID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCorpID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCRID</td> <td><a href="#">mailxml_base:CRIDType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:ApptType</td> <td><a href="#">mailxml_base:apptTypeType</a></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>	required				mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>					mailxml_tm:ApptType	<a href="#">mailxml_base:apptTypeType</a>	optional			
Name	Type	Use	Default	Fixed	annotation																																
mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>	required																																			
mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>																																				
mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>																																				
mailxml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>																																				
mailxml_tm:ApptType	<a href="#">mailxml_base:apptTypeType</a>	optional																																			
annotation	documentation A report or message indicating delivery closeout status for an unscheduled delivery.																																				

element **UnscheduledConsigneeGoodsReceipt/ApptBlockUnscheduledGoodsReceipt**

diagram					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm				
type	<a href="#">mailxml_tm:apptBlockUnscheduledGoodsType</a>				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex
isRef	0				
content	complex				
children	<a href="#">mailxml_tm:MailClass</a> <a href="#">mailxml_tm:ActualConsigneeFacility</a> <a href="#">mailxml_tm:ActualTruckArrival</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ActualStartUnload</a> <a href="#">mailxml_tm:ActualEndUnload</a> <a href="#">mailxml_tm:ApptStatus</a> <a href="#">mailxml_tm:Irregularities</a> <a href="#">mailxml_tm:Resolution</a> <a href="#">mailxml_tm:ActualBedload</a> <a href="#">mailxml_tm:ActualTotalPalletCount</a> <a href="#">mailxml_tm:ActualPalletCount</a> <a href="#">mailxml_tm:ValueAddedService</a>				


### element UnscheduledConsigneeGoodsReceipt/DetailInfo

diagram	<pre> classDiagram     class mailxml_tm:detailInfoType {         mailxml_tm:ShipperContainerGr...         mailxml_tm:ConsigneeContain...         mailxml_tm:StartTheClockDate         mailxml_tm:ShipperGroupingID...         mailxml_tm:MaildatSummary         mailxml_tm:USPSSummary         mailxml_tm:ConsigneeContentID     }     mailxml_tm:detailInfo &lt; -- mailxml_tm:detailInfoType     mailxml_tm:detailInfo --&gt; mailxml_tm:MaildatSummary : 1..∞     mailxml_tm:detailInfo --&gt; mailxml_tm:USPSSummary     mailxml_tm:detailInfo --&gt; mailxml_tm:ConsigneeContentID   </pre>								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_tm:detailInfoType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	unbounded	content	complex
isRef	0								
minOcc	0								
maxOcc	unbounded								
content	complex								
children	<a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:USPSSummary</a> <a href="#">mailxml_tm:ConsigneeContentID</a>								


### element UnscheduledConsigneeGoodsReceipt/TrailerInfo

diagram	<pre> classDiagram     class mailxml_tm:trailerInfoType {         mailxml_tm:Trailer         mailxml_tm:Carrier         mailxml_tm:BillOfLadingNumber     }     mailxml_tm:trailerInfo &lt; -- mailxml_tm:trailerInfoType     mailxml_tm:trailerInfo --&gt; mailxml_tm:BillOfLadingNumber : 1..2   </pre>								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_tm:trailerInfoType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#">mailxml_tm:Trailer</a> <a href="#">mailxml_tm:Carrier</a> <a href="#">mailxml_tm:BillOfLadingNumber</a>								

### element UnscheduledConsigneeGoodsReceipt/ReturnInfo

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>mailxml_defs:returnInfoType</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<b>mailxml_defs:ConsigneeFacility</b> <b>mailxml_defs:ErrorWarning</b> <b>mailxml_defs:ContainerErrorWarningBlock</b>								

### element UnscheduledConsigneeGoodsReceiptDelivery


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
properties	content complex
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_defs:DataRecipient</a> <a href="#">mailxml_tm:UserLicenseCode</a> <a href="#">mailxml_tm:MaildatJobID</a> <a href="#">mailxml_tm:CustomerGroupID</a> <a href="#">mailxml_tm:MailingGroupID</a> <a href="#">mailxml_tm:PushMessageID</a> <a href="#">mailxml_tm:ApptBlockUnscheduledGoodsReceipt</a> <a href="#">mailxml_tm:DetailInfo</a> <a href="#">mailxml_tm:TrailerInfo</a>

annotation	documentation Delivery by the USPS of an unscheduled consignee goods receipt.
------------	--

### element **UnscheduledConsigneeGoodsReceiptDelivery/SubmittingParty**

diagram	<pre> classDiagram     participant IDType {         &lt;&lt;mailxml_defs:participantIDType&gt;&gt;         &lt;&lt;attributes&gt;&gt;         MailerID6         MailerID9         CRID         SchedulerID         MaildatUserLicense         ShippingAgentID         ReceivingAgentID     }     SubmittingParty &lt; -- IDType     </pre>																																																
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>content</td> <td>complex</td> </tr> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table> <tr> <td>Name</td> <td>Type</td> <td>Use</td> <td>Default</td> <td>Fixed</td> <td>annotation</td> </tr> <tr> <td>mailerID6</td> <td><b>mailxml_base:mailerID6Type</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailerID9</td> <td><b>mailxml_base:mailerID9Type</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>CRID</td> <td><b>mailxml_base:CRIDType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>SchedulerID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>MaildatUserLicense</td> <td><b>mailxml_base:userLicenseCodeType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>ShippingAgentID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>ReceivingAgentID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailerID6	<b>mailxml_base:mailerID6Type</b>					mailerID9	<b>mailxml_base:mailerID9Type</b>					CRID	<b>mailxml_base:CRIDType</b>					SchedulerID	<b>mailxml_base:s12</b>					MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					ShippingAgentID	<b>mailxml_base:s12</b>					ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailerID9	<b>mailxml_base:mailerID9Type</b>																																																
CRID	<b>mailxml_base:CRIDType</b>																																																
SchedulerID	<b>mailxml_base:s12</b>																																																
MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
ShippingAgentID	<b>mailxml_base:s12</b>																																																
ReceivingAgentID	<b>mailxml_base:s12</b>																																																

### element UnscheduledConsigneeGoodsReceiptDelivery/SubmittingSoftware

diagram																																					
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																				
type	<b>mailxml_defs:submittingSoftwareType</b>																																				
properties	isRef 0 content complex																																				
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:SoftwareName</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Vendor</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Version</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalDate</td> <td><b>xs:date</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalKey</td> <td><b>xs:string</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SoftwareName	<b>xs:string</b>	required				mailxml_defs:Vendor	<b>xs:string</b>	required				mailxml_defs:Version	<b>xs:string</b>	required				mailxml_defs:ApprovalDate	<b>xs:date</b>					mailxml_defs:ApprovalKey	<b>xs:string</b>				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_defs:SoftwareName	<b>xs:string</b>	required																																			
mailxml_defs:Vendor	<b>xs:string</b>	required																																			
mailxml_defs:Version	<b>xs:string</b>	required																																			
mailxml_defs:ApprovalDate	<b>xs:date</b>																																				
mailxml_defs:ApprovalKey	<b>xs:string</b>																																				

### element UnscheduledConsigneeGoodsReceiptDelivery/UserLicenseCode

diagram													
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>												
type	<b>mailxml_base:userLicenseCodeType</b>												
properties	isRef 0 content simple												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	4		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	4												
whiteSpace	preserve												

### element UnscheduledConsigneeGoodsReceiptDelivery/MaildatJobID

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:jobIDType</b>
properties	isRef 0 content simple

	facets	Kind minLength maxLength whiteSpace	Value 1 8 preserve	annotation
--	--------	--	-----------------------------	------------

#### element **UnscheduledConsigneeGoodsReceiptDelivery/CustomerGroupID**

diagram			
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm		
type	<b>mailxml_base:s25</b>		
properties	isRef 0 content simple		
facets	Kind minLength maxLength whiteSpace	Value 1 25 preserve	annotation

#### element **UnscheduledConsigneeGoodsReceiptDelivery/MailingGroupID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:nonNegativeInteger</b>
properties	isRef 0 content simple

#### element **UnscheduledConsigneeGoodsReceiptDelivery/PushMessageID**

diagram			
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm		
type	<b>mailxml_base:s25</b>		
properties	isRef 0 minOcc 0 maxOcc 1 content simple		
facets	Kind minLength maxLength whiteSpace	Value 1 25 preserve	annotation

element **UnscheduledConsigneeGoodsReceiptDelivery/ApptBlockUnscheduledGoodsReceipt**

diagram					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm				
type	<a href="#">mailxml_tm:apptBlockUnscheduledGoodsType</a>				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex
isRef	0				
content	complex				
children	<a href="#">mailxml_tm:MailClass</a> <a href="#">mailxml_tm:ActualConsigneeFacility</a> <a href="#">mailxml_tm:ActualTruckArrival</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ActualStartUnload</a> <a href="#">mailxml_tm:ActualEndUnload</a> <a href="#">mailxml_tm:ApptStatus</a> <a href="#">mailxml_tm:Irregularities</a> <a href="#">mailxml_tm:Resolution</a> <a href="#">mailxml_tm:ActualBedload</a> <a href="#">mailxml_tm:ActualTotalPalletCount</a> <a href="#">mailxml_tm:ActualPalletCount</a> <a href="#">mailxml_tm:ValueAddedService</a>				

### element UnscheduledConsigneeGoodsReceiptDelivery/DetailInfo

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_tm:detailInfoType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	unbounded	content	complex
isRef	0								
minOcc	0								
maxOcc	unbounded								
content	complex								
children	<a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:USPSSummary</a> <a href="#">mailxml_tm:ConsigneeContentID</a>								

### element UnscheduledConsigneeGoodsReceiptDelivery/TrailerInfo

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_tm:trailerInfoType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#">mailxml_tm:Trailer</a> <a href="#">mailxml_tm:Carrier</a> <a href="#">mailxml_tm:BillOfLadingNumber</a>								

## element UnscheduledConsigneeGoodsReceiptNotification

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
properties	content complex
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:CRID</a> <a href="#">mailxml_tm:PushMessageID</a> <a href="#">mailxml_tm:UserLicenseCode</a> <a href="#">mailxml_tm:MaildatJobID</a> <a href="#">mailxml_tm:CustomerGroupID</a> <a href="#">mailxml_tm:MailingGroupID</a> <a href="#">mailxml_tm:NotificationDate</a>
annotation	<p>documentation</p> <p>Notification by USPS that an unscheduled consignee goods receipt is ready for pickup.</p>

## element UnscheduledConsigneeGoodsReceiptNotification/SubmittingParty

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_defs:participantIDType</a>
properties	isRef 0 content complex

			Use	Default	Fixed	annotation
attributes	Name mailxml_defs:MailerID6 mailxml_defs:MailerID9 mailxml_defs:CRID mailxml_defs:SchedulerID mailxml_defs:MaildatUserLicense mailxml_defs:ShippingAgentID mailxml_defs:ReceivingAgentID	Type <b>mailxml_base:mailerID6Type</b> <b>mailxml_base:mailerID9Type</b> <b>mailxml_base:CRIDType</b> <b>mailxml_base:s12</b> <b>mailxml_base:userLicenseCodeType</b> <b>mailxml_base:s12</b> <b>mailxml_base:s12</b>				

### element **UnscheduledConsigneeGoodsReceiptNotification/SubmittingSoftware**


diagram	<pre> graph LR     A[mailxml_tm:Submitting Software] --&gt; B[mailxml_defs:submittingSoftwareType]     B --&gt; C[SoftwareName]     B --&gt; D[Vendor]     B --&gt; E[Version]     B --&gt; F[ApprovalDate]     B --&gt; G[ApprovalKey]   </pre>																																				
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																				
type	<b>mailxml_defs:submittingSoftwareType</b>																																				
properties	isRef 0 content complex																																				
attributes	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:SoftwareName</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Vendor</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Version</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalDate</td> <td><b>xs:date</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalKey</td> <td><b>xs:string</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SoftwareName	<b>xs:string</b>	required				mailxml_defs:Vendor	<b>xs:string</b>	required				mailxml_defs:Version	<b>xs:string</b>	required				mailxml_defs:ApprovalDate	<b>xs:date</b>					mailxml_defs:ApprovalKey	<b>xs:string</b>				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_defs:SoftwareName	<b>xs:string</b>	required																																			
mailxml_defs:Vendor	<b>xs:string</b>	required																																			
mailxml_defs:Version	<b>xs:string</b>	required																																			
mailxml_defs:ApprovalDate	<b>xs:date</b>																																				
mailxml_defs:ApprovalKey	<b>xs:string</b>																																				

### element **UnscheduledConsigneeGoodsReceiptNotification/CRID**

diagram	<pre> graph LR     A[mailxml_tm:CRID] --&gt; B[mailxml_base:CRIDType]   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:CRIDType</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1

	maxLength 15 pattern ([0-9])*
--	----------------------------------

**element UnscheduledConsigneeGoodsReceiptNotification/PushMessageID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s25</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 25 whiteSpace preserve


**element UnscheduledConsigneeGoodsReceiptNotification/UserLicenseCode**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:userLicenseCodeType</b>
properties	isRef 0 content simple
facets	Kind Value annotation minLength 1 maxLength 4 whiteSpace preserve


**element UnscheduledConsigneeGoodsReceiptNotification/MaildatJobID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:jobIDType</b>
properties	isRef 0 content simple
facets	Kind Value annotation minLength 1 maxLength 8 whiteSpace preserve

**element UnscheduledConsigneeGoodsReceiptNotification/CustomerGroupID**

diagram	 mailxml_tm:CustomerGroupID
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s25</b>
properties	isRef 0 content simple
facets	Kind Value annotation minLength 1 maxLength 25 whiteSpace preserve

**element UnscheduledConsigneeGoodsReceiptNotification/MailingGroupID**

diagram	 mailxml_tm:MailingGroupID
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:nonNegativeInteger</b>
properties	isRef 0 content simple

**element UnscheduledConsigneeGoodsReceiptNotification/NotificationDate**

diagram	 mailxml_tm:NotificationDate
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:date</b>
properties	isRef 0 content simple

## element **USPSDeliveryContentUpdatedDelivery**

diagram	<pre> classDiagram     class USPSDeliveryContentUpdatedD...     class grp {         mailxml_defs:LargeTrans...         mailxml_defs:MessageGroupID         mailxml_defs:TotalMessageCou...         mailxml_defs:MessageSerialNu...         mailxml_defs:TransmittedRecor...         mailxml_defs:TotalRecordsAcros...         mailxml_defs:LastMessage     }     class mailxml_tm {         SubmittingParty         SubmittingSoftware         DataRecipient         PushMessageID         DeliveryContentUp...     }     USPSDeliveryContentUpdatedD... "Delivery of content update information by USPS."     USPSDeliveryContentUpdatedD... --&gt; grp     USPSDeliveryContentUpdatedD... --&gt; mailxml_tm     multiplicity "1..∞" at DeliveryContentUp...   </pre>																																										
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																										
properties	content complex																																										
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_defs:DataRecipient</a> <a href="#">mailxml_tm:PushMessageID</a> <a href="#">mailxml_tm:DeliveryContentUpdated</a>																																										
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:MessageGroupID</td> <td><b>mailxml_base:s20</b></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:TotalMessageCount</td> <td><b>xs:positiveInteger</b></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MessageSerialNumber</td> <td><b>xs:positiveInteger</b></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:TransmittedRecordCount</td> <td><b>xs:positiveInteger</b></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:TotalRecordsAcrossMessages</td> <td><b>xs:positiveInteger</b></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:LastMessage</td> <td><b>mailxml_base:yesNo</b></td> <td>optional</td> <td>No</td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MessageGroupID	<b>mailxml_base:s20</b>	optional				mailxml_defs:TotalMessageCount	<b>xs:positiveInteger</b>	optional				mailxml_defs:MessageSerialNumber	<b>xs:positiveInteger</b>	optional				mailxml_defs:TransmittedRecordCount	<b>xs:positiveInteger</b>	optional				mailxml_defs:TotalRecordsAcrossMessages	<b>xs:positiveInteger</b>	optional				mailxml_defs:LastMessage	<b>mailxml_base:yesNo</b>	optional	No		
Name	Type	Use	Default	Fixed	annotation																																						
mailxml_defs:MessageGroupID	<b>mailxml_base:s20</b>	optional																																									
mailxml_defs:TotalMessageCount	<b>xs:positiveInteger</b>	optional																																									
mailxml_defs:MessageSerialNumber	<b>xs:positiveInteger</b>	optional																																									
mailxml_defs:TransmittedRecordCount	<b>xs:positiveInteger</b>	optional																																									
mailxml_defs:TotalRecordsAcrossMessages	<b>xs:positiveInteger</b>	optional																																									
mailxml_defs:LastMessage	<b>mailxml_base:yesNo</b>	optional	No																																								
annotation	<p>documentation</p> <p>Delivery of content update information by USPS.</p>																																										

element **USPSDeliveryContentUpdatedDelivery/SubmittingParty**

diagram	<pre> classDiagram     participantIDType "7" as mailxml_defs:participantIDType     submittingParty "6" as mailxml_tm:SubmittingParty     participantIDType "o" -- "6" mailxml_tm:SubmittingParty     participantIDType "o" &lt; -- "7" mailxml_base:mailerID6Type     participantIDType "o" &lt; -- "7" mailxml_base:mailerID9Type     participantIDType "o" &lt; -- "7" mailxml_base:CRIDType     participantIDType "o" &lt; -- "7" mailxml_base:s12     participantIDType "o" &lt; -- "7" mailxml_base:userLicenseCodeType     participantIDType "o" &lt; -- "7" mailxml_base:s12     participantIDType "o" &lt; -- "7" mailxml_base:s12   </pre>																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex																																								
isRef	0																																																
minOcc	0																																																
maxOcc	1																																																
content	complex																																																
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:MailerID6</td><td><b>mailxml_base:mailerID6Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MailerID9</td><td><b>mailxml_base:mailerID9Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:CRID</td><td><b>mailxml_base:CRIDType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatUserLicense</td><td><b>mailxml_base:userLicenseCodeType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShippingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ReceivingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

**element USPSDeliveryContentUpdatedDelivery/SubmittingSoftware**

diagram	<pre> graph TD     SS[mailxml_tm:SubmittingSoftware] --&gt; S[mailxml_defs:submittingSoftwareType]     S --&gt; SN[mailxml_defs:SoftwareName]     S --&gt; V[mailxml_defs:Vendor]     S --&gt; Ver[mailxml_defs:Version]     S --&gt; AD[mailxml_defs:ApprovalDate]     S --&gt; AK[mailxml_defs:ApprovalKey]   </pre>																																				
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																				
type	<b>mailxml_defs:submittingSoftwareType</b>																																				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex																												
isRef	0																																				
minOcc	0																																				
maxOcc	1																																				
content	complex																																				
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:SoftwareName</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td></tr> <tr> <td>mailxml_defs:Vendor</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td></tr> <tr> <td>mailxml_defs:Version</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td></tr> <tr> <td>mailxml_defs:ApprovalDate</td> <td><b>xs:date</b></td> <td></td> <td></td> <td></td> <td></td></tr> <tr> <td>mailxml_defs:ApprovalKey</td> <td><b>xs:string</b></td> <td></td> <td></td> <td></td> <td></td></tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SoftwareName	<b>xs:string</b>	required				mailxml_defs:Vendor	<b>xs:string</b>	required				mailxml_defs:Version	<b>xs:string</b>	required				mailxml_defs:ApprovalDate	<b>xs:date</b>					mailxml_defs:ApprovalKey	<b>xs:string</b>				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_defs:SoftwareName	<b>xs:string</b>	required																																			
mailxml_defs:Vendor	<b>xs:string</b>	required																																			
mailxml_defs:Version	<b>xs:string</b>	required																																			
mailxml_defs:ApprovalDate	<b>xs:date</b>																																				
mailxml_defs:ApprovalKey	<b>xs:string</b>																																				

**element USPSDeliveryContentUpdatedDelivery/PushMessageID**

diagram	<pre> graph TD     PM[mailxml_tm:PushMessageID]     PM --&gt; F[minLength]     PM --&gt; FM[maxLength]     PM --&gt; WS:whiteSpace   </pre>												
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s25</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td><td>1</td> <td></td></tr> <tr> <td>maxLength</td><td>25</td> <td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td> <td></td></tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	25		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	25												
whiteSpace	preserve												

## element USPSDeliveryContentUpdatedDelivery/DeliveryContentUpdated

diagram	<pre> classDiagram     class mailxml_tm {         class deliveryContentUpdatedType {             attribute maixml_tm:ConsigneeApptID             attribute maixml_tm:SchedulerID             attribute maixml_tm:SchedulerCorpID             attribute maixml_tm:SchedulerCRID             attribute maixml_tm:FullContentReplace...         }     }     class mailxml_tm {         class DeliveryContentUpd {             association "1..∞" to deliveryContentUpdatedType         }     }     class mailxml_tm {         class ConsigneeFacility {             association "1..∞" to deliveryContentUpdatedType         }     }     class mailxml_tm {         class DestinationEntry {             association "1..∞" to deliveryContentUpdatedType         }     }     class mailxml_tm {         class ContentDetailInfoUpdate {             association "1..∞" to deliveryContentUpdatedType         }     }     class mailxml_tm {         class ContentCancelled {             association "1..∞" to deliveryContentUpdatedType         }     }     class mailxml_tm {         class ContentCancelInfo {             association "1..∞" to deliveryContentUpdatedType         }     }     class mailxml_tm {         class ReturnInfo {             association "1..∞" to deliveryContentUpdatedType         }     } </pre>																																				
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																				
type	<a href="#">mailxml_tm:deliveryContentUpdatedType</a>																																				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>1</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	1	maxOcc	unbounded	content	complex																												
isRef	0																																				
minOcc	1																																				
maxOcc	unbounded																																				
content	complex																																				
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ContentDetailInfoUpdate</a> <a href="#">mailxml_tm:ContentCancelled</a> <a href="#">mailxml_tm:ContentCancelInfo</a> <a href="#">mailxml_tm:ReturnInfo</a>																																				
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>maixml_tm:ConsigneeApptID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>maixml_tm:SchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>maixml_tm:SchedulerCorpID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>maixml_tm:SchedulerCRID</td> <td><a href="#">mailxml_base:CRIDType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>maixml_tm:FullContentReplacement</td> <td><a href="#">mailxml_base:yesNo</a></td> <td></td> <td>No</td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	maixml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>					maixml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>					maixml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>					maixml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>					maixml_tm:FullContentReplacement	<a href="#">mailxml_base:yesNo</a>		No		
Name	Type	Use	Default	Fixed	annotation																																
maixml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>																																				
maixml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>																																				
maixml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>																																				
maixml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>																																				
maixml_tm:FullContentReplacement	<a href="#">mailxml_base:yesNo</a>		No																																		

## element **USPSDeliveryContentUpdatedNotification**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
properties	content complex
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_defs:DataRecipient</a> <a href="#">mailxml_tm:PushMessageID</a> <a href="#">mailxml_tm:NotificationDate</a> <a href="#">mailxml_tm:NotificationSummary</a>
annotation	documentation Notification from USPS to Mailer/Preparer/Condolidator that mailing content has been changed.

## element **USPSDeliveryContentUpdatedNotification/SubmittingParty**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_defs:participantIDType</b>
properties	isRef 0 minOcc 0 maxOcc 1 content complex
attributes	Name mailxml_defs:MailerID6 Type <b>mailxml_base:mailerID6Type</b> Use Default Fixed annotation

	mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>
	mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>
	mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>
	mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>
	mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>
	mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>

#### element **USPSDeliveryContentUpdatedNotification/SubmittingSoftware**


diagram	<pre> classDiagram     class mailxml_tm::SubmittingSoftware     class mailxml_defs::submittingSoftwareType {         SoftwareName : xs:string         Vendor : xs:string         Version : xs:string         ApprovalDate : xs:date         ApprovalKey : xs:string     }     SubmittingSoftware "1" -- "0..1" submittingSoftwareType   </pre>																																				
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																				
type	<b>mailxml_defs:submittingSoftwareType</b>																																				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex																												
isRef	0																																				
minOcc	0																																				
maxOcc	1																																				
content	complex																																				
attributes	<table> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> <tr> <td>mailxml_defs:SoftwareName</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Vendor</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Version</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalDate</td> <td><b>xs:date</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalKey</td> <td><b>xs:string</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SoftwareName	<b>xs:string</b>	required				mailxml_defs:Vendor	<b>xs:string</b>	required				mailxml_defs:Version	<b>xs:string</b>	required				mailxml_defs:ApprovalDate	<b>xs:date</b>					mailxml_defs:ApprovalKey	<b>xs:string</b>				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_defs:SoftwareName	<b>xs:string</b>	required																																			
mailxml_defs:Vendor	<b>xs:string</b>	required																																			
mailxml_defs:Version	<b>xs:string</b>	required																																			
mailxml_defs:ApprovalDate	<b>xs:date</b>																																				
mailxml_defs:ApprovalKey	<b>xs:string</b>																																				

#### element **USPSDeliveryContentUpdatedNotification/PushMessageID**


diagram	<pre> classDiagram     class mailxml_tm::PushMessageID   </pre>								
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>								
type	<b>mailxml_base:s25</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple
isRef	0								
minOcc	0								
maxOcc	1								
content	simple								
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1			
Kind	Value	annotation							
minLength	1								

	<pre>maxLength    25 whiteSpace   preserve</pre>
--	--

#### element **USPSDeliveryContentUpdatedNotification/NotificationDate**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:date</b>
properties	<pre>isRef  0 content simple</pre>

#### element **USPSDeliveryContentUpdatedNotification/NotificationSummary**

diagram																																																	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
properties	<pre>isRef  0 minOcc 1 maxOcc unbounded content complex</pre>																																																
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:ConsigneeApptID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCorpID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCRID</td> <td><b>mailxml_base:CRIDType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerContentID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:ConsigneeContentID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:DestinationEntry</td> <td><b>mailxml_base:yesNo</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>					mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>					mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>					mailxml_tm:SchedulerCRID	<b>mailxml_base:CRIDType</b>					mailxml_tm:SchedulerContentID	<b>mailxml_base:s12</b>					mailxml_tm:ConsigneeContentID	<b>mailxml_base:s12</b>					mailxml_tm:DestinationEntry	<b>mailxml_base:yesNo</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>																																																
mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>																																																
mailxml_tm:SchedulerCRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_tm:SchedulerContentID	<b>mailxml_base:s12</b>																																																
mailxml_tm:ConsigneeContentID	<b>mailxml_base:s12</b>																																																
mailxml_tm:DestinationEntry	<b>mailxml_base:yesNo</b>																																																

## element **USPSDeliveryContentUpdatedQueryRequest**

diagram	<pre> classDiagram     class USPSDeliveryContentUpdatedQ {         grp mailxml_defs:MailXMLHe...         mailxml_defs:CustomerGroupID         mailxml_defs:MailingGroupID         mailxml_defs:MaildatJobID         mailxml_defs:UserLicenseCode     }     class mailxml_tm:SubmittingParty     class mailxml_tm:SubmittingSoftware     class mailxml_tm:SubmitterTrackingID     class mailxml_tm:DestinationEntry     class mailxml_tm:USPSDeliveryContentParameters      USPSDeliveryContentUpdatedQ "1..∞" --&gt; mailxml_tm:SubmittingParty     USPSDeliveryContentUpdatedQ "1..∞" --&gt; mailxml_tm:SubmittingSoftware     USPSDeliveryContentUpdatedQ "1..∞" --&gt; mailxml_tm:SubmitterTrackingID     USPSDeliveryContentUpdatedQ "1..∞" --&gt; mailxml_tm:DestinationEntry     USPSDeliveryContentUpdatedQ "1..∞" --&gt; mailxml_tm:USPSDeliveryContentParameters   </pre>																														
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																														
properties	content complex																														
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:USPSDeliveryContentParameters</a>																														
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:CustomerGroupID</td> <td><b>mailxml_base:s25</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MailingGroupID</td> <td><b>xs:nonNegativeInteger</b></td> <td></td> <td>required</td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MaildatJobID</td> <td><b>mailxml_base:jobIDType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:UserLicenseCode</td> <td><b>mailxml_base:userLicenseCodeType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:CustomerGroupID	<b>mailxml_base:s25</b>					mailxml_defs:MailingGroupID	<b>xs:nonNegativeInteger</b>		required			mailxml_defs:MaildatJobID	<b>mailxml_base:jobIDType</b>					mailxml_defs:UserLicenseCode	<b>mailxml_base:userLicenseCodeType</b>				
Name	Type	Use	Default	Fixed	annotation																										
mailxml_defs:CustomerGroupID	<b>mailxml_base:s25</b>																														
mailxml_defs:MailingGroupID	<b>xs:nonNegativeInteger</b>		required																												
mailxml_defs:MaildatJobID	<b>mailxml_base:jobIDType</b>																														
mailxml_defs:UserLicenseCode	<b>mailxml_base:userLicenseCodeType</b>																														
annotation	documentation Query request for updated content from USPS																														

### element **USPSDeliveryContentUpdatedQueryRequest/SubmittingParty**

diagram	<pre> classDiagram     class mailxml_tmSubmittingParty     class mailxml_defsParticipantIDType {         &lt;&lt;attributes&gt;&gt;         mailxml_defsMailerID6         mailxml_defsMailerID9         mailxml_defsCRID         mailxml_defsSchedulerID         mailxml_defsMaildatUserLicense         mailxml_defsShippingAgentID         mailxml_defsReceivingAgentID     }     mailxml_tmSubmittingParty "1" -- "1" mailxml_defsParticipantIDType   </pre>																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:MailerID6</td><td><b>mailxml_base:mailerID6Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MailerID9</td><td><b>mailxml_base:mailerID9Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:CRID</td><td><b>mailxml_base:CRIDType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatUserLicense</td><td><b>mailxml_base:userLicenseCodeType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShippingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ReceivingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

### element **USPSDeliveryContentUpdatedQueryRequest/SubmittingSoftware**

diagram	<pre> classDiagram     class mailxml_tmSubmittingSoftware     class mailxml_defsSubmittingSoftwareType {         &lt;&lt;attributes&gt;&gt;         mailxml_defsSoftwareName         mailxml_defsVendor         mailxml_defsVersion         mailxml_defsApprovalDate         mailxml_defsApprovalKey     }     mailxml_tmSubmittingSoftware "1" -- "1" mailxml_defsSubmittingSoftwareType   </pre>
---------	--

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
type	<b>mailxml_defs:submittingSoftwareType</b>					
properties	isRef 0 content complex					
attributes	Name mailxml_defs:SoftwareName	Type <b>xs:string</b>	Use required	Default	Fixed	annotation
	mailxml_defs:Vendor	<b>xs:string</b>	required			
	mailxml_defs:Version	<b>xs:string</b>	required			
	mailxml_defs:ApprovalDate	<b>xs:date</b>				
	mailxml_defs:ApprovalKey	<b>xs:string</b>				

#### element **USPSDeliveryContentUpdatedQueryRequest/SubmitterTrackingID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s20</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

#### element **USPSDeliveryContentUpdatedQueryRequest/DestinationEntry**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

element **USPSDeliveryContentUpdatedQueryRequest/USPSDeliveryContentUpdatedQueryParameters**


diagram	<pre> classDiagram     class USPSDeliveryContentUpdatedQueryParameters {         &lt;&lt;grp mailxml_tm:DeliveryContentUpdatedQueryParameters&gt;&gt;         ConsigneeApptID         SchedulerID         SchedulerCorpID         SchedulerCRID         SchedulerContentID         ConsigneeContentID         RetrieveContentUpdatedStartDate         RetrieveContentUpdatedEndDate     } </pre>																																																						
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																						
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>1</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	1	maxOcc	unbounded	content	complex																																														
isRef	0																																																						
minOcc	1																																																						
maxOcc	unbounded																																																						
content	complex																																																						
attributes	<table> <thead> <tr> <th>Name</th><th>Type</th><th>Use</th><th>Default</th><th>Fixed</th><th>annotation</th></tr> </thead> <tbody> <tr> <td>mailxml_tm:ConsigneeApptID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:SchedulerID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:SchedulerCorpID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:SchedulerCRID</td><td><b>mailxml_base:CRIDType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:SchedulerContentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:ConsigneeContentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:RetrieveContentUpdatedStartDate</td><td><b>xs:date</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:RetrieveContentUpdatedEndDate</td><td><b>xs:date</b></td><td></td><td></td><td></td><td></td></tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>					mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>					mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>					mailxml_tm:SchedulerCRID	<b>mailxml_base:CRIDType</b>					mailxml_tm:SchedulerContentID	<b>mailxml_base:s12</b>					mailxml_tm:ConsigneeContentID	<b>mailxml_base:s12</b>					mailxml_tm:RetrieveContentUpdatedStartDate	<b>xs:date</b>					mailxml_tm:RetrieveContentUpdatedEndDate	<b>xs:date</b>				
Name	Type	Use	Default	Fixed	annotation																																																		
mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>																																																						
mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>																																																						
mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>																																																						
mailxml_tm:SchedulerCRID	<b>mailxml_base:CRIDType</b>																																																						
mailxml_tm:SchedulerContentID	<b>mailxml_base:s12</b>																																																						
mailxml_tm:ConsigneeContentID	<b>mailxml_base:s12</b>																																																						
mailxml_tm:RetrieveContentUpdatedStartDate	<b>xs:date</b>																																																						
mailxml_tm:RetrieveContentUpdatedEndDate	<b>xs:date</b>																																																						

## element USPSDeliveryContentUpdatedQueryResponse

diagram	<p>The diagram illustrates the structure of the <code>USPSDeliveryContentUpdatedQueryResponse</code> element. It consists of two main parts: a list of attributes and a list of children.</p> <ul style="list-style-type: none"> <li><b>Attributes:</b> <ul style="list-style-type: none"> <li><code>grp mailxml_defs:MailXMLHe...</code></li> <li><code>mailxml_defs:CustomerGroupID</code></li> <li><code>mailxml_defs:MailingGroupID</code></li> <li><code>mailxml_defs:MaildatJobID</code></li> <li><code>mailxml_defs:UserLicenseCode</code></li> <li><code>grp mailxml_defs:LargeTrans...</code></li> <li><code>mailxml_defs:MessageGroupID</code></li> <li><code>mailxml_defs:TotalMessageCou...</code></li> <li><code>mailxml_defs:MessageSerialNu...</code></li> <li><code>mailxml_defs:TransmittedRecor...</code></li> <li><code>mailxml_defs:TotalRecordsAcro...</code></li> <li><code>mailxml_defs:LastMessage</code></li> </ul> </li> <li><b>Children:</b> <ul style="list-style-type: none"> <li><code>mailxml_tm:TrackingID</code></li> <li><code>mailxml_tm:SubmitterTrackingID</code></li> <li><code>mailxml_tm:QueryResults</code></li> <li><code>mailxml_defs:QueryError</code></li> </ul> </li> </ul> <p><code>USPSDeliveryContentUpdatedQ...</code> Response to the query for updated content from USPS</p> <p>Error issued when the query data cannot be provided.</p>																																																
namespace	<code>http://idealliance.org/Specs/mailxml23.0/mailxml_tm</code>																																																
properties	content complex																																																
children	<code>mailxml_tm:TrackingID</code> <code>mailxml_tm:SubmitterTrackingID</code> <code>mailxml_tm:QueryResults</code> <code>mailxml_defs:QueryError</code>																																																
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><code>mailxml_defs:CustomerGroupID</code></td> <td><code>mailxml_base:s25</code></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><code>mailxml_defs:MailingGroupID</code></td> <td><code>xs:nonNegativeInteger</code></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td><code>mailxml_defs:MaildatJobID</code></td> <td><code>mailxml_base:jobIDType</code></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><code>mailxml_defs:UserLicenseCode</code></td> <td><code>mailxml_base:userLicenseCodeType</code></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><code>mailxml_defs:MessageGroupID</code></td> <td><code>mailxml_base:s20</code></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td><code>mailxml_defs:TotalMessageCount</code></td> <td><code>xs:positiveInteger</code></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td><code>mailxml_defs:MessageSerialNumber</code></td> <td><code>xs:positiveInteger</code></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<code>mailxml_defs:CustomerGroupID</code>	<code>mailxml_base:s25</code>					<code>mailxml_defs:MailingGroupID</code>	<code>xs:nonNegativeInteger</code>	required				<code>mailxml_defs:MaildatJobID</code>	<code>mailxml_base:jobIDType</code>					<code>mailxml_defs:UserLicenseCode</code>	<code>mailxml_base:userLicenseCodeType</code>					<code>mailxml_defs:MessageGroupID</code>	<code>mailxml_base:s20</code>	optional				<code>mailxml_defs:TotalMessageCount</code>	<code>xs:positiveInteger</code>	optional				<code>mailxml_defs:MessageSerialNumber</code>	<code>xs:positiveInteger</code>	optional			
Name	Type	Use	Default	Fixed	annotation																																												
<code>mailxml_defs:CustomerGroupID</code>	<code>mailxml_base:s25</code>																																																
<code>mailxml_defs:MailingGroupID</code>	<code>xs:nonNegativeInteger</code>	required																																															
<code>mailxml_defs:MaildatJobID</code>	<code>mailxml_base:jobIDType</code>																																																
<code>mailxml_defs:UserLicenseCode</code>	<code>mailxml_base:userLicenseCodeType</code>																																																
<code>mailxml_defs:MessageGroupID</code>	<code>mailxml_base:s20</code>	optional																																															
<code>mailxml_defs:TotalMessageCount</code>	<code>xs:positiveInteger</code>	optional																																															
<code>mailxml_defs:MessageSerialNumber</code>	<code>xs:positiveInteger</code>	optional																																															

	mailxml_defs:TransmittedRecordCount	<b>xs:positiveInteger</b>	optiona
	mailxml_defs:TotalRecordsAcrossMessages	<b>xs:positiveInteger</b>	optiona
	mailxml_defs:LastMessage	<b>mailxml_base:yesNo</b>	optiona No
annotation	documentation Response to the query for updated content from USPS		


#### element **USPSDeliveryContentUpdatedQueryResponse/TrackingID**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

#### element **USPSDeliveryContentUpdatedQueryResponse/SubmitterTrackingID**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

#### element **USPSDeliveryContentUpdatedQueryResponse/QueryResults**


diagram	
---------	--

namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_defs:LargeTransactionDividerResult</a> <a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:DeliveryContentUpdated</a>

element **USPSDeliveryContentUpdatedQueryResponse/QueryResults/SubmittingParty**

diagram	<pre> classDiagram     participantIDType {         &lt;&lt;attributes&gt;&gt;         MailerID6         MailerID9         CRID         SchedulerID         MaildatUserLicense         ShippingAgentID         ReceivingAgentID     }     SubmittingParty {         &lt;&lt;Relationship&gt;&gt;         participantIDType     }     participantIDType &lt; -- SubmittingParty   </pre>																																																
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	isRef 0 minOcc 0 maxOcc 1 content complex																																																
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:MailerID6</td> <td><a href="#">mailxml_base:mailerID6Type</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MailerID9</td> <td><a href="#">mailxml_base:mailerID9Type</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:CRID</td> <td><a href="#">mailxml_base:CRIDType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MaildatUserLicense</td> <td><a href="#">mailxml_base:userLicenseCodeType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ShippingAgentID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ReceivingAgentID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<a href="#">mailxml_base:mailerID6Type</a>					mailxml_defs:MailerID9	<a href="#">mailxml_base:mailerID9Type</a>					mailxml_defs:CRID	<a href="#">mailxml_base:CRIDType</a>					mailxml_defs:SchedulerID	<a href="#">mailxml_base:s12</a>					mailxml_defs:MaildatUserLicense	<a href="#">mailxml_base:userLicenseCodeType</a>					mailxml_defs:ShippingAgentID	<a href="#">mailxml_base:s12</a>					mailxml_defs:ReceivingAgentID	<a href="#">mailxml_base:s12</a>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<a href="#">mailxml_base:mailerID6Type</a>																																																
mailxml_defs:MailerID9	<a href="#">mailxml_base:mailerID9Type</a>																																																
mailxml_defs:CRID	<a href="#">mailxml_base:CRIDType</a>																																																
mailxml_defs:SchedulerID	<a href="#">mailxml_base:s12</a>																																																
mailxml_defs:MaildatUserLicense	<a href="#">mailxml_base:userLicenseCodeType</a>																																																
mailxml_defs:ShippingAgentID	<a href="#">mailxml_base:s12</a>																																																
mailxml_defs:ReceivingAgentID	<a href="#">mailxml_base:s12</a>																																																

element **USPSDeliveryContentUpdatedQueryResponse/QueryResults/SubmittingSoftware**

diagram																																					
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																				
type	<b>mailxml_defs:submittingSoftwareType</b>																																				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex																												
isRef	0																																				
minOcc	0																																				
maxOcc	1																																				
content	complex																																				
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:SoftwareName</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td></tr> <tr> <td>mailxml_defs:Vendor</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td></tr> <tr> <td>mailxml_defs:Version</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td></tr> <tr> <td>mailxml_defs:ApprovalDate</td> <td><b>xs:date</b></td> <td></td> <td></td> <td></td> <td></td></tr> <tr> <td>mailxml_defs:ApprovalKey</td> <td><b>xs:string</b></td> <td></td> <td></td> <td></td> <td></td></tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SoftwareName	<b>xs:string</b>	required				mailxml_defs:Vendor	<b>xs:string</b>	required				mailxml_defs:Version	<b>xs:string</b>	required				mailxml_defs:ApprovalDate	<b>xs:date</b>					mailxml_defs:ApprovalKey	<b>xs:string</b>				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_defs:SoftwareName	<b>xs:string</b>	required																																			
mailxml_defs:Vendor	<b>xs:string</b>	required																																			
mailxml_defs:Version	<b>xs:string</b>	required																																			
mailxml_defs:ApprovalDate	<b>xs:date</b>																																				
mailxml_defs:ApprovalKey	<b>xs:string</b>																																				

element **USPSDeliveryContentUpdatedQueryResponse/QueryResults/DeliveryContentUpdated**

diagram	<pre> classDiagram     class mailxml_tm {         deliveryContentUpdatedType {             attributes: ConsigneeApptID, SchedulerID, SchedulerCorpID, SchedulerCRID, FullContentReplace...             associations: DeliveryContentUp..., ConsigneeFacility, DestinationEntry, ContentDetailInfoU..., ContentCancelled, ContentCancelInfo, ReturnInfo         }     } </pre>																																				
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																				
type	<a href="#">mailxml_tm:deliveryContentUpdatedType</a>																																				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>1</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	1	maxOcc	unbounded	content	complex																												
isRef	0																																				
minOcc	1																																				
maxOcc	unbounded																																				
content	complex																																				
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ContentDetailInfoUpdate</a> <a href="#">mailxml_tm:ContentCancelled</a> <a href="#">mailxml_tm:ContentCancelInfo</a> <a href="#">mailxml_tm:ReturnInfo</a>																																				
attributes	<table> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> <tr> <td>mailxml_tm:ConsigneeApptID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCorpID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCRID</td> <td><a href="#">mailxml_base:CRIDType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:FullContentReplacement</td> <td><a href="#">mailxml_base:yesNo</a></td> <td></td> <td>No</td> <td></td> <td></td> </tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>					mailxml_tm:FullContentReplacement	<a href="#">mailxml_base:yesNo</a>		No		
Name	Type	Use	Default	Fixed	annotation																																
mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>																																				
mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>																																				
mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>																																				
mailxml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>																																				
mailxml_tm:FullContentReplacement	<a href="#">mailxml_base:yesNo</a>		No																																		

complexType **actualBedloadType**

diagram	<pre> classDiagram     class actualBedloadType {         attributes: HandlingUnit         associations: ActualBedloadPerce..., ActualBedloadCount     } </pre>
---------	--

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
children	<a href="#">mailxml_tm:ActualBedloadPercent</a> <a href="#">mailxml_tm:ActualBedloadCount</a>					
used by	elements <a href="#">apptBlockGoodsType/ActualBedload</a> <a href="#">apptBlockUnscheduledGoodsType/ActualBedload</a>					
attributes	Name <a href="#">mailxml_tm:HandlingUnit</a>	Type <a href="#">mailxml_base:palletHandlingUnitType</a>	Use required	Default	Fixed	annotation

#### attribute **actualBedloadType/@HandlingUnit**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
type	<a href="#">mailxml_base:palletHandlingUnitType</a>					
properties	isRef 0 use required					
facets	Kind	Value	annotation			
	enumeration	Airbox				
	enumeration	Sacks				
	enumeration	Bundles				
	enumeration	MixedLengthTrays				
	enumeration	1ft Tray				
	enumeration	2ft Tray				
	enumeration	EMM Tray				
	enumeration	Flat Tub				
	enumeration	Parcels				


#### element **actualBedloadType/ActualBedloadPercent**

diagram	 <a href="#">mailxml_tm:ActualBedloadPerce...</a>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">xs:nonNegativeInteger</a>
properties	isRef 0 content simple

#### element **actualBedloadType/ActualBedloadCount**

diagram	 <a href="#">mailxml_tm:ActualBedloadCount</a>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">xs:nonNegativeInteger</a>
properties	isRef 0 content simple


### complexType **actualPalletType**

diagram													
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>												
children	<a href="#">mailxml_tm:ActualPalletCount</a>												
used by	elements <a href="#">apptBlockGoodsType/ActualPalletCount</a> <a href="#">apptBlockUnscheduledGoodsType/ActualPalletCount</a>												
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><a href="#">mailxml_tm:HandlingUnit</a></td> <td><a href="#">mailxml_base:palletHandlingUnitType</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:HandlingUnit</a>	<a href="#">mailxml_base:palletHandlingUnitType</a>	required			
Name	Type	Use	Default	Fixed	annotation								
<a href="#">mailxml_tm:HandlingUnit</a>	<a href="#">mailxml_base:palletHandlingUnitType</a>	required											

### attribute **actualPalletType/@HandlingUnit**

namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																														
type	<a href="#">mailxml_base:palletHandlingUnitType</a>																														
properties	<table> <thead> <tr> <th>isRef</th> <th>0</th> <th>use</th> <th>required</th> </tr> </thead> </table>	isRef	0	use	required																										
isRef	0	use	required																												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Airbox</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Sacks</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Bundles</td> <td></td> </tr> <tr> <td>enumeration</td> <td>MixedLengthTrays</td> <td></td> </tr> <tr> <td>enumeration</td> <td>1ft Tray</td> <td></td> </tr> <tr> <td>enumeration</td> <td>2ft Tray</td> <td></td> </tr> <tr> <td>enumeration</td> <td>EMM Tray</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Flat Tub</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Parcels</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	enumeration	Airbox		enumeration	Sacks		enumeration	Bundles		enumeration	MixedLengthTrays		enumeration	1ft Tray		enumeration	2ft Tray		enumeration	EMM Tray		enumeration	Flat Tub		enumeration	Parcels	
Kind	Value	annotation																													
enumeration	Airbox																														
enumeration	Sacks																														
enumeration	Bundles																														
enumeration	MixedLengthTrays																														
enumeration	1ft Tray																														
enumeration	2ft Tray																														
enumeration	EMM Tray																														
enumeration	Flat Tub																														
enumeration	Parcels																														

### element **actualPalletType/ActualPalletCount**

diagram					
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>				
type	<a href="#">xs:nonNegativeInteger</a>				
properties	<table> <thead> <tr> <th>isRef</th> <th>0</th> <th>content</th> <th>simple</th> </tr> </thead> </table>	isRef	0	content	simple
isRef	0	content	simple		

### complexType allDeliveryApptCloseoutAcceptType

diagram																															
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																														
children	<a href="#">mailxml_tm:ConsigneeGoodsReceipt</a> <a href="#">mailxml_tm:UnscheduledConsigneeGoodsReceipt</a>																														
used by	element <a href="#">AllApptCloseoutDelivery/FullServiceAllApptCloseoutAccept</a>																														
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:CloseoutResponseID</td> <td><a href="#">mailxml_base:s12</a></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:CreatorSchedulerCorpID</td> <td><a href="#">mailxml_base:s12</a></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:CreatorSchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:CreatorSchedulerCRID</td> <td><a href="#">mailxml_base:CRIDType</a></td> <td>optional</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:CloseoutResponseID	<a href="#">mailxml_base:s12</a>	optional				mailxml_tm:CreatorSchedulerCorpID	<a href="#">mailxml_base:s12</a>	optional				mailxml_tm:CreatorSchedulerID	<a href="#">mailxml_base:s12</a>	optional				mailxml_tm:CreatorSchedulerCRID	<a href="#">mailxml_base:CRIDType</a>	optional			
Name	Type	Use	Default	Fixed	annotation																										
mailxml_tm:CloseoutResponseID	<a href="#">mailxml_base:s12</a>	optional																													
mailxml_tm:CreatorSchedulerCorpID	<a href="#">mailxml_base:s12</a>	optional																													
mailxml_tm:CreatorSchedulerID	<a href="#">mailxml_base:s12</a>	optional																													
mailxml_tm:CreatorSchedulerCRID	<a href="#">mailxml_base:CRIDType</a>	optional																													
annotation	documentation Response indicating that all delivery appointments have been closed.																														

### complexType AppointmentInfoType


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm

children	<a href="#">mailxml_tm:ConsigneeApptID</a> <a href="#">mailxml_tm:AppointmentDate</a> <a href="#">mailxml_tm:ApptType</a> <a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:SchedulerID</a> <a href="#">mailxml_tm:SchedulerCRID</a>
----------	---


#### element AppointmentInfoType/ConsigneeApptID

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s12</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>12</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	12		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	12												
whiteSpace	preserve												

#### element AppointmentInfoType/AppointmentDate

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>xs:dateTime</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple
isRef	0								
minOcc	0								
maxOcc	1								
content	simple								

#### element AppointmentInfoType/ApptType

diagram																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm															
type	<b>mailxml_base:apptTypeType</b>															
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple							
isRef	0															
minOcc	0															
maxOcc	1															
content	simple															
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>enumeration</td><td>Pallet</td><td></td></tr> <tr> <td>enumeration</td><td>DropAndPick</td><td></td></tr> <tr> <td>enumeration</td><td>Speedline</td><td></td></tr> <tr> <td>enumeration</td><td>Bedload</td><td></td></tr> </table>	Kind	Value	annotation	enumeration	Pallet		enumeration	DropAndPick		enumeration	Speedline		enumeration	Bedload	
Kind	Value	annotation														
enumeration	Pallet															
enumeration	DropAndPick															
enumeration	Speedline															
enumeration	Bedload															

### element AppointmentInfoType/ConsigneeFacility

diagram	<pre> sequenceDiagram     participant CF as mailxml_tm:ConsigneeFacility     participant CNT as mailxml_defs:CompanyName     participant FN as mailxml_defs:FacilityNumber     participant FA1 as mailxml_defs:FacilityAddress     participant FA2 as mailxml_defs:FacilityAddress     participant FN2 as mailxml_defs:FacilityName     participant FT as mailxml_defs:FacilityType     participant URL as mailxml_defs:URL     participant CC as mailxml_defs:CommonContact      CF-&gt;&gt;CNT:      CNT--&gt;&gt;FN     FN--&gt;&gt;FA1     FN--&gt;&gt;FA2     FA1--&gt;&gt;FN2     FA1--&gt;&gt;FT     FA1--&gt;&gt;URL     FA1--&gt;&gt;CC   </pre> <p>mailxml_tm:ConsigneeFacility</p> <p>mailxml_defs:CompanyName</p> <p>mailxml_defs:FacilityNumber</p> <p>mailxml_defs:FacilityAddress</p> <p>mailxml_defs:FacilityAddress</p> <p>mailxml_defs:FacilityName</p> <p>mailxml_defs:FacilityType</p> <p>mailxml_defs:URL</p> <p>mailxml_defs:CommonContact</p> <p>0..∞</p>								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	mailxml_defs:consigneeFacilityType								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<p>mailxml_defs:CompanyName mailxml_defs:FacilityNumber mailxml_defs:FacilityAddress      mailxml_defs:FacilityAddress mailxml_defs:FacilityName mailxml_defs:FacilityType mailxml_defs:URL      mailxml_defs:CommonContact</p>								

### element AppointmentInfoType/SchedulerID


diagram	<p>mailxml_tm:SchedulerID</p>												
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	mailxml_base:s12												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>12</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	12		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	12												
whiteSpace	preserve												

### element AppointmentInfoType/SchedulerCRID

diagram	<p>mailxml_tm:SchedulerCRID</p>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm

type	<b>mailxml_base:CRIDType</b>		
properties	isRef 0 minOcc 0 maxOcc 1 content simple		
facets	Kind Value annotation minLength 1 maxLength 15 pattern ([0-9])*		

complexType **apptBlockGoodsType**



namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
children	<a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:MailClass</a> <a href="#">mailxml_tm:ScheduledConsigneeFacility</a> <a href="#">mailxml_tm:ActualConsigneeFacility</a> <a href="#">mailxml_tm:ScheduledAppt</a> <a href="#">mailxml_tm:ActualTruckArrival</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ActualStartUnload</a> <a href="#">mailxml_tm:ActualEndUnload</a> <a href="#">mailxml_tm:ApptStatus</a> <a href="#">mailxml_tm:ContainerCount</a> <a href="#">mailxml_tm:ContainerErrorDescription</a> <a href="#">mailxml_tm:ContainerID</a> <a href="#">mailxml_tm:ContainerType</a> <a href="#">mailxml_tm:IMcb</a> <a href="#">mailxml_tm:IMtb</a> <a href="#">mailxml_tm:IMpb</a> <a href="#">mailxml_tm:ApptMethod</a> <a href="#">mailxml_tm:USPSDetail</a> <a href="#">mailxml_tm:VerificationLocation</a> <a href="#">mailxml_tm:TransportationMethod</a> <a href="#">mailxml_tm:ActualTotalPalletCount</a> <a href="#">mailxml_tm:ActualPalletCount</a> <a href="#">mailxml_tm:EvsSamplingTime</a> <a href="#">mailxml_tm:EFileSamplingTime</a> <a href="#">mailxml_tm:Irregularities</a> <a href="#">mailxml_tm:Resolution</a> <a href="#">mailxml_tm:ActualBedload</a> <a href="#">mailxml_tm:ExemptionCode</a> <a href="#">mailxml_tm:ValueAddedService</a>
used by	elements <a href="#">ConsigneeGoodsReceipt/ApptBlockGoodsReceipt</a> <a href="#">ConsigneeGoodsReceiptDelivery/ApptBlockGoodsReceipt</a>

#### element apptBlockGoodsType/DestinationEntry

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

#### element apptBlockGoodsType/MailClass

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:mailClassType</b>
properties	isRef 0 minOcc 1 maxOcc unbounded content simple
facets	Kind Value annotation enumeration 1 enumeration 2 enumeration 3 enumeration 4 enumeration 6

### element apptBlockGoodsType/ScheduledConsigneeFacility

diagram	<pre> sequenceDiagram     participant SCF as mailxml_tm:ScheduledConsigneeFacility     participant CFT as mailxml_defs:consigneeFacilityType     participant CN as mailxml_defs:CompanyName     participant FN as mailxml_defs:FacilityNumber     participant FA1 as mailxml_defs:FacilityAddress     participant FA2 as mailxml_defs:FacilityAddress     participant FN as mailxml_defs:FacilityName     participant FT as mailxml_defs:FacilityType     participant URL as mailxml_defs:URL     participant CC as mailxml_defs:CommonContact      SCF-&gt;&gt;CFT:      activate CFT     CFT--&gt;&gt;CN:      activate CN     CN--&gt;&gt;SCF:      deactivate CN     CFT--&gt;&gt;FN:      activate FN     FN--&gt;&gt;SCF:      deactivate FN     CFT--&gt;&gt;FA1:      activate FA1     FA1--&gt;&gt;SCF:      deactivate FA1     CFT--&gt;&gt;FA2:      activate FA2     FA2--&gt;&gt;SCF:      deactivate FA2     CFT--&gt;&gt;FN:      activate FN     FN--&gt;&gt;SCF:      deactivate FN     CFT--&gt;&gt;FT:      activate FT     FT--&gt;&gt;SCF:      deactivate FT     CFT--&gt;&gt;URL:      activate URL     URL--&gt;&gt;SCF:      deactivate URL     CFT--&gt;&gt;CC:      activate CC     CC--&gt;&gt;SCF:      deactivate CC   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	mailxml_defs:consigneeFacilityType
properties	isRef 0 content complex
children	mailxml_defs:CompanyName mailxml_defs:FacilityNumber mailxml_defs:FacilityAddress mailxml_defs:FacilityAddress mailxml_defs:FacilityName mailxml_defs:FacilityType mailxml_defs:URL mailxml_defs:CommonContact

### element apptBlockGoodsType/StartTheClockDate


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	xs:date
properties	isRef 0 minOcc 0 maxOcc 1 content simple

### element apptBlockGoodsType/ContainerCount

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	mailxml_base:s06
properties	isRef 0 minOcc 0 maxOcc unbounded content simple

facets	Kind minLength maxLength whiteSpace	Value 1 6 preserve	annotation
--------	--	-----------------------------	------------

#### element **apptBlockGoodsType/ContainerErrorDescription**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:s500</b>
properties	isRef 0 minOcc 0 maxOcc unbounded content simple
facets	Kind Value annotation minLength 1 maxLength 500 whiteSpace preserve

#### element **apptBlockGoodsType/ContainerID**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:s06</b>
properties	isRef 0 minOcc 0 maxOcc unbounded content simple
facets	Kind Value annotation minLength 1 maxLength 6 whiteSpace preserve

#### element **apptBlockGoodsType/ContainerType**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:mailXMLContainerType</b>
properties	isRef 0 minOcc 0 maxOcc unbounded content simple

facets	Kind	Value	annotation
	enumeration	1	
	enumeration	2	
	enumeration	3	
	enumeration	4	
	enumeration	5	
	enumeration	6	
	enumeration	7	
	enumeration	8	
	enumeration	9	
	enumeration	10	
	enumeration	11	
	enumeration	12	
	enumeration	13	
	enumeration	14	
	enumeration	E	
	enumeration	F	
	enumeration	L	
	enumeration	O	
	enumeration	P	
	enumeration	S	
	enumeration	T	
	enumeration	V	
	enumeration	B	
	enumeration	U	
	enumeration	Z	
	enumeration	X	
	enumeration	H	
	enumeration	A	
	enumeration	G	
	enumeration	D	
	enumeration	R	
	enumeration	C	
	enumeration	CT	
	enumeration	M	
	enumeration	AB	
	enumeration	Y	

### element apptBlockGoodsType/IMcb


diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:IMcbType</b>

properties	isRef 0 minOcc 0 maxOcc unbounded content simple
facets	Kind Value annotation minLength 21 maxLength 24


#### element apptBlockGoodsType/IMtb

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:IMtbType</b>
properties	isRef 0 minOcc 0 maxOcc unbounded content simple
facets	Kind Value annotation minLength 24 maxLength 24

#### element apptBlockGoodsType/IMpb


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:IMpbType</b>
properties	isRef 0 minOcc 0 maxOcc unbounded content simple
facets	Kind Value annotation minLength 21 maxLength 34

#### element apptBlockGoodsType/ApptMethod


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:apptMethodType</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Online enumeration Phone

	enumeration Webservices - Detail
	enumeration Webservices - No Detail

#### element apptBlockGoodsType/USPSDetail

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_tm:uspsDetailType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#">mailxml_tm:USPSMultiApptID</a> <a href="#">mailxml_tm:USPSClosedBySV</a>								


#### element apptBlockGoodsType/VerificationLocation

diagram										
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm									
type	<a href="#">mailxml_tm:verificationLocationType</a>									
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple	
isRef	0									
minOcc	0									
maxOcc	1									
content	simple									
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>enumeration</td><td>BMEU</td><td></td></tr> <tr> <td>enumeration</td><td>DMU</td><td></td></tr> </table>	Kind	Value	annotation	enumeration	BMEU		enumeration	DMU	
Kind	Value	annotation								
enumeration	BMEU									
enumeration	DMU									


#### element apptBlockGoodsType/TransportationMethod

diagram										
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm									
type	<a href="#">mailxml_base:transportationMethodType</a>									
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple	
isRef	0									
minOcc	0									
maxOcc	1									
content	simple									
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>enumeration</td><td>USPS</td><td></td></tr> <tr> <td>enumeration</td><td>Mailer</td><td></td></tr> </table>	Kind	Value	annotation	enumeration	USPS		enumeration	Mailer	
Kind	Value	annotation								
enumeration	USPS									
enumeration	Mailer									

### element apptBlockGoodsType/ActualTotalPalletCount

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:nonNegativeInteger</b>
properties	<p>isRef 0  minOcc 0  maxOcc 1  content simple</p>


### element apptBlockGoodsType/ActualPalletCount

diagram																	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																
type	<b>mailxml_tm:actualPalletType</b>																
properties	<p>isRef 0  minOcc 0  maxOcc unbounded  content complex</p>																
children	<b>mailxml_tm:ActualPalletCount</b>																
attributes	<table> <tr> <td>Name</td> <td><a href="#">mailxml_tm:HandlingUnit</a></td> <td>Type</td> <td><a href="#">mailxml_base:palletHandlingUnitType</a></td> <td>Use</td> <td>Default</td> <td>Fixed</td> <td>annotation</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>required</td> <td></td> <td></td> <td></td> </tr> </table>	Name	<a href="#">mailxml_tm:HandlingUnit</a>	Type	<a href="#">mailxml_base:palletHandlingUnitType</a>	Use	Default	Fixed	annotation					required			
Name	<a href="#">mailxml_tm:HandlingUnit</a>	Type	<a href="#">mailxml_base:palletHandlingUnitType</a>	Use	Default	Fixed	annotation										
				required													

### element apptBlockGoodsType/EvsSamplingTime

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:dateTime</b>
properties	<p>isRef 0  minOcc 0  maxOcc 1  content simple</p>

### element apptBlockGoodsType/EFileSamplingTime

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_tm:EFileSamplingTimeType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	unbounded	content	complex
isRef	0								
minOcc	0								
maxOcc	unbounded								
content	complex								
children	<a href="#">mailxml_tm:EFileNumber</a> <a href="#">mailxml_tm:EFileSamplingTime</a>								

### element apptBlockGoodsType/Irrregularities


diagram																																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																															
type	<a href="#">mailxml_base:closeoutIrregularitiesType</a>																																																															
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	unbounded	content	simple																																																							
isRef	0																																																															
minOcc	0																																																															
maxOcc	unbounded																																																															
content	simple																																																															
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>B</td><td></td></tr> <tr> <td>enumeration</td><td>C</td><td></td></tr> <tr> <td>enumeration</td><td>D</td><td></td></tr> <tr> <td>enumeration</td><td>DR</td><td></td></tr> <tr> <td>enumeration</td><td>G</td><td></td></tr> <tr> <td>enumeration</td><td>IA</td><td></td></tr> <tr> <td>enumeration</td><td>IM</td><td></td></tr> <tr> <td>enumeration</td><td>I</td><td></td></tr> <tr> <td>enumeration</td><td>IF</td><td></td></tr> <tr> <td>enumeration</td><td>L</td><td></td></tr> <tr> <td>enumeration</td><td>M</td><td></td></tr> <tr> <td>enumeration</td><td>MI</td><td></td></tr> <tr> <td>enumeration</td><td>NP</td><td></td></tr> <tr> <td>enumeration</td><td>O</td><td></td></tr> <tr> <td>enumeration</td><td>OW</td><td></td></tr> <tr> <td>enumeration</td><td>NM</td><td></td></tr> <tr> <td>enumeration</td><td>P</td><td></td></tr> <tr> <td>enumeration</td><td>VS</td><td></td></tr> <tr> <td>enumeration</td><td>CP</td><td></td></tr> <tr> <td>enumeration</td><td>CM</td><td></td></tr> </tbody> </table>	Kind	Value	annotation	enumeration	B		enumeration	C		enumeration	D		enumeration	DR		enumeration	G		enumeration	IA		enumeration	IM		enumeration	I		enumeration	IF		enumeration	L		enumeration	M		enumeration	MI		enumeration	NP		enumeration	O		enumeration	OW		enumeration	NM		enumeration	P		enumeration	VS		enumeration	CP		enumeration	CM	
Kind	Value	annotation																																																														
enumeration	B																																																															
enumeration	C																																																															
enumeration	D																																																															
enumeration	DR																																																															
enumeration	G																																																															
enumeration	IA																																																															
enumeration	IM																																																															
enumeration	I																																																															
enumeration	IF																																																															
enumeration	L																																																															
enumeration	M																																																															
enumeration	MI																																																															
enumeration	NP																																																															
enumeration	O																																																															
enumeration	OW																																																															
enumeration	NM																																																															
enumeration	P																																																															
enumeration	VS																																																															
enumeration	CP																																																															
enumeration	CM																																																															

	enumeration SM enumeration AR enumeration IO enumeration MN enumeration MS enumeration MF enumeration MA enumeration NF enumeration IP enumeration PD
--	--

#### element **apptBlockGoodsType/Resolution**


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:closeoutResolutionType</b>
properties	isRef 0 minOcc 0 maxOcc unbounded content simple
facets	Kind Value annotation enumeration DCD enumeration DCO enumeration DRL enumeration INR

#### element **apptBlockGoodsType/ActualBedload**


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_tm:actualBedloadType</b>
properties	isRef 0 minOcc 0 maxOcc unbounded content complex
children	<a href="#">mailxml_tm:ActualBedloadPercent</a> <a href="#">mailxml_tm:ActualBedloadCount</a>

attributes	Name <a href="#">mailxml_tm:HandlingUnit</a>	Type <a href="#">mailxml_base:palletHandlingUnitType</a>	Use required	Default	Fixed	annotation
------------	---	---	-----------------	---------	-------	------------

**element apptBlockGoodsType/ExemptionCode**

diagram																			
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																		
type	<a href="#">mailxml_base:exemptionCodeType</a>																		
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	unbounded	content	simple										
isRef	0																		
minOcc	0																		
maxOcc	unbounded																		
content	simple																		
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>enumeration</td><td>APO</td><td></td></tr> <tr> <td>enumeration</td><td>APS</td><td></td></tr> <tr> <td>enumeration</td><td>CAPC</td><td></td></tr> <tr> <td>enumeration</td><td>DUE</td><td></td></tr> <tr> <td>enumeration</td><td>HC</td><td></td></tr> </table>	Kind	Value	annotation	enumeration	APO		enumeration	APS		enumeration	CAPC		enumeration	DUE		enumeration	HC	
Kind	Value	annotation																	
enumeration	APO																		
enumeration	APS																		
enumeration	CAPC																		
enumeration	DUE																		
enumeration	HC																		

**element apptBlockGoodsType/ValueAddedService**

diagram																																																				
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																																			
type	<a href="#">mailxml_tm:valueAddedServiceType</a>																																																			
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple																																											
isRef	0																																																			
minOcc	0																																																			
maxOcc	1																																																			
content	simple																																																			
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>enumeration</td><td>D1</td><td></td></tr> <tr> <td>enumeration</td><td>D2</td><td></td></tr> <tr> <td>enumeration</td><td>D3</td><td></td></tr> <tr> <td>enumeration</td><td>D4</td><td></td></tr> <tr> <td>enumeration</td><td>D5</td><td></td></tr> <tr> <td>enumeration</td><td>D6</td><td></td></tr> <tr> <td>enumeration</td><td>D7</td><td></td></tr> <tr> <td>enumeration</td><td>D8</td><td></td></tr> <tr> <td>enumeration</td><td>D9</td><td></td></tr> <tr> <td>enumeration</td><td>D10</td><td></td></tr> <tr> <td>enumeration</td><td>D11</td><td></td></tr> <tr> <td>enumeration</td><td>D12</td><td></td></tr> <tr> <td>enumeration</td><td>D13</td><td></td></tr> <tr> <td>enumeration</td><td>D14</td><td></td></tr> <tr> <td>enumeration</td><td>D15</td><td></td></tr> <tr> <td>enumeration</td><td>D16</td><td></td></tr> </table>	Kind	Value	annotation	enumeration	D1		enumeration	D2		enumeration	D3		enumeration	D4		enumeration	D5		enumeration	D6		enumeration	D7		enumeration	D8		enumeration	D9		enumeration	D10		enumeration	D11		enumeration	D12		enumeration	D13		enumeration	D14		enumeration	D15		enumeration	D16	
Kind	Value	annotation																																																		
enumeration	D1																																																			
enumeration	D2																																																			
enumeration	D3																																																			
enumeration	D4																																																			
enumeration	D5																																																			
enumeration	D6																																																			
enumeration	D7																																																			
enumeration	D8																																																			
enumeration	D9																																																			
enumeration	D10																																																			
enumeration	D11																																																			
enumeration	D12																																																			
enumeration	D13																																																			
enumeration	D14																																																			
enumeration	D15																																																			
enumeration	D16																																																			

	enumeration D17 enumeration D18 enumeration D19 enumeration D20
--	--

### complexType apptBlockRequestType

diagram	<pre> sequenceDiagram     participant APPT as apptBlockRequestType     participant CF as mailxml_tm:ConsigneeFacility     participant PA as mailxml_tm:PreferredAppt     participant OA as mailxml_tm:OptionalAppt     participant CM as mailxml_tm:Comment      APPT-&gt;&gt;CF:      activate CF     CF--&gt;&gt;PA:      activate PA     PA--&gt;&gt;OA:      activate OA     OA--&gt;&gt;CM:      activate CM     CM--&gt;&gt;PA:      deactivate CM     deactivate OA     deactivate PA   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:PreferredAppt</a> <a href="#">mailxml_tm:OptionalAppt</a> <a href="#">mailxml_tm:Comment</a>
used by	elements <a href="#">DeliveryApptCancelCreateRequest/ApptBlock</a> <a href="#">DeliveryReApptRequest/ApptBlock</a>


### element apptBlockRequestType/ConsigneeFacility

diagram	<pre> sequenceDiagram     participant CF as mailxml_tm:ConsigneeFacility     participant CFT as mailxml_defs:consigneeFacilityType     participant CC as mailxml_defs:CommonContact      CF-&gt;&gt;CFT:      activate CFT     CFT--&gt;&gt;CC:      activate CC     CC--&gt;&gt;CF:      deactivate CC   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_defs:consigneeFacilityType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_defs:CompanyName</a> <a href="#">mailxml_defs:FacilityNumber</a> <a href="#">mailxml_defs:FacilityAddress</a> <a href="#">mailxml_defs:FacilityAddress</a> <a href="#">mailxml_defs:FacilityName</a> <a href="#">mailxml_defs:FacilityType</a> <a href="#">mailxml_defs:URL</a> <a href="#">mailxml_defs:CommonContact</a> 0..∞

element **apptBlockRequestType/PreferredAppt**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:dateTime</b>
properties	isRef 0 content simple

element **apptBlockRequestType/OptionalAppt**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_tm:optionalApptType</b>
properties	isRef 0 minOcc 0 maxOcc unbounded content complex
children	<a href="#">mailxml_tm:Start</a> <a href="#">mailxml_tm:End</a>

element **apptBlockRequestType/Comment**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s256</b>												
properties	isRef 0 minOcc 0 maxOcc 1 content simple												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>256</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	256		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	256												
whiteSpace	preserve												

**complexType apptBlockUnscheduledGoodsType**

diagram	<pre> sequenceDiagram     participant APPT as apptBlockUnscheduledGoodsType     participant MAILCLASS as mailxml_tm:MailClass     participant ACTUALCONSIGNEE as mailxml_tm:ActualConsigneeFacility     participant ACTUALTRUCKARRIVAL as mailxml_tm:ActualTruckArrival     participant STARTCLOCKDATE as mailxml_tm:StartTheClockDate     participant ACTUALSTARTUNLOAD as mailxml_tm:ActualStartUnload     participant ACTUALENDUNLOAD as mailxml_tm:ActualEndUnload     participant APPTSTATUS as mailxml_tm:ApptStatus     participant IRREGULARITIES as mailxml_tm:Irregularities     participant RESOLUTION as mailxml_tm:Resolution     participant ACTUALBEDLOAD as mailxml_tm:ActualBedload     participant ACTUALTOTALPALLET as mailxml_tm:ActualTotalPalletCount     participant ACTUALPALLETCOUNT as mailxml_tm:ActualPalletCount     participant VALUEADDEDSERVICE as mailxml_tm:ValueAddedService      APPT-&gt;&gt;MAILCLASS:      APPT--&gt;&gt;ACTUALCONSIGNEE:      ACTUALCONSIGNEE--&gt;&gt;ACTUALTRUCKARRIVAL:      ACTUALCONSIGNEE--&gt;&gt;STARTCLOCKDATE:      ACTUALCONSIGNEE--&gt;&gt;ACTUALSTARTUNLOAD:      ACTUALCONSIGNEE--&gt;&gt;ACTUALENDUNLOAD:      ACTUALCONSIGNEE--&gt;&gt;APPTSTATUS:      ACTUALCONSIGNEE--&gt;&gt;IRREGULARITIES:      ACTUALCONSIGNEE--&gt;&gt;RESOLUTION:      ACTUALCONSIGNEE--&gt;&gt;ACTUALBEDLOAD:      ACTUALCONSIGNEE--&gt;&gt;ACTUALTOTALPALLET:      ACTUALCONSIGNEE--&gt;&gt;ACTUALPALLETCOUNT:      ACTUALCONSIGNEE--&gt;&gt;VALUEADDEDSERVICE:    </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
children	<a href="#">mailxml_tm:MailClass</a> <a href="#">mailxml_tm:ActualConsigneeFacility</a> <a href="#">mailxml_tm:ActualTruckArrival</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ActualStartUnload</a> <a href="#">mailxml_tm:ActualEndUnload</a> <a href="#">mailxml_tm:ApptStatus</a> <a href="#">mailxml_tm:Irregularities</a> <a href="#">mailxml_tm:Resolution</a> <a href="#">mailxml_tm:ActualBedload</a> <a href="#">mailxml_tm:ActualTotalPalletCount</a> <a href="#">mailxml_tm:ActualPalletCount</a> <a href="#">mailxml_tm:ValueAddedService</a>
used by	elements <a href="#">UnscheduledConsigneeGoodsReceipt/ApptBlockUnscheduledGoodsReceipt</a> <a href="#">UnscheduledConsigneeGoodsReceiptDelivery/ApptBlockUnscheduledGoodsReceipt</a>

**element apptBlockUnscheduledGoodsType/MailClass**

diagram	<pre> sequenceDiagram     participant MAILCLASS as mailxml_tm:MailClass     participant APPT as apptBlockUnscheduledGoodsType      APPT--&gt;&gt;MAILCLASS:    </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm

type	<b>mailxml_base:mailClassType</b>
properties	isRef 0 minOcc 1 maxOcc unbounded content simple
facets	Kind Value annotation enumeration 1 enumeration 2 enumeration 3 enumeration 4 enumeration 6

#### element **apptBlockUnscheduledGoodsType/StartTheClockDate**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:date</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple

#### element **apptBlockUnscheduledGoodsType/Irregularities**


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:closeoutIrregularitiesType</b>
properties	isRef 0 minOcc 0 maxOcc unbounded content simple
facets	Kind Value annotation enumeration B enumeration C enumeration D enumeration DR enumeration G enumeration IA enumeration IM enumeration I enumeration IF enumeration L enumeration M enumeration MI enumeration NP

	enumeration O
	enumeration OW
	enumeration NM
	enumeration P
	enumeration VS
	enumeration CP
	enumeration CM
	enumeration SM
	enumeration AR
	enumeration IO
	enumeration MN
	enumeration MS
	enumeration MF
	enumeration MA
	enumeration NF
	enumeration IP
	enumeration PD


**element apptBlockUnscheduledGoodsType/Resolution**

diagram																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm															
type	<b>mailxml_base:closeoutResolutionType</b>															
properties	isRef 0 minOcc 0 maxOcc unbounded content simple															
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>DCD</td> <td></td> </tr> <tr> <td>enumeration</td> <td>DCO</td> <td></td> </tr> <tr> <td>enumeration</td> <td>DRL</td> <td></td> </tr> <tr> <td>enumeration</td> <td>INR</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	enumeration	DCD		enumeration	DCO		enumeration	DRL		enumeration	INR	
Kind	Value	annotation														
enumeration	DCD															
enumeration	DCO															
enumeration	DRL															
enumeration	INR															


element **apptBlockUnscheduledGoodsType/ActualBedload**

diagram																	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																
type	<a href="#">mailxml_tm:actualBedloadType</a>																
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	unbounded	content	complex								
isRef	0																
minOcc	0																
maxOcc	unbounded																
content	complex																
children	<a href="#">mailxml_tm:ActualBedloadPercent</a> <a href="#">mailxml_tm:ActualBedloadCount</a>																
attributes	<table> <tr> <td>Name</td><td></td><td>Type</td><td></td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td></td><td><a href="#">mailxml_tm:HandlingUnit</a></td><td><a href="#">mailxml_base:palletHandlingUnitType</a></td><td></td><td>required</td><td></td><td></td><td></td></tr> </table>	Name		Type		Use	Default	Fixed	annotation		<a href="#">mailxml_tm:HandlingUnit</a>	<a href="#">mailxml_base:palletHandlingUnitType</a>		required			
Name		Type		Use	Default	Fixed	annotation										
	<a href="#">mailxml_tm:HandlingUnit</a>	<a href="#">mailxml_base:palletHandlingUnitType</a>		required													

element **apptBlockUnscheduledGoodsType/ActualTotalPalletCount**


diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">xs:nonNegativeInteger</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple
isRef	0								
minOcc	0								
maxOcc	1								
content	simple								

element **apptBlockUnscheduledGoodsType/ActualPalletCount**

diagram					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm				
type	<a href="#">mailxml_tm:actualPalletType</a>				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> </table>	isRef	0	minOcc	0
isRef	0				
minOcc	0				

	maxOcc content	unbounded complex					
children	<a href="#">mailxml_tm:ActualPalletCount</a>						
attributes	Name <a href="#">mailxml_tm:HandlingUnit</a>	Type <a href="#">mailxml_base:palletHandlingUnitType</a>	Use required	Default	Fixed	annotation	

element **apptBlockUnscheduledGoodsType/ValueAddedService**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:valueAddedServiceType</a>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation enumeration D1 enumeration D2 enumeration D3 enumeration D4 enumeration D5 enumeration D6 enumeration D7 enumeration D8 enumeration D9 enumeration D10 enumeration D11 enumeration D12 enumeration D13 enumeration D14 enumeration D15 enumeration D16 enumeration D17 enumeration D18 enumeration D19 enumeration D20


**complexType apptBlockUpdateType**

diagram	<pre> graph LR     apptBlockUpdateType[apptBlockUpdateType] --- ConsigneeFacility[mailxml_tm:ConsigneeFacility]     ConsigneeFacility --- PreferredAppt[mailxml_tm:PreferredAppt]     PreferredAppt --- OptionalAppt[mailxml_tm:OptionalAppt]     PreferredAppt --- ETA[mailxml_tm:ETA]     PreferredAppt --- Comment[mailxml_tm:Comment]     </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:PreferredAppt</a> <a href="#">mailxml_tm:OptionalAppt</a> <a href="#">mailxml_tm:ETA</a> <a href="#">mailxml_tm:Comment</a>
used by	element <a href="#">DeliveryApptUpdate/ApptBlockUpdate</a>

**element apptBlockUpdateType/ConsigneeFacility**

diagram	<pre> graph LR     ConsigneeFacility[mailxml_tm:ConsigneeFacility] --- consigneeFacilityType[mailxml_defs:consigneeFacilityType]     consigneeFacilityType --- CompanyName[mailxml_defs:CompanyName]     CompanyName --- FacilityNumber[mailxml_defs:FacilityNumber]     FacilityNumber --- FacilityAddress[mailxml_defs:FacilityAddress]     FacilityAddress --- FacilityName[mailxml_defs:FacilityName]     FacilityName --- FacilityType[mailxml_defs:FacilityType]     FacilityType --- URL[mailxml_defs:URL]     URL --- CommonContact[mailxml_defs:CommonContact]     </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_defs:consigneeFacilityType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_defs:CompanyName</a> <a href="#">mailxml_defs:FacilityNumber</a> <a href="#">mailxml_defs:FacilityAddress</a> <a href="#">mailxml_defs:FacilityAddress</a> <a href="#">mailxml_defs:FacilityName</a> <a href="#">mailxml_defs:FacilityType</a> <a href="#">mailxml_defs:URL</a> <a href="#">mailxml_defs:CommonContact</a>

**element apptBlockUpdateType/PreferredAppt**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:dateTime</b>
properties	isRef 0 minOcc 0 maxOcc unbounded content simple


**element apptBlockUpdateType/OptionalAppt**

diagram	 0..∞
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:dateTime</b>
properties	isRef 0 minOcc 0 maxOcc unbounded content simple

**element apptBlockUpdateType/ETA**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:dateTime</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple

**element apptBlockUpdateType/Comment**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s26</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 256 whiteSpace preserve

**complexType apptCloseoutDetailType**

diagram	<pre> graph LR     apptCloseoutDetailType[apptCloseoutDetailType] --&gt; UserID[mailxml_tm:UserID]     apptCloseoutDetailType --&gt; ApptCloseOut[mailxml_tm:ApptCloseOut]     ApptCloseOut -.-&gt; ApptCloseoutEmployeeContactInfo[mailxml_tm:ApptCloseoutEmployeeContactInfo]   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
children	<a href="#">mailxml_tm:UserID</a> <a href="#">mailxml_tm:ApptCloseOut</a> <a href="#">mailxml_tm:ApptCloseoutEmployeeContactInfo</a>
used by	element <a href="#">apptInfoType/ApptCloseOutDetail</a>

**element apptCloseoutDetailType/UserID**

diagram	<pre> graph LR     UserID[mailxml_tm:UserID]   </pre>												
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>												
type	<b>mailxml_base:s12</b>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	content	simple								
isRef	0												
content	simple												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>12</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	12		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	12												
whiteSpace	preserve												

**element apptCloseoutDetailType/ApptCloseOut**

diagram	<pre> graph LR     ApptCloseOut[mailxml_tm:ApptCloseOut]   </pre>				
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>				
type	<b>xs:dateTime</b>				
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	content	simple
isRef	0				
content	simple				

element **apptCloseoutDetailType/ApptCloseoutEmployeeContactInfo**

diagram	<pre> classDiagram     class mailxml_tm::ApptCloseoutEmployeeContactInfo     class mailxml_defs::commonContactType {         &lt;&lt;attributes&gt;&gt;         mailxml_defs::ContactType         mailxml_defs::ContactName         mailxml_defs::Telephone         mailxml_defs::MobilePhone         mailxml_defs::Email         mailxml_defs::Fax         mailxml_defs::GPSCoordinates         mailxml_defs::ContactID     }     mailxml_tm::ApptCloseoutEmployeeContactInfo --&gt; mailxml_defs::commonContactType     mailxml_tm::ApptCloseoutEmployeeContactInfo *--&gt; mailxml_defs::commonContactType   </pre>												
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_defs:commonContactType</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex				
isRef	0												
minOcc	0												
maxOcc	1												
content	complex												
children	<b>mailxml_defs:ContactName mailxml_defs:Telephone mailxml_defs:MobilePhone mailxml_defs:Email mailxml_defs:Fax mailxml_defs:GPSCoordinates mailxml_defs:ContactID</b>												
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:ContactType</td><td><b>mailxml_base:contactType</b></td><td>required</td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:ContactType	<b>mailxml_base:contactType</b>	required			
Name	Type	Use	Default	Fixed	annotation								
mailxml_defs:ContactType	<b>mailxml_base:contactType</b>	required											

complexType **apptCloseoutNotAvailableResponseType**

diagram	<pre> classDiagram     class apptCloseoutNotAvailableResponse     class grp {         mailxml_tm::InductionCloseoutNotAvailableResponse     }     grp {         &lt;&lt;attributes&gt;&gt;         mailxml_tm::ConsigneeApptID         mailxml_tm::SchedulerID         mailxml_tm::SchedulerCorpID     }     apptCloseoutNotAvailableResponse --&gt; grp     apptCloseoutNotAvailableResponse *--&gt; grp     grp *--&gt; mailxml_tm::ReturnCode     grp *--&gt; mailxml_tm::ReturnDescription   </pre>
---------	---

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
children	<a href="#">mailxml_tm:ReturnCode</a> <a href="#">mailxml_tm:ReturnDescription</a>					
used by	element <a href="#">ApptInductionCloseoutResponse</a> / <a href="#">ApptInductionCloseoutReject</a>					
attributes	Name mailxml_tm:ConsigneeApptID	Type <b>mailxml_base:s12</b>	Use required	Default	Fixed	annotation
	mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>	optional			
	mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>	required			


#### element **apptCloseoutNotAvailableResponseType/ReturnCode**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:ns04</b>
properties	isRef 0 content simple
facets	Kind Value annotation pattern [0-9]{4}

#### element **apptCloseoutNotAvailableResponseType/ReturnDescription**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s260</b>
properties	isRef 0 content simple
facets	Kind Value annotation minLength 1 maxLength 260 whiteSpace preserve

### complexType apptCloseoutResponseType

diagram																									
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																								
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:ApptInfo</a> <a href="#">mailxml_tm:ContainerInductionInfo</a>																								
used by	element <a href="#">ApptInductionCloseoutResponse/ApptInductionCloseoutAccept</a>																								
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_tm:ConsigneeApptID</td><td><b>mailxml_base:s12</b></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:SchedulerID</td><td><b>mailxml_base:s12</b></td><td>optional</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:SchedulerCorpID</td><td><b>mailxml_base:s12</b></td><td>required</td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>	required				mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>	optional				mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>	required			
Name	Type	Use	Default	Fixed	annotation																				
mailxml_tm:ConsigneeApptID	<b>mailxml_base:s12</b>	required																							
mailxml_tm:SchedulerID	<b>mailxml_base:s12</b>	optional																							
mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>	required																							

### element apptCloseoutResponseType/TrackingID

diagram													
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>20</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												


element **apptCloseoutResponseType/ApptInfo**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:apptInfoType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:ApptConsigneeID</a> <a href="#">mailxml_tm:ApptState</a> <a href="#">mailxml_tm:ScheduledAppt</a> <a href="#">mailxml_tm:ActualTruckArrival</a> <a href="#">mailxml_tm:ActualStartUnload</a> <a href="#">mailxml_tm:ActualEndUnload</a> <a href="#">mailxml_tm:ApptCloseOutDetail</a>

element **apptCloseoutResponseType/ContainerInductionInfo**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:containerInductionInfoType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:ContainerType</a>

### complexType apptInfoType

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
children	<a href="#">mailxml_tm:ApptConsigneeID</a> <a href="#">mailxml_tm:ApptState</a> <a href="#">mailxml_tm:ScheduledAppt</a> <a href="#">mailxml_tm:ActualTruckArrival</a> <a href="#">mailxml_tm:ActualStartUnload</a> <a href="#">mailxml_tm:ActualEndUnload</a> <a href="#">mailxml_tm:ApptCloseOutDetail</a>
used by	element <a href="#">apptCloseoutResponseType/ApptInfo</a>

### element apptInfoType/ApptConsigneeID

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_base:s12</a>
properties	isRef 0 content simple
facets	Kind Value annotation minLength 1 maxLength 12 whiteSpace preserve

### element apptInfoType/ApptState

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_base:apptStateType</a>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Scheduled enumeration Arrived enumeration ApptValidated

	<p>enumeration WaitingToBeUnloaded</p> <p>enumeration Unloading</p> <p>enumeration FinishedUnloading</p> <p>enumeration ResolvingProblems</p> <p>enumeration Rejected</p> <p>enumeration Closed</p>
--	---

#### element apptInfoType/ApptCloseOutDetail

diagram	<pre> classDiagram     class ApptCloseOutDetail {         &lt;&lt;mailxml_tm:ApptCloseOutDetail&gt;&gt;     }     class UserID {         &lt;&lt;mailxml_tm:UserID&gt;&gt;     }     class ApptCloseOut {         &lt;&lt;mailxml_tm:ApptCloseOut&gt;&gt;     }     class ApptCloseoutEmployeeContactInfo {         &lt;&lt;mailxml_tm:ApptCloseoutEmployeeContactInfo&gt;&gt;     }      ApptCloseOutDetail "3..4" --&gt; UserID :      ApptCloseOutDetail "3..4" --&gt; ApptCloseOut :      ApptCloseOutDetail "3..4" --&gt; ApptCloseoutEmployeeContactInfo :    </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:apptCloseoutDetailType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:UserID</a> <a href="#">mailxml_tm:ApptCloseOut</a> <a href="#">mailxml_tm:ApptCloseoutEmployeeContactInfo</a>

#### complexType availableApptType

diagram	<pre> classDiagram     class availableApptType {         &lt;&lt;availableApptType&gt;&gt;     }     class Start {         &lt;&lt;mailxml_tm:Start&gt;&gt;     }     class End {         &lt;&lt;mailxml_tm:End&gt;&gt;     }     class Units {         &lt;&lt;mailxml_tm:Units&gt;&gt;     }     class ReturnInfo {         &lt;&lt;mailxml_tm:ReturnInfo&gt;&gt;     }      availableApptType "3..4" --&gt; Start :      availableApptType "3..4" --&gt; End :      availableApptType "3..4" --&gt; Units :      availableApptType "3..4" --&gt; ReturnInfo :    </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
children	<a href="#">mailxml_tm:Start</a> <a href="#">mailxml_tm:End</a> <a href="#">mailxml_tm:Units</a> <a href="#">mailxml_tm:ReturnInfo</a>
used by	element <a href="#">OpenApptQueryResponse/QueryResults/AvailableAppt</a>


#### element availableApptType/Start

diagram	<pre> classDiagram     class Start {         &lt;&lt;mailxml_tm:Start&gt;&gt;     }      Start   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">xs:dateTime</a>
properties	isRef 0 content simple

### element availableApptType/End

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:dateTime</b>
properties	isRef 0 content simple

### element availableApptType/Units

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:UnitLoadType</a> <a href="#">mailxml_tm:Quantity</a>


### element availableApptType/Units/UnitLoadType

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:unitLoadType</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration CrossDockPallets enumeration WorkingPallets enumeration Trailers


### element availableApptType/Units/Quantity

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:n06</b>
properties	isRef 0 content simple
facets	Kind Value annotation totalDigits 6

### element availableApptType/ReturnInfo

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>mailxml_defs:returnInfoType</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<b>mailxml_defs:ConsigneeFacility</b> <b>mailxml_defs:ErrorWarning</b> <b>mailxml_defs:ContainerErrorWarningBlock</b>								

### complexType availableHourType

diagram																	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																
used by	element <b>availableSlotType/AvailableHours</b>																
attributes	<table> <tr> <td>Name</td><td><a href="#">mailxml_tm:PreferredAppt</a></td><td>Type</td><td><a href="#">xs:dateTime</a></td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td></td><td><a href="#">mailxml_tm:AvailableSlots</a></td><td></td><td><a href="#">mailxml_base:s02</a></td><td></td><td></td><td></td><td></td></tr> </table>	Name	<a href="#">mailxml_tm:PreferredAppt</a>	Type	<a href="#">xs:dateTime</a>	Use	Default	Fixed	annotation		<a href="#">mailxml_tm:AvailableSlots</a>		<a href="#">mailxml_base:s02</a>				
Name	<a href="#">mailxml_tm:PreferredAppt</a>	Type	<a href="#">xs:dateTime</a>	Use	Default	Fixed	annotation										
	<a href="#">mailxml_tm:AvailableSlots</a>		<a href="#">mailxml_base:s02</a>														

### attribute availableHourType/@PreferredAppt

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:dateTime</b>
properties	isRef 0

### attribute availableHourType/@AvailableSlots

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s02</b>
properties	isRef 0
facets	Kind Value annotation

	minLength 1 maxLength 2 whiteSpace preserve
--	---

### complexType availableSlotType

diagram	<pre> graph LR     availableSlotType[availableSlotType] --- MailClass[mailxml_tm:MailClass]     availableSlotType --- Perishable[mailxml_tm:Perishable]     availableSlotType --- AvailableHours[mailxml_tm:AvailableHours]     MailClass -- "1..∞" --&gt; AvailableHours   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
children	<a href="#">mailxml_tm:MailClass</a> <a href="#">mailxml_tm:Perishable</a> <a href="#">mailxml_tm:AvailableHours</a>
used by	element <a href="#">DeliveryApptQueryResponse/QueryResults/AvailableSlots</a>

### element availableSlotType/MailClass

diagram	<pre> graph LR     availableSlotType[availableSlotType] --- MailClass[mailxml_tm:MailClass]     MailClass -- "1..∞" --&gt; AvailableHours   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_base:mailClassType</a>
properties	isRef 0 minOcc 1 maxOcc unbounded content simple
facets	Kind Value annotation enumeration 1 enumeration 2 enumeration 3 enumeration 4 enumeration 6

### element availableSlotType/Perishable

diagram	<pre> graph LR     availableSlotType[availableSlotType] --- Perishable[mailxml_tm:Perishable]   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_base:yesNo</a>
properties	isRef 0 minOcc 0 maxOcc 1 content simple

facets	Kind enumeration	Value Yes	annotation
	enumeration	No	

### element availableSlotType/AvailableHours

diagram	<pre> classDiagram     class AvailableHours {         &lt;&lt;mailxml_tm:AvailableHours&gt;&gt;     }     class availableHourType {         &lt;&lt;mailxml_tm:availableHourType&gt;&gt;         attribute PreferredAppt         attribute AvailableSlots     }     AvailableHours "1..∞" --&gt; availableHourType   </pre>																		
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																		
type	<a href="#">mailxml_tm:availableHourType</a>																		
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>1</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	1	maxOcc	unbounded	content	complex										
isRef	0																		
minOcc	1																		
maxOcc	unbounded																		
content	complex																		
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><a href="#">mailxml_tm:PreferredAppt</a></td> <td><a href="#">xs:dateTime</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:AvailableSlots</a></td> <td><a href="#">mailxml_base:s02</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:PreferredAppt</a>	<a href="#">xs:dateTime</a>					<a href="#">mailxml_tm:AvailableSlots</a>	<a href="#">mailxml_base:s02</a>				
Name	Type	Use	Default	Fixed	annotation														
<a href="#">mailxml_tm:PreferredAppt</a>	<a href="#">xs:dateTime</a>																		
<a href="#">mailxml_tm:AvailableSlots</a>	<a href="#">mailxml_base:s02</a>																		

### complexType bedloadHandlingUnitType


diagram	<pre> classDiagram     class bedloadHandlingUnitType {         &lt;&lt;bedloadHandlingUnitType&gt;&gt;         attribute Count     }     class PreSortLevel {         &lt;&lt;mailxml_tm:PreSortLevel&gt;&gt;     }     class IMpb {         &lt;&lt;mailxml_tm:IMpb&gt;&gt;     }     class IMtb {         &lt;&lt;mailxml_tm:IMtb&gt;&gt;     }     bedloadHandlingUnitType "0..∞" --&gt; PreSortLevel     bedloadHandlingUnitType --&gt; IMpb     bedloadHandlingUnitType --&gt; IMtb   </pre>												
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>												
children	<a href="#">mailxml_tm:PreSortLevel</a> <a href="#">mailxml_tm:IMpb</a> <a href="#">mailxml_tm:IMtb</a>												
used by	elements <a href="#">bedloadUnitType/Bundles</a> <a href="#">bedloadUnitType/Parcels</a> <a href="#">bedloadUnitType/Sacks</a>												
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><a href="#">mailxml_tm:Count</a></td> <td><a href="#">xs:nonNegativeInteger</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:Count</a>	<a href="#">xs:nonNegativeInteger</a>	required			
Name	Type	Use	Default	Fixed	annotation								
<a href="#">mailxml_tm:Count</a>	<a href="#">xs:nonNegativeInteger</a>	required											

### attribute bedloadHandlingUnitType/@Count

namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
-----------	---

type	<b>xs:nonNegativeInteger</b>
properties	isRef 0 use required

#### element **bedloadHandlingUnitType/PreSortLevel**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_tm:presortType</b>
properties	isRef 0 minOcc 0 maxOcc unbounded content complex
attributes	Name Type Use Default Fixed annotation <a href="#">mailxml_tm:ContainerLevel</a> <a href="#">mailxml_base:containerLevelType</a> required <a href="#">mailxml_tm:Count</a> <a href="#">xs:nonNegativeInteger</a> required

#### element **bedloadHandlingUnitType/IMpb**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:IMpbType</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 21 maxLength 34

#### element **bedloadHandlingUnitType/IMtb**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:IMtbType</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple

facets	Kind	Value	annotation
	minLength	24	
	maxLength	24	

### complexType bedloadUnitType

diagram	<pre> sequenceDiagram     participant A as bedloadUnitType     participant B as USPSContainerInfo     participant C as 1..∞     participant D as Sacks     participant E as Trays     participant F as Parcels     participant G as Bundles      A-&gt;&gt;B     activate B     B--&gt;&gt;C     activate C     C--&gt;&gt;D     activate D     C--&gt;&gt;E     activate E     C--&gt;&gt;F     activate F     C--&gt;&gt;G     activate G   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
children	<a href="#">mailxml_tm:USPSContainerInfo</a> <a href="#">mailxml_tm:Sacks</a> <a href="#">mailxml_tm:Trays</a> <a href="#">mailxml_tm:Parcels</a> <a href="#">mailxml_tm:Bundles</a>
used by	elements <a href="#">contentUspsSummaryType/Bedload</a> <a href="#">contentUspsSummaryUpdateType/Bedload</a> <a href="#">uspsSummaryType/Bedload</a>

element **bedloadUnitType/USPSContainerInfo**

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#"><u>mailxml_tm:uspsContainerInfoType</u></a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#"><u>mailxml_tm:MailOwnerCRID</u></a> <a href="#"><u>mailxml_tm:MailOwnerID</u></a> <a href="#"><u>mailxml_tm:USPSPublicationID</u></a> <a href="#"><u>mailxml_tm:ActualPieceCount</u></a> <a href="#"><u>mailxml_tm:ContainerWeight</u></a> <a href="#"><u>mailxml_tm:IMcb</u></a> <a href="#"><u>mailxml_tm:IMcbInfo</u></a> <a href="#"><u>mailxml_tm:SiblingBarcode</u></a> <a href="#"><u>mailxml_tm:PostInductionStatus</u></a> <a href="#"><u>mailxml_tm:ContainerDestination3digitZIP</u></a> <a href="#"><u>mailxml_tm:ContainerDestination5digitZIP</u></a>								

### element bedloadUnitType/Sacks

diagram	<pre> classDiagram     class mailxml_tm {         &lt;&lt;bedloadHandlingUnitType&gt;&gt;         attributes Count         PreSortLevel     }     class mailxml_tm {         &lt;&lt;Sacks&gt;&gt;     }     PreSortLevel *--&gt; IMpb     PreSortLevel *--&gt; IMtb     Sacks --&gt; bedloadHandlingUnitType   </pre>												
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>												
type	<a href="#">mailxml_tm:bedloadHandlingUnitType</a>												
properties	isRef 0 content complex												
children	<a href="#">mailxml_tm:PreSortLevel</a> <a href="#">mailxml_tm:IMpb</a> <a href="#">mailxml_tm:IMtb</a>												
attributes	<table> <tr> <th>Name</th><th>Type</th><th>Use</th><th>Default</th><th>Fixed</th><th>annotation</th></tr> <tr> <td><a href="#">mailxml_tm:Count</a></td><td><a href="#">xs:nonNegativeInteger</a></td><td>required</td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:Count</a>	<a href="#">xs:nonNegativeInteger</a>	required			
Name	Type	Use	Default	Fixed	annotation								
<a href="#">mailxml_tm:Count</a>	<a href="#">xs:nonNegativeInteger</a>	required											

### element bedloadUnitType/Trays

diagram	<pre> classDiagram     class mailxml_tm {         &lt;&lt;trayHandlingUnitType&gt;&gt;         attributes Count         Type     }     class mailxml_tm {         &lt;&lt;Trays&gt;&gt;     }     PreSortLevel *--&gt; IMpb     PreSortLevel *--&gt; IMtb     Trays --&gt; trayHandlingUnitType   </pre>												
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>												
type	<a href="#">mailxml_tm:trayHandlingUnitType</a>												
properties	isRef 0 content complex												
children	<a href="#">mailxml_tm:PreSortLevel</a> <a href="#">mailxml_tm:IMpb</a> <a href="#">mailxml_tm:IMtb</a>												
attributes	<table> <tr> <th>Name</th><th>Type</th><th>Use</th><th>Default</th><th>Fixed</th><th>annotation</th></tr> <tr> <td><a href="#">mailxml_tm:Count</a></td><td><a href="#">xs:nonNegativeInteger</a></td><td>required</td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:Count</a>	<a href="#">xs:nonNegativeInteger</a>	required			
Name	Type	Use	Default	Fixed	annotation								
<a href="#">mailxml_tm:Count</a>	<a href="#">xs:nonNegativeInteger</a>	required											

	<a href="#">mailxml_tm:Type</a>	<a href="#">mailxml_base:trayType</a>	MixedLengthTrays
--	---------------------------------	---------------------------------------	------------------

### element **bedloadUnitType/Parcels**

diagram	<pre> classDiagram     class mailxml_tm {         class bedloadHandlingUnitType {             attribute Count             multiplicity 0..∞             association Parcels --&gt; PreSortLevel             PreSortLevel --&gt; IMpb             PreSortLevel --&gt; IMtb         }     }   </pre>								
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>								
type	<a href="#">mailxml_tm:bedloadHandlingUnitType</a>								
properties	isRef 0 content complex								
children	<a href="#">mailxml_tm:PreSortLevel</a> <a href="#">mailxml_tm:IMpb</a> <a href="#">mailxml_tm:IMtb</a>								
attributes	<table> <tr> <td>Name</td> <td><a href="#">mailxml_tm:Count</a></td> <td>Type</td> <td><a href="#">xs:nonNegativeInteger</a></td> <td>Use</td> <td>Default</td> <td>Fixed</td> <td>annotation</td> </tr> </table>	Name	<a href="#">mailxml_tm:Count</a>	Type	<a href="#">xs:nonNegativeInteger</a>	Use	Default	Fixed	annotation
Name	<a href="#">mailxml_tm:Count</a>	Type	<a href="#">xs:nonNegativeInteger</a>	Use	Default	Fixed	annotation		

### element **bedloadUnitType/Bundles**

diagram	<pre> classDiagram     class mailxml_tm {         class bedloadHandlingUnitType {             attribute Count             multiplicity 0..∞             association Bundles --&gt; PreSortLevel             PreSortLevel --&gt; IMpb             PreSortLevel --&gt; IMtb         }     }   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:bedloadHandlingUnitType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:PreSortLevel</a> <a href="#">mailxml_tm:IMpb</a> <a href="#">mailxml_tm:IMtb</a>

attributes	Name <a href="#">mailxml_tm:Count</a>	Type <b>xs:nonNegativeInteger</b>	Use required	Default	Fixed	annotation
------------	--	--------------------------------------	-----------------	---------	-------	------------

### complexType **carrierType**

diagram	<pre> classDiagram     class carrierType {         CarrierName         CarrierCRID         CarrierAddress         URL         &lt;&lt;CommonContact&gt;&gt; *-- "0..∞" CarrierAddress     }   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
children	<a href="#">mailxml_tm:CarrierName</a> <a href="#">mailxml_tm:CarrierCRID</a> <a href="#">mailxml_tm:CarrierAddress</a> <a href="#">mailxml_tm:URL</a> <a href="#">mailxml_tm:CommonContact</a>
used by	element <a href="#">trailerInfoType/Carrier</a>

### element **carrierType/CarrierName**

diagram													
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>												
type	<b>mailxml_base:s40</b>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	content	simple								
isRef	0												
content	simple												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>40</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	40		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	40												
whiteSpace	preserve												

### element **carrierType/CarrierCRID**

diagram										
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>									
type	<b>mailxml_base:CRIDType</b>									
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple	
isRef	0									
minOcc	0									
maxOcc	1									
content	simple									
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>15</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	15	
Kind	Value	annotation								
minLength	1									
maxLength	15									

	pattern	([0-9])*
--	---------	----------

### element carrierType/CarrierAddress

diagram	<pre> classDiagram     class mailxml_tm::CarrierAddress     class mailxml_defs::addressType {         &lt;&lt;attributes&gt;&gt;         mailxml_defs::CommunicationRole     }     class mailxml_defs::Address1     class mailxml_defs::Address2     class mailxml_defs::Address3     class mailxml_defs::Address4     class mailxml_defs::City     class mailxml_defs::County     class mailxml_defs::State     class mailxml_defs::ZipCode     class mailxml_defs::GPSCoordinates      CarrierAddress &lt; -- addressType     addressType "1..&gt; Address1     addressType "1..&gt; Address2     addressType "1..&gt; Address3     addressType "1..&gt; Address4     addressType "1..&gt; City     addressType "1..&gt; County     addressType "1..&gt; State     addressType "1..&gt; ZipCode     addressType "1..&gt; GPSCoordinates   </pre>												
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_defs:addressType</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex				
isRef	0												
minOcc	0												
maxOcc	1												
content	complex												
children	<b>mailxml_defs:Address1 mailxml_defs:Address2 mailxml_defs:Address3 mailxml_defs:Address4 mailxml_defs:City mailxml_defs:County mailxml_defs:State mailxml_defs:ZipCode mailxml_defs:GPSCoordinates</b>												
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:CommunicationRole</td> <td><b>mailxml_base:communicationRoleType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:CommunicationRole	<b>mailxml_base:communicationRoleType</b>				
Name	Type	Use	Default	Fixed	annotation								
mailxml_defs:CommunicationRole	<b>mailxml_base:communicationRoleType</b>												

### element carrierType/URL

diagram	<pre> classDiagram     class mailxml_tm::URL   </pre>						
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm						
type	<b>xs:anyURI</b>						
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1
isRef	0						
minOcc	0						
maxOcc	1						

	content simple
--	----------------


### element carrierType/CommonContact

diagram	<pre> classDiagram     class mailxml_tm::CommonContact     class mailxml_defs::commonContactType {         attribute mailxml_defs::ContactType         association "0..∞" --&gt; mailxml_tm::CommonContact         sequence             mailxml_defs::ContactName             mailxml_defs::Telephone             mailxml_defs::MobilePhone             mailxml_defs::Email             mailxml_defs::Fax             mailxml_defs::GPSCoordinates             mailxml_defs::ContactID "0..∞"     } </pre>									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm									
type	<b>mailxml_defs:commonContactType</b>									
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	unbounded	content	complex	
isRef	0									
minOcc	0									
maxOcc	unbounded									
content	complex									
children	<b>mailxml_defs:ContactName</b> <b>mailxml_defs:Telephone</b> <b>mailxml_defs:MobilePhone</b> <b>mailxml_defs:Email</b> <b>mailxml_defs:Fax</b> <b>mailxml_defs:GPSCoordinates</b> <b>mailxml_defs:ContactID</b>									
attributes	<table> <tr> <td>Name</td><td>mailxml_defs:ContactType</td> <td>Type</td><td><b>mailxml_base:contactType</b></td> <td>Use</td><td>required</td> <td>Default</td><td>Fixed</td> <td>annotation</td> </tr> </table>	Name	mailxml_defs:ContactType	Type	<b>mailxml_base:contactType</b>	Use	required	Default	Fixed	annotation
Name	mailxml_defs:ContactType	Type	<b>mailxml_base:contactType</b>	Use	required	Default	Fixed	annotation		


### complexType containerInductionInfoType

diagram	<pre> classDiagram     class containerInductionInfoType     class mailxml_tm::ContainerType     containerInductionInfoType &lt; -- mailxml_tm::ContainerType </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
children	<b>mailxml_tm:ContainerType</b>
used by	element <a href="#">apptCloseoutResponseType/ContainerInductionInfo</a>

element **containerInductionInfoType/ContainerType**

diagram																																																																																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																																																																															
type	<b>mailxml_base:mailXMLContainerType</b>																																																																																																															
properties	<table> <tr><td>isRef</td><td>0</td></tr> <tr><td>minOcc</td><td>0</td></tr> <tr><td>maxOcc</td><td>1</td></tr> <tr><td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple																																																																																																							
isRef	0																																																																																																															
minOcc	0																																																																																																															
maxOcc	1																																																																																																															
content	simple																																																																																																															
facets	<table> <thead> <tr><th>Kind</th><th>Value</th><th>annotation</th></tr> </thead> <tbody> <tr><td>enumeration</td><td>1</td><td></td></tr> <tr><td>enumeration</td><td>2</td><td></td></tr> <tr><td>enumeration</td><td>3</td><td></td></tr> <tr><td>enumeration</td><td>4</td><td></td></tr> <tr><td>enumeration</td><td>5</td><td></td></tr> <tr><td>enumeration</td><td>6</td><td></td></tr> <tr><td>enumeration</td><td>7</td><td></td></tr> <tr><td>enumeration</td><td>8</td><td></td></tr> <tr><td>enumeration</td><td>9</td><td></td></tr> <tr><td>enumeration</td><td>10</td><td></td></tr> <tr><td>enumeration</td><td>11</td><td></td></tr> <tr><td>enumeration</td><td>12</td><td></td></tr> <tr><td>enumeration</td><td>13</td><td></td></tr> <tr><td>enumeration</td><td>14</td><td></td></tr> <tr><td>enumeration</td><td>E</td><td></td></tr> <tr><td>enumeration</td><td>F</td><td></td></tr> <tr><td>enumeration</td><td>L</td><td></td></tr> <tr><td>enumeration</td><td>O</td><td></td></tr> <tr><td>enumeration</td><td>P</td><td></td></tr> <tr><td>enumeration</td><td>S</td><td></td></tr> <tr><td>enumeration</td><td>T</td><td></td></tr> <tr><td>enumeration</td><td>V</td><td></td></tr> <tr><td>enumeration</td><td>B</td><td></td></tr> <tr><td>enumeration</td><td>U</td><td></td></tr> <tr><td>enumeration</td><td>Z</td><td></td></tr> <tr><td>enumeration</td><td>X</td><td></td></tr> <tr><td>enumeration</td><td>H</td><td></td></tr> <tr><td>enumeration</td><td>A</td><td></td></tr> <tr><td>enumeration</td><td>G</td><td></td></tr> <tr><td>enumeration</td><td>D</td><td></td></tr> <tr><td>enumeration</td><td>R</td><td></td></tr> <tr><td>enumeration</td><td>C</td><td></td></tr> <tr><td>enumeration</td><td>CT</td><td></td></tr> <tr><td>enumeration</td><td>M</td><td></td></tr> <tr><td>enumeration</td><td>AB</td><td></td></tr> <tr><td>enumeration</td><td>Y</td><td></td></tr> </tbody> </table>	Kind	Value	annotation	enumeration	1		enumeration	2		enumeration	3		enumeration	4		enumeration	5		enumeration	6		enumeration	7		enumeration	8		enumeration	9		enumeration	10		enumeration	11		enumeration	12		enumeration	13		enumeration	14		enumeration	E		enumeration	F		enumeration	L		enumeration	O		enumeration	P		enumeration	S		enumeration	T		enumeration	V		enumeration	B		enumeration	U		enumeration	Z		enumeration	X		enumeration	H		enumeration	A		enumeration	G		enumeration	D		enumeration	R		enumeration	C		enumeration	CT		enumeration	M		enumeration	AB		enumeration	Y	
Kind	Value	annotation																																																																																																														
enumeration	1																																																																																																															
enumeration	2																																																																																																															
enumeration	3																																																																																																															
enumeration	4																																																																																																															
enumeration	5																																																																																																															
enumeration	6																																																																																																															
enumeration	7																																																																																																															
enumeration	8																																																																																																															
enumeration	9																																																																																																															
enumeration	10																																																																																																															
enumeration	11																																																																																																															
enumeration	12																																																																																																															
enumeration	13																																																																																																															
enumeration	14																																																																																																															
enumeration	E																																																																																																															
enumeration	F																																																																																																															
enumeration	L																																																																																																															
enumeration	O																																																																																																															
enumeration	P																																																																																																															
enumeration	S																																																																																																															
enumeration	T																																																																																																															
enumeration	V																																																																																																															
enumeration	B																																																																																																															
enumeration	U																																																																																																															
enumeration	Z																																																																																																															
enumeration	X																																																																																																															
enumeration	H																																																																																																															
enumeration	A																																																																																																															
enumeration	G																																																																																																															
enumeration	D																																																																																																															
enumeration	R																																																																																																															
enumeration	C																																																																																																															
enumeration	CT																																																																																																															
enumeration	M																																																																																																															
enumeration	AB																																																																																																															
enumeration	Y																																																																																																															

### complexType contentCancelType

diagram																									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																								
children	<a href="#">mailxml_tm:ReturnInfo</a>																								
used by	elements <a href="#">deliveryContentCancelRequestType/ContentCancel</a> <a href="#">deliveryContentCancelResponseType/DeliveryContentCancelAccept/ContentCancel</a> <a href="#">deliveryContentCancelResponseType/DeliveryContentCancelReject/ContentCancel</a> <a href="#">deliveryContentUpdatedType/ContentCancelInfo</a>																								
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><a href="#">mailxml_tm:SchedulerContentID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:ConsigneeContentID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:ConsigneeApptID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:SchedulerContentID</a>	<a href="#">mailxml_base:s12</a>	required				<a href="#">mailxml_tm:ConsigneeContentID</a>	<a href="#">mailxml_base:s12</a>	required				<a href="#">mailxml_tm:ConsigneeApptID</a>	<a href="#">mailxml_base:s12</a>				
Name	Type	Use	Default	Fixed	annotation																				
<a href="#">mailxml_tm:SchedulerContentID</a>	<a href="#">mailxml_base:s12</a>	required																							
<a href="#">mailxml_tm:ConsigneeContentID</a>	<a href="#">mailxml_base:s12</a>	required																							
<a href="#">mailxml_tm:ConsigneeApptID</a>	<a href="#">mailxml_base:s12</a>																								

#### attribute contentCancelType/@SchedulerContentID

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s12</b>
properties	isRef 0 use required
facets	Kind Value annotation minLength 1 maxLength 12 whiteSpace preserve

#### attribute contentCancelType/@ConsigneeContentID

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s12</b>
properties	isRef 0 use required
facets	Kind Value annotation minLength 1 maxLength 12 whiteSpace preserve

#### attribute contentCancelType/@ConsigneeApptID

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
-----------	---

type	<b>mailxml_base:s12</b>												
properties	isRef 0												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>12</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	12		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	12												
whiteSpace	preserve												

element **contentCancelType/ReturnInfo**

diagram	<pre> classDiagram     class mailxml_tm::optReturnInfoType     class mailxml_tm::ReturnInfo     class mailxml_tm::ConsigneeFacility     class mailxml_tm::ReturnCode     class mailxml_tm::ReturnDescription      optReturnInfoType "0..1" -- "0..1" ReturnInfo     optReturnInfoType "0..1" -- "0..1" ConsigneeFacility     optReturnInfoType "0..infinity" -- "0..infinity" ReturnCode     ReturnCode "0..infinity" -- "0..infinity" ReturnDescription   </pre>								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_tm:optReturnInfoType</a>								
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>complex</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:ReturnCode</a> <a href="#">mailxml_tm:ReturnDescription</a>								

complexType **contentDetailInfoType**

diagram	<pre> classDiagram     class contentDetailInfoType {         mailxml_tm:LogisticsSchedulerID         mailxml_tm:LogisticsCorpID         mailxml_tm:LogisticsSchedulerCRID     }     class DestinationEntry {         mailxml_tm:ShipperContainerGroupingID         mailxml_tm:ConsigneeContainerGroupingID         mailxml_tm:ShipperGroupingID         mailxml_tm:ScheduledInductionDate         mailxml_tm:NumberOfDaysStale     }     contentDetailInfoType "1..&gt;" DestinationEntry     DestinationEntry "1..&gt;" MaildatSummary     DestinationEntry "1..&gt;" ContentUSPSSummary   </pre>																								
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																								
children	<a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:ScheduledInductionDate</a> <a href="#">mailxml_tm:NumberOfDaysStale</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:ContentUSPSSummary</a>																								
used by	elements <a href="#">DeliveryContentCreateRequest/ContentDetailInfo</a> <a href="#">StaleContentQueryResponse/QueryResults/ContentDetailInfo</a> <a href="#">deliverySummaryType/ContentDetailInfo</a> <a href="#">deliveryContentAcceptType/ContentDetailInfo</a>																								
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><a href="#">mailxml_tm:LogisticsSchedulerID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:LogisticsCorpID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:LogisticsSchedulerCRID</a></td> <td><a href="#">mailxml_base:CRIDType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:LogisticsSchedulerID</a>	<a href="#">mailxml_base:s12</a>					<a href="#">mailxml_tm:LogisticsCorpID</a>	<a href="#">mailxml_base:s12</a>					<a href="#">mailxml_tm:LogisticsSchedulerCRID</a>	<a href="#">mailxml_base:CRIDType</a>				
Name	Type	Use	Default	Fixed	annotation																				
<a href="#">mailxml_tm:LogisticsSchedulerID</a>	<a href="#">mailxml_base:s12</a>																								
<a href="#">mailxml_tm:LogisticsCorpID</a>	<a href="#">mailxml_base:s12</a>																								
<a href="#">mailxml_tm:LogisticsSchedulerCRID</a>	<a href="#">mailxml_base:CRIDType</a>																								

attribute **contentDetailInfoType/@LogisticsSchedulerID**

namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																
type	<a href="#">mailxml_base:s12</a>																
properties	isRef 0																
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>12</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </tbody> </table>					Kind	Value	annotation	minLength	1		maxLength	12		whiteSpace	preserve	
Kind	Value	annotation															
minLength	1																
maxLength	12																
whiteSpace	preserve																

attribute **contentDetailInfoType/@LogisticsCorpID**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm		
type	<b>mailxml_base:s12</b>		
properties	isRef 0		
facets	Kind	Value	annotation
	minLength	1	
	maxLength	12	
	whiteSpace	preserve	

attribute **contentDetailInfoType/@LogisticsSchedulerCRID**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm		
type	<b>mailxml_base:CRIDType</b>		
properties	isRef 0		
facets	Kind	Value	annotation
	minLength	1	
	maxLength	15	
	pattern	([0-9])*	


element **contentDetailInfoType/DestinationEntry**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No


element **contentDetailInfoType/ShipperContainerGroupingID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s16</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 16 whiteSpace preserve

**element contentDetailInfoType/ConsigneeContainerGroupingID**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s16</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>16</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	16		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	16												
whiteSpace	preserve												


**element contentDetailInfoType/ShipperGroupingIDDescription**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s50</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>50</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	50		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	50												
whiteSpace	preserve												

**element contentDetailInfoType/ScheduledInductionDate**

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>mailxml_base:scheduledInductionDateType</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple
isRef	0								
minOcc	0								
maxOcc	1								
content	simple								

**element contentDetailInfoType/NumberOfDaysStale**


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:ns02</b>

properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation pattern [0-9]{2}

### element contentDetailInfoType/MaildatSummary

diagram	<pre> classDiagram     class mailxml_tm {         mailxml_tm:maildatSummaryType     }     class mailxml_tm {         mailxml_tm:MaildatSummary     }     mailxml_tm:maildatSummaryType "2" -- "1" mailxml_tm:MaildatSummary     mailxml_tm:maildatSummaryType "2" -- "1" mailxml_tm:UserLicenseCode     mailxml_tm:maildatSummaryType "2" -- "1" mailxml_tm:MaildatJobID     mailxml_tm:maildatSummaryType "2" -- "1" mailxml_tm:DatabaseContainerID     mailxml_tm:maildatSummaryType "2" -- "2" mailxml_tm:IMcb     mailxml_tm:maildatSummaryType "2" -- "2" mailxml_tm:VerificationZip4     mailxml_tm:maildatSummaryType "2" -- "2" mailxml_tm:IMpb     mailxml_tm:maildatSummaryType "2" -- "2" mailxml_tm:IMtb   </pre>																		
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																		
type	<a href="#">mailxml_tm:maildatSummaryType</a>																		
properties	isRef 0 content complex																		
children	<a href="#">mailxml_tm:UserLicenseCode</a> <a href="#">mailxml_tm:MaildatJobID</a> <a href="#">mailxml_tm:DatabaseContainerID</a> <a href="#">mailxml_tm:IMcb</a> <a href="#">mailxml_tm:VerificationZip4</a> <a href="#">mailxml_tm:IMpb</a> <a href="#">mailxml_tm:IMtb</a>																		
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><a href="#">mailxml_tm:IncludedInSummarizationBlock</a></td> <td><a href="#">mailxml_base:yesNo</a></td> <td></td> <td>No</td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:SchedulerContentID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:IncludedInSummarizationBlock</a>	<a href="#">mailxml_base:yesNo</a>		No			<a href="#">mailxml_tm:SchedulerContentID</a>	<a href="#">mailxml_base:s12</a>				
Name	Type	Use	Default	Fixed	annotation														
<a href="#">mailxml_tm:IncludedInSummarizationBlock</a>	<a href="#">mailxml_base:yesNo</a>		No																
<a href="#">mailxml_tm:SchedulerContentID</a>	<a href="#">mailxml_base:s12</a>																		

element **contentDetailInfoType/ContentUSPSSummary**



namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
type	<a href="#">mailxml_tm:contentUspsSummaryType</a>					
properties	isRef 0 content complex					
children	<a href="#">mailxml_tm:DestinationDiscountIndicator</a> <a href="#">mailxml_tm:ZoneSkippingIndicator</a> <a href="#">mailxml_tm:FullServiceIndicator</a> <a href="#">mailxml_tm:eInductionIndicator</a> <a href="#">mailxml_tm:Pallets</a> <a href="#">mailxml_tm:Bedload</a> <a href="#">mailxml_tm:Perishable</a> <a href="#">mailxml_tm:MailClass</a> <a href="#">mailxml_tm:RateType</a> <a href="#">mailxml_tm:InHomeStart</a> <a href="#">mailxml_tm:InHomeEnd</a> <a href="#">mailxml_tm:ProcessingCategory</a> <a href="#">mailxml_tm:PriorityMailIndicator</a> <a href="#">mailxml_tm:VerificationLocation</a> <a href="#">mailxml_tm:NewsIndicator</a> <a href="#">mailxml_tm:EvsIndicator</a> <a href="#">mailxml_tm:MailContentName</a> <a href="#">mailxml_tm:MailPreparerID</a> <a href="#">mailxml_tm:MailPreparerCRID</a> <a href="#">mailxml_tm:AdvanceMailingID</a> <a href="#">mailxml_tm:EFileNumber</a> <a href="#">mailxml_tm:ContainsAutoMail</a>					
attributes	Name <a href="#">mailxml_tm:SchedulerContentID</a> <a href="#">mailxml_tm:ConsigneeContentID</a>	Type <a href="#">mailxml_base:s12</a> <a href="#">mailxml_base:s12</a>	Use required	Default	Fixed	annotation

### complexType contentDetailInfoUpdateType

diagram	<pre> classDiagram     class contentDetailInfoUpdateType {         LogisticsSchedulerID         LogisticsCorpID         LogisticsSchedulerCRID     }     class ShipperContainerGroupingID     class ConsigneeContainerGroupingID     class ShipperGroupingID     class ScheduledInductionDate     class MaildatSummary     class ContentUSPSSummary      contentDetailInfoUpdateType "1..&gt;"--&gt; ShipperContainerGroupingID     contentDetailInfoUpdateType "1..&gt;"--&gt; ConsigneeContainerGroupingID     contentDetailInfoUpdateType "1..&gt;"--&gt; ShipperGroupingID     contentDetailInfoUpdateType "1..&gt;"--&gt; ScheduledInductionDate     contentDetailInfoUpdateType "1..&gt;"--&gt; MaildatSummary     contentDetailInfoUpdateType "1..&gt;"--&gt; ContentUSPSSummary   </pre>					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
children	<a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:ScheduledInductionDate</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:ContentUSPSSummary</a>					
used by	elements <a href="#">DeliveryContentQueryResponse/QueryResults/ContentDetailInfoUpdate</a> <a href="#">DeliveryContentUpdateRequest/ContentDetailInfoUpdate</a> <a href="#">deliveryContentUpdateAcceptType/ContentDetailInfoUpdate</a> <a href="#">deliveryContentUpdatedType/ContentDetailInfoUpdate</a> <a href="#">PartnerApptBlockType/ContentDetailInfoUpdate</a>					
attributes	Name <a href="#">mailxml_tm:LogisticsSchedulerID</a> <a href="#">mailxml_tm:LogisticsCorpID</a> <a href="#">mailxml_tm:LogisticsSchedulerCRID</a>	Type <a href="#">mailxml_base:s12</a> <a href="#">mailxml_base:s12</a> <a href="#">mailxml_base:CRIDType</a>	Use	Default	Fixed	annotation

attribute **contentDetailInfoUpdateType/@LogisticsSchedulerID**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm		
type	<b>mailxml_base:s12</b>		
properties	isRef 0		
facets	Kind	Value	annotation
	minLength	1	
	maxLength	12	
	whiteSpace	preserve	

attribute **contentDetailInfoUpdateType/@LogisticsCorpID**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm		
type	<b>mailxml_base:s12</b>		
properties	isRef 0		
facets	Kind	Value	annotation
	minLength	1	
	maxLength	12	
	whiteSpace	preserve	


attribute **contentDetailInfoUpdateType/@LogisticsSchedulerCRID**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm		
type	<b>mailxml_base:CRIDType</b>		
properties	isRef 0		
facets	Kind	Value	annotation
	minLength	1	
	maxLength	15	
	pattern	([0-9])*	


element **contentDetailInfoUpdateType/ShipperContainerGroupingID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s16</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 16 whiteSpace preserve


**element contentDetailInfoUpdateType/ConsigneeContainerGroupingID**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s16</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>16</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	16		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	16												
whiteSpace	preserve												

**element contentDetailInfoUpdateType/ShipperGroupingIDDescription**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s50</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>50</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	50		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	50												
whiteSpace	preserve												


**element contentDetailInfoUpdateType/ScheduledInductionDate**

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>mailxml_base:scheduledInductionDateType</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple
isRef	0								
minOcc	0								
maxOcc	1								
content	simple								

element **contentDetailInfoUpdateType/MaildatSummary**


diagram	<pre> classDiagram     class mailxml_tm::MaildatSummaryType {         &lt;&lt;attributes&gt;&gt;         mailxml_tm::IncludedInSummarizationBlock         mailxml_tm::SchedulerContentID     }     class mailxml_tm::MaildatSummary {         &lt;&lt;Relationships&gt;&gt;         --&gt; mailxml_tm::MaildatSummaryType     }     class mailxml_tm::UserLicenseCode     class mailxml_tm::MaildatJobID     class mailxml_tm::DatabaseContainerID     class mailxml_tm::IMcb     class mailxml_tm::VerificationZip4     class mailxml_tm::IMPb     class mailxml_tm::IMtb     mailxml_tm::MaildatSummary "1" --&gt; "1" mailxml_tm::UserLicenseCode     mailxml_tm::MaildatSummary "1" --&gt; "1" mailxml_tm::MaildatJobID     mailxml_tm::MaildatSummary "1" --&gt; "1" mailxml_tm::DatabaseContainerID     mailxml_tm::MaildatSummary "*" --&gt; "1" mailxml_tm::IMcb     mailxml_tm::MaildatSummary "*" --&gt; "1" mailxml_tm::VerificationZip4     mailxml_tm::MaildatSummary "*" --&gt; "1" mailxml_tm::IMPb     mailxml_tm::MaildatSummary "*" --&gt; "1" mailxml_tm::IMtb   </pre>																		
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																		
type	<a href="#">mailxml_tm:MaildatSummaryType</a>																		
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex														
isRef	0																		
content	complex																		
children	<a href="#">mailxml_tm:UserLicenseCode</a> <a href="#">mailxml_tm:MaildatJobID</a> <a href="#">mailxml_tm:DatabaseContainerID</a> <a href="#">mailxml_tm:IMcb</a> <a href="#">mailxml_tm:VerificationZip4</a> <a href="#">mailxml_tm:IMPb</a> <a href="#">mailxml_tm:IMtb</a>																		
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><a href="#">mailxml_tm:IncludedInSummarizationBlock</a></td> <td><a href="#">mailxml_base:yesNo</a></td> <td></td> <td>No</td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:SchedulerContentID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:IncludedInSummarizationBlock</a>	<a href="#">mailxml_base:yesNo</a>		No			<a href="#">mailxml_tm:SchedulerContentID</a>	<a href="#">mailxml_base:s12</a>				
Name	Type	Use	Default	Fixed	annotation														
<a href="#">mailxml_tm:IncludedInSummarizationBlock</a>	<a href="#">mailxml_base:yesNo</a>		No																
<a href="#">mailxml_tm:SchedulerContentID</a>	<a href="#">mailxml_base:s12</a>																		

element **contentDetailInfoUpdateType/ContentUSPSSummary**



namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
type	<a href="#"><b>mailxml_tm:contentUspsSummaryUpdateType</b></a>					
properties	isRef 0 content complex					
children	<a href="#"><b>mailxml_tm:DestinationDiscountIndicator</b></a> <a href="#"><b>mailxml_tm:ZoneSkippingIndicator</b></a> <a href="#"><b>mailxml_tm:FullServiceIndicator</b></a> <a href="#"><b>mailxml_tm:eInductionIndicator</b></a> <a href="#"><b>mailxml_tm:Pallets</b></a> <a href="#"><b>mailxml_tm:Bedload</b></a> <a href="#"><b>mailxml_tm:Perishable</b></a> <a href="#"><b>mailxml_tm:MailClass</b></a> <a href="#"><b>mailxml_tm:RateType</b></a> <a href="#"><b>mailxml_tm:InHomeStart</b></a> <a href="#"><b>mailxml_tm:InHomeEnd</b></a> <a href="#"><b>mailxml_tm:ProcessingCategory</b></a> <a href="#"><b>mailxml_tm:PriorityMailIndicator</b></a> <a href="#"><b>mailxml_tm:VerificationLocation</b></a> <a href="#"><b>mailxml_tm:NewsIndicator</b></a> <a href="#"><b>mailxml_tm:EvsIndicator</b></a> <a href="#"><b>mailxml_tm:MailContentName</b></a> <a href="#"><b>mailxml_tm:MailPreparerID</b></a> <a href="#"><b>mailxml_tm:MailPreparerCRID</b></a> <a href="#"><b>mailxml_tm:AdvanceMailingID</b></a> <a href="#"><b>mailxml_tm:EFileNumber</b></a> <a href="#"><b>mailxml_tm:ContainsAutoMail</b></a>					
attributes	Name	Type	Use	Default	Fixed	annotation
	<a href="#"><b>mailxml_tm:SchedulerContentID</b></a>	<b>mailxml_base:s12</b>	required			
	<a href="#"><b>mailxml_tm:ConsigneeContentID</b></a>	<b>mailxml_base:s12</b>	required			

complexType **contentUspsSummaryType**



namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																		
children	<a href="#">mailxml_tm:DestinationDiscountIndicator</a> <a href="#">mailxml_tm:ZoneSkippingIndicator</a> <a href="#">mailxml_tm:FullServiceIndicator</a> <a href="#">mailxml_tm:eInductionIndicator</a> <a href="#">mailxml_tm:Pallets</a> <a href="#">mailxml_tm:Bedload</a> <a href="#">mailxml_tm:Perishable</a> <a href="#">mailxml_tm:MailClass</a> <a href="#">mailxml_tm:RateType</a> <a href="#">mailxml_tm:InHomeStart</a> <a href="#">mailxml_tm:InHomeEnd</a> <a href="#">mailxml_tm:ProcessingCategory</a> <a href="#">mailxml_tm:PriorityMailIndicator</a> <a href="#">mailxml_tm:VerificationLocation</a> <a href="#">mailxml_tm:NewsIndicator</a> <a href="#">mailxml_tm:EvsIndicator</a> <a href="#">mailxml_tm:MailContentName</a> <a href="#">mailxml_tm:MailPreparerID</a> <a href="#">mailxml_tm:MailPreparerCRID</a> <a href="#">mailxml_tm:AdvanceMailingID</a> <a href="#">mailxml_tm:EFileNumber</a> <a href="#">mailxml_tm:ContainsAutoMail</a>																		
used by	element <a href="#">contentDetailInfoType/ContentUSPSSummary</a>																		
attributes	<table> <tr> <td>Name</td> <td>Type</td> <td>Use</td> <td>Default</td> <td>Fixed</td> <td>annotation</td> </tr> <tr> <td><a href="#">mailxml_tm:SchedulerContentID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:ConsigneeContentID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:SchedulerContentID</a>	<a href="#">mailxml_base:s12</a>	required				<a href="#">mailxml_tm:ConsigneeContentID</a>	<a href="#">mailxml_base:s12</a>				
Name	Type	Use	Default	Fixed	annotation														
<a href="#">mailxml_tm:SchedulerContentID</a>	<a href="#">mailxml_base:s12</a>	required																	
<a href="#">mailxml_tm:ConsigneeContentID</a>	<a href="#">mailxml_base:s12</a>																		

#### attribute **contentUspsSummaryType/@SchedulerContentID**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s12</b>												
properties	isRef 0 use required												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>12</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	12		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	12												
whiteSpace	preserve												


#### attribute **contentUspsSummaryType/@ConsigneeContentID**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s12</b>												
properties	isRef 0												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>12</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	12		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	12												
whiteSpace	preserve												


#### element **contentUspsSummaryType/DestinationDiscountIndicator**

diagram										
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm									
type	<b>mailxml_base:yesNo</b>									
properties	isRef 0 content simple									
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>enumeration</td> <td>Yes</td> <td></td> </tr> <tr> <td>enumeration</td> <td>No</td> <td></td> </tr> </table>	Kind	Value	annotation	enumeration	Yes		enumeration	No	
Kind	Value	annotation								
enumeration	Yes									
enumeration	No									


**element `contentUspsSummaryType/ZoneSkippingIndicator`**

diagram	 mailxml_tm:Zone SkippingIndica...
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No


**element `contentUspsSummaryType/FullServiceIndicator`**

diagram	 mailxml_tm:FullServiceIndicator
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation enumeration Yes enumeration No


**element `contentUspsSummaryType/eInductionIndicator`**

diagram	 mailxml_tm:eInductionIndicator
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation enumeration Yes enumeration No

### element contentUspsSummaryType/Pallets

diagram																									
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																								
type	<a href="#">mailxml_tm:palletUnitType</a>																								
properties	<p>isRef 0  minOcc 0  maxOcc unbounded  content complex</p>																								
children	<a href="#">mailxml_tm:PalletPreSortLevel</a> <a href="#">mailxml_tm:USPSContainerInfo</a>																								
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><a href="#">mailxml_tm:Count</a></td> <td><a href="#">xs:nonNegativeInteger</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:HandlingUnitType</a></td> <td><a href="#">mailxml_base:palletHandlingUnitType</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:PalletType</a></td> <td><a href="#">mailxml_base:palletType</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:Count</a>	<a href="#">xs:nonNegativeInteger</a>	required				<a href="#">mailxml_tm:HandlingUnitType</a>	<a href="#">mailxml_base:palletHandlingUnitType</a>	required				<a href="#">mailxml_tm:PalletType</a>	<a href="#">mailxml_base:palletType</a>	required			
Name	Type	Use	Default	Fixed	annotation																				
<a href="#">mailxml_tm:Count</a>	<a href="#">xs:nonNegativeInteger</a>	required																							
<a href="#">mailxml_tm:HandlingUnitType</a>	<a href="#">mailxml_base:palletHandlingUnitType</a>	required																							
<a href="#">mailxml_tm:PalletType</a>	<a href="#">mailxml_base:palletType</a>	required																							

### element contentUspsSummaryType/Bedload

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:bedloadUnitType</a>
properties	<p>isRef 0  minOcc 0  maxOcc 1  content complex</p>

children	<a href="#">mailxml_tm:USPSContainerInfo</a> <a href="#">mailxml_tm:Sacks</a> <a href="#">mailxml_tm:Trays</a> <a href="#">mailxml_tm:Parcels</a> <a href="#">mailxml_tm:Bundles</a>
----------	--

element **contentUspsSummaryType/Perishable**

diagram	 mailxml_tm:Perishable
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

element **contentUspsSummaryType/MailClass**

diagram	 mailxml_tm:MailClass
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:mailClassType</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration 1 enumeration 2 enumeration 3 enumeration 4 enumeration 6

element **contentUspsSummaryType/RateType**

diagram	 mailxml_tm:RateType
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:rateType</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation enumeration R enumeration L enumeration B enumeration C enumeration S enumeration S1

	enumeration S2
	enumeration S3
	enumeration S4
	enumeration S5
	enumeration S6
	enumeration S7
	enumeration F
	enumeration A
	enumeration N
	enumeration P
	enumeration T
	enumeration D
	enumeration X
	enumeration H
	enumeration M
	enumeration Z
	enumeration E
	enumeration E4
	enumeration G
	enumeration 1
	enumeration 2
	enumeration 3
	enumeration 4
	enumeration J
	enumeration K
	enumeration V
	enumeration W
	enumeration Y
	enumeration Q

#### element **contentUspsSummaryType/InHomeStart**


diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>xs:dateTime</b>								
properties	<table> <tr><td>isRef</td><td>0</td></tr> <tr><td>minOcc</td><td>0</td></tr> <tr><td>maxOcc</td><td>1</td></tr> <tr><td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple
isRef	0								
minOcc	0								
maxOcc	1								
content	simple								

#### element **contentUspsSummaryType/InHomeEnd**


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm

type	<b>xs:dateTime</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple


#### element **contentUspsSummaryType/ProcessingCategory**

diagram																																					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																				
type	<b>mailxml_base:processingCategoryType</b>																																				
properties	isRef 0 content simple																																				
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>LT</td> <td></td> </tr> <tr> <td>enumeration</td> <td>FL</td> <td></td> </tr> <tr> <td>enumeration</td> <td>CD</td> <td></td> </tr> <tr> <td>enumeration</td> <td>OS</td> <td></td> </tr> <tr> <td>enumeration</td> <td>MP</td> <td></td> </tr> <tr> <td>enumeration</td> <td>IR</td> <td></td> </tr> <tr> <td>enumeration</td> <td>PF</td> <td></td> </tr> <tr> <td>enumeration</td> <td>CM</td> <td></td> </tr> <tr> <td>enumeration</td> <td>NP</td> <td></td> </tr> <tr> <td>enumeration</td> <td>SP</td> <td></td> </tr> <tr> <td>enumeration</td> <td>MB</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	enumeration	LT		enumeration	FL		enumeration	CD		enumeration	OS		enumeration	MP		enumeration	IR		enumeration	PF		enumeration	CM		enumeration	NP		enumeration	SP		enumeration	MB	
Kind	Value	annotation																																			
enumeration	LT																																				
enumeration	FL																																				
enumeration	CD																																				
enumeration	OS																																				
enumeration	MP																																				
enumeration	IR																																				
enumeration	PF																																				
enumeration	CM																																				
enumeration	NP																																				
enumeration	SP																																				
enumeration	MB																																				

#### element **contentUspsSummaryType/PriorityMailIndicator**

diagram										
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm									
type	<b>mailxml_base:yesNo</b>									
properties	isRef 0 content simple default No									
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Yes</td> <td></td> </tr> <tr> <td>enumeration</td> <td>No</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	enumeration	Yes		enumeration	No	
Kind	Value	annotation								
enumeration	Yes									
enumeration	No									

#### element **contentUspsSummaryType/VerificationLocation**


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_tm:verificationLocationType</b>

properties	isRef 0 content simple
facets	Kind Value annotation enumeration BMEU enumeration DMU


#### element **contentUspsSummaryType/NewsIndicator**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

#### element **contentUspsSummaryType/EvsIndicator**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation enumeration Yes enumeration No

#### element **contentUspsSummaryType/MailContentName**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s30</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 30 whiteSpace preserve

**element contentUspsSummaryType/MailPreparerID**

diagram	mailxml_tm:MailPreparerID												
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s12</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>12</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	12		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	12												
whiteSpace	preserve												


**element contentUspsSummaryType/MailPreparerCRID**

diagram	mailxml_tm:MailPreparerCRID												
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:CRIDType</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>15</td><td></td></tr> <tr> <td>pattern</td><td>([0-9])*</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	15		pattern	([0-9])*	
Kind	Value	annotation											
minLength	1												
maxLength	15												
pattern	([0-9])*												


**element contentUspsSummaryType/AdvanceMailingID**

diagram	mailxml_tm:AdvanceMailingID 0..∞												
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s09</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	unbounded	content	simple				
isRef	0												
minOcc	0												
maxOcc	unbounded												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>9</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	9		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	9												
whiteSpace	preserve												


**element contentUspsSummaryType/EFileNumber**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s22</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation <b>minLength</b> 1 <b>maxLength</b> 22 <b>whiteSpace</b> preserve

**element contentUspsSummaryType/ContainsAutoMail**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation <b>enumeration</b> Yes <b>enumeration</b> No

complexType **contentUspsSummaryUpdateType**



namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																		
children	<a href="#">mailxml_tm:DestinationDiscountIndicator</a> <a href="#">mailxml_tm:ZoneSkippingIndicator</a> <a href="#">mailxml_tm:FullServiceIndicator</a> <a href="#">mailxml_tm:eInductionIndicator</a> <a href="#">mailxml_tm:Pallets</a> <a href="#">mailxml_tm:Bedload</a> <a href="#">mailxml_tm:Perishable</a> <a href="#">mailxml_tm:MailClass</a> <a href="#">mailxml_tm:RateType</a> <a href="#">mailxml_tm:InHomeStart</a> <a href="#">mailxml_tm:InHomeEnd</a> <a href="#">mailxml_tm:ProcessingCategory</a> <a href="#">mailxml_tm:PriorityMailIndicator</a> <a href="#">mailxml_tm:VerificationLocation</a> <a href="#">mailxml_tm:NewsIndicator</a> <a href="#">mailxml_tm:EvsIndicator</a> <a href="#">mailxml_tm:MailContentName</a> <a href="#">mailxml_tm:MailPreparerID</a> <a href="#">mailxml_tm:MailPreparerCRID</a> <a href="#">mailxml_tm:AdvanceMailingID</a> <a href="#">mailxml_tm:EFileNumber</a> <a href="#">mailxml_tm:ContainsAutoMail</a>																		
used by	element <a href="#">contentDetailInfoUpdateType/ContentUSPSSummary</a>																		
attributes	<table> <tr> <td>Name</td> <td>Type</td> <td>Use</td> <td>Default</td> <td>Fixed</td> <td>annotation</td> </tr> <tr> <td><a href="#">mailxml_tm:SchedulerContentID</a></td> <td><b>mailxml_base:s12</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:ConsigneeContentID</a></td> <td><b>mailxml_base:s12</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:SchedulerContentID</a>	<b>mailxml_base:s12</b>	required				<a href="#">mailxml_tm:ConsigneeContentID</a>	<b>mailxml_base:s12</b>	required			
Name	Type	Use	Default	Fixed	annotation														
<a href="#">mailxml_tm:SchedulerContentID</a>	<b>mailxml_base:s12</b>	required																	
<a href="#">mailxml_tm:ConsigneeContentID</a>	<b>mailxml_base:s12</b>	required																	

#### attribute **contentUspsSummaryUpdateType/@SchedulerContentID**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s12</b>
properties	isRef 0 use required
facets	Kind Value annotation minLength 1 maxLength 12 whiteSpace preserve


#### attribute **contentUspsSummaryUpdateType/@ConsigneeContentID**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s12</b>
properties	isRef 0 use required
facets	Kind Value annotation minLength 1 maxLength 12 whiteSpace preserve


#### element **contentUspsSummaryUpdateType/DestinationDiscountIndicator**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No


**element contentUspsSummaryUpdateType/ZoneSkippingIndicator**

diagram	 mailxml_tm:Zone SkippingIndica...
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation enumeration Yes enumeration No


**element contentUspsSummaryUpdateType/FullServiceIndicator**

diagram	 mailxml_tm:FullServiceIndicator
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation enumeration Yes enumeration No


**element contentUspsSummaryUpdateType/eInductionIndicator**

diagram	 mailxml_tm:eInductionIndicator
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation enumeration Yes enumeration No

### element **contentUspsSummaryUpdateType/Pallets**

diagram																			
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																		
type	<a href="#">mailxml_tm:palletUnitType</a>																		
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	unbounded	content	complex										
isRef	0																		
minOcc	0																		
maxOcc	unbounded																		
content	complex																		
children	<a href="#">mailxml_tm:PalletPreSortLevel</a> <a href="#">mailxml_tm:USPSContainerInfo</a>																		
attributes	<table> <tr> <td>Name <a href="#">mailxml_tm:Count</a></td><td>Type <a href="#">xs:nonNegativeInteger</a></td><td>Use required</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td><a href="#">mailxml_tm:HandlingUnitType</a></td><td><a href="#">mailxml_base:palletHandlingUnitType</a></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td><a href="#">mailxml_tm:PalletType</a></td><td><a href="#">mailxml_base:palletType</a></td><td>required</td><td></td><td></td><td></td></tr> </table>	Name <a href="#">mailxml_tm:Count</a>	Type <a href="#">xs:nonNegativeInteger</a>	Use required	Default	Fixed	annotation	<a href="#">mailxml_tm:HandlingUnitType</a>	<a href="#">mailxml_base:palletHandlingUnitType</a>	required				<a href="#">mailxml_tm:PalletType</a>	<a href="#">mailxml_base:palletType</a>	required			
Name <a href="#">mailxml_tm:Count</a>	Type <a href="#">xs:nonNegativeInteger</a>	Use required	Default	Fixed	annotation														
<a href="#">mailxml_tm:HandlingUnitType</a>	<a href="#">mailxml_base:palletHandlingUnitType</a>	required																	
<a href="#">mailxml_tm:PalletType</a>	<a href="#">mailxml_base:palletType</a>	required																	

### element **contentUspsSummaryUpdateType/Bedload**

diagram									
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>								
type	<a href="#">mailxml_tm:bedloadUnitType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								

children	<a href="#">mailxml_tm:USPSContainerInfo</a> <a href="#">mailxml_tm:Sacks</a> <a href="#">mailxml_tm:Trays</a> <a href="#">mailxml_tm:Parcels</a> <a href="#">mailxml_tm:Bundles</a>
----------	--


element **contentUspsSummaryUpdateType/Perishable**

diagram	 mailxml_tm:Perishable
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

element **contentUspsSummaryUpdateType/MailClass**

diagram	 mailxml_tm:MailClass
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:mailClassType</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration 1 enumeration 2 enumeration 3 enumeration 4 enumeration 6

element **contentUspsSummaryUpdateType/RateType**

diagram	 mailxml_tm:RateType
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:rateType</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation enumeration R enumeration L enumeration B enumeration C enumeration S enumeration S1

	enumeration S2
	enumeration S3
	enumeration S4
	enumeration S5
	enumeration S6
	enumeration S7
	enumeration F
	enumeration A
	enumeration N
	enumeration P
	enumeration T
	enumeration D
	enumeration X
	enumeration H
	enumeration M
	enumeration Z
	enumeration E
	enumeration E4
	enumeration G
	enumeration 1
	enumeration 2
	enumeration 3
	enumeration 4
	enumeration J
	enumeration K
	enumeration V
	enumeration W
	enumeration Y
	enumeration Q

#### element **contentUspsSummaryUpdateType/InHomeStart**

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>xs:dateTime</b>								
properties	<table> <tr><td>isRef</td><td>0</td></tr> <tr><td>minOcc</td><td>0</td></tr> <tr><td>maxOcc</td><td>1</td></tr> <tr><td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple
isRef	0								
minOcc	0								
maxOcc	1								
content	simple								

#### element **contentUspsSummaryUpdateType/InHomeEnd**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm

type	<b>xs:dateTime</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple

element **contentUspsSummaryUpdateType/ProcessingCategory**

diagram	 <a href="#">mailxml_tm:ProcessingCategory</a>																																				
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																				
type	<b>mailxml_base:processingCategoryType</b>																																				
properties	isRef 0 content simple																																				
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>LT</td> <td></td> </tr> <tr> <td>enumeration</td> <td>FL</td> <td></td> </tr> <tr> <td>enumeration</td> <td>CD</td> <td></td> </tr> <tr> <td>enumeration</td> <td>OS</td> <td></td> </tr> <tr> <td>enumeration</td> <td>MP</td> <td></td> </tr> <tr> <td>enumeration</td> <td>IR</td> <td></td> </tr> <tr> <td>enumeration</td> <td>PF</td> <td></td> </tr> <tr> <td>enumeration</td> <td>CM</td> <td></td> </tr> <tr> <td>enumeration</td> <td>NP</td> <td></td> </tr> <tr> <td>enumeration</td> <td>SP</td> <td></td> </tr> <tr> <td>enumeration</td> <td>MB</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	enumeration	LT		enumeration	FL		enumeration	CD		enumeration	OS		enumeration	MP		enumeration	IR		enumeration	PF		enumeration	CM		enumeration	NP		enumeration	SP		enumeration	MB	
Kind	Value	annotation																																			
enumeration	LT																																				
enumeration	FL																																				
enumeration	CD																																				
enumeration	OS																																				
enumeration	MP																																				
enumeration	IR																																				
enumeration	PF																																				
enumeration	CM																																				
enumeration	NP																																				
enumeration	SP																																				
enumeration	MB																																				

element **contentUspsSummaryUpdateType/PriorityMailIndicator**

diagram	 <a href="#">mailxml_tm:PriorityMailIndicator</a>									
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>									
type	<b>mailxml_base:yesNo</b>									
properties	isRef 0 content simple default No									
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Yes</td> <td></td> </tr> <tr> <td>enumeration</td> <td>No</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	enumeration	Yes		enumeration	No	
Kind	Value	annotation								
enumeration	Yes									
enumeration	No									

element **contentUspsSummaryUpdateType/VerificationLocation**


diagram	 <a href="#">mailxml_tm:VerificationLocation</a>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_tm:verificationLocationType</b>

properties	isRef 0 content simple
facets	Kind Value annotation enumeration BMEU enumeration DMU


#### element **contentUspsSummaryUpdateType/NewsIndicator**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

#### element **contentUspsSummaryUpdateType/EvsIndicator**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation enumeration Yes enumeration No

#### element **contentUspsSummaryUpdateType/MailContentName**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s30</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 30 whiteSpace preserve

**element contentUspsSummaryUpdateType/MailPreparerID**

diagram	mailxml_tm:MailPreparerID												
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s12</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>12</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	12		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	12												
whiteSpace	preserve												


**element contentUspsSummaryUpdateType/MailPreparerCRID**

diagram	mailxml_tm:MailPreparerCRID												
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:CRIDType</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>15</td><td></td></tr> <tr> <td>pattern</td><td>([0-9])*</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	15		pattern	([0-9])*	
Kind	Value	annotation											
minLength	1												
maxLength	15												
pattern	([0-9])*												


**element contentUspsSummaryUpdateType/AdvanceMailingID**

diagram	mailxml_tm:AdvanceMailingID 0..∞												
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s09</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	unbounded	content	simple				
isRef	0												
minOcc	0												
maxOcc	unbounded												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>9</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	9		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	9												
whiteSpace	preserve												

element **contentUspsSummaryUpdateType/EFileName**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s22</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>22</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	22		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	22												
whiteSpace	preserve												

element **contentUspsSummaryUpdateType/ContainsAutoMail**

diagram										
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm									
type	<b>mailxml_base:yesNo</b>									
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple	
isRef	0									
minOcc	0									
maxOcc	1									
content	simple									
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>enumeration</td><td>Yes</td><td></td></tr> <tr> <td>enumeration</td><td>No</td><td></td></tr> </table>	Kind	Value	annotation	enumeration	Yes		enumeration	No	
Kind	Value	annotation								
enumeration	Yes									
enumeration	No									

complexType **csaDispatchType**

diagram	<pre> classDiagram     class csaDispatchType {         mailxml_tm:CSATemplate         mailxml_tm:DispatchTime         mailxml_tm:ArrivalTime         mailxml_tm:DaysOfWeek         mailxml_tm:TripNumber         mailxml_tm:RecurringApptSeqID         mailxml_tm:USPSPublicationID         mailxml_tm:TripVolume         mailxml_tm:ContainerDestinationZipCode         mailxml_tm:FacilityLocaleKey         mailxml_tm:MailClass         mailxml_tm:PackageServicesS...         mailxml_tm:ProcessingCategory         mailxml_tm:ProcessingCode         mailxml_tm:ProcessingCodeLa...         mailxml_tm:MinimumLoadForC...         mailxml_tm:ContainerReadyTime         mailxml_tm:SeparationNumber         mailxml_tm:LabelTo         mailxml_tm:LabelToZip         mailxml_tm:CriticalAcceptanceT...     } </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
children	<a href="#">mailxml_tm:DispatchTime</a> <a href="#">mailxml_tm:ArrivalTime</a> <a href="#">mailxml_tm:DaysOfWeek</a> <a href="#">mailxml_tm:TripNumber</a> <a href="#">mailxml_tm:RecurringApptSeqID</a> <a href="#">mailxml_tm:USPSPublicationID</a> <a href="#">mailxml_tm:TripVolume</a> <a href="#">mailxml_tm:ContainerDestinationZipCode</a> <a href="#">mailxml_tm:FacilityLocaleKey</a> <a href="#">mailxml_tm:MailClass</a>

	<a href="#">mailxml_tm:PackageServicesSubClass</a> <a href="#">mailxml_tm:ProcessingCategory</a> <a href="#">mailxml_tm:ProcessingCode</a> <a href="#">mailxml_tm:ProcessingCodeLabel</a> <a href="#">mailxml_tm:MinimumLoadForContainer</a> <a href="#">mailxml_tm:ContainerReadyTime</a> <a href="#">mailxml_tm:SeparationNumber</a> <a href="#">mailxml_tm:LabelTo</a> <a href="#">mailxml_tm:LabelToZip</a> <a href="#">mailxml_tm:CriticalAcceptanceTime</a>
used by	element <a href="#">csalInfoType/CSADispatch</a>
attributes	Name <a href="#">mailxml_tm:CSATemplate</a> Type <a href="#">mailxml_tm:csaTemplateType</a> Use Default Fixed annotation

#### attribute **csaDispatchType/@CSATemplate**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm		
type	<a href="#">mailxml_tm:csaTemplateType</a>		
properties	isRef 0		
facets	Kind enumeration	Value PVDS-PER	annotation
	enumeration	DMU-C	
	enumeration	DMU-P	
	enumeration	BMEU	
	enumeration	UPVDS-PER	
	enumeration	UDMU-C	
	enumeration	UDMU-P	
	enumeration	UBMEU	
	enumeration	U	

#### element **csaDispatchType/DispatchTime**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">xs:time</a>
properties	isRef 0 minOcc 0 maxOcc 1 content simple

#### element **csaDispatchType/ArrivalTime**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_base:s05</a>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 5

	whiteSpace preserve
--	---------------------


**element csaDispatchType/DaysOfWeek**

diagram																																					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																				
type	<b>mailxml_base:daysOfWeekType</b>																																				
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple																												
isRef	0																																				
minOcc	0																																				
maxOcc	1																																				
content	simple																																				
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>MON</td> <td></td> </tr> <tr> <td>enumeration</td> <td>TUE</td> <td></td> </tr> <tr> <td>enumeration</td> <td>WED</td> <td></td> </tr> <tr> <td>enumeration</td> <td>THU</td> <td></td> </tr> <tr> <td>enumeration</td> <td>FRI</td> <td></td> </tr> <tr> <td>enumeration</td> <td>SAT</td> <td></td> </tr> <tr> <td>enumeration</td> <td>SUN</td> <td></td> </tr> <tr> <td>enumeration</td> <td>MF</td> <td></td> </tr> <tr> <td>enumeration</td> <td>MS</td> <td></td> </tr> <tr> <td>enumeration</td> <td>ALL</td> <td></td> </tr> <tr> <td>enumeration</td> <td>H</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	enumeration	MON		enumeration	TUE		enumeration	WED		enumeration	THU		enumeration	FRI		enumeration	SAT		enumeration	SUN		enumeration	MF		enumeration	MS		enumeration	ALL		enumeration	H	
Kind	Value	annotation																																			
enumeration	MON																																				
enumeration	TUE																																				
enumeration	WED																																				
enumeration	THU																																				
enumeration	FRI																																				
enumeration	SAT																																				
enumeration	SUN																																				
enumeration	MF																																				
enumeration	MS																																				
enumeration	ALL																																				
enumeration	H																																				

**element csaDispatchType/TripNumber**


diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>mailxml_base:n05</b>								
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple
isRef	0								
minOcc	0								
maxOcc	1								
content	simple								
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>5</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	totalDigits	5			
Kind	Value	annotation							
totalDigits	5								

**element csaDispatchType/RecurringApptSeqID**

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>mailxml_base:s06</b>								
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple
isRef	0								
minOcc	0								
maxOcc	1								
content	simple								

facets	Kind minLength maxLength whiteSpace	Value 1 6 preserve	annotation
--------	--	-----------------------------	------------

#### element **csaDispatchType/USPSPublicationID**

diagram			
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm		
type	<b>mailxml_base:s09</b>		
properties	isRef 0 minOcc 0 maxOcc 1 content simple		
facets	Kind minLength maxLength whiteSpace		
	Value 1 9 preserve		


#### element **csaDispatchType/TripVolume**

diagram			
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm		
type	<b>mailxml_base:n03</b>		
properties	isRef 0 minOcc 0 maxOcc 1 content simple		
facets	Kind totalDigits		
	Value 3		

#### element **csaDispatchType/ContainerDestinationZipCode**

diagram			
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm		
type	<b>mailxml_base:s11</b>		
properties	isRef 0 minOcc 0 maxOcc unbounded content simple		
facets	Kind minLength maxLength whiteSpace		
	Value 1 11 preserve		


### element csaDispatchType/FacilityLocaleKey

diagram	 mailxml_tm:FacilityLocaleKey												
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s06</b>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	content	simple								
isRef	0												
content	simple												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>6</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	6		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	6												
whiteSpace	preserve												


### element csaDispatchType/MailClass

diagram	 mailxml_tm:MailClass																		
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																		
type	<b>mailxml_base:mailClassType</b>																		
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	content	simple														
isRef	0																		
content	simple																		
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>enumeration</td> <td>1</td> <td></td> </tr> <tr> <td>enumeration</td> <td>2</td> <td></td> </tr> <tr> <td>enumeration</td> <td>3</td> <td></td> </tr> <tr> <td>enumeration</td> <td>4</td> <td></td> </tr> <tr> <td>enumeration</td> <td>6</td> <td></td> </tr> </table>	Kind	Value	annotation	enumeration	1		enumeration	2		enumeration	3		enumeration	4		enumeration	6	
Kind	Value	annotation																	
enumeration	1																		
enumeration	2																		
enumeration	3																		
enumeration	4																		
enumeration	6																		


### element csaDispatchType/PackageServicesSubClass

diagram	 mailxml_tm:Package Services Su...																		
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																		
type	<b>mailxml_tm:packageServicesType</b>																		
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple										
isRef	0																		
minOcc	0																		
maxOcc	1																		
content	simple																		
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>enumeration</td> <td>PS</td> <td></td> </tr> <tr> <td>enumeration</td> <td>BPM</td> <td></td> </tr> <tr> <td>enumeration</td> <td>LIB</td> <td></td> </tr> <tr> <td>enumeration</td> <td>MEDIA</td> <td></td> </tr> <tr> <td>enumeration</td> <td>PP</td> <td></td> </tr> </table>	Kind	Value	annotation	enumeration	PS		enumeration	BPM		enumeration	LIB		enumeration	MEDIA		enumeration	PP	
Kind	Value	annotation																	
enumeration	PS																		
enumeration	BPM																		
enumeration	LIB																		
enumeration	MEDIA																		
enumeration	PP																		


### element csaDispatchType/ProcessingCategory

diagram	 mailxml_tm:ProcessingCategory																																				
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																				
type	<a href="#">mailxml_base:processingCategoryType</a>																																				
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	content	simple																																
isRef	0																																				
content	simple																																				
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>LT</td> <td></td> </tr> <tr> <td>enumeration</td> <td>FL</td> <td></td> </tr> <tr> <td>enumeration</td> <td>CD</td> <td></td> </tr> <tr> <td>enumeration</td> <td>OS</td> <td></td> </tr> <tr> <td>enumeration</td> <td>MP</td> <td></td> </tr> <tr> <td>enumeration</td> <td>IR</td> <td></td> </tr> <tr> <td>enumeration</td> <td>PF</td> <td></td> </tr> <tr> <td>enumeration</td> <td>CM</td> <td></td> </tr> <tr> <td>enumeration</td> <td>NP</td> <td></td> </tr> <tr> <td>enumeration</td> <td>SP</td> <td></td> </tr> <tr> <td>enumeration</td> <td>MB</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	enumeration	LT		enumeration	FL		enumeration	CD		enumeration	OS		enumeration	MP		enumeration	IR		enumeration	PF		enumeration	CM		enumeration	NP		enumeration	SP		enumeration	MB	
Kind	Value	annotation																																			
enumeration	LT																																				
enumeration	FL																																				
enumeration	CD																																				
enumeration	OS																																				
enumeration	MP																																				
enumeration	IR																																				
enumeration	PF																																				
enumeration	CM																																				
enumeration	NP																																				
enumeration	SP																																				
enumeration	MB																																				

### element csaDispatchType/ProcessingCode

diagram	 mailxml_tm:ProcessingCode																								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																								
type	<a href="#">mailxml_tm:processingCodeType</a>																								
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple																
isRef	0																								
minOcc	0																								
maxOcc	1																								
content	simple																								
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>S</td> <td></td> </tr> <tr> <td>enumeration</td> <td>MXDS</td> <td></td> </tr> <tr> <td>enumeration</td> <td>L</td> <td></td> </tr> <tr> <td>enumeration</td> <td>WKG</td> <td></td> </tr> <tr> <td>enumeration</td> <td>A</td> <td></td> </tr> <tr> <td>enumeration</td> <td>MXDA</td> <td></td> </tr> <tr> <td>enumeration</td> <td>SP</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	enumeration	S		enumeration	MXDS		enumeration	L		enumeration	WKG		enumeration	A		enumeration	MXDA		enumeration	SP	
Kind	Value	annotation																							
enumeration	S																								
enumeration	MXDS																								
enumeration	L																								
enumeration	WKG																								
enumeration	A																								
enumeration	MXDA																								
enumeration	SP																								

### element csaDispatchType/ProcessingCodeLabel

diagram	 mailxml_tm:ProcessingCodeLa...
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_base:s20</a>
properties	isRef 0

	minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

#### element csaDispatchType/MinimumLoadForContainer

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:n02</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation totalDigits 2

#### element csaDispatchType/ContainerReadyTime

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:time</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple

#### element csaDispatchType/SeparationNumber


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:n03</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation totalDigits 3

#### element csaDispatchType/LabelTo


diagram	
---------	--

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm		
type	<b>mailxml_base:s25</b>		
properties	isRef 0 minOcc 0 maxOcc 1 content simple		
facets	Kind Value annotation minLength 1 maxLength 25 whiteSpace preserve		


#### element csaDispatchType/LabelToZip

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s05</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 5 whiteSpace preserve

#### element csaDispatchType/CriticalAcceptanceTime

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s05</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 5 whiteSpace preserve

### complexType csalInfoType

diagram																			
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																		
children	<a href="#">mailxml_tm:CSADispatch</a> <a href="#">mailxml_tm:ReturnInfo</a>																		
used by	element <a href="#">CustomerSupplierAgreementQueryResponse/QueryResults/CSAInfo</a>																		
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><a href="#">mailxml_tm:CSAEffectiveDate</a></td> <td><a href="#">xs:date</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:CSAStatus</a></td> <td><a href="#">mailxml_tm:csaStatusType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:CSAEffectiveDate</a>	<a href="#">xs:date</a>					<a href="#">mailxml_tm:CSAStatus</a>	<a href="#">mailxml_tm:csaStatusType</a>				
Name	Type	Use	Default	Fixed	annotation														
<a href="#">mailxml_tm:CSAEffectiveDate</a>	<a href="#">xs:date</a>																		
<a href="#">mailxml_tm:CSAStatus</a>	<a href="#">mailxml_tm:csaStatusType</a>																		


### attribute csalInfoType/@CSAEffectiveDate

namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">xs:date</a>
properties	isRef 0

### attribute csalInfoType/@CSAStatus


namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																		
type	<a href="#">mailxml_tm:csaStatusType</a>																		
properties	isRef 0																		
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>ACT</td> <td></td> </tr> <tr> <td>enumeration</td> <td>PEN</td> <td></td> </tr> <tr> <td>enumeration</td> <td>INACT</td> <td></td> </tr> <tr> <td>enumeration</td> <td>INCOMP</td> <td></td> </tr> <tr> <td>enumeration</td> <td>PREAPP</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	enumeration	ACT		enumeration	PEN		enumeration	INACT		enumeration	INCOMP		enumeration	PREAPP	
Kind	Value	annotation																	
enumeration	ACT																		
enumeration	PEN																		
enumeration	INACT																		
enumeration	INCOMP																		
enumeration	PREAPP																		

element **csalinfoType/CSADispatch**



type	<a href="#"><b>mailxml_tm:csaDispatchType</b></a>					
properties	isRef 0 minOcc 1 maxOcc unbounded content complex					
children	<a href="#">mailxml_tm:DispatchTime</a> <a href="#">mailxml_tm:ArrivalTime</a> <a href="#">mailxml_tm:DaysOfWeek</a> <a href="#">mailxml_tm:TripNumber</a> <a href="#">mailxml_tm:RecurringApptSeqID</a> <a href="#">mailxml_tm:USPSPublicationID</a> <a href="#">mailxml_tm:TripVolume</a> <a href="#">mailxml_tm:ContainerDestinationZipCode</a> <a href="#">mailxml_tm:FacilityLocaleKey</a> <a href="#">mailxml_tm:MailClass</a> <a href="#">mailxml_tm:PackageServicesSubClass</a> <a href="#">mailxml_tm:ProcessingCategory</a> <a href="#">mailxml_tm:ProcessingCode</a> <a href="#">mailxml_tm:ProcessingCodeLabel</a> <a href="#">mailxml_tm:MinimumLoadForContainer</a> <a href="#">mailxml_tm:ContainerReadyTime</a> <a href="#">mailxml_tm:SeparationNumber</a> <a href="#">mailxml_tm:LabelTo</a> <a href="#">mailxml_tm:LabelToZip</a> <a href="#">mailxml_tm:CriticalAcceptanceTime</a>					
attributes	Name <a href="#">mailxml_tm:CSATemplate</a>	Type <a href="#"><b>mailxml_tm:csaTemplateType</b></a>	Use	Default	Fixed	annotation

### element **csalInfoType/ReturnInfo**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_defs:basicReturnInfoType</b>
properties	isRef 0 minOcc 0 maxOcc 1 content complex
children	<a href="#">mailxml_defs:ReturnCode</a> <a href="#">mailxml_defs:ReturnDescription</a> <a href="#">mailxml_defs:errorWarning</a> <a href="#">mailxml_defs:ContainerErrorW...</a>

complexType **deliveryApptAcceptType**


diagram	<pre> classDiagram     class deliveryApptAcceptType {         grp mailxml_defs:ResponseM...         mailxml_defs:ShipperApptRequ...         mailxml_defs:ConsigneeApptID         mailxml_defs:SchedulerID         mailxml_defs:SchedulerCorpID         mailxml_defs:SchedulerCRID         mailxml_defs:ShipperMultiStopID         mailxml_defs:ConsigneeMultiSt...         mailxml_defs:ShipperStopNumb...         mailxml_defs:ApptType         mailxml_defs:PickupOrDelivery         mailxml_defs:PalletPositionCount         mailxml_defs:IncludesElectroni...     }     class mailxml_tm:DestinationEntry     class mailxml_tm:RecurringAppt     class mailxml_tm:OneTimeAppt     class mailxml_tm:DetailInfo     class mailxml_tm:TrailerInfo     class mailxml_tm:ConsigneeFacility     class mailxml_tm:Comment     class mailxml_tm:ReturnInfo      deliveryApptAcceptType "1..∞" -- "1..∞" mailxml_tm:DestinationEntry     deliveryApptAcceptType "1..∞" -- "1..∞" mailxml_tm:RecurringAppt     deliveryApptAcceptType "1..∞" -- "1..∞" mailxml_tm:OneTimeAppt     deliveryApptAcceptType "1..∞" -- "1..∞" mailxml_tm:DetailInfo     deliveryApptAcceptType "1..∞" -- "1..∞" mailxml_tm:TrailerInfo     deliveryApptAcceptType "1..∞" -- "1..∞" mailxml_tm:ConsigneeFacility     deliveryApptAcceptType "1..∞" -- "1..∞" mailxml_tm:Comment     deliveryApptAcceptType "1..∞" -- "1..∞" mailxml_tm:ReturnInfo   </pre>						
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm						
children	<a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:RecurringAppt</a> <a href="#">mailxml_tm:OneTimeAppt</a> <a href="#">mailxml_tm:DetailInfo</a> <a href="#">mailxml_tm:TrailerInfo</a> <a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:Comment</a> <a href="#">mailxml_tm:ReturnInfo</a>						
used by	elements <a href="#">DeliveryApptCancelCreateResponse/DeliveryApptAccept</a> <a href="#">DeliveryApptCreateResponse/DeliveryApptCreateAccept</a>						
attributes	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>Annotation</th> </tr> </thead> </table>	Name	Type	Use	Default	Fixed	Annotation
Name	Type	Use	Default	Fixed	Annotation		

	mailxml_defs:ShipperApptRequestID	<b>mailxml_base:s12</b>	require d
	mailxml_defs:ConsigneeApptID	<b>mailxml_base:s12</b>	require d
	mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>	
	mailxml_defs:SchedulerCorpID	<b>mailxml_base:s12</b>	
	mailxml_defs:SchedulerCRID	<b>mailxml_base:CRIDType</b>	
	mailxml_defs:ShipperMultiStopID	<b>mailxml_base:s12</b>	
	mailxml_defs:ConsigneeMultiStopID	<b>mailxml_base:s12</b>	
	mailxml_defs:ShipperStopNumber	<b>mailxml_base:n06</b>	
	mailxml_defs:ApptType	<b>mailxml_base:apptTypeType</b>	require d
	mailxml_defs:PickupOrDelivery	<b>mailxml_base:pickupOrDeliveryTyp e</b>	
	mailxml_defs:PalletPositionCount	<b>mailxml_base:n02</b>	
	mailxml_defs:IncludesElectronicLoa d	<b>mailxml_base:yesNo</b>	

#### element **deliveryApptAcceptType/DestinationEntry**


diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

#### element **deliveryApptAcceptType/RecurringAppt**


diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#"><b>mailxml_tm:recurringApptType</b></a>

properties	isRef 0 content complex
children	<a href="#">mailxml_tm:EffectiveStartDate</a> <a href="#">mailxml_tm:EffectiveEndDate</a> <a href="#">mailxml_tm:ApptTime</a> <a href="#">mailxml_tm:DayFrequency</a> <a href="#">mailxml_tm:WeekFrequency</a>

#### element deliveryApptAcceptType/OneTimeAppt

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:oneTimeApptType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:PreferredAppt</a> <a href="#">mailxml_tm:OptionalAppt</a>

#### element deliveryApptAcceptType/DetailInfo

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:detailInfoType</a>
properties	isRef 0 minOcc 1 maxOcc unbounded content complex
children	<a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:USPSSummary</a> <a href="#">mailxml_tm:ConsigneeContentID</a>

element **deliveryApptAcceptType/TrailerInfo**

diagram	<pre> classDiagram     class mailxml_tm::trailerInfoType {         mailxml_tm::TrailerInfo         mailxml_tm::Trailer "0..2"         mailxml_tm::Carrier "0..1"         mailxml_tm::BillOfLadingNumber "1..2"     }     mailxml_tm::TrailerInfo --&gt; mailxml_tm::trailerInfoType     mailxml_tm::Trailer --&gt; mailxml_tm::trailerInfoType     mailxml_tm::Carrier --&gt; mailxml_tm::trailerInfoType     mailxml_tm::BillOfLadingNumber --&gt; mailxml_tm::trailerInfoType   </pre>								
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>								
type	<a href="#"><u>mailxml_tm:trailerInfoType</u></a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#"><u>mailxml_tm:Trailer</u></a> <a href="#"><u>mailxml_tm:Carrier</u></a> <a href="#"><u>mailxml_tm:BillOfLadingNumber</u></a>								


element **deliveryApptAcceptType/ConsigneeFacility**

diagram	<pre> classDiagram     class mailxml_tm::ConsigneeFacility     class mailxml_defs::CompanyName     class mailxml_defs::FacilityNumber     class mailxml_defs::FacilityAddress     class mailxml_defs::FacilityName     class mailxml_defs::FacilityType     class mailxml_defs::URL     class mailxml_defs::CommonContact      mailxml_tm::ConsigneeFacility --&gt; mailxml_defs::consigneeFacilityType     mailxml_defs::CompanyName --&gt; mailxml_defs::consigneeFacilityType     mailxml_defs::FacilityNumber --&gt; mailxml_defs::consigneeFacilityType     mailxml_defs::FacilityAddress --&gt; mailxml_defs::consigneeFacilityType     mailxml_defs::FacilityName --&gt; mailxml_defs::consigneeFacilityType     mailxml_defs::FacilityType --&gt; mailxml_defs::consigneeFacilityType     mailxml_defs::URL --&gt; mailxml_defs::consigneeFacilityType     mailxml_defs::CommonContact --&gt; mailxml_defs::consigneeFacilityType   </pre>				
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>				
type	<a href="#"><u>mailxml_defs:consigneeFacilityType</u></a>				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex
isRef	0				
content	complex				
children	<a href="#"><u>mailxml_defs:CompanyName</u></a> <a href="#"><u>mailxml_defs:FacilityNumber</u></a> <a href="#"><u>mailxml_defs:FacilityAddress</u></a> <a href="#"><u>mailxml_defs:FacilityName</u></a> <a href="#"><u>mailxml_defs:FacilityType</u></a> <a href="#"><u>mailxml_defs:URL</u></a> <a href="#"><u>mailxml_defs:CommonContact</u></a>				


**element deliveryApptAcceptType/Comment**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s256</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>256</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	256		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	256												
whiteSpace	preserve												

**element deliveryApptAcceptType/ReturnInfo**

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>mailxml_defs:returnInfoType</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<b>mailxml_defs:ConsigneeFacility</b> <b>mailxml_defs:ErrorWarning</b> <b>mailxml_defs:ContainerErrorWarningBlock</b>								

**complexType deliveryApptContentRemoveAcceptType**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
children	<b>mailxml_tm:ContentID</b>
used by	element <a href="#">DeliveryApptContentRemoveResponse/DeliveryApptContentRemoveAccept</a>

**element deliveryApptContentRemoveAcceptType/ContentID**

diagram	<pre> classDiagram     class mailxml_tm[ContentID]     class mailxml_defs[contentIDType]     mailxml_tm "1..&gt;" mailxml_defs     mailxml_defs {         attribute ConsigneeContentID         attribute SchedulerContentID     }   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_defs:contentIDType</b>
properties	isRef 0 content complex
attributes	Name mailxml_defs:ConsigneeContentID Type <b>mailxml_base:s12</b> Use required Default Fixed annotation mailxml_defs:SchedulerContentID <b>mailxml_base:s12</b>


**complexType deliveryApptContentRemoveRejectType**

diagram	<pre> sequenceDiagram     participant DA as deliveryApptContentRemoveReject...     participant C as ContentID     participant RI as ReturnInfo     DA-&gt;&gt;C:      activate C     C-&gt;&gt;RI:      deactivate C   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
children	<a href="#">mailxml_tm:ContentID</a> <a href="#">mailxml_tm:ReturnInfo</a>
used by	element <a href="#">DeliveryApptContentRemoveResponse/DeliveryApptContentRemoveReject</a>

**element deliveryApptContentRemoveRejectType/ContentID**

diagram	<pre> classDiagram     class mailxml_tm[ContentID]     class mailxml_defs[contentIDType]     mailxml_tm "1..&gt;" mailxml_defs     mailxml_defs {         attribute ConsigneeContentID         attribute SchedulerContentID     }   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_defs:contentIDType</b>
properties	isRef 0 content complex
attributes	Name mailxml_defs:ConsigneeContentID Type <b>mailxml_base:s12</b> Use required Default Fixed annotation mailxml_defs:SchedulerContentID <b>mailxml_base:s12</b>

element **deliveryApptContentRemoveRejectType/ReturnInfo**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_defs:basicReturnInfoType</b>
properties	isRef 0 content complex
children	<b>mailxml_defs:ReturnCode</b> <b>mailxml_defs:ReturnDescription</b> <b>mailxml_defs:errorWarning</b> <b>mailxml_defs:ContainerErrorWarningBlock</b>

complexType **deliveryApptRejectType**

diagram	<pre> classDiagram     class deliveryApptRejectType {         grp mailxml_defs:RequestMs...             mailxml_defs:ShipperApptRequ...             mailxml_defs:ConsigneeApptID             mailxml_defs:SchedulerID             mailxml_defs:SchedulerCorpID             mailxml_defs:SchedulerCRID             mailxml_defs:ShipperMultiStopID             mailxml_defs:ConsigneeMultiStopID             mailxml_defs:ShipperStopNumber             mailxml_defs:ApptType             mailxml_defs:PickupOrDelivery             mailxml_defs:PalletPositionCount             mailxml_defs:IncludesElectronicLoad         }         mailxml_tm:ReturnInfo     } </pre>																																																																														
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																																																														
children	<a href="#">mailxml_tm:ReturnInfo</a>																																																																														
used by	elements <a href="#">DeliveryApptCreateResponse/DeliveryApptCreateReject</a> <a href="#">DeliveryApptCancelCreateResponse/DeliveryApptReject</a>																																																																														
attributes	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:ShipperApptRequestID</td> <td><b>mailxml_base:s12</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ConsigneeApptID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerCorpID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerCRID</td> <td><b>mailxml_base:CRIDType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ShipperMultiStopID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ConsigneeMultiStopID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ShipperStopNumber</td> <td><b>mailxml_base:n06</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApptType</td> <td><b>mailxml_base:apptTypeType</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:PickupOrDelivery</td> <td><b>mailxml_base:pickupOrDeliveryType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:PalletPositionCount</td> <td><b>mailxml_base:n02</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:IncludesElectronicLoad</td> <td><b>mailxml_base:yesNo</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:ShipperApptRequestID	<b>mailxml_base:s12</b>	required				mailxml_defs:ConsigneeApptID	<b>mailxml_base:s12</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:SchedulerCorpID	<b>mailxml_base:s12</b>					mailxml_defs:SchedulerCRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:ShipperMultiStopID	<b>mailxml_base:s12</b>					mailxml_defs:ConsigneeMultiStopID	<b>mailxml_base:s12</b>					mailxml_defs:ShipperStopNumber	<b>mailxml_base:n06</b>					mailxml_defs:ApptType	<b>mailxml_base:apptTypeType</b>	required				mailxml_defs:PickupOrDelivery	<b>mailxml_base:pickupOrDeliveryType</b>					mailxml_defs:PalletPositionCount	<b>mailxml_base:n02</b>					mailxml_defs:IncludesElectronicLoad	<b>mailxml_base:yesNo</b>				
Name	Type	Use	Default	Fixed	annotation																																																																										
mailxml_defs:ShipperApptRequestID	<b>mailxml_base:s12</b>	required																																																																													
mailxml_defs:ConsigneeApptID	<b>mailxml_base:s12</b>																																																																														
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																																														
mailxml_defs:SchedulerCorpID	<b>mailxml_base:s12</b>																																																																														
mailxml_defs:SchedulerCRID	<b>mailxml_base:CRIDType</b>																																																																														
mailxml_defs:ShipperMultiStopID	<b>mailxml_base:s12</b>																																																																														
mailxml_defs:ConsigneeMultiStopID	<b>mailxml_base:s12</b>																																																																														
mailxml_defs:ShipperStopNumber	<b>mailxml_base:n06</b>																																																																														
mailxml_defs:ApptType	<b>mailxml_base:apptTypeType</b>	required																																																																													
mailxml_defs:PickupOrDelivery	<b>mailxml_base:pickupOrDeliveryType</b>																																																																														
mailxml_defs:PalletPositionCount	<b>mailxml_base:n02</b>																																																																														
mailxml_defs:IncludesElectronicLoad	<b>mailxml_base:yesNo</b>																																																																														

element **deliveryApptRejectType/ReturnInfo**

diagram	<pre> classDiagram     class mailxml_tm::ReturnInfo     class mailxml_defs::returnInfoType     class mailxml_defs::ConsigneeFacility     class mailxml_defs::ErrorWarning     class mailxml_defs::ContainerErrorW...      mailxml_tm::ReturnInfo --&gt; mailxml_defs::returnInfoType     mailxml_tm::ReturnInfo --&gt; mailxml_defs::ConsigneeFacility     mailxml_tm::ReturnInfo --&gt; mailxml_defs::ErrorWarning     mailxml_tm::ReturnInfo --&gt; mailxml_defs::ContainerErrorW...   </pre>				
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>				
type	<b>mailxml_defs:returnInfoType</b>				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex
isRef	0				
content	complex				
children	<b>mailxml_defs:ConsigneeFacility</b> <b>mailxml_defs:ErrorWarning</b> <b>mailxml_defs:ContainerErrorWarningBlock</b>				

complexType **deliveryApptShellAcceptType**

diagram	<pre> classDiagram     class deliveryApptShellAcceptType {         &lt;&lt;attributes&gt;&gt;             grp mailxml_defs:RequestMs...             mailxml_defs:ShipperApptRequ...             mailxml_defs:ConsigneeApptID             mailxml_defs:SchedulerID             mailxml_defs:SchedulerCorpID             mailxml_defs:SchedulerCRID             mailxml_defs:ShipperMultiStopID             mailxml_defs:ConsigneeMultiSt...             mailxml_defs:ShipperStopNumb...             mailxml_defs:ApptType             mailxml_defs:PickupOrDelivery             mailxml_defs:PalletPositionCount             mailxml_defs:IncludesElectroni...         }     }     mailxml_tm:ConsigneeFacility     mailxml_tm:RecurringAppt     mailxml_tm:OneTimeAppt     mailxml_tm:TrailerInfo     mailxml_tm:DestinationEntry     mailxml_tm:MailClass     mailxml_tm:ReturnInfo     mailxml_tm:ConsigneeFacility --&gt; mailxml_tm:RecurringAppt     mailxml_tm:RecurringAppt --&gt; mailxml_tm:OneTimeAppt     mailxml_tm:RecurringAppt --&gt; mailxml_tm:TrailerInfo     mailxml_tm:OneTimeAppt --&gt; mailxml_tm:TrailerInfo     mailxml_tm:TrailerInfo --&gt; mailxml_tm:DestinationEntry     mailxml_tm:DestinationEntry --&gt; mailxml_tm:MailClass     mailxml_tm:MailClass --&gt; mailxml_tm:ReturnInfo   </pre>												
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:RecurringAppt</a> <a href="#">mailxml_tm:OneTimeAppt</a> <a href="#">mailxml_tm:TrailerInfo</a> <a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:MailClass</a> <a href="#">mailxml_tm:ReturnInfo</a>												
used by	elements <a href="#">DeliveryApptShellUpdateResponse/DeliveryApptShellAccept</a> <a href="#">DeliveryApptShellCreateResponse/DeliveryApptShellCreateAccept</a>												
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:ShipperApptRequestID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td>required</td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	Annotation	mailxml_defs:ShipperApptRequestID	<b>mailxml_base:s12</b>		required		
Name	Type	Use	Default	Fixed	Annotation								
mailxml_defs:ShipperApptRequestID	<b>mailxml_base:s12</b>		required										

	mailxml_defs:ConsigneeApptID mailxml_defs:SchedulerID mailxml_defs:SchedulerCorpID mailxml_defs:SchedulerCRID mailxml_defs:ShipperMultiStopID mailxml_defs:ConsigneeMultiStopID mailxml_defs:ShipperStopNumber mailxml_defs:ApptType mailxml_defs:PickupOrDelivery mailxml_defs:PalletPositionCount mailxml_defs:IncludesElectronicLoad	<b>mailxml_base:s12</b> <b>mailxml_base:s12</b> <b>mailxml_base:s12</b> <b>mailxml_base:CRIDType</b> <b>mailxml_base:s12</b> <b>mailxml_base:s12</b> <b>mailxml_base:n06</b> <b>mailxml_base:apptTypeType</b> <b>mailxml_base:pickupOrDeliveryType</b> <b>mailxml_base:n02</b> <b>mailxml_base:yesNo</b>	required
--	---	--	----------

### element **deliveryApptShellAcceptType/ConsigneeFacility**

diagram	<pre> classDiagram     class mailxml_tm {         ConsigneeFacility     }     class mailxml_defs {         consigneeFacilityType         CompanyName         FacilityNumber         FacilityAddress         FacilityName         FacilityType         URL         CommonContact     }      mailxml_tm::ConsigneeFacility &lt; -- mailxml_defs::consigneeFacilityType     mailxml_tm::ConsigneeFacility --&gt; mailxml_defs::CompanyName     mailxml_tm::ConsigneeFacility --&gt; mailxml_defs::FacilityNumber     mailxml_tm::ConsigneeFacility --&gt; mailxml_defs::FacilityAddress     mailxml_tm::ConsigneeFacility --&gt; mailxml_defs::FacilityAddress     mailxml_defs::FacilityAddress *--&gt; mailxml_defs::FacilityName     mailxml_defs::FacilityAddress *--&gt; mailxml_defs::FacilityType     mailxml_defs::FacilityAddress *--&gt; mailxml_defs::URL     mailxml_defs::FacilityAddress *--&gt; mailxml_defs::CommonContact   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_defs:consigneeFacilityType</b>
properties	isRef 0 content complex
children	<b>mailxml_defs:CompanyName</b> <b>mailxml_defs:FacilityNumber</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityName</b> <b>mailxml_defs:FacilityType</b> <b>mailxml_defs:URL</b> <b>mailxml_defs:CommonContact</b>


element **deliveryApptShellAcceptType/RecurringAppt**

diagram	<pre> classDiagram     class RecurringAppt     class recurringApptType {         EffectiveStartDate         EffectiveEndDate         ApptTime         DayFrequency         WeekFrequency     }     RecurringAppt "*" --&gt; "1..∞" recurringApptType     DayFrequency "1..∞"     WeekFrequency "1..∞"   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:recurringApptType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:EffectiveStartDate</a> <a href="#">mailxml_tm:EffectiveEndDate</a> <a href="#">mailxml_tm:ApptTime</a> <a href="#">mailxml_tm:DayFrequency</a> <a href="#">mailxml_tm:WeekFrequency</a>

element **deliveryApptShellAcceptType/OneTimeAppt**

diagram	<pre> classDiagram     class OneTimeAppt     class oneTimeApptType {         PreferredAppt         OptionalAppt     }     OneTimeAppt "*" --&gt; "0..∞" oneTimeApptType   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:oneTimeApptType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:PreferredAppt</a> <a href="#">mailxml_tm:OptionalAppt</a>

### element deliveryApptShellAcceptType/TrailerInfo

diagram									
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>								
type	<a href="#">mailxml_tm:trailerInfoType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#">mailxml_tm:Trailer</a> <a href="#">mailxml_tm:Carrier</a> <a href="#">mailxml_tm:BillOfLadingNumber</a>								


### element deliveryApptShellAcceptType/DestinationEntry

diagram										
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>									
type	<a href="#">mailxml_base:yesNo</a>									
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	content	simple					
isRef	0									
content	simple									
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>enumeration</td><td>Yes</td><td></td></tr> <tr> <td>enumeration</td><td>No</td><td></td></tr> </table>	Kind	Value	annotation	enumeration	Yes		enumeration	No	
Kind	Value	annotation								
enumeration	Yes									
enumeration	No									

### element deliveryApptShellAcceptType/MailClass

diagram																
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>															
type	<a href="#">mailxml_base:mailClassType</a>															
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>1</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	1	maxOcc	unbounded	content	simple							
isRef	0															
minOcc	1															
maxOcc	unbounded															
content	simple															
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>enumeration</td><td>1</td><td></td></tr> <tr> <td>enumeration</td><td>2</td><td></td></tr> <tr> <td>enumeration</td><td>3</td><td></td></tr> <tr> <td>enumeration</td><td>4</td><td></td></tr> </table>	Kind	Value	annotation	enumeration	1		enumeration	2		enumeration	3		enumeration	4	
Kind	Value	annotation														
enumeration	1															
enumeration	2															
enumeration	3															
enumeration	4															

element **deliveryApptShellAcceptType/ReturnInfo**

diagram									
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>								
type	<b>mailxml_defs:returnInfoType</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<b>mailxml_defs:ConsigneeFacility</b> <b>mailxml_defs:ErrorWarning</b> <b>mailxml_defs:ContainerErrorWarningBlock</b>								

**complexType deliveryApptShellCancelRequestType**


diagram	<pre> classDiagram     class deliveryApptShellCancelRequestType {         compartment attributes             grp mailxml_defs:RequestM...                 mailxml_defs:ShipperApptRequ...                 mailxml_defs:ConsigneeApptID                 mailxml_defs:SchedulerID                 mailxml_defs:SchedulerCorpID                 mailxml_defs:SchedulerCRID                 mailxml_defs:ShipperMultiStopID                 mailxml_defs:ConsigneeMultiSto...                 mailxml_defs:ShipperStopNumb...                 mailxml_defs:ApptType                 mailxml_defs:PickupOrDelivery                 mailxml_defs:PalletPositionCount                 mailxml_defs:IncludesElectroni...             end             mailxml_tm:SubmittingParty             mailxml_tm:SubmittingSoftware             mailxml_tm:SubmitterTrackingID             mailxml_tm:DestinationEntry             mailxml_tm:ReturnInfo         end     } </pre>																																										
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																										
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ReturnInfo</a>																																										
used by	element <a href="#">DeliveryApptShellCancelRequest</a>																																										
attributes	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:ShipperApptRequestID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ConsigneeApptID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerCorpID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerCRID</td> <td><a href="#">mailxml_base:CRIDType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ShipperMultiStopID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required				mailxml_defs:ConsigneeApptID	<a href="#">mailxml_base:s12</a>					mailxml_defs:SchedulerID	<a href="#">mailxml_base:s12</a>					mailxml_defs:SchedulerCorpID	<a href="#">mailxml_base:s12</a>					mailxml_defs:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>					mailxml_defs:ShipperMultiStopID	<a href="#">mailxml_base:s12</a>				
Name	Type	Use	Default	Fixed	annotation																																						
mailxml_defs:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required																																									
mailxml_defs:ConsigneeApptID	<a href="#">mailxml_base:s12</a>																																										
mailxml_defs:SchedulerID	<a href="#">mailxml_base:s12</a>																																										
mailxml_defs:SchedulerCorpID	<a href="#">mailxml_base:s12</a>																																										
mailxml_defs:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>																																										
mailxml_defs:ShipperMultiStopID	<a href="#">mailxml_base:s12</a>																																										

	<p>mailxml_defs:ConsigneeMultiStopID      <b>mailxml_base:s12</b></p> <p>mailxml_defs:ShipperStopNumber      <b>mailxml_base:n06</b></p> <p>mailxml_defs:ApptType      <b>mailxml_base:apptTypeType</b> required</p> <p>mailxml_defs:PickupOrDelivery      <b>mailxml_base:pickupOrDeliveryType</b></p> <p>mailxml_defs:PalletPositionCount      <b>mailxml_base:n02</b></p> <p>mailxml_defs:IncludesElectronicLoad      <b>mailxml_base:yesNo</b></p>
--	--

### element **deliveryApptShellCancelRequestType/SubmittingParty**

diagram	<pre> classDiagram     class SubmittingParty {         &lt;&lt;mailxml_tm&gt;&gt;     }     class participantIDType {         &lt;&lt;mailxml_defs&gt;&gt;         &lt;&lt;attributes&gt;&gt;             MailerID6             MailerID9             CRID             SchedulerID             MaildatUserLicense             ShippingAgentID             ReceivingAgentID         end     }     SubmittingParty "1" -- "0..1" participantIDType   </pre>																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <thead> <tr> <th>isRef</th><th>0</th> </tr> <tr> <th>content</th><th>complex</th> </tr> </thead> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table> <thead> <tr> <th>Name</th><th>Type</th><th>Use</th><th>Default</th><th>Fixed</th><th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:MailerID6</td><td><b>mailxml_base:mailerID6Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MailerID9</td><td><b>mailxml_base:mailerID9Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:CRID</td><td><b>mailxml_base:CRIDType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatUserLicense</td><td><b>mailxml_base:userLicenseCodeType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShippingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ReceivingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

### element deliveryApptShellCancelRequestType/SubmittingSoftware

diagram																																					
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																				
type	<b>mailxml_defs:submittingSoftwareType</b>																																				
properties	isRef 0 content complex																																				
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:SoftwareName</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Vendor</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:Version</td> <td><b>xs:string</b></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalDate</td> <td><b>xs:date</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApprovalKey</td> <td><b>xs:string</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SoftwareName	<b>xs:string</b>	required				mailxml_defs:Vendor	<b>xs:string</b>	required				mailxml_defs:Version	<b>xs:string</b>	required				mailxml_defs:ApprovalDate	<b>xs:date</b>					mailxml_defs:ApprovalKey	<b>xs:string</b>				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_defs:SoftwareName	<b>xs:string</b>	required																																			
mailxml_defs:Vendor	<b>xs:string</b>	required																																			
mailxml_defs:Version	<b>xs:string</b>	required																																			
mailxml_defs:ApprovalDate	<b>xs:date</b>																																				
mailxml_defs:ApprovalKey	<b>xs:string</b>																																				

### element deliveryApptShellCancelRequestType/SubmitterTrackingID


diagram													
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>												
type	<b>mailxml_base:s20</b>												
properties	isRef 0 minOcc 0 maxOcc 1 content simple												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>20</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

### element deliveryApptShellCancelRequestType/DestinationEntry


diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:yesNo</b>

properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No


#### element deliveryApptShellCancelRequestType/ReturnInfo

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:optReturnInfoType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:ReturnCode</a> <a href="#">mailxml_tm:ReturnDescription</a>

#### complexType deliveryApptShellCancelResponseType

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
children	<a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:DeliveryApptCancelAccept</a> <a href="#">mailxml_tm:DeliveryApptCancelReject</a>
used by	element <a href="#">DeliveryApptShellCancelResponse</a>

#### element deliveryApptShellCancelResponseType/SubmitterTrackingID

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_base:s20</a>
properties	isRef 0 minOcc 0 maxOcc 1 content simple

	facets	Kind	Value	annotation
		minLength	1	
		maxLength	20	
		whiteSpace	preserve	

#### element **deliveryApptShellCancelResponseType/TrackingID**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>20</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

#### element **deliveryApptShellCancelResponseType/DeliveryApptCancelAccept**

diagram	
---------	---

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
properties	isRef 0 content complex					
children	<a href="#">mailxml_tm:DestinationEntry</a>					
attributes	Name	Type	Use	Default	Fixed	annotation
	mailxml_defs:ShipperApptRequestID	<b>mailxml_base:s12</b>	required			
	mailxml_defs:ConsigneeApptID	<b>mailxml_base:s12</b>	required			
	mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>				
	mailxml_defs:SchedulerCorpID	<b>mailxml_base:s12</b>				
	mailxml_defs:SchedulerCRID	<b>mailxml_base:CRIDType</b>				
	mailxml_defs:ShipperMultiStopID	<b>mailxml_base:s12</b>				
	mailxml_defs:ConsigneeMultiStopID	<b>mailxml_base:s12</b>				
	mailxml_defs:ShipperStopNumber	<b>mailxml_base:n06</b>				
	mailxml_defs:ApptType	<b>mailxml_base:apptTypeType</b>	required			
	mailxml_defs:PickupOrDelivery	<b>mailxml_base:pickupOrDeliveryType</b>				
	mailxml_defs:PalletPositionCount	<b>mailxml_base:n02</b>				
	mailxml_defs:IncludesElectronicLoad	<b>mailxml_base:yesNo</b>				

#### element **deliveryApptShellCancelResponseType/DeliveryApptCancelAccept/DestinationEntry**

diagram	 <a href="#">mailxml_tm:DestinationEntry</a>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

element **deliveryApptShellCancelResponseType/DeliveryApptCancelReject**


diagram																																																																									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																																								
properties	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 10%;">isRef</td><td style="width: 10%;">0</td> </tr> <tr> <td>content</td><td>complex</td> </tr> </table>	isRef	0	content	complex																																																																				
isRef	0																																																																								
content	complex																																																																								
children	<a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ReturnInfo</a>																																																																								
attributes	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Name</th><th>Type</th><th>Use</th><th>Default</th><th>Fixed</th><th>annotation</th></tr> </thead> <tbody> <tr> <td>mailxml_defs:ShipperApptRequestID</td><td><a href="#">mailxml_base:s12</a></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ConsigneeApptID</td><td><a href="#">mailxml_base:s12</a></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerID</td><td><a href="#">mailxml_base:s12</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerCorpID</td><td><a href="#">mailxml_base:s12</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerCRID</td><td><a href="#">mailxml_base:CRIDType</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShipperMultiStopID</td><td><a href="#">mailxml_base:s12</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ConsigneeMultiStopID</td><td><a href="#">mailxml_base:s12</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShipperStopNumber</td><td><a href="#">mailxml_base:n06</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ApptType</td><td><a href="#">mailxml_base:apptTypeType</a></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:PickupOrDelivery</td><td><a href="#">mailxml_base:pickupOrDeliveryType</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:PalletPositionCount</td><td><a href="#">mailxml_base:n02</a></td><td></td><td></td><td></td><td></td></tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required				mailxml_defs:ConsigneeApptID	<a href="#">mailxml_base:s12</a>	required				mailxml_defs:SchedulerID	<a href="#">mailxml_base:s12</a>					mailxml_defs:SchedulerCorpID	<a href="#">mailxml_base:s12</a>					mailxml_defs:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>					mailxml_defs:ShipperMultiStopID	<a href="#">mailxml_base:s12</a>					mailxml_defs:ConsigneeMultiStopID	<a href="#">mailxml_base:s12</a>					mailxml_defs:ShipperStopNumber	<a href="#">mailxml_base:n06</a>					mailxml_defs:ApptType	<a href="#">mailxml_base:apptTypeType</a>	required				mailxml_defs:PickupOrDelivery	<a href="#">mailxml_base:pickupOrDeliveryType</a>					mailxml_defs:PalletPositionCount	<a href="#">mailxml_base:n02</a>				
Name	Type	Use	Default	Fixed	annotation																																																																				
mailxml_defs:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required																																																																							
mailxml_defs:ConsigneeApptID	<a href="#">mailxml_base:s12</a>	required																																																																							
mailxml_defs:SchedulerID	<a href="#">mailxml_base:s12</a>																																																																								
mailxml_defs:SchedulerCorpID	<a href="#">mailxml_base:s12</a>																																																																								
mailxml_defs:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>																																																																								
mailxml_defs:ShipperMultiStopID	<a href="#">mailxml_base:s12</a>																																																																								
mailxml_defs:ConsigneeMultiStopID	<a href="#">mailxml_base:s12</a>																																																																								
mailxml_defs:ShipperStopNumber	<a href="#">mailxml_base:n06</a>																																																																								
mailxml_defs:ApptType	<a href="#">mailxml_base:apptTypeType</a>	required																																																																							
mailxml_defs:PickupOrDelivery	<a href="#">mailxml_base:pickupOrDeliveryType</a>																																																																								
mailxml_defs:PalletPositionCount	<a href="#">mailxml_base:n02</a>																																																																								

	mailxml_defs:IncludesElectronicLoa d	mailxml_base:yesNo
--	---	--------------------

element **deliveryApptShellCancelResponseType/DeliveryApptCancelReject/DestinationEntry**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	mailxml_base:yesNo
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

element **deliveryApptShellCancelResponseType/DeliveryApptCancelReject/ReturnInfo**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	mailxml_defs:returnInfoType
properties	isRef 0 content complex
children	mailxml_defs:ConsigneeFacility mailxml_defs:ErrorWarning mailxml_defs:ContainerErrorW...

**complexType deliveryApptShellRejectType**


diagram	<pre> classDiagram     class deliveryApptShellRejectType {         grp mailxml_defs:RequestMs...             mailxml_defs:ShipperApptRequ...             mailxml_defs:ConsigneeApptID             mailxml_defs:SchedulerID             mailxml_defs:SchedulerCorpID             mailxml_defs:SchedulerCRID             mailxml_defs:ShipperMultiStopID             mailxml_defs:ConsigneeMultiSt...             mailxml_defs:ShipperStopNumb...             mailxml_defs:ApptType             mailxml_defs:PickupOrDelivery             mailxml_defs:PalletPositionCount             mailxml_defs:IncludesElectroni...         end         mailxml_tm:DestinationEntry         mailxml_tm:ReturnInfo     } </pre>																																																																								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																																								
children	<a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ReturnInfo</a>																																																																								
used by	elements <a href="#">DeliveryApptShellCreateResponse/DeliveryApptShellCreateReject</a> <a href="#">DeliveryApptShellUpdateResponse/DeliveryApptShellReject</a>																																																																								
attributes	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>Annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:ShipperApptRequestID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ConsigneeApptID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerCorpID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerCRID</td> <td><a href="#">mailxml_base:CRIDType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ShipperMultiStopID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ConsigneeMultiStopID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ShipperStopNumber</td> <td><a href="#">mailxml_base:n06</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApptType</td> <td><a href="#">mailxml_base:apptTypeType</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:PickupOrDelivery</td> <td><a href="#">mailxml_base:pickupOrDeliveryType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:PalletPositionCount</td> <td><a href="#">mailxml_base:n02</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	Annotation	mailxml_defs:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required				mailxml_defs:ConsigneeApptID	<a href="#">mailxml_base:s12</a>					mailxml_defs:SchedulerID	<a href="#">mailxml_base:s12</a>					mailxml_defs:SchedulerCorpID	<a href="#">mailxml_base:s12</a>					mailxml_defs:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>					mailxml_defs:ShipperMultiStopID	<a href="#">mailxml_base:s12</a>					mailxml_defs:ConsigneeMultiStopID	<a href="#">mailxml_base:s12</a>					mailxml_defs:ShipperStopNumber	<a href="#">mailxml_base:n06</a>					mailxml_defs:ApptType	<a href="#">mailxml_base:apptTypeType</a>	required				mailxml_defs:PickupOrDelivery	<a href="#">mailxml_base:pickupOrDeliveryType</a>					mailxml_defs:PalletPositionCount	<a href="#">mailxml_base:n02</a>				
Name	Type	Use	Default	Fixed	Annotation																																																																				
mailxml_defs:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required																																																																							
mailxml_defs:ConsigneeApptID	<a href="#">mailxml_base:s12</a>																																																																								
mailxml_defs:SchedulerID	<a href="#">mailxml_base:s12</a>																																																																								
mailxml_defs:SchedulerCorpID	<a href="#">mailxml_base:s12</a>																																																																								
mailxml_defs:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>																																																																								
mailxml_defs:ShipperMultiStopID	<a href="#">mailxml_base:s12</a>																																																																								
mailxml_defs:ConsigneeMultiStopID	<a href="#">mailxml_base:s12</a>																																																																								
mailxml_defs:ShipperStopNumber	<a href="#">mailxml_base:n06</a>																																																																								
mailxml_defs:ApptType	<a href="#">mailxml_base:apptTypeType</a>	required																																																																							
mailxml_defs:PickupOrDelivery	<a href="#">mailxml_base:pickupOrDeliveryType</a>																																																																								
mailxml_defs:PalletPositionCount	<a href="#">mailxml_base:n02</a>																																																																								

	mailxml_defs:IncludesElectronicLoa d	mailxml_base:yesNo
--	---	--------------------

element **deliveryApptShellRejectType/DestinationEntry**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	mailxml_base:yesNo
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

element **deliveryApptShellRejectType/ReturnInfo**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	mailxml_defs:returnInfoType
properties	isRef 0 content complex
children	mailxml_defs:ConsigneeFacility mailxml_defs:ErrorWarning mailxml_defs:ContainerErrorW...

#### **complexType deliveryApptTransportationUpdateRequestType**

diagram	<pre> classDiagram     class deliveryApptTransportationUpdateRequest {         grp mailxml_tm:DeliveryApptT...         mailxml_tm:ShipperApptReque...         mailxml_tm:ConsigneeApptID         mailxml_tm:SchedulerContentID         mailxml_tm:SchedulerID     }     class SubmittingParty     class SubmittingSoftware     class SubmitterTrackingID     class TrailerInfo      deliveryApptTransportationUpdateRequest "1" -- "*" SubmittingParty :      deliveryApptTransportationUpdateRequest "1" -- "*" SubmittingSoftware :      deliveryApptTransportationUpdateRequest "1" -- "*" SubmitterTrackingID :      deliveryApptTransportationUpdateRequest "1" -- "*" TrailerInfo :   </pre>																														
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																														
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:TrailerInfo</a>																														
used by	element <a href="#">DeliveryApptTransportationUpdateRequest</a>																														
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:ShipperApptRequestID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:ConsigneeApptID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerContentID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required				mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>	required				mailxml_tm:SchedulerContentID	<a href="#">mailxml_base:s12</a>	required				mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>	required			
Name	Type	Use	Default	Fixed	annotation																										
mailxml_tm:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required																													
mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>	required																													
mailxml_tm:SchedulerContentID	<a href="#">mailxml_base:s12</a>	required																													
mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>	required																													

element **deliveryApptTransportationUpdateRequestType/SubmittingParty**

diagram	<pre> graph LR     SP[mailxml_tm:SubmittingParty] --- PID[mailxml_defs:participantIDType]     PID --- A[attributes]     A --- M6[mailxml_defs:MailerID6]     A --- M9[mailxml_defs:MailerID9]     A --- CRID[mailxml_defs:CRID]     A --- SCHED[mailxml_defs:SchedulerID]     A --- ML[mailxml_defs:MaildatUserLicense]     A --- SAID[mailxml_defs:ShippingAgentID]     A --- RAID[mailxml_defs:ReceivingAgentID]   </pre>																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:MailerID6</td><td><b>mailxml_base:mailerID6Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MailerID9</td><td><b>mailxml_base:mailerID9Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:CRID</td><td><b>mailxml_base:CRIDType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatUserLicense</td><td><b>mailxml_base:userLicenseCodeType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShippingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ReceivingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

element **deliveryApptTransportationUpdateRequestType/SubmittingSoftware**


diagram	<pre> graph LR     SS[mailxml_tm:SubmittingSoftware] --- SST[mailxml_defs:submittingSoftwareType]     SST --- A[attributes]     A --- SN[mailxml_defs:SoftwareName]     A --- V[mailxml_defs:Vendor]     A --- V2[mailxml_defs:Version]     A --- AD[mailxml_defs:ApprovalDate]     A --- AK[mailxml_defs:ApprovalKey]   </pre>
---------	---

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
type	<b>mailxml_defs:submittingSoftwareType</b>					
properties	isRef 0 content complex					
attributes	Name mailxml_defs:SoftwareName mailxml_defs:Vendor mailxml_defs:Version mailxml_defs:ApprovalDate mailxml_defs:ApprovalKey	Type <b>xs:string</b> <b>xs:string</b> <b>xs:string</b> <b>xs:date</b> <b>xs:string</b>	Use required required required	Default	Fixed	annotation


#### element **deliveryApptTransportationUpdateRequestType/SubmitterTrackingID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s20</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

#### element **deliveryApptTransportationUpdateRequestType/TrailerInfo**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_tm:trailerInfoType</b>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:Trailer</a> <a href="#">mailxml_tm:Carrier</a> <a href="#">mailxml_tm:BillOfLadingNumber</a>

**complexType deliveryApptTransportationUpdateResponseType**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
children	<a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:DeliveryApptTransportationAccept</a> <a href="#">mailxml_tm:DeliveryApptTransportationReject</a>
used by	element <a href="#">DeliveryApptTransportationUpdateResponse</a>


**element deliveryApptTransportationUpdateResponseType/SubmitterTrackingID**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>20</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												


**element deliveryApptTransportationUpdateResponseType/TrackingID**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>20</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

element **deliveryApptTransportationUpdateResponseType/DeliveryApptTransportationAccept**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:trailerInfoType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:Trailer</a> <a href="#">mailxml_tm:Carrier</a> <a href="#">mailxml_tm:BillOfLadingNumber</a>

element **deliveryApptTransportationUpdateResponseType/DeliveryApptTransportationReject**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_defs:returnInfoType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_defs:ConsigneeFacility</a> <a href="#">mailxml_defs:ErrorWarning</a> <a href="#">mailxml_defs:ContainerErrorWarningBlock</a>

### complexType deliveryApptUpdateAcceptType


diagram							
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm						
children	<a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:RecurringAppt</a> <a href="#">mailxml_tm:OneTimeAppt</a> <a href="#">mailxml_tm:DetailInfo</a> <a href="#">mailxml_tm:TrailerInfo</a> <a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:Comment</a> <a href="#">mailxml_tm:ReturnInfo</a>						
used by	element <a href="#">DeliveryApptUpdateResponse/DeliveryApptUpdateAccept</a>						
attributes	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>Annotations</th> </tr> </thead> </table>	Name	Type	Use	Default	Fixed	Annotations
Name	Type	Use	Default	Fixed	Annotations		

	mailxml_defs:ShipperApptRequestID	<b>mailxml_base:s12</b>	require d
	mailxml_defs:ConsigneeApptID	<b>mailxml_base:s12</b>	require d
	mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>	
	mailxml_defs:SchedulerCorpID	<b>mailxml_base:s12</b>	
	mailxml_defs:SchedulerCRID	<b>mailxml_base:CRIDType</b>	
	mailxml_defs:ShipperMultiStopID	<b>mailxml_base:s12</b>	
	mailxml_defs:ConsigneeMultiStopID	<b>mailxml_base:s12</b>	
	mailxml_defs:ShipperStopNumber	<b>mailxml_base:n06</b>	
	mailxml_defs:ApptType	<b>mailxml_base:apptTypeType</b>	require d
	mailxml_defs:PickupOrDelivery	<b>mailxml_base:pickupOrDeliveryTyp e</b>	
	mailxml_defs:PalletPositionCount	<b>mailxml_base:n02</b>	
	mailxml_defs:IncludesElectronicLoa d	<b>mailxml_base:yesNo</b>	

#### element **deliveryApptUpdateAcceptType/DestinationEntry**


diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

#### element **deliveryApptUpdateAcceptType/RecurringAppt**


diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_tm:recurringApptType</b>

properties	isRef 0 content complex
children	<a href="#">mailxml_tm:EffectiveStartDate</a> <a href="#">mailxml_tm:EffectiveEndDate</a> <a href="#">mailxml_tm:ApptTime</a> <a href="#">mailxml_tm:DayFrequency</a> <a href="#">mailxml_tm:WeekFrequency</a>

#### element deliveryApptUpdateAcceptType/OneTimeAppt

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:oneTimeApptType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:PreferredAppt</a> <a href="#">mailxml_tm:OptionalAppt</a>

#### element deliveryApptUpdateAcceptType/DetailInfo

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:detailInfoType</a>
properties	isRef 0 minOcc 1 maxOcc unbounded content complex
children	<a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:USPSSummary</a> <a href="#">mailxml_tm:ConsigneeContentID</a>

element **deliveryApptUpdateAcceptType/TrailerInfo**

diagram	<pre> classDiagram     class mailxml_tm::trailerInfoType {         mailxml_tm::Trailer         mailxml_tm::Carrier         mailxml_tm::BillOfLadingNumber     }     mailxml_tm::TrailerInfo &lt; -- trailerInfoType     mailxml_tm::Trailer &lt; -- trailerInfoType     mailxml_tm::Carrier &lt; -- trailerInfoType     mailxml_tm::BillOfLadingNumber &lt; -- trailerInfoType     mailxml_tm::Trailer "0..2"     mailxml_tm::BillOfLadingNumber "1..2"   </pre>								
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>								
type	<a href="#">mailxml_tm:trailerInfoType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#">mailxml_tm:Trailer</a> <a href="#">mailxml_tm:Carrier</a> <a href="#">mailxml_tm:BillOfLadingNumber</a>								


element **deliveryApptUpdateAcceptType/ConsigneeFacility**

diagram	<pre> classDiagram     class mailxml_tm::ConsigneeFacility     class mailxml_defs::CompanyName     class mailxml_defs::FacilityNumber     class mailxml_defs::FacilityAddress     class mailxml_defs::FacilityName     class mailxml_defs::FacilityType     class mailxml_defs::URL     class mailxml_defs::CommonContact      mailxml_tm::ConsigneeFacility &lt; -- consigneeFacilityType     mailxml_tm::ConsigneeFacility --&gt; mailxml_defs::CompanyName     mailxml_tm::ConsigneeFacility --&gt; mailxml_defs::FacilityAddress     mailxml_tm::ConsigneeFacility --&gt; mailxml_defs::FacilityName     mailxml_tm::ConsigneeFacility --&gt; mailxml_defs::FacilityType     mailxml_tm::ConsigneeFacility --&gt; mailxml_defs::URL     mailxml_tm::ConsigneeFacility --&gt; mailxml_defs::CommonContact     mailxml_tm::ConsigneeFacility "0..1"     mailxml_defs::CommonContact "0..∞"   </pre>				
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>				
type	<a href="#">mailxml_defs:consigneeFacilityType</a>				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex
isRef	0				
content	complex				
children	<a href="#">mailxml_defs:CompanyName</a> <a href="#">mailxml_defs:FacilityNumber</a> <a href="#">mailxml_defs:FacilityAddress</a> <a href="#">mailxml_defs:FacilityName</a> <a href="#">mailxml_defs:FacilityType</a> <a href="#">mailxml_defs:URL</a> <a href="#">mailxml_defs:CommonContact</a>				

**element deliveryApptUpdateAcceptType/Comment**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s256</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>256</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	256		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	256												
whiteSpace	preserve												

**element deliveryApptUpdateAcceptType/ReturnInfo**

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>mailxml_defs:returnInfoType</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<b>mailxml_defs:ConsigneeFacility</b> <b>mailxml_defs:ErrorWarning</b> <b>mailxml_defs:ContainerErrorWarningBlock</b>								

**complexType deliveryApptUpdateRejectType**

diagram	<pre> classDiagram     class deliveryApptUpdateRejectType {         &lt;&lt;grp mailxml_defs:RequestMs...&gt;&gt;             mailxml_defs:ShipperApptRequ...             mailxml_defs:ConsigneeApptID             mailxml_defs:SchedulerID             mailxml_defs:SchedulerCorpID             mailxml_defs:SchedulerCRID             mailxml_defs:ShipperMultiStopID             mailxml_defs:ConsigneeMultiSt...             mailxml_defs:ShipperStopNumb...             mailxml_defs:ApptType             mailxml_defs:PickupOrDelivery             mailxml_defs:PalletPositionCount             mailxml_defs:IncludesElectroni...         &lt;&lt;mailxml_tm:ReturnInfo&gt;&gt;     } </pre>																																																																														
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																																														
children	<a href="#">mailxml_tm:ReturnInfo</a>																																																																														
used by	element <a href="#">DeliveryApptUpdateResponse/DeliveryApptUpdateReject</a>																																																																														
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:ShipperApptRequestID</td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ConsigneeApptID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerCorpID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerCRID</td> <td><a href="#">mailxml_base:CRIDType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ShipperMultiStopID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ConsigneeMultiStopID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ShipperStopNumber</td> <td><a href="#">mailxml_base:n06</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ApptType</td> <td><a href="#">mailxml_base:apptTypeType</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:PickupOrDelivery</td> <td><a href="#">mailxml_base:pickupOrDeliveryType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:PalletPositionCount</td> <td><a href="#">mailxml_base:n02</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:IncludesElectronicLoad</td> <td><a href="#">mailxml_base:yesNo</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required				mailxml_defs:ConsigneeApptID	<a href="#">mailxml_base:s12</a>					mailxml_defs:SchedulerID	<a href="#">mailxml_base:s12</a>					mailxml_defs:SchedulerCorpID	<a href="#">mailxml_base:s12</a>					mailxml_defs:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>					mailxml_defs:ShipperMultiStopID	<a href="#">mailxml_base:s12</a>					mailxml_defs:ConsigneeMultiStopID	<a href="#">mailxml_base:s12</a>					mailxml_defs:ShipperStopNumber	<a href="#">mailxml_base:n06</a>					mailxml_defs:ApptType	<a href="#">mailxml_base:apptTypeType</a>	required				mailxml_defs:PickupOrDelivery	<a href="#">mailxml_base:pickupOrDeliveryType</a>					mailxml_defs:PalletPositionCount	<a href="#">mailxml_base:n02</a>					mailxml_defs:IncludesElectronicLoad	<a href="#">mailxml_base:yesNo</a>				
Name	Type	Use	Default	Fixed	annotation																																																																										
mailxml_defs:ShipperApptRequestID	<a href="#">mailxml_base:s12</a>	required																																																																													
mailxml_defs:ConsigneeApptID	<a href="#">mailxml_base:s12</a>																																																																														
mailxml_defs:SchedulerID	<a href="#">mailxml_base:s12</a>																																																																														
mailxml_defs:SchedulerCorpID	<a href="#">mailxml_base:s12</a>																																																																														
mailxml_defs:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>																																																																														
mailxml_defs:ShipperMultiStopID	<a href="#">mailxml_base:s12</a>																																																																														
mailxml_defs:ConsigneeMultiStopID	<a href="#">mailxml_base:s12</a>																																																																														
mailxml_defs:ShipperStopNumber	<a href="#">mailxml_base:n06</a>																																																																														
mailxml_defs:ApptType	<a href="#">mailxml_base:apptTypeType</a>	required																																																																													
mailxml_defs:PickupOrDelivery	<a href="#">mailxml_base:pickupOrDeliveryType</a>																																																																														
mailxml_defs:PalletPositionCount	<a href="#">mailxml_base:n02</a>																																																																														
mailxml_defs:IncludesElectronicLoad	<a href="#">mailxml_base:yesNo</a>																																																																														

element **deliveryApptUpdateRejectType/ReturnInfo**

diagram	<pre> classDiagram     class mailxml_tm::ReturnInfo     class mailxml_tm::ConsigneeFacility     class mailxml_tm::ErrorWarning     class mailxml_tm::ContainerErrorWarningBlock     class mailxml_defs::returnInfoType      mailxml_tm::ReturnInfo --&gt; mailxml_defs::returnInfoType     mailxml_tm::returnInfoType &lt; -- mailxml_tm::ConsigneeFacility     mailxml_tm::returnInfoType &lt; -- mailxml_tm::ErrorWarning     mailxml_tm::returnInfoType &lt; -- mailxml_tm::ContainerErrorWarningBlock   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_defs:returnInfoType</b>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:ErrorWarning</a> <a href="#">mailxml_tm:ContainerErrorWarningBlock</a>

complexType **deliveryContentAcceptType**

diagram	<pre> classDiagram     class deliveryContentAcceptType     class mailxml_tm::DeliveryContentAcceptType     class mailxml_tm::ConsigneeApptID     class mailxml_tm::SchedulerID     class mailxml_tm::SchedulerCorpID     class mailxml_tm::SchedulerCRID     class mailxml_tm::ConsigneeFacility     class mailxml_tm::DestinationEntry     class mailxml_tm::ContentDetailInfo     class mailxml_tm::ReturnInfo      deliveryContentAcceptType --&gt; mailxml_tm::DeliveryContentAcceptType     mailxml_tm::DeliveryContentAcceptType &lt; -- mailxml_tm::ConsigneeApptID     mailxml_tm::DeliveryContentAcceptType &lt; -- mailxml_tm::SchedulerID     mailxml_tm::DeliveryContentAcceptType &lt; -- mailxml_tm::SchedulerCorpID     mailxml_tm::DeliveryContentAcceptType &lt; -- mailxml_tm::SchedulerCRID     mailxml_tm::DeliveryContentAcceptType &lt; -- mailxml_tm::ConsigneeFacility     mailxml_tm::DeliveryContentAcceptType &lt; -- mailxml_tm::DestinationEntry     mailxml_tm::DeliveryContentAcceptType &lt; -- mailxml_tm::ContentDetailInfo     mailxml_tm::DeliveryContentAcceptType --&gt; mailxml_tm::ReturnInfo   </pre>																		
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																		
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ContentDetailInfo</a> <a href="#">mailxml_tm:ReturnInfo</a>																		
used by	element <a href="#">DeliveryContentCreateResponse/DeliveryContentAccept</a>																		
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:ConsigneeApptID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>				
Name	Type	Use	Default	Fixed	annotation														
mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>																		
mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>																		

	mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>
	mailxml_tm:SchedulerCRID	<b>mailxml_base:CRIDType</b>

### element **deliveryContentAcceptType/ConsigneeFacility**

diagram	<pre> classDiagram     class mailxml_tm_ConsigneeFacility {         &lt;&lt;mailxml_tm&gt;&gt;     }     class mailxml_defs_ConsigneeFacilityType {         &lt;&lt;mailxml_defs&gt;&gt;         &lt;&lt;mailxml_tm&gt;&gt;         isRef 0         minOcc 0         maxOcc 1         content complex         CompanyName         FacilityNumber         FacilityAddress "0..∞"         FacilityName         FacilityType         URL         CommonContact     }     mailxml_tm_ConsigneeFacility --&gt; mailxml_defs_ConsigneeFacilityType   </pre>								
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>								
type	<b>mailxml_defs:consigneeFacilityType</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<b>mailxml_defs:CompanyName</b> <b>mailxml_defs:FacilityNumber</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityName</b> <b>mailxml_defs:FacilityType</b> <b>mailxml_defs:URL</b> <b>mailxml_defs:CommonContact</b>								


### element **deliveryContentAcceptType/DestinationEntry**

diagram	<pre> classDiagram     class mailxml_tm_DestinationEntry {         &lt;&lt;mailxml_tm&gt;&gt;     }     class mailxml_base_yesNo {         &lt;&lt;mailxml_base&gt;&gt;         isRef 0         content simple     }     mailxml_tm_DestinationEntry --&gt; mailxml_base_yesNo   </pre>									
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>									
type	<b>mailxml_base:yesNo</b>									
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	content	simple					
isRef	0									
content	simple									
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>enumeration</td><td>Yes</td><td></td></tr> <tr> <td>enumeration</td><td>No</td><td></td></tr> </table>	Kind	Value	annotation	enumeration	Yes		enumeration	No	
Kind	Value	annotation								
enumeration	Yes									
enumeration	No									


element **deliveryContentAcceptType/ContentDetailInfo**

diagram	<pre> classDiagram     class mailxml_tm:contentDetailInfoType {         mailxml_tm:LogisticsSchedulerID         mailxml_tm:LogisticsCorpID         mailxml_tm:LogisticsSchedulerCRID     }     class mailxml_tm:ContentDetailInfo     class mailxml_tm:DestinationEntry {         mailxml_tm:ShipperContainerGroupingID         mailxml_tm:ConsigneeContainerGroupingID         mailxml_tm:ShipperGroupingIDDescription         mailxml_tm:ScheduledInductionDate         mailxml_tm:NumberOfDaysStale     }     class mailxml_tm:MaildatSummary     class mailxml_tm:ContentUSPSSummary      mailxml_tm:ContentDetailInfo "1..∞" -- "1..∞" mailxml_tm:DestinationEntry     mailxml_tm:DestinationEntry "1..∞" -- "1..∞" mailxml_tm:MaildatSummary     mailxml_tm:DestinationEntry "1..∞" -- "1..∞" mailxml_tm:ContentUSPSSummary   </pre>																								
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																								
type	<a href="#">mailxml_tm:contentDetailInfoType</a>																								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>1</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	1	maxOcc	unbounded	content	complex																
isRef	0																								
minOcc	1																								
maxOcc	unbounded																								
content	complex																								
children	<a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:ScheduledInductionDate</a> <a href="#">mailxml_tm:NumberOfDaysStale</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:ContentUSPSSummary</a>																								
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><a href="#">mailxml_tm:LogisticsSchedulerID</a></td><td><a href="#">mailxml_base:s12</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td><a href="#">mailxml_tm:LogisticsCorpID</a></td><td><a href="#">mailxml_base:s12</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td><a href="#">mailxml_tm:LogisticsSchedulerCRID</a></td><td><a href="#">mailxml_base:CRIDType</a></td><td></td><td></td><td></td><td></td></tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:LogisticsSchedulerID</a>	<a href="#">mailxml_base:s12</a>					<a href="#">mailxml_tm:LogisticsCorpID</a>	<a href="#">mailxml_base:s12</a>					<a href="#">mailxml_tm:LogisticsSchedulerCRID</a>	<a href="#">mailxml_base:CRIDType</a>				
Name	Type	Use	Default	Fixed	annotation																				
<a href="#">mailxml_tm:LogisticsSchedulerID</a>	<a href="#">mailxml_base:s12</a>																								
<a href="#">mailxml_tm:LogisticsCorpID</a>	<a href="#">mailxml_base:s12</a>																								
<a href="#">mailxml_tm:LogisticsSchedulerCRID</a>	<a href="#">mailxml_base:CRIDType</a>																								

element **deliveryContentAcceptType/ReturnInfo**

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>mailxml_defs:returnInfoType</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<b>mailxml_defs:ConsigneeFacility</b> <b>mailxml_defs:ErrorWarning</b> <b>mailxml_defs:ContainerErrorWarningBlock</b>								

complexType **deliveryContentCancelRequestType**

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
children	<b>mailxml_tm:SubmittingParty</b> <b>mailxml_tm:SubmittingSoftware</b> <b>mailxml_tm:SubmitterTrackingID</b> <b>mailxml_tm:DestinationEntry</b> <b>mailxml_tm:ContentCancel</b>								
used by	element <a href="#">DeliveryContentCancelRequest</a>								
attributes	<table> <tr> <td>Name</td><td>mailxml_tm:SchedulerID</td> <td>Type</td><td><b>mailxml_base:s12</b></td> <td>Use</td><td>Default</td> <td>Fixed</td> <td>annotation</td> </tr> </table>	Name	mailxml_tm:SchedulerID	Type	<b>mailxml_base:s12</b>	Use	Default	Fixed	annotation
Name	mailxml_tm:SchedulerID	Type	<b>mailxml_base:s12</b>	Use	Default	Fixed	annotation		

	mailxml_tm:SchedulerCorpID	<b>mailxml_base:s12</b>
	mailxml_tm:SchedulerCRID	<b>mailxml_base:CRIDType</b>

element **deliveryContentCancelRequestType/SubmittingParty**

diagram	<pre> classDiagram     class mailxml_tmSubmittingParty     class mailxml_defsParticipantIDType {         &lt;&lt;attributes&gt;&gt;         mailxml_defsMailerID6         mailxml_defsMailerID9         mailxml_defsCRID         mailxml_defsSchedulerID         mailxml_defsMaildatUserLicense         mailxml_defsShippingAgentID         mailxml_defsReceivingAgentID     }     mailxml_tmSubmittingParty "1" -- "1" mailxml_defsParticipantIDType   </pre>																																																
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td><td>0</td> </tr> <tr> <td>content</td><td>complex</td> </tr> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:MailerID6</td> <td><b>mailxml_base:mailerID6Type</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MailerID9</td> <td><b>mailxml_base:mailerID9Type</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:CRID</td> <td><b>mailxml_base:CRIDType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MaildatUserLicense</td> <td><b>mailxml_base:userLicenseCodeType</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ShippingAgentID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ReceivingAgentID</td> <td><b>mailxml_base:s12</b></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

### element **deliveryContentCancelRequestType/SubmittingSoftware**

diagram	<pre> classDiagram     mailxml_tm::SubmittingSoftware &lt; -- mailxml_defs::submittingSoftwareType     mailxml_defs::submittingSoftwareType {         SoftwareName : xs:string         Vendor : xs:string         Version : xs:string         ApprovalDate : xs:date         ApprovalKey : xs:string     }   </pre>																																				
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																																				
type	<b>mailxml_defs:submittingSoftwareType</b>																																				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																
isRef	0																																				
content	complex																																				
attributes	<table> <thead> <tr> <th>Name</th><th>Type</th><th>Use</th><th>Default</th><th>Fixed</th><th>annotation</th></tr> </thead> <tbody> <tr> <td>mailxml_defs:SoftwareName</td><td>xs:string</td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:Vendor</td><td>xs:string</td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:Version</td><td>xs:string</td><td>required</td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ApprovalDate</td><td>xs:date</td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ApprovalKey</td><td>xs:string</td><td></td><td></td><td></td><td></td></tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:SoftwareName	xs:string	required				mailxml_defs:Vendor	xs:string	required				mailxml_defs:Version	xs:string	required				mailxml_defs:ApprovalDate	xs:date					mailxml_defs:ApprovalKey	xs:string				
Name	Type	Use	Default	Fixed	annotation																																
mailxml_defs:SoftwareName	xs:string	required																																			
mailxml_defs:Vendor	xs:string	required																																			
mailxml_defs:Version	xs:string	required																																			
mailxml_defs:ApprovalDate	xs:date																																				
mailxml_defs:ApprovalKey	xs:string																																				

### element **deliveryContentCancelRequestType/SubmitterTrackingID**

diagram	<pre> classDiagram     mailxml_tm::SubmitterTrackingID   </pre>												
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <thead> <tr> <th>Kind</th><th>Value</th><th>annotation</th></tr> </thead> <tbody> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>20</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

### element **deliveryContentCancelRequestType/DestinationEntry**

diagram	<pre> classDiagram     mailxml_tm::DestinationEntry   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:yesNo</b>

properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

### element deliveryContentCancelRequestType/ContentCancel

diagram	<pre> classDiagram     class mailxml_tm::ContentCancel {         mailxml_tm::SchedulerContentID         mailxml_tm::ConsigneeContentID         mailxml_tm::ConsigneeApptID     }     class mailxml_tm::ReturnInfo     mailxml_tm::ContentCancel "1..∞" -- "1..∞" mailxml_tm::ReturnInfo   </pre>																								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																								
type	<a href="#">mailxml_tm:contentCancelType</a>																								
properties	isRef 0 minOcc 1 maxOcc unbounded content complex																								
children	<a href="#">mailxml_tm:ReturnInfo</a>																								
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><a href="#">mailxml_tm:SchedulerContentID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:ConsigneeContentID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:ConsigneeApptID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:SchedulerContentID</a>	<a href="#">mailxml_base:s12</a>	required				<a href="#">mailxml_tm:ConsigneeContentID</a>	<a href="#">mailxml_base:s12</a>	required				<a href="#">mailxml_tm:ConsigneeApptID</a>	<a href="#">mailxml_base:s12</a>				
Name	Type	Use	Default	Fixed	annotation																				
<a href="#">mailxml_tm:SchedulerContentID</a>	<a href="#">mailxml_base:s12</a>	required																							
<a href="#">mailxml_tm:ConsigneeContentID</a>	<a href="#">mailxml_base:s12</a>	required																							
<a href="#">mailxml_tm:ConsigneeApptID</a>	<a href="#">mailxml_base:s12</a>																								

### complexType deliveryContentCancelResponseType

diagram	<pre> sequenceDiagram     participant DCNR as deliveryContentCancelRespons...     participant T as mailxml_tm::TrackingID     participant ST as mailxml_tm::SubmitterTrackingID     participant DC as mailxml_tm::DeliveryContentCa...     participant DC as mailxml_tm::DeliveryContentCa...     DC-&gt;&gt;T:      activate T     T-&gt;&gt;DC:      deactivate T     activate DC     DC--&gt;&gt;DC:      deactivate DC   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
children	<a href="#">mailxml_tm:TrackingID</a> <a href="#">mailxml_tm:SubmitterTrackingID</a> <a href="#">mailxml_tm:DeliveryContentCancelAccept</a> <a href="#">mailxml_tm:DeliveryContentCancelReject</a>
used by	element <a href="#">DeliveryContentCancelResponse</a>


**element deliveryContentCancelResponseType/TrackingID**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>20</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

**element deliveryContentCancelResponseType/SubmitterTrackingID**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s20</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>20</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	20		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	20												
whiteSpace	preserve												

**element deliveryContentCancelResponseType/DeliveryContentCancelAccept**


diagram					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex
isRef	0				
content	complex				

children	<a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ContentCancel</a>					
attributes	Name <a href="#">mailxml_tm:SchedulerID</a>	Type <b>mailxml_base:s12</b>	Use	Default	Fixed	annotation
	<a href="#">mailxml_tm:SchedulerCorpID</a>	<b>mailxml_base:s12</b>				
	<a href="#">mailxml_tm:SchedulerCRID</a>	<b>mailxml_base:CRIDType</b>				

element **deliveryContentCancelResponseType/DeliveryContentCancelAccept/DestinationEntry**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

element **deliveryContentCancelResponseType/DeliveryContentCancelAccept/ContentCancel**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:contentCancelType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_tm:ReturnInfo</a>
attributes	Name <a href="#">mailxml_tm:SchedulerContentID</a> Type <b>mailxml_base:s12</b> Use required <a href="#">mailxml_tm:ConsigneeContentID</a> Type <b>mailxml_base:s12</b> Use required <a href="#">mailxml_tm:ConsigneeApptID</a> Type <b>mailxml_base:s12</b>

element **deliveryContentCancelResponseType/DeliveryContentCancelReject**

diagram	<pre> classDiagram     class mailxml_tm {         class DeliveryContentCancelResponseType {             class DeliveryContentCancelReject {                 attribute grp mailxml_tm:DeliveryConte...                 attribute mailxml_tm:SchedulerID                 attribute mailxml_tm:SchedulerCorpID                 attribute mailxml_tm:SchedulerCRID                 child mailxml_tm:DestinationEntry                 child mailxml_tm:ContentCancel                 child mailxml_tm:ReturnInfo             }         }     }   </pre>																								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																								
properties	<table> <tr> <td>isRef</td><td>0</td> </tr> <tr> <td>content</td><td>complex</td> </tr> </table>	isRef	0	content	complex																				
isRef	0																								
content	complex																								
children	<a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ContentCancel</a> <a href="#">mailxml_tm:ReturnInfo</a>																								
attributes	<table> <tr> <th>Name</th><th>Type</th><th>Use</th><th>Default</th><th>Fixed</th><th>annotation</th></tr> <tr> <td>mailxml_tm:SchedulerID</td><td><a href="#">mailxml_base:s12</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:SchedulerCorpID</td><td><a href="#">mailxml_base:s12</a></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_tm:SchedulerCRID</td><td><a href="#">mailxml_base:CRIDType</a></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>				
Name	Type	Use	Default	Fixed	annotation																				
mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>																								
mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>																								
mailxml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>																								

element **deliveryContentCancelResponseType/DeliveryContentCancelReject/DestinationEntry**

diagram	<pre> classDiagram     class mailxml_tm {         class DestinationEntry     }   </pre>									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm									
type	<a href="#">mailxml_base:yesNo</a>									
properties	<table> <tr> <td>isRef</td><td>0</td> </tr> <tr> <td>content</td><td>simple</td> </tr> </table>	isRef	0	content	simple					
isRef	0									
content	simple									
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>enumeration</td><td>Yes</td><td></td></tr> <tr> <td>enumeration</td><td>No</td><td></td></tr> </table>	Kind	Value	annotation	enumeration	Yes		enumeration	No	
Kind	Value	annotation								
enumeration	Yes									
enumeration	No									

element **deliveryContentCancelResponseType/DeliveryContentCancelReject/ContentCancel**

diagram	<pre> classDiagram     class mailxml_tm::ContentCancel     class mailxml_tm::ReturnInfo     mailxml_tm::ContentCancel "0..1" -- "1..1" mailxml_tm::ReturnInfo     mailxml_tm::ContentCancel &lt; -- mailxml_tm::contentCancelType     mailxml_tm::contentCancelType &lt; -- attributes     attributes &amp;gt; mailxml_tm::SchedulerContentID     attributes &amp;gt; mailxml_tm::ConsigneeContentID     attributes &amp;gt; mailxml_tm::ConsigneeApptID   </pre>																								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																								
type	<a href="#">mailxml_tm:contentCancelType</a>																								
properties	isRef 0 content complex																								
children	<a href="#">mailxml_tm:ReturnInfo</a>																								
attributes	<table> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> <tr> <td><a href="#">mailxml_tm:SchedulerContentID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:ConsigneeContentID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:ConsigneeApptID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:SchedulerContentID</a>	<a href="#">mailxml_base:s12</a>	required				<a href="#">mailxml_tm:ConsigneeContentID</a>	<a href="#">mailxml_base:s12</a>	required				<a href="#">mailxml_tm:ConsigneeApptID</a>	<a href="#">mailxml_base:s12</a>				
Name	Type	Use	Default	Fixed	annotation																				
<a href="#">mailxml_tm:SchedulerContentID</a>	<a href="#">mailxml_base:s12</a>	required																							
<a href="#">mailxml_tm:ConsigneeContentID</a>	<a href="#">mailxml_base:s12</a>	required																							
<a href="#">mailxml_tm:ConsigneeApptID</a>	<a href="#">mailxml_base:s12</a>																								

element **deliveryContentCancelResponseType/DeliveryContentCancelReject/ReturnInfo**

diagram	<pre> classDiagram     class mailxml_tm::ReturnInfo     class mailxml_defs::ConsigneeFacility     class mailxml_defs::ErrorWarning     class mailxml_defs::ContainerErrorW...     mailxml_tm::ReturnInfo "0..1" -- "0..1" mailxml_defs::ConsigneeFacility     mailxml_tm::ReturnInfo "0..1..infinity" -- "0..infinity" mailxml_defs::ErrorWarning     mailxml_tm::ReturnInfo "0..1..infinity" -- "0..infinity" mailxml_defs::ContainerErrorW...     mailxml_tm::ReturnInfo &lt; -- mailxml_defs::returnInfoType   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_defs:returnInfoType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_defs:ConsigneeFacility</a> <a href="#">mailxml_defs:ErrorWarning</a> <a href="#">mailxml_defs:ContainerErrorWarningBlock</a>

**complexType deliveryContentRejectType**

diagram	<pre> classDiagram     class deliveryContentRejectType     class grp {         mailxml_tm:DeliveryConte...         mailxml_tm:ConsigneeApptID         mailxml_tm:SchedulerID         mailxml_tm:SchedulerCorpID         mailxml_tm:SchedulerCRID     }     class mailxml_tm:DestinationEntry     class mailxml_tm:ReturnInfo      deliveryContentRejectType "2" --&gt; grp     grp "2" --&gt; mailxml_tm:DestinationEntry     grp "2" --&gt; mailxml_tm:ReturnInfo   </pre>																														
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																														
children	<a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ReturnInfo</a>																														
used by	element <a href="#">DeliveryContentCreateResponse/DeliveryContentReject</a>																														
attributes	<table> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> <tr> <td>mailxml_tm:ConsigneeApptID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCorpID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCRID</td> <td><a href="#">mailxml_base:CRIDType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>				
Name	Type	Use	Default	Fixed	annotation																										
mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>																														
mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>																														
mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>																														
mailxml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>																														

**element deliveryContentRejectType/DestinationEntry**

diagram	<pre> classDiagram     class mailxml_tm:DestinationEntry   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_base:yesNo</a>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

element **deliveryContentRejectType/ReturnInfo**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_defs:returnInfoType</b>
properties	isRef 0 content complex
children	<b>mailxml_defs:ConsigneeFacility</b> <b>mailxml_defs:ErrorWarning</b> <b>mailxml_defs:ContainerErrorWarningBlock</b>

complexType **deliveryContentUpdateAcceptType**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
children	<b>mailxml_tm:ConsigneeFacility</b> <b>mailxml_tm:DestinationEntry</b> <b>mailxml_tm:ContentDetailInfoUpdate</b> <b>mailxml_tm:ReturnInfo</b>
used by	element <a href="#">DeliveryContentUpdateResponse/DeliveryContentUpdateAccept</a>
attributes	Name Type Use Default Fixed annotation

	mailxml_tm:ConsigneeApptID	mailxml_base:s12	
	mailxml_tm:SchedulerID	mailxml_base:s12	
	mailxml_tm:SchedulerCorpID	mailxml_base:s12	
	mailxml_tm:SchedulerCRID	mailxml_base:CRIDType	
	mailxml_tm:FullContentReplacement	mailxml_base:yesNo	No

#### element deliveryContentUpdateAcceptType/ConsigneeFacility

diagram	<pre> classDiagram     class mailxml_tm_ConsigneeFacility     class mailxml_defs_ConsigneeFacilityType {         CompanyName         FacilityNumber         FacilityAddress "0..infinity"         FacilityName         FacilityType         URL         CommonContact     }     mailxml_tm_ConsigneeFacility --&gt; mailxml_defs_ConsigneeFacilityType   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_defs:consigneeFacilityType</b>
properties	isRef 0 minOcc 0 maxOcc 1 content complex
children	<b>mailxml_defs:CompanyName</b> <b>mailxml_defs:FacilityNumber</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityName</b> <b>mailxml_defs:FacilityType</b> <b>mailxml_defs:URL</b> <b>mailxml_defs:CommonContact</b>

#### element deliveryContentUpdateAcceptType/DestinationEntry

diagram	<pre> classDiagram     class mailxml_tm_DestinationEntry   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

element **deliveryContentUpdateAcceptType/ContentDetailInfoUpdate**

diagram	<pre> classDiagram     class mailxml_tm::contentDetailInfoUpdateType {         &lt;&lt;attributes&gt;&gt;         mailxml_tm::LogisticsSchedulerID         mailxml_tm::LogisticsCorpID         mailxml_tm::LogisticsSchedulerCRID     }     class mailxml_tm::ContentDetailInfoUpdate {         &lt;&lt;multiplicity&gt;&gt; 1..∞     }     class mailxml_tm::ShipperContainerGroupingID     class mailxml_tm::ConsigneeContainerGroupingID     class mailxml_tm::ShipperGroupingIDDescription     class mailxml_tm::ScheduledInductionDate     class mailxml_tm::MaildatSummary {         &lt;&lt;multiplicity&gt;&gt; 1..∞     }     class mailxml_tm::ContentUSPSSummary      mailxml_tm::contentDetailInfoUpdateType "1..∞" --&gt; mailxml_tm::ContentDetailInfoUpdate     mailxml_tm::ContentDetailInfoUpdate "*" --&gt; mailxml_tm::ShipperContainerGroupingID     mailxml_tm::ContentDetailInfoUpdate "*" --&gt; mailxml_tm::ConsigneeContainerGroupingID     mailxml_tm::ContentDetailInfoUpdate "*" --&gt; mailxml_tm::ShipperGroupingIDDescription     mailxml_tm::ContentDetailInfoUpdate "*" --&gt; mailxml_tm::ScheduledInductionDate     mailxml_tm::ContentDetailInfoUpdate "*" --&gt; mailxml_tm::MaildatSummary     mailxml_tm::ContentDetailInfoUpdate "*" --&gt; mailxml_tm::ContentUSPSSummary   </pre>																								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																								
type	<a href="#"><u>mailxml_tm:contentDetailInfoUpdateType</u></a>																								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>1</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	1	maxOcc	unbounded	content	complex																
isRef	0																								
minOcc	1																								
maxOcc	unbounded																								
content	complex																								
children	<a href="#"><u>mailxml_tm:ShipperContainerGroupingID</u></a> <a href="#"><u>mailxml_tm:ConsigneeContainerGroupingID</u></a> <a href="#"><u>mailxml_tm:ShipperGroupingIDDescription</u></a> <a href="#"><u>mailxml_tm:ScheduledInductionDate</u></a> <a href="#"><u>mailxml_tm:MaildatSummary</u></a> <a href="#"><u>mailxml_tm:ContentUSPSSummary</u></a>																								
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><a href="#"><u>mailxml_tm:LogisticsSchedulerID</u></a></td><td><a href="#"><u>mailxml_base:s12</u></a></td><td></td><td></td><td></td><td></td></tr> <tr> <td><a href="#"><u>mailxml_tm:LogisticsCorpID</u></a></td><td><a href="#"><u>mailxml_base:s12</u></a></td><td></td><td></td><td></td><td></td></tr> <tr> <td><a href="#"><u>mailxml_tm:LogisticsSchedulerCRID</u></a></td><td><a href="#"><u>mailxml_base:CRIDType</u></a></td><td></td><td></td><td></td><td></td></tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#"><u>mailxml_tm:LogisticsSchedulerID</u></a>	<a href="#"><u>mailxml_base:s12</u></a>					<a href="#"><u>mailxml_tm:LogisticsCorpID</u></a>	<a href="#"><u>mailxml_base:s12</u></a>					<a href="#"><u>mailxml_tm:LogisticsSchedulerCRID</u></a>	<a href="#"><u>mailxml_base:CRIDType</u></a>				
Name	Type	Use	Default	Fixed	annotation																				
<a href="#"><u>mailxml_tm:LogisticsSchedulerID</u></a>	<a href="#"><u>mailxml_base:s12</u></a>																								
<a href="#"><u>mailxml_tm:LogisticsCorpID</u></a>	<a href="#"><u>mailxml_base:s12</u></a>																								
<a href="#"><u>mailxml_tm:LogisticsSchedulerCRID</u></a>	<a href="#"><u>mailxml_base:CRIDType</u></a>																								

**element deliveryContentUpdateAcceptType/ReturnInfo**

diagram	<pre> classDiagram     class mailxml_tm::ReturnInfo     class mailxml_defs::returnInfoType {         mailxml_tm::ConsigneeFacility         mailxml_tm::ErrorWarning         mailxml_tm::ContainerErrorW...     }     mailxml_tm::ReturnInfo --&gt; returnInfoType   </pre>								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>mailxml_defs:returnInfoType</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<b>mailxml_tm:ConsigneeFacility</b> <b>mailxml_tm:ErrorWarning</b> <b>mailxml_tm:ContainerErrorWarningBlock</b>								

**complexType deliveryContentUpdatedType**

diagram	<pre> classDiagram     class deliveryContentUpdatedType     class grp {         mailxml_tm::ConsigneeApptID         mailxml_tm::SchedulerID         mailxml_tm::SchedulerCorpID         mailxml_tm::SchedulerCRID         mailxml_tm::FullContentReplace...     }     class mailxml_tm::ConsigneeFacility     class mailxml_tm::DestinationEntry     class mailxml_tm::ContentDetailInfoUpdate {         mailxml_tm::ContentCancelled         mailxml_tm::ContentCancelInfo     }     class mailxml_tm::ReturnInfo     deliveryContentUpdatedType --&gt; grp     deliveryContentUpdatedType --&gt; ConsigneeFacility     deliveryContentUpdatedType --&gt; DestinationEntry     deliveryContentUpdatedType --&gt; ContentDetailInfoUpdate     ContentDetailInfoUpdate --&gt; ContentCancelled     ContentDetailInfoUpdate --&gt; ContentCancelInfo     ContentDetailInfoUpdate --&gt; ReturnInfo   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
children	<b>mailxml_tm:ConsigneeFacility</b> <b>mailxml_tm:DestinationEntry</b> <b>mailxml_tm:ContentDetailInfoUpdate</b>

	<a href="#">mailxml_tm:ContentCancelled</a> <a href="#">mailxml_tm:ContentCancelInfo</a> <a href="#">mailxml_tm:ReturnInfo</a>					
used by	elements <a href="#">USPSDeliveryContentUpdatedDelivery/DeliveryContentUpdated</a> <a href="#">USPSDeliveryContentUpdatedQueryResponse/QueryResults/DeliveryContentUpdated</a>					
attributes	Name mailxml_tm:ConsigneeApptID mailxml_tm:SchedulerID mailxml_tm:SchedulerCorpID mailxml_tm:SchedulerCRID mailxml_tm:FullContentReplacement	Type <b>mailxml_base:s12</b> <b>mailxml_base:s12</b> <b>mailxml_base:s12</b> <b>mailxml_base:CRIDType</b> <b>mailxml_base:yesNo</b>	Use	Default	Fixed	annotation
					No	

### element **deliveryContentUpdatedType/ConsigneeFacility**

diagram	<pre> classDiagram     class mailxml_tm_ConsigneeFacility     class mailxml_defs_ConsigneeFacilityType {         mailxml_defs_CompanyName         mailxml_defs_FacilityNumber         mailxml_defs_FacilityAddress "0..infinity"         mailxml_defs_FacilityName         mailxml_defs_FacilityType         mailxml_defs_URL         mailxml_defs_CommonContact     }     mailxml_tm_ConsigneeFacility "..." --&gt; mailxml_defs_ConsigneeFacilityType   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_defs:consigneeFacilityType</b>
properties	isRef 0 minOcc 0 maxOcc 1 content complex
children	<b>mailxml_defs:CompanyName</b> <b>mailxml_defs:FacilityNumber</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityName</b> <b>mailxml_defs:FacilityType</b> <b>mailxml_defs:URL</b> <b>mailxml_defs:CommonContact</b>

### element **deliveryContentUpdatedType/DestinationEntry**

diagram	<b>mailxml_tm:DestinationEntry</b>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation

	enumeration Yes
	enumeration No

### element **deliveryContentUpdatedType/ContentDetailInfoUpdate**

diagram	<pre> classDiagram     class mailxml_tm:contentDetailInfoUpdateType {         mailxml_tm:LogisticsSchedulerID         mailxml_tm:LogisticsCorpID         mailxml_tm:LogisticsSchedulerCRID     }     mailxml_tm:ContentDetailInfoUpdate &lt; -- mailxml_tm:contentDetailInfoUpdateType     mailxml_tm:ContentDetailInfoUpdate "1..∞" --&gt; mailxml_tm:ShipperContainerGroupingID     mailxml_tm:ShipperContainerGroupingID *--&gt; mailxml_tm:ConsigneeContainerGroupingID     mailxml_tm:ConsigneeContainerGroupingID *--&gt; mailxml_tm:ShipperGroupingIDDescription     mailxml_tm:ShipperGroupingIDDescription *--&gt; mailxml_tm:ScheduledInductionDate     mailxml_tm:ScheduledInductionDate *--&gt; mailxml_tm:MaildatSummary     mailxml_tm:MaildatSummary *--&gt; mailxml_tm:ContentUSPSSummary   </pre>																								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																								
type	<a href="#">mailxml_tm:contentDetailInfoUpdateType</a>																								
properties	<table border="1"> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>1</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	1	maxOcc	unbounded	content	complex																
isRef	0																								
minOcc	1																								
maxOcc	unbounded																								
content	complex																								
children	<a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:ScheduledInductionDate</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:ContentUSPSSummary</a>																								
attributes	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><a href="#">mailxml_tm:LogisticsSchedulerID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:LogisticsCorpID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:LogisticsSchedulerCRID</a></td> <td><a href="#">mailxml_base:CRIDType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:LogisticsSchedulerID</a>	<a href="#">mailxml_base:s12</a>					<a href="#">mailxml_tm:LogisticsCorpID</a>	<a href="#">mailxml_base:s12</a>					<a href="#">mailxml_tm:LogisticsSchedulerCRID</a>	<a href="#">mailxml_base:CRIDType</a>				
Name	Type	Use	Default	Fixed	annotation																				
<a href="#">mailxml_tm:LogisticsSchedulerID</a>	<a href="#">mailxml_base:s12</a>																								
<a href="#">mailxml_tm:LogisticsCorpID</a>	<a href="#">mailxml_base:s12</a>																								
<a href="#">mailxml_tm:LogisticsSchedulerCRID</a>	<a href="#">mailxml_base:CRIDType</a>																								

### element **deliveryContentUpdatedType/ContentCancelled**

diagram	<pre> classDiagram     class mailxml_tm:ContentCancelled {         *--&gt; mailxml_tm:ContentCancelled     }   </pre>				
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm				
type	<a href="#">mailxml_base:yesNo</a>				
properties	<table border="1"> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	content	simple
isRef	0				
content	simple				
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> </table>	Kind	Value	annotation	
Kind	Value	annotation			

	enumeration Yes
	enumeration No

element **deliveryContentUpdatedType/ContentCancelInfo**

diagram	<pre> classDiagram     class mailxml_tm:ContentCancelInfo     class mailxml_tm:ReturnInfo     mailxml_tm:ContentCancelInfo "3..&gt;" mailxml_tm:ReturnInfo     mailxml_tm:ContentCancelInfo &lt; -- mailxml_tm:contentCancelType     mailxml_tm:contentCancelType &lt; -- mailxml_tm:SchedulerContentID     mailxml_tm:contentCancelType &lt; -- mailxml_tm:ConsigneeContentID     mailxml_tm:contentCancelType &lt; -- mailxml_tm:ConsigneeApptID   </pre>																								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																								
type	<a href="#">mailxml_tm:contentCancelType</a>																								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																				
isRef	0																								
content	complex																								
children	<a href="#">mailxml_tm:ReturnInfo</a>																								
attributes	<table> <thead> <tr> <th>Name</th><th>Type</th><th>Use</th><th>Default</th><th>Fixed</th><th>annotation</th></tr> </thead> <tbody> <tr> <td><a href="#">mailxml_tm:SchedulerContentID</a></td><td><a href="#">mailxml_base:s12</a></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td><a href="#">mailxml_tm:ConsigneeContentID</a></td><td><a href="#">mailxml_base:s12</a></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td><a href="#">mailxml_tm:ConsigneeApptID</a></td><td><a href="#">mailxml_base:s12</a></td><td></td><td></td><td></td><td></td></tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:SchedulerContentID</a>	<a href="#">mailxml_base:s12</a>	required				<a href="#">mailxml_tm:ConsigneeContentID</a>	<a href="#">mailxml_base:s12</a>	required				<a href="#">mailxml_tm:ConsigneeApptID</a>	<a href="#">mailxml_base:s12</a>				
Name	Type	Use	Default	Fixed	annotation																				
<a href="#">mailxml_tm:SchedulerContentID</a>	<a href="#">mailxml_base:s12</a>	required																							
<a href="#">mailxml_tm:ConsigneeContentID</a>	<a href="#">mailxml_base:s12</a>	required																							
<a href="#">mailxml_tm:ConsigneeApptID</a>	<a href="#">mailxml_base:s12</a>																								

element **deliveryContentUpdatedType/ReturnInfo**

diagram	<pre> classDiagram     class mailxml_tm:ReturnInfo     class mailxml_defs:ConsigneeFacility     class mailxml_defs:ErrorWarning     class mailxml_defs:ContainerErrorW...     mailxml_tm:ReturnInfo "0..1" --&gt; mailxml_defs:ConsigneeFacility     mailxml_tm:ReturnInfo "0..1" --&gt; mailxml_defs:ErrorWarning     mailxml_tm:ReturnInfo "0..1" --&gt; mailxml_defs:ContainerErrorW...   </pre>								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_defs:returnInfoType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#">mailxml_defs:ConsigneeFacility</a> <a href="#">mailxml_defs:ErrorWarning</a> <a href="#">mailxml_defs:ContainerErrorWarningBlock</a>								

### complexType deliveryContentUpdateRejectType

diagram	<pre> classDiagram     class deliveryContentUpdateRejectTy...         grp mailxml_tm:DeliveryConte...             mailxml_tm:ConsigneeApptID             mailxml_tm:SchedulerID             mailxml_tm:SchedulerCorpID             mailxml_tm:SchedulerCRID             mailxml_tm:FullContentReplace...         end         mailxml_tm:DestinationEntry         mailxml_tm:ReturnInfo     end </pre>																																				
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																				
children	<a href="#">mailxml_tm:DestinationEntry</a> <a href="#">mailxml_tm:ReturnInfo</a>																																				
used by	element <a href="#">DeliveryContentUpdateResponse/DeliveryContentUpdateReject</a>																																				
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:ConsigneeApptID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCorpID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:SchedulerCRID</td> <td><a href="#">mailxml_base:CRIDType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:FullContentReplacement</td> <td><a href="#">mailxml_base:yesNo</a></td> <td></td> <td>No</td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>					mailxml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>					mailxml_tm:FullContentReplacement	<a href="#">mailxml_base:yesNo</a>		No		
Name	Type	Use	Default	Fixed	annotation																																
mailxml_tm:ConsigneeApptID	<a href="#">mailxml_base:s12</a>																																				
mailxml_tm:SchedulerID	<a href="#">mailxml_base:s12</a>																																				
mailxml_tm:SchedulerCorpID	<a href="#">mailxml_base:s12</a>																																				
mailxml_tm:SchedulerCRID	<a href="#">mailxml_base:CRIDType</a>																																				
mailxml_tm:FullContentReplacement	<a href="#">mailxml_base:yesNo</a>		No																																		

### element deliveryContentUpdateRejectType/DestinationEntry

diagram	<pre> classDiagram     class DestinationEntry </pre>									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm									
type	<a href="#">mailxml_base:yesNo</a>									
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	content	simple					
isRef	0									
content	simple									
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>enumeration</td> <td>Yes</td> <td></td> </tr> <tr> <td>enumeration</td> <td>No</td> <td></td> </tr> </table>	Kind	Value	annotation	enumeration	Yes		enumeration	No	
Kind	Value	annotation								
enumeration	Yes									
enumeration	No									

element **deliveryContentUpdateRejectType/ReturnInfo**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_defs:returnInfoType</b>
properties	isRef 0 content complex
children	<b>mailxml_defs:ConsigneeFacility mailxml_tm:ErrorWarning mailxml_tm:ContainerErrorWarningBlock</b>

complexType **deliverySummaryType**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
children	<b>mailxml_tm:ConsigneeFacility mailxml_tm:DestinationEntry mailxml_tm:ContentDetailInfo</b>
used by	element <a href="#">StaleContentDelivery/DeliverySummary</a>

### element deliverySummaryType/ConsigneeFacility

diagram	<pre> classDiagram     class mailxml_tm_ConsigneeFacility     class mailxml_defs_ConsigneeFacilityType {         CompanyName         FacilityNumber         FacilityAddress "0..∞"         FacilityName         FacilityType         URL         CommonContact     }     mailxml_tm_ConsigneeFacility "•" --&gt; mailxml_defs_ConsigneeFacilityType   </pre>								
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>								
type	<b>mailxml_defs:consigneeFacilityType</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<b>mailxml_defs:CompanyName</b> <b>mailxml_defs:FacilityNumber</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityName</b> <b>mailxml_defs:FacilityType</b> <b>mailxml_defs:URL</b> <b>mailxml_defs:CommonContact</b>								


### element deliverySummaryType/DestinationEntry

diagram	<pre> classDiagram     class mailxml_tm_DestinationEntry   </pre>									
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>									
type	<b>mailxml_base:yesNo</b>									
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	content	simple					
isRef	0									
content	simple									
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>enumeration</td><td>Yes</td><td></td></tr> <tr> <td>enumeration</td><td>No</td><td></td></tr> </table>	Kind	Value	annotation	enumeration	Yes		enumeration	No	
Kind	Value	annotation								
enumeration	Yes									
enumeration	No									


element **deliverySummaryType/ContentDetailInfo**

diagram	<pre> classDiagram     class mailxml_tm::contentDetailInfoType {         mailxml_tm::LogisticsSchedulerID         mailxml_tm::LogisticsCorpID         mailxml_tm::LogisticsSchedulerCRID     }     class mailxml_tm::ContentDetailInfo     class mailxml_tm::DestinationEntry     class mailxml_tm::ShipperContainerGr...     class mailxml_tm::ConsigneeContain...     class mailxml_tm::ShipperGroupingID...     class mailxml_tm::ScheduledInductio...     class mailxml_tm::NumberOfDaysStale     class mailxml_tm::MaildatSummary     class mailxml_tm::ContentUSPSSum...      mailxml_tm::ContentDetailInfo "0..∞" --&gt; mailxml_tm::contentDetailInfoType     mailxml_tm::contentDetailInfoType "1..∞" --&gt; mailxml_tm::MaildatSummary     mailxml_tm::contentDetailInfoType "1..∞" --&gt; mailxml_tm::ContentUSPSSum...   </pre>																								
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																								
type	<a href="#"><u>mailxml_tm:contentDetailInfoType</u></a>																								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	unbounded	content	complex																
isRef	0																								
minOcc	0																								
maxOcc	unbounded																								
content	complex																								
children	<a href="#"><u>mailxml_tm:DestinationEntry</u></a> <a href="#"><u>mailxml_tm:ShipperContainerGroupingID</u></a> <a href="#"><u>mailxml_tm:ConsigneeContainerGroupingID</u></a> <a href="#"><u>mailxml_tm:ShipperGroupingIDDescription</u></a> <a href="#"><u>mailxml_tm:ScheduledInductionDate</u></a> <a href="#"><u>mailxml_tm:NumberOfDaysStale</u></a> <a href="#"><u>mailxml_tm:MaildatSummary</u></a> <a href="#"><u>mailxml_tm:ContentUSPSSummary</u></a>																								
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><a href="#"><u>mailxml_tm:LogisticsSchedulerID</u></a></td><td><a href="#"><u>mailxml_base:s12</u></a></td><td></td><td></td><td></td><td></td></tr> <tr> <td><a href="#"><u>mailxml_tm:LogisticsCorpID</u></a></td><td><a href="#"><u>mailxml_base:s12</u></a></td><td></td><td></td><td></td><td></td></tr> <tr> <td><a href="#"><u>mailxml_tm:LogisticsSchedulerCRID</u></a></td><td><a href="#"><u>mailxml_base:CRIDType</u></a></td><td></td><td></td><td></td><td></td></tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#"><u>mailxml_tm:LogisticsSchedulerID</u></a>	<a href="#"><u>mailxml_base:s12</u></a>					<a href="#"><u>mailxml_tm:LogisticsCorpID</u></a>	<a href="#"><u>mailxml_base:s12</u></a>					<a href="#"><u>mailxml_tm:LogisticsSchedulerCRID</u></a>	<a href="#"><u>mailxml_base:CRIDType</u></a>				
Name	Type	Use	Default	Fixed	annotation																				
<a href="#"><u>mailxml_tm:LogisticsSchedulerID</u></a>	<a href="#"><u>mailxml_base:s12</u></a>																								
<a href="#"><u>mailxml_tm:LogisticsCorpID</u></a>	<a href="#"><u>mailxml_base:s12</u></a>																								
<a href="#"><u>mailxml_tm:LogisticsSchedulerCRID</u></a>	<a href="#"><u>mailxml_base:CRIDType</u></a>																								

### complexType detailInfoType

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
children	<a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:StartTheClockDate</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:USPSSummary</a> <a href="#">mailxml_tm:ConsigneeContentID</a>
used by	elements <a href="#">ConsigneeGoodsReceipt/DetailInfo</a> <a href="#">ConsigneeGoodsReceiptDelivery/DetailInfo</a> <a href="#">DeliveryApptCancelCreateRequest/DetailInfo</a> <a href="#">DeliveryApptCreateRequest/DetailInfo</a> <a href="#">DeliveryApptQueryRequest/DetailInfo</a> <a href="#">DeliveryApptQueryResponse/QueryResults/DetailInfo</a> <a href="#">DeliveryApptUpdate/DetailInfo</a> <a href="#">DeliveryApptUpdateRequest/DetailInfo</a> <a href="#">DeliveryReApptRequest/DetailInfo</a> <a href="#">PickupApptCreateRequest/DetailInfo</a> <a href="#">PickupApptCreateResponse/PickupApptCreateAccept/DetailInfo</a> <a href="#">PickupApptCreateResponse/PickupApptCreateReject/DetailInfo</a> <a href="#">PickupApptUpdateRequest/DetailInfo</a> <a href="#">PickupApptUpdateResponse/PickupApptUpdateAccept/DetailInfo</a> <a href="#">PickupApptUpdateResponse/PickupApptUpdateReject/DetailInfo</a> <a href="#">UnscheduledConsigneeGoodsReceipt/DetailInfo</a> <a href="#">UnscheduledConsigneeGoodsReceiptDelivery/DetailInfo</a> <a href="#">deliveryApptAcceptType/DetailInfo</a> <a href="#">deliveryApptUpdateAcceptType/DetailInfo</a>

### element detailInfoType/ShipperContainerGroupingID

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s16</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 16 whiteSpace preserve

### element detailInfoType/ConsigneeContainerGroupingID


diagram	
---------	---

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm		
type	<b>mailxml_base:s16</b>		
properties	isRef	0	
	minOcc	0	
	maxOcc	1	
	content	simple	
facets	Kind	Value	annotation
	minLength	1	
	maxLength	16	
	whiteSpace	preserve	

**element detailInfoType/StartTheClockDate**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:date</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple


**element detailInfoType/ShipperGroupingIDDescription**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s50</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 50 whiteSpace preserve

element **detailInfoType/MaildatSummary**

diagram	<pre> classDiagram     class mailxml_tm::MaildatSummaryType {         &lt;&lt;attributes&gt;&gt;         mailxml_tm::IncludedInSummarizationBlock         mailxml_tm::SchedulerContentID     }     class mailxml_tm::MaildatSummary {         &lt;&lt;Relationships&gt;&gt;         --&gt; mailxml_tm::MaildatSummaryType     }     class mailxml_tm::UserLicenseCode     class mailxml_tm::MaildatJobID     class mailxml_tm::DatabaseContainerID     class mailxml_tm::IMcb     class mailxml_tm::VerificationZip4     class mailxml_tm::IMPb     class mailxml_tm::IMtb     mailxml_tm::MaildatSummary "1" --&gt; "1" mailxml_tm::UserLicenseCode     mailxml_tm::MaildatSummary "1" --&gt; "1" mailxml_tm::MaildatJobID     mailxml_tm::MaildatSummary "1" --&gt; "1" mailxml_tm::DatabaseContainerID     mailxml_tm::MaildatSummary "*" --&gt; "1" mailxml_tm::IMcb     mailxml_tm::MaildatSummary "*" --&gt; "1" mailxml_tm::VerificationZip4     mailxml_tm::MaildatSummary "*" --&gt; "1" mailxml_tm::IMPb     mailxml_tm::MaildatSummary "*" --&gt; "1" mailxml_tm::IMtb   </pre>																		
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																		
type	<a href="#">mailxml_tm:MaildatSummaryType</a>																		
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex														
isRef	0																		
content	complex																		
children	<a href="#">mailxml_tm:UserLicenseCode</a> <a href="#">mailxml_tm:MaildatJobID</a> <a href="#">mailxml_tm:DatabaseContainerID</a> <a href="#">mailxml_tm:IMcb</a> <a href="#">mailxml_tm:VerificationZip4</a> <a href="#">mailxml_tm:IMPb</a> <a href="#">mailxml_tm:IMtb</a>																		
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><a href="#">mailxml_tm:IncludedInSummarizationBlock</a></td> <td><a href="#">mailxml_base:yesNo</a></td> <td></td> <td>No</td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:SchedulerContentID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:IncludedInSummarizationBlock</a>	<a href="#">mailxml_base:yesNo</a>		No			<a href="#">mailxml_tm:SchedulerContentID</a>	<a href="#">mailxml_base:s12</a>				
Name	Type	Use	Default	Fixed	annotation														
<a href="#">mailxml_tm:IncludedInSummarizationBlock</a>	<a href="#">mailxml_base:yesNo</a>		No																
<a href="#">mailxml_tm:SchedulerContentID</a>	<a href="#">mailxml_base:s12</a>																		

element **detailInfoType/USPSSummary**




namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
type	<a href="#">mailxml_tm:uspsSummaryType</a>					
properties	isRef 0 content complex					
children	<a href="#">mailxml_tm:DestinationDiscountIndicator</a> <a href="#">mailxml_tm:ZoneSkippingIndicator</a> <a href="#">mailxml_tm:FullServiceIndicator</a> <a href="#">mailxml_tm:eInductionIndicator</a> <a href="#">mailxml_tm:Pallets</a> <a href="#">mailxml_tm:Bedload</a> <a href="#">mailxml_tm:Perishable</a> <a href="#">mailxml_tm:MailClass</a> <a href="#">mailxml_tm:RateType</a> <a href="#">mailxml_tm:InHomeStart</a> <a href="#">mailxml_tm:InHomeEnd</a> <a href="#">mailxml_tm:ProcessingCategory</a> <a href="#">mailxml_tm:NewsIndicator</a> <a href="#">mailxml_tm:PriorityMailIndicator</a> <a href="#">mailxml_tm:VerificationLocation</a> <a href="#">mailxml_tm:EvsIndicator</a> <a href="#">mailxml_tm:MailContentName</a> <a href="#">mailxml_tm:MailPreparerID</a> <a href="#">mailxml_tm:MailPreparerCRID</a> <a href="#">mailxml_tm:AdvanceMailingID</a> <a href="#">mailxml_tm:EFileNumber</a> <a href="#">mailxml_tm:ContainsAutoMail</a>					
attributes	Name <a href="#">mailxml_tm:SchedulerContentID</a> <a href="#">mailxml_tm:ConsigneeContentID</a>	Type <a href="#">mailxml_base:s12</a> <a href="#">mailxml_base:s12</a>	Use	Default	Fixed	annotation

#### element detailInfoType/ConsigneeContentID

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_base:s12</a>
properties	isRef 0 content simple
facets	Kind Value annotation minLength 1 maxLength 12 whiteSpace preserve

#### complexType eFileSamplingTimeType

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
children	<a href="#">mailxml_tm:EfileNumber</a> <a href="#">mailxml_tm:EfileSamplingTime</a>
used by	element <a href="#">apptBlockGoodsType/EfileSamplingTime</a>

#### element eFileSamplingTimeType/EfileNumber


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_base:s22</a>
properties	isRef 0 content simple
facets	Kind Value annotation

	minLength 1 maxLength 22 whiteSpace preserve
--	--

### element eFileSamplingTimeType/EFileSamplingTime

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:dateTime</b>
properties	isRef 0 content simple

### complexType maildatSummaryType

diagram																			
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																		
children	<a href="#">mailxml_tm:UserLicenseCode</a> <a href="#">mailxml_tm:MaildatJobID</a> <a href="#">mailxml_tm:DatabaseContainerID</a> <a href="#">mailxml_tm:IMcb</a> <a href="#">mailxml_tm:VerificationZip4</a> <a href="#">mailxml_tm:IMpb</a> <a href="#">mailxml_tm:IMtb</a>																		
used by	elements <a href="#">contentDetailInfoType/MaildatSummary</a> <a href="#">contentDetailInfoUpdateType/MaildatSummary</a> <a href="#">detailInfoType/MaildatSummary</a>																		
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><a href="#">mailxml_tm:IncludedInSummarizationBlock</a></td> <td><a href="#">mailxml_base:yesNo</a></td> <td></td> <td>No</td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:SchedulerContentID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:IncludedInSummarizationBlock</a>	<a href="#">mailxml_base:yesNo</a>		No			<a href="#">mailxml_tm:SchedulerContentID</a>	<a href="#">mailxml_base:s12</a>				
Name	Type	Use	Default	Fixed	annotation														
<a href="#">mailxml_tm:IncludedInSummarizationBlock</a>	<a href="#">mailxml_base:yesNo</a>		No																
<a href="#">mailxml_tm:SchedulerContentID</a>	<a href="#">mailxml_base:s12</a>																		

### attribute maildatSummaryType/@IncludedInSummarizationBlock


namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
-----------	---

type	<b>mailxml_base:yesNo</b>		
properties	isRef 0 default No		
facets	Kind enumeration Value annotation Yes enumeration No		

attribute **maildatSummaryType/@SchedulerContentID**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm		
type	<b>mailxml_base:s12</b>		
properties	isRef 0		
facets	Kind minLength Value annotation 1 maxLength 12 whiteSpace preserve		

element **maildatSummaryType/UserLicenseCode**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:userLicenseCodeType</b>
properties	isRef 0 content simple
facets	Kind minLength Value annotation 1 maxLength 4 whiteSpace preserve

element **maildatSummaryType/MaildatJobID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:jobIDType</b>
properties	isRef 0 content simple
facets	Kind minLength Value annotation 1 maxLength 8 whiteSpace preserve


### element maildatSummaryType/DatabaseContainerID

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:databaseContainerIDType</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation totalDigits 6

### element maildatSummaryType/IMcb

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:IMcbType</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 21 maxLength 24

### element maildatSummaryType/VerificationZip4

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:ns09</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation pattern [0-9]{9}

### element maildatSummaryType/IMpb


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:IMpbType</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation

	minLength 21 maxLength 34
--	------------------------------

#### element maildatSummaryType/IMtb

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:IMtbType</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 24 maxLength 24


#### complexType oneTimeApptType

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
children	<a href="#">mailxml_tm:PreferredAppt</a> <a href="#">mailxml_tm:OptionalAppt</a>
used by	elements <a href="#">DeliveryApptCreateRequest/OneTimeAppt</a> <a href="#">DeliveryApptQueryRequest/OneTimeAppt</a> <a href="#">DeliveryApptQueryResponse/QueryResults/OneTimeAppt</a> <a href="#">DeliveryApptUpdateRequest/OneTimeAppt</a> <a href="#">DeliveryApptShellCreateRequest/OneTimeAppt</a> <a href="#">DeliveryApptShellUpdateRequest/OneTimeAppt</a> <a href="#">deliveryApptAcceptType/OneTimeAppt</a> <a href="#">deliveryApptUpdateAcceptType/OneTimeAppt</a> <a href="#">deliveryApptShellAcceptType/OneTimeAppt</a>


#### element oneTimeApptType/PreferredAppt

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:dateTime</b>
properties	isRef 0 content simple

### element **oneTimeApptType/OptionalAppt**

diagram									
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>								
type	<a href="#">mailxml_tm:optionalApptType</a>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	unbounded	content	complex
isRef	0								
minOcc	0								
maxOcc	unbounded								
content	complex								
children	<a href="#">mailxml_tm:Start</a> <a href="#">mailxml_tm:End</a>								

### complexType **optionalApptType**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
children	<a href="#">mailxml_tm:Start</a> <a href="#">mailxml_tm:End</a>
used by	elements <a href="#">OpenApptQueryRequest/OptionalAppt_apptBlockRequestType/OptionalAppt</a> <a href="#">oneTimeApptType/OptionalAppt_pickupApptBlockRequestType/OptionalAppt</a>


### element **optionalApptType/Start**

diagram					
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>				
type	<b>xs:dateTime</b>				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	content	simple
isRef	0				
content	simple				


### element **optionalApptType/End**

diagram					
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>				
type	<b>xs:dateTime</b>				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	content	simple
isRef	0				
content	simple				

### complexType optReturnInfoType

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:ReturnCode</a> <a href="#">mailxml_tm:ReturnDescription</a>
used by	elements <a href="#">DeliveryApptCancelRequest/ReturnInfo</a> <a href="#">contentCancelType/ReturnInfo</a> <a href="#">deliveryApptShellCancelRequestType/ReturnInfo</a>

### element optReturnInfoType/ConsigneeFacility

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_defs:consigneeFacilityType</a>
properties	isRef 0 content complex
children	<a href="#">mailxml_defs:CompanyName</a> <a href="#">mailxml_defs:FacilityNumber</a> <a href="#">mailxml_defs:FacilityAddress</a> <a href="#">mailxml_defs:FacilityAddress</a> <a href="#">mailxml_defs:FacilityName</a> <a href="#">mailxml_defs:FacilityType</a> <a href="#">mailxml_defs:URL</a> <a href="#">mailxml_defs:CommonContact</a>

### element optReturnInfoType/ReturnCode


diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_base:ns04</a>
properties	isRef 0 minOcc 0

	maxOcc 1 content simple
facets	Kind Value annotation pattern [0-9]{4}

#### element optReturnInfoType/ReturnDescription

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	mailxml_base:s260
properties	isRef 0 content simple
facets	Kind Value annotation minLength 1 maxLength 260 whiteSpace preserve

#### complexType palletPresortType

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
children	<a href="#">mailxml_tm:USPSContainerInfo</a>
used by	element <a href="#">palletUnitType/PalletPreSortLevel</a>
attributes	Name mailxml_tm:ContainerLevel Type mailxml_base:containerLevelType Use required Name mailxml_tm:Count Type xs:nonNegativeInteger Use required

#### attribute palletPresortType/@ContainerLevel

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	mailxml_base:containerLevelType
properties	isRef 0 use required
facets	Kind Value annotation enumeration A enumeration B enumeration C enumeration D enumeration E

	enumeration F
	enumeration G
	enumeration H
	enumeration I
	enumeration J
	enumeration K
	enumeration M
	enumeration N
	enumeration P
	enumeration Q
	enumeration R
	enumeration S
	enumeration T
	enumeration U
	enumeration V
	enumeration W
	enumeration X
	enumeration Y
	enumeration Z
	enumeration AA
	enumeration AB
	enumeration AC
	enumeration AD
	enumeration AE
	enumeration AF
	enumeration AG
	enumeration AH
	enumeration AI
	enumeration AJ
	enumeration AK
	enumeration AL
	enumeration AM
	enumeration AN
	enumeration AO
	enumeration AP
	enumeration AQ
	enumeration AR
	enumeration AS
	enumeration AT
	enumeration BA
	enumeration BB
	enumeration BC
	enumeration BD
	enumeration BE
	enumeration BF
	enumeration BG

	enumeration BH enumeration BI enumeration BJ enumeration BK enumeration BL enumeration BM
--	--

**attribute `palletPresortType/@Count`**

namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>xs:nonNegativeInteger</b>
properties	isRef 0 use required

**element `palletPresortType/USPSContainerInfo`**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#"><b>mailxml_tm:uspsContainerInfoType</b></a>
properties	isRef 0 minOcc 0

	maxOcc 1 content complex
children	<a href="#">mailxml_tm:MailOwnerCRID</a> <a href="#">mailxml_tm:MailOwnerId</a> <a href="#">mailxml_tm:USPSPublicationID</a> <a href="#">mailxml_tm:ActualPieceCount</a> <a href="#">mailxml_tm:ContainerWeight</a> <a href="#">mailxml_tm:IMcb</a> <a href="#">mailxml_tm:IMcbInfo</a> <a href="#">mailxml_tm:SiblingBarcode</a> <a href="#">mailxml_tm:PostInductionStatus</a> <a href="#">mailxml_tm:ContainerDestination3digitZIP</a> <a href="#">mailxml_tm:ContainerDestination5digitZIP</a>

### complexType **palletUnitType**

diagram	<pre> classDiagram     class palletUnitType {         mailxml_tm:Count         mailxml_tm:HandlingUnitType         mailxml_tm:PalletType     }     palletUnitType "1..∞" --&gt; "1..∞" palletUnitType :      palletUnitType "1..∞" --&gt; mailxml_tm:PalletPreSortLevel     palletUnitType "1..∞" --&gt; mailxml_tm:USPSContainerInfo   </pre>																								
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																								
children	<a href="#">mailxml_tm:PalletPreSortLevel</a> <a href="#">mailxml_tm:USPSContainerInfo</a>																								
used by	elements <a href="#">contentUspsSummaryType/Pallets</a> <a href="#">contentUspsSummaryUpdateType/Pallets</a> <a href="#">uspsSummaryType/Pallets</a>																								
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><a href="#">mailxml_tm:Count</a></td> <td><a href="#">xs:nonNegativeInteger</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:HandlingUnitType</a></td> <td><a href="#">mailxml_base:palletHandlingUnitType</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:PalletType</a></td> <td><a href="#">mailxml_base:palletType</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:Count</a>	<a href="#">xs:nonNegativeInteger</a>	required				<a href="#">mailxml_tm:HandlingUnitType</a>	<a href="#">mailxml_base:palletHandlingUnitType</a>	required				<a href="#">mailxml_tm:PalletType</a>	<a href="#">mailxml_base:palletType</a>	required			
Name	Type	Use	Default	Fixed	annotation																				
<a href="#">mailxml_tm:Count</a>	<a href="#">xs:nonNegativeInteger</a>	required																							
<a href="#">mailxml_tm:HandlingUnitType</a>	<a href="#">mailxml_base:palletHandlingUnitType</a>	required																							
<a href="#">mailxml_tm:PalletType</a>	<a href="#">mailxml_base:palletType</a>	required																							

### attribute **palletUnitType/@Count**

namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">xs:nonNegativeInteger</a>
properties	isRef 0 use required

### attribute **palletUnitType/@HandlingUnitType**

namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>															
type	<a href="#">mailxml_base:palletHandlingUnitType</a>															
properties	isRef 0 use required															
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Airbox</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Sacks</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Bundles</td> <td></td> </tr> <tr> <td>enumeration</td> <td>MixedLengthTrays</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	enumeration	Airbox		enumeration	Sacks		enumeration	Bundles		enumeration	MixedLengthTrays	
Kind	Value	annotation														
enumeration	Airbox															
enumeration	Sacks															
enumeration	Bundles															
enumeration	MixedLengthTrays															

	enumeration 1ft Tray enumeration 2ft Tray enumeration EMM Tray enumeration Flat Tub enumeration Parcels
--	---

**attribute `palletUnitType/@PalletType`**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm	
type	<b>mailxml_base:palletType</b>	
properties	isRef 0 use required	
facets	Kind Value enumeration Airbox enumeration Pallet enumeration EIRS 61 - Hamper, Large Canvas enumeration EIRS 61P - Hamper, Large Plastic enumeration EIRS 66 - General Purpose Mail Container w/Gate enumeration EIRS 68 - Eastern Region Mail Container w/Web Door enumeration EIRS 84 - Wire Container Rigid enumeration EIRS 84C - Collapsible Wire Container	annotation

**element `palletUnitType/PalletPreSortLevel`**

diagram	<pre> classDiagram     class mailxml_tm:palletPresortType {         &lt;&lt;attributes&gt;&gt;         mailxml_tm:ContainerLevel         mailxml_tm:Count     }     class mailxml_tm:PalletPreSortLevel     mailxml_tm:PalletPreSortLevel "1..∞" --&gt; mailxml_tm:palletPresortType   </pre>																		
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																		
type	<b>mailxml_tm:palletPresortType</b>																		
properties	isRef 0 minOcc 1 maxOcc unbounded content complex																		
children	<b>mailxml_tm:USPSContainerInfo</b>																		
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><a href="#">mailxml_tm:ContainerLevel</a></td> <td><a href="#">mailxml_base:containerLevelType</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:Count</a></td> <td><a href="#">xs:nonNegativeInteger</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:ContainerLevel</a>	<a href="#">mailxml_base:containerLevelType</a>	required				<a href="#">mailxml_tm:Count</a>	<a href="#">xs:nonNegativeInteger</a>	required			
Name	Type	Use	Default	Fixed	annotation														
<a href="#">mailxml_tm:ContainerLevel</a>	<a href="#">mailxml_base:containerLevelType</a>	required																	
<a href="#">mailxml_tm:Count</a>	<a href="#">xs:nonNegativeInteger</a>	required																	

element **palletUnitType/USPSContainerInfo**

diagram					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm				
type	<a href="#">mailxml_tm:uspsContainerInfoType</a>				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex
isRef	0				
content	complex				
children	<a href="#">mailxml_tm:MailOwnerCRID</a> <a href="#">mailxml_tm:MailOwnerID</a> <a href="#">mailxml_tm:USPSPublicationID</a> <a href="#">mailxml_tm:ActualPieceCount</a> <a href="#">mailxml_tm:ContainerWeight</a> <a href="#">mailxml_tm:IMcb</a> <a href="#">mailxml_tm:IMcbInfo</a> <a href="#">mailxml_tm:SiblingBarcode</a> <a href="#">mailxml_tm:PostInductionStatus</a> <a href="#">mailxml_tm:ContainerDestination3digitZIP</a> <a href="#">mailxml_tm:ContainerDestination5digitZIP</a>				

### complexType PartnerApptBlockType

diagram	<pre>sequenceDiagram     participant PA as PartnerApptBlockType     participant CF as mailxml_tm:ConsigneeFacility     participant CA as mailxml_tm:ConsigneeApptID     participant SA as mailxml_tm:ScheduledAppt     participant CM as mailxml_tm:Comment     participant MC as mailxml_tm:MailClass     participant TI as mailxml_tm:TrailerInfo     participant CDI as mailxml_tm:ContentDetailInfoUpdate      PA-&gt;&gt;CF:      PA-&gt;&gt;CA:      PA-&gt;&gt;SA:      PA-&gt;&gt;CM:      PA-&gt;&gt;MC:      PA-&gt;&gt;TI:      repeat PA-&gt;&gt;CDI:          CDI--&gt;&gt;PA:      end</pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:ConsigneeApptID</a> <a href="#">mailxml_tm:ScheduledAppt</a> <a href="#">mailxml_tm:Comment</a> <a href="#">mailxml_tm:MailClass</a> <a href="#">mailxml_tm:TrailerInfo</a> <a href="#">mailxml_tm:ContentDetailInfoUpdate</a>
used by	element <a href="#">PartnerApptQueryResponse/QueryResults/ApptBlock</a>

### element PartnerApptBlockType/ConsigneeFacility


diagram	<pre>sequenceDiagram     participant CF as mailxml_tm:ConsigneeFacility     participant CFDef as mailxml_defs:consigneeFacilityType     participant CN as mailxml_defs:CompanyName     participant FN as mailxml_defs:FacilityNumber     participant FA as mailxml_defs:FacilityAddress     participant FNDef as mailxml_defs:FacilityName     participant FT as mailxml_defs:FacilityType     participant URL as mailxml_defs:URL     participant CC as mailxml_defs:CommonContact      CF-&gt;&gt;CFDef:      CFDef-&gt;&gt;CN:      CFDef-&gt;&gt;FN:      CFDef-&gt;&gt;FA:      CFDef-&gt;&gt;FNDef:      CFDef-&gt;&gt;FT:      CFDef-&gt;&gt;URL:      repeat CF-&gt;&gt;CC:          CC--&gt;&gt;CF:      end</pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_defs:consigneeFacilityType</a>
properties	isRef 0 minOcc 0 maxOcc 1 content complex
children	<a href="#">mailxml_defs:CompanyName</a> <a href="#">mailxml_defs:FacilityNumber</a> <a href="#">mailxml_defs:FacilityAddress</a> <a href="#">mailxml_defs:FacilityName</a> <a href="#">mailxml_defs:FacilityType</a> <a href="#">mailxml_defs:URL</a>

	<b>mailxml_defs:CommonContact</b>
--	-----------------------------------

**element PartnerApptBlockType/ConsigneeApptID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s12</b>
properties	isRef 0 content simple
facets	Kind Value annotation minLength 1 maxLength 12 whiteSpace preserve

**element PartnerApptBlockType/ScheduledAppt**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:dateTime</b>
properties	isRef 0 content simple
used by	complexTypes <a href="#">apptBlockGoodsType</a> <a href="#">apptInfoType</a>

**element PartnerApptBlockType/Comment**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s256</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 256 whiteSpace preserve

**element PartnerApptBlockType/MailClass**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm

type	<b>mailxml_base:mailClassType</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration 1 enumeration 2 enumeration 3 enumeration 4 enumeration 6

### element PartnerApptBlockType/TrailerInfo

diagram	<pre> classDiagram     class trailerInfoType {         &lt;&lt;mailxml_tm&gt;&gt;         &lt;&lt;trailerInfoType&gt;&gt;         &lt;&lt;carrier&gt;&gt;         &lt;&lt;billOfLadingNumber&gt;&gt;     }     trailerInfoType "0..2" -- "1..2" : &lt;&lt;trailer&gt;&gt;     trailerInfoType "1..2" -- "1..2" : &lt;&lt;carrier&gt;&gt;     trailerInfoType "1..2" -- "1..2" : &lt;&lt;billOfLadingNumber&gt;&gt;     trailerInfoType "0..1" -- "1..1" : &lt;&lt;trailerInfo&gt;&gt;   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#"><b>mailxml_tm:trailerInfoType</b></a>
properties	isRef 0 minOcc 0 maxOcc 1 content complex
children	<a href="#"><b>mailxml_tm:Trailer</b></a> <a href="#"><b>mailxml_tm:Carrier</b></a> <a href="#"><b>mailxml_tm:BillOfLadingNumber</b></a>

## element PartnerApptBlockType/ContentDetailInfoUpdate

diagram	<pre> classDiagram     class mailxml_tm::contentDetailInfoUpdateType {         attribute mailxml_tm::LogisticsSchedulerID         attribute mailxml_tm::LogisticsCorpID         attribute mailxml_tm::LogisticsSchedulerCRID         0..∞ ContentDetailInfoUpdate         mailxml_tm::ShipperContainerGr...         mailxml_tm::ConsigneeContain...         mailxml_tm::ShipperGroupingID...         mailxml_tm::ScheduledInducti...         mailxml_tm::MaildatSummary         mailxml_tm::ContentUSPSSum...     } </pre>																								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																								
type	<a href="#">mailxml_tm:contentDetailInfoUpdateType</a>																								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	unbounded	content	complex																
isRef	0																								
minOcc	0																								
maxOcc	unbounded																								
content	complex																								
children	<a href="#">mailxml_tm:ShipperContainerGroupingID</a> <a href="#">mailxml_tm:ConsigneeContainerGroupingID</a> <a href="#">mailxml_tm:ShipperGroupingIDDescription</a> <a href="#">mailxml_tm:ScheduledInductionDate</a> <a href="#">mailxml_tm:MaildatSummary</a> <a href="#">mailxml_tm:ContentUSPSSummary</a>																								
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><a href="#">mailxml_tm:LogisticsSchedulerID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:LogisticsCorpID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:LogisticsSchedulerCRID</a></td> <td><a href="#">mailxml_base:CRIDType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:LogisticsSchedulerID</a>	<a href="#">mailxml_base:s12</a>					<a href="#">mailxml_tm:LogisticsCorpID</a>	<a href="#">mailxml_base:s12</a>					<a href="#">mailxml_tm:LogisticsSchedulerCRID</a>	<a href="#">mailxml_base:CRIDType</a>				
Name	Type	Use	Default	Fixed	annotation																				
<a href="#">mailxml_tm:LogisticsSchedulerID</a>	<a href="#">mailxml_base:s12</a>																								
<a href="#">mailxml_tm:LogisticsCorpID</a>	<a href="#">mailxml_base:s12</a>																								
<a href="#">mailxml_tm:LogisticsSchedulerCRID</a>	<a href="#">mailxml_base:CRIDType</a>																								

## complexType partnerContentAssignmentType

diagram	<pre> classDiagram     class partnerContentAssignmentType {         mailxml_tm::PartnerIdentifier         mailxml_tm::ConsigneeContentID         1..∞ DestinationEntry     } </pre> <p>Type to define the combination of ConsigneeContentIDs and assigned users</p>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
children	<a href="#">mailxml_tm:PartnerIdentifier</a> <a href="#">mailxml_tm:ConsigneeContentID</a> <a href="#">mailxml_tm:DestinationEntry</a>
used by	elements <a href="#">PartnerContentAssignmentRequest/PartnerContentAssignedTo</a> <a href="#">PartnerContentAssignmentResponse/PartnerContentAssignmentAccepted</a>

annotation	documentation Type to define the combination of ConsigneeContentIDs and assigned users
------------	---

element **partnerContentAssignmentType/PartnerIdentifier**

diagram	<pre> classDiagram     class mailxml_tm::PartnerIdentifier     class mailxml_defs::participantIDType {         &lt;&lt;attributes&gt;&gt;         mailxml_defs::MailerID6         mailxml_defs::MailerID9         mailxml_defs::CRID         mailxml_defs::SchedulerID         mailxml_defs::MaildatUserLicense         mailxml_defs::ShippingAgentID         mailxml_defs::ReceivingAgentID     }     PartnerIdentifier "1" -- "1" participantIDType   </pre>																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																
type	<b>mailxml_defs:participantIDType</b>																																
properties	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 10%;">isRef</td><td style="width: 10%;">0</td><td style="width: 10%;">content</td><td style="width: 10%;">complex</td><td style="width: 10%;"></td><td style="width: 10%;"></td><td style="width: 10%;"></td><td style="width: 10%;"></td></tr> </table>	isRef	0	content	complex																												
isRef	0	content	complex																														
attributes	<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 25%;">Name</th><th style="width: 25%;">Type</th><th style="width: 25%;">Use</th><th style="width: 25%;">Default</th></tr> </thead> <tbody> <tr> <td>mailxml_defs:MailerID6</td><td><b>mailxml_base:mailerID6Type</b></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MailerID9</td><td><b>mailxml_base:mailerID9Type</b></td><td></td><td></td></tr> <tr> <td>mailxml_defs:CRID</td><td><b>mailxml_base:CRIDType</b></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerID</td><td><b>mailxml_base:s12</b></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatUserLicense</td><td><b>mailxml_base:userLicenseCodeType</b></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShippingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ReceivingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td></tr> </tbody> </table>	Name	Type	Use	Default	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>			mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>			mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>			mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>			mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>			mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>			mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>		
Name	Type	Use	Default																														
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																

element **partnerContentAssignmentType/ConsigneeContentID**


diagram									
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>								
type	<b>mailxml_base:s12</b>								
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>1</td> </tr> <tr> <td>maxOcc</td> <td>unbounded</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	1	maxOcc	unbounded	content	simple
isRef	0								
minOcc	1								
maxOcc	unbounded								
content	simple								
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1			
Kind	Value	annotation							
minLength	1								

	<pre>maxLength    12 whiteSpace  preserve</pre>
--	---

#### element partnerContentAssignmentType/DestinationEntry

diagram										
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm									
type	<b>mailxml_base:yesNo</b>									
properties	<table> <tr> <td>isRef</td><td>0</td> </tr> <tr> <td>content</td><td>simple</td> </tr> </table>	isRef	0	content	simple					
isRef	0									
content	simple									
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td> </tr> <tr> <td>enumeration</td><td>Yes</td><td></td> </tr> <tr> <td>enumeration</td><td>No</td><td></td> </tr> </table>	Kind	Value	annotation	enumeration	Yes		enumeration	No	
Kind	Value	annotation								
enumeration	Yes									
enumeration	No									

#### complexType pickupApptBlockRequestType

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
children	<a href="#">mailxml_tm:SubmittingParty</a> <a href="#">mailxml_tm:SubmittingSoftware</a> <a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:PickupLocation</a> <a href="#">mailxml_tm:PreferredAppt</a> <a href="#">mailxml_tm:OptionalAppt</a> <a href="#">mailxml_tm:Comment</a> <a href="#">mailxml_tm:TransportationResponsibility</a>
used by	elements <a href="#">PickupApptCreateRequest/ApptBlock</a> <a href="#">PickupApptUpdateRequest/ApptBlock</a> <a href="#">PickupApptCreateResponse/PickupApptCreateReject/ApptInfo</a> <a href="#">PickupApptUpdateResponse/PickupApptUpdateReject/ApptInfo</a>

### element pickupApptBlockRequestType/SubmittingParty

diagram	<pre> classDiagram     participant Party     participant IDType      Party "1" -- "7" IDType     IDType {         mailxml_defs:MailerID6         mailxml_defs:MailerID9         mailxml_defs:CRID         mailxml_defs:SchedulerID         mailxml_defs:MaildatUserLicense         mailxml_defs:ShippingAgentID         mailxml_defs:ReceivingAgentID     }   </pre>																																																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
type	<b>mailxml_defs:participantIDType</b>																																																
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	content	complex																																												
isRef	0																																																
content	complex																																																
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td>mailxml_defs:MailerID6</td><td><b>mailxml_base:mailerID6Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MailerID9</td><td><b>mailxml_base:mailerID9Type</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:CRID</td><td><b>mailxml_base:CRIDType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:SchedulerID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:MaildatUserLicense</td><td><b>mailxml_base:userLicenseCodeType</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ShippingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> <tr> <td>mailxml_defs:ReceivingAgentID</td><td><b>mailxml_base:s12</b></td><td></td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>					mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>					mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>					mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>					mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>					mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>					mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	<b>mailxml_base:mailerID6Type</b>																																																
mailxml_defs:MailerID9	<b>mailxml_base:mailerID9Type</b>																																																
mailxml_defs:CRID	<b>mailxml_base:CRIDType</b>																																																
mailxml_defs:SchedulerID	<b>mailxml_base:s12</b>																																																
mailxml_defs:MaildatUserLicense	<b>mailxml_base:userLicenseCodeType</b>																																																
mailxml_defs:ShippingAgentID	<b>mailxml_base:s12</b>																																																
mailxml_defs:ReceivingAgentID	<b>mailxml_base:s12</b>																																																

### element pickupApptBlockRequestType/SubmittingSoftware

diagram	<pre> classDiagram     participant Software     participant SoftwareType      Software "1" -- "5" SoftwareType     SoftwareType {         mailxml_defs:SoftwareName         mailxml_defs:Vendor         mailxml_defs:Version         mailxml_defs:ApprovalDate         mailxml_defs:ApprovalKey     }   </pre>
---------	--

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
type	<b>mailxml_defs:submittingSoftwareType</b>					
properties	isRef 0 content complex	Type <b>xs:string</b>	Use required	Default	Fixed	annotation
attributes	Name mailxml_defs:SoftwareName	Type <b>xs:string</b>	Use required			
	mailxml_defs:Vendor	Type <b>xs:string</b>	Use required			
	mailxml_defs:Version	Type <b>xs:string</b>	Use required			
	mailxml_defs:ApprovalDate	Type <b>xs:date</b>	Use required			
	mailxml_defs:ApprovalKey	Type <b>xs:string</b>	Use required			

### element **pickupApptBlockRequestType/ConsigneeFacility**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_defs:consigneeFacilityType</b>
properties	isRef 0 minOcc 0 maxOcc 1 content complex
children	<b>mailxml_defs:CompanyName</b> <b>mailxml_defs:FacilityNumber</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityName</b> <b>mailxml_defs:FacilityType</b> <b>mailxml_defs:URL</b> <b>mailxml_defs:CommonContact</b>

### element pickupApptBlockRequestType/PickupLocation

diagram	<pre> sequenceDiagram     participant PL as mailxml_tm:PickupLocation     participant CFT as mailxml_defs:consigneeFacilityType     participant CNAME as mailxml_defs:CompanyName     participant FN as mailxml_defs:FacilityNumber     participant FA as mailxml_defs:FacilityAddress     participant FNAME as mailxml_defs:FacilityName     participant FT as mailxml_defs:FacilityType     participant URL as mailxml_defs:URL     participant CC as mailxml_defs:CommonContact      PL-&gt;&gt;CFT:      activate CFT     CNAME     FN     FA     FNAME     FT     URL     CC     deactivate CFT   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_defs:consigneeFacilityType</a>
properties	isRef 0 content complex
children	mailxml_defs:CompanyName mailxml_defs:FacilityNumber mailxml_defs:FacilityAddress mailxml_defs:FacilityAddress mailxml_defs:FacilityName mailxml_defs:FacilityType mailxml_defs:URL mailxml_defs:CommonContact

### element pickupApptBlockRequestType/PreferredAppt

diagram	<pre> sequenceDiagram     participant PA as mailxml_tm:PreferredAppt   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">xs:dateTime</a>
properties	isRef 0 content simple

### element pickupApptBlockRequestType/OptionalAppt

diagram	<pre> sequenceDiagram     participant OA as mailxml_tm:OptionalAppt     participant OAT as mailxml_tm:optionalApptType     participant S as mailxml_tm:Start     participant E as mailxml_tm:End      OA-&gt;&gt;OAT:      activate OAT     S     E     deactivate OAT   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:optionalApptType</a>

properties	isRef 0 minOcc 0 maxOcc unbounded content complex
children	<a href="#">mailxml_tm:Start</a> <a href="#">mailxml_tm:End</a>


#### element pickupApptBlockRequestType/Comment

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s256</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 256 whiteSpace preserve

#### element pickupApptBlockRequestType/TransportationResponsibility

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:responsibleTransportationPartyType</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Shipper enumeration Consignee

#### complexType presortType

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
used by	elements <a href="#">bedloadHandlingUnitType/PreSortLevel</a> <a href="#">trayHandlingUnitType/PreSortLevel</a>
attributes	Name <a href="#">mailxml_tm:ContainerLevel</a> Type <a href="#">mailxml_base:containerLevelType</a> Use required Name <a href="#">mailxml_tm:Count</a> Type <a href="#">xs:nonNegativeInteger</a> Use required

attribute **presortType/@ContainerLevel**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm		
type	<b>mailxml_base:containerLevelType</b>		
properties	isRef 0 use required		
facets	Kind	Value	annotation
	enumeration	A	
	enumeration	B	
	enumeration	C	
	enumeration	D	
	enumeration	E	
	enumeration	F	
	enumeration	G	
	enumeration	H	
	enumeration	I	
	enumeration	J	
	enumeration	K	
	enumeration	M	
	enumeration	N	
	enumeration	P	
	enumeration	Q	
	enumeration	R	
	enumeration	S	
	enumeration	T	
	enumeration	U	
	enumeration	V	
	enumeration	W	
	enumeration	X	
	enumeration	Y	
	enumeration	Z	
	enumeration	AA	
	enumeration	AB	
	enumeration	AC	
	enumeration	AD	
	enumeration	AE	
	enumeration	AF	
	enumeration	AG	
	enumeration	AH	
	enumeration	AI	
	enumeration	AJ	
	enumeration	AK	
	enumeration	AL	
	enumeration	AM	
	enumeration	AN	
	enumeration	AO	
	enumeration	AP	

	enumeration AQ
	enumeration AR
	enumeration AS
	enumeration AT
	enumeration BA
	enumeration BB
	enumeration BC
	enumeration BD
	enumeration BE
	enumeration BF
	enumeration BG
	enumeration BH
	enumeration BI
	enumeration BJ
	enumeration BK
	enumeration BL
	enumeration BM

**attribute `presortType/@Count`**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:nonNegativeInteger</b>
properties	isRef 0 use required

complexType recurringApptBlockType

diagram																																																	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:RecurringData</a> <a href="#">mailxml_tm:RecurringApptStatus</a> <a href="#">mailxml_tm:USPSSummary</a> <a href="#">mailxml_tm:PostalClass</a> <a href="#">mailxml_tm:ReturnInfo</a>																																																
used by	element <a href="#">RecurringApptQueryResponse/QueryResults/RecurringApptBlock</a>																																																
attributes	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_tm:CreatorSchedulerID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:CreatorSchedulerCorpID</td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:CreatorSchedulerCRID</td> <td><a href="#">mailxml_base:CRIDType</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:RecurringApptID</td> <td><a href="#">mailxml_base:s08</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:ApptType</td> <td><a href="#">mailxml_base:apptTypeType</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:RecurringApptStatus</td> <td><a href="#">mailxml_base:recurringStatusType</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_tm:RetrieveContentUpdatedStartDate</td> <td><a href="#">xs:date</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_tm:CreatorSchedulerID	<a href="#">mailxml_base:s12</a>					mailxml_tm:CreatorSchedulerCorpID	<a href="#">mailxml_base:s12</a>					mailxml_tm:CreatorSchedulerCRID	<a href="#">mailxml_base:CRIDType</a>					mailxml_tm:RecurringApptID	<a href="#">mailxml_base:s08</a>	required				mailxml_tm:ApptType	<a href="#">mailxml_base:apptTypeType</a>	required				mailxml_tm:RecurringApptStatus	<a href="#">mailxml_base:recurringStatusType</a>	required				mailxml_tm:RetrieveContentUpdatedStartDate	<a href="#">xs:date</a>				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_tm:CreatorSchedulerID	<a href="#">mailxml_base:s12</a>																																																
mailxml_tm:CreatorSchedulerCorpID	<a href="#">mailxml_base:s12</a>																																																
mailxml_tm:CreatorSchedulerCRID	<a href="#">mailxml_base:CRIDType</a>																																																
mailxml_tm:RecurringApptID	<a href="#">mailxml_base:s08</a>	required																																															
mailxml_tm:ApptType	<a href="#">mailxml_base:apptTypeType</a>	required																																															
mailxml_tm:RecurringApptStatus	<a href="#">mailxml_base:recurringStatusType</a>	required																																															
mailxml_tm:RetrieveContentUpdatedStartDate	<a href="#">xs:date</a>																																																

	mailxml_tm:RetrieveContentUpdatedEndDate	<b>xs:date</b>
--	--	----------------

**element recurringApptBlockType/ConsigneeFacility**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_defs:consigneeFacilityType</b>
properties	isRef 0 content complex
children	<b>mailxml_defs:CompanyName</b> <b>mailxml_defs:FacilityNumber</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityName</b> <b>mailxml_defs:FacilityType</b> <b>mailxml_defs:URL</b> <b>mailxml_defs:CommonContact</b>

**element recurringApptBlockType/RecurringData**


diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>

type	<a href="#"><b>mailxml_tm:recurringApptType</b></a>
properties	isRef 0 content complex
children	<a href="#"><b>mailxml_tm:EffectiveStartDate</b></a> <a href="#"><b>mailxml_tm:EffectiveEndDate</b></a> <a href="#"><b>mailxml_tm:ApptTime</b></a> <a href="#"><b>mailxml_tm:DayFrequency</b></a> <a href="#"><b>mailxml_tm:WeekFrequency</b></a>

element **recurringApptBlockType/RecurringApptStatus**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:recurringStatusType</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Active enumeration Pending enumeration All

element **recurringApptBlockType/USPSSummary**




namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm					
type	<a href="#">mailxml_tm:uspsSummaryType</a>					
properties	isRef 0 minOcc 0 maxOcc unbounded content complex					
children	<a href="#">mailxml_tm:DestinationDiscountIndicator</a> <a href="#">mailxml_tm:ZoneSkippingIndicator</a> <a href="#">mailxml_tm:FullServiceIndicator</a> <a href="#">mailxml_tm:eInductionIndicator</a> <a href="#">mailxml_tm:Pallets</a> <a href="#">mailxml_tm:Bedload</a> <a href="#">mailxml_tm:Perishable</a> <a href="#">mailxml_tm:MailClass</a> <a href="#">mailxml_tm:RateType</a> <a href="#">mailxml_tm:InHomeStart</a> <a href="#">mailxml_tm:InHomeEnd</a> <a href="#">mailxml_tm:ProcessingCategory</a> <a href="#">mailxml_tm:NewsIndicator</a> <a href="#">mailxml_tm:PriorityMailIndicator</a> <a href="#">mailxml_tm:VerificationLocation</a> <a href="#">mailxml_tm:EvsIndicator</a> <a href="#">mailxml_tm:MailContentName</a> <a href="#">mailxml_tm:MailPreparerID</a> <a href="#">mailxml_tm:MailPreparerCRID</a> <a href="#">mailxml_tm:AdvanceMailingID</a> <a href="#">mailxml_tm:EFileNumber</a> <a href="#">mailxml_tm:ContainsAutoMail</a>					
attributes	Name	Type	Use	Default	Fixed	annotation
	<a href="#">mailxml_tm:SchedulerContentID</a>	<a href="#">mailxml_base:s12</a>				
	<a href="#">mailxml_tm:ConsigneeContentID</a>	<a href="#">mailxml_base:s12</a>				

#### element recurringApptBlockType/PostalClass

diagram																			
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																		
type	<a href="#">mailxml_base:mailClassType</a>																		
properties	isRef 0 minOcc 1 maxOcc unbounded content simple																		
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>1</td> <td></td> </tr> <tr> <td>enumeration</td> <td>2</td> <td></td> </tr> <tr> <td>enumeration</td> <td>3</td> <td></td> </tr> <tr> <td>enumeration</td> <td>4</td> <td></td> </tr> <tr> <td>enumeration</td> <td>6</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	enumeration	1		enumeration	2		enumeration	3		enumeration	4		enumeration	6	
Kind	Value	annotation																	
enumeration	1																		
enumeration	2																		
enumeration	3																		
enumeration	4																		
enumeration	6																		

#### element recurringApptBlockType/ReturnInfo

diagram	
---------	--

namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_defs:basicReturnInfoType</b>
properties	isRef 0 minOcc 0 maxOcc 1 content complex
children	<a href="#">mailxml_defs:ReturnCode</a> <a href="#">mailxml_defs:ReturnDescription</a> <a href="#">mailxml_defs:errorWarning</a> <a href="#">mailxml_defs:ContainerErrorWarningBlock</a>

### complexType recurringApptType

diagram	<pre> classDiagram     class recurringApptType {         mailxml_tm:EffectiveStartDate         mailxml_tm:EffectiveEndDate         mailxml_tm:ApptTime         mailxml_tm:DayFrequency     }     mailxml_tm:DayFrequency "1..∞" --&gt; mailxml_tm:WeekFrequency   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
children	<a href="#">mailxml_tm:EffectiveStartDate</a> <a href="#">mailxml_tm:EffectiveEndDate</a> <a href="#">mailxml_tm:ApptTime</a> <a href="#">mailxml_tm:DayFrequency</a> <a href="#">mailxml_tm:WeekFrequency</a>
used by	elements <a href="#">DeliveryApptCreateRequest/RecurringAppt</a> <a href="#">DeliveryApptQueryRequest/RecurringAppt</a> <a href="#">DeliveryApptQueryResponse/QueryResults/RecurringAppt</a> <a href="#">DeliveryApptUpdateRequest/RecurringAppt</a> <a href="#">DeliveryApptShellCreateRequest/RecurringAppt</a> <a href="#">DeliveryApptShellUpdateRequest/RecurringAppt</a> <a href="#">deliveryApptAcceptType/RecurringAppt</a> <a href="#">deliveryApptUpdateAcceptType/RecurringAppt</a> <a href="#">deliveryApptShellAcceptType/RecurringAppt</a> <a href="#">recurringApptBlockType/RecurringData</a>

### element recurringApptType/EffectiveStartDate

diagram	<pre> classDiagram     class recurringApptType {         mailxml_tm:EffectiveStartDate     }   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>xs:date</b>
properties	isRef 0 content simple

### element recurringApptType/EffectiveEndDate

diagram	<pre> classDiagram     class recurringApptType {         mailxml_tm:EffectiveEndDate     }   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>xs:date</b>

properties	isRef 0 content simple
------------	---------------------------

#### element recurringApptType/ApptTime

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:time</b>
properties	isRef 0 content simple

#### element recurringApptType/DayFrequency

diagram																												
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																											
type	<b>mailxml_base:dayFrequencyType</b>																											
properties	isRef 0 minOcc 1 maxOcc unbounded content simple																											
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Daily</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Monday</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Tuesday</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Wednesday</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Thursday</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Friday</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Saturday</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Sunday</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	enumeration	Daily		enumeration	Monday		enumeration	Tuesday		enumeration	Wednesday		enumeration	Thursday		enumeration	Friday		enumeration	Saturday		enumeration	Sunday	
Kind	Value	annotation																										
enumeration	Daily																											
enumeration	Monday																											
enumeration	Tuesday																											
enumeration	Wednesday																											
enumeration	Thursday																											
enumeration	Friday																											
enumeration	Saturday																											
enumeration	Sunday																											

#### element recurringApptType/WeekFrequency

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:weekFrequencyType</b>												
properties	isRef 0 minOcc 1 maxOcc unbounded content simple												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Weekly</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Bi-Weekly</td> <td></td> </tr> <tr> <td>enumeration</td> <td>First</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	enumeration	Weekly		enumeration	Bi-Weekly		enumeration	First	
Kind	Value	annotation											
enumeration	Weekly												
enumeration	Bi-Weekly												
enumeration	First												

	enumeration Second enumeration Third enumeration Fourth enumeration Fifth enumeration Sixth
--	---

### complexType slotAvailabilityType

diagram	<pre> graph LR     SA[slotAvailabilityType] --- AP[ApptType]     AP --- MC[MailClass]     MC --- PER[Perishable]     PER -.-&gt; APPTIME1[ApptStartTime]     PER -.-&gt; APPTIME2[ApptEndTime]     PER -.-&gt; AT[ApplyTiers]     </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
children	<a href="#">mailxml_tm:ApptType</a> <a href="#">mailxml_tm:MailClass</a> <a href="#">mailxml_tm:Perishable</a> <a href="#">mailxml_tm:ApptStartTime</a> <a href="#">mailxml_tm:ApptEndTime</a> <a href="#">mailxml_tm:ApplyTiers</a>
used by	elements <a href="#">DeliveryApptQueryRequest/SlotAvailability</a> <a href="#">DeliveryApptQueryResponse/QueryResults/SlotAvailability</a>

### element slotAvailabilityType/ApptType

diagram																
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>															
type	<a href="#">mailxml_base:apptTypeType</a>															
properties	isRef 0 content simple															
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Pallet</td> <td></td> </tr> <tr> <td>enumeration</td> <td>DropAndPick</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Speedline</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Bedload</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	enumeration	Pallet		enumeration	DropAndPick		enumeration	Speedline		enumeration	Bedload	
Kind	Value	annotation														
enumeration	Pallet															
enumeration	DropAndPick															
enumeration	Speedline															
enumeration	Bedload															

### element slotAvailabilityType/MailClass

diagram	
---------	--

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:mailClassType</b>
properties	isRef 0 minOcc 1 maxOcc unbounded content simple
facets	Kind Value annotation enumeration 1 enumeration 2 enumeration 3 enumeration 4 enumeration 6

#### element slotAvailabilityType/Perishable

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation enumeration Yes enumeration No

#### element slotAvailabilityType/ApptStartTime

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:dateTime</b>
properties	isRef 0 content simple

#### element slotAvailabilityType/ApptEndTime

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:dateTime</b>
properties	isRef 0 content simple

**element slotAvailabilityType/ApplyTiers**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

**complexType staleContentNotificationElementType**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
children	<a href="#">mailxml_tm:ConsigneeFacility</a> <a href="#">mailxml_tm:ConsigneeContentID</a> <a href="#">mailxml_tm:NumberOfDaysStale</a> <a href="#">mailxml_tm:DestinationEntry</a>
used by	element <a href="#">StaleContentNotification/StaleContentNotificationElement</a>

**element staleContentNotificationElementType/ConsigneeFacility**


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm

type	<b>mailxml_defs:consigneeFacilityType</b>
properties	isRef 0 minOcc 0 maxOcc 1 content complex
children	<b>mailxml_defs:CompanyName</b> <b>mailxml_defs:FacilityNumber</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityAddress</b> <b>mailxml_defs:FacilityName</b> <b>mailxml_defs:FacilityType</b> <b>mailxml_defs:URL</b> <b>mailxml_defs:CommonContact</b>

#### element **staleContentNotificationElementType/ConsigneeContentID**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:s12</b>
properties	isRef 0 content simple
facets	Kind Value annotation minLength 1 maxLength 12 whiteSpace preserve

#### element **staleContentNotificationElementType/NumberOfDaysStale**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:ns02</b>
properties	isRef 0 content simple
facets	Kind Value annotation pattern [0-9]{2}

#### element **staleContentNotificationElementType/DestinationEntry**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

**complexType trailerInfoType**

diagram	<pre> sequenceDiagram     trailerInfoType --&gt; *     * --&gt; mailxml_tm:Trailer     mailxml_tm:Trailer ..&gt; *     * --&gt; mailxml_tm:Carrier     mailxml_tm:Carrier ..&gt; mailxml_tm:BillOfLadingNumber   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
children	<a href="#">mailxml_tm:Trailer</a> <a href="#">mailxml_tm:Carrier</a> <a href="#">mailxml_tm:BillOfLadingNumber</a>
used by	elements <a href="#">deliveryApptTransportationUpdateResponseType/DeliveryApptTransportationAccept</a> <a href="#">ConsigneeGoodsReceipt/TrailerInfo</a> <a href="#">ConsigneeGoodsReceiptDelivery/TrailerInfo</a> <a href="#">DeliveryApptCancelCreateRequest/TrailerInfo</a> <a href="#">DeliveryApptCreateRequest/TrailerInfo</a> <a href="#">DeliveryApptQueryRequest/TrailerInfo</a> <a href="#">DeliveryApptQueryResponse/QueryResults/TrailerInfo</a> <a href="#">DeliveryApptUpdate/TrailerInfo</a> <a href="#">DeliveryApptUpdateRequest/TrailerInfo</a> <a href="#">DeliveryApptShellCreateRequest/TrailerInfo</a> <a href="#">DeliveryApptShellUpdateRequest/TrailerInfo</a> <a href="#">DeliveryReApptRequest/TrailerInfo</a> <a href="#">UnscheduledConsigneeGoodsReceipt/TrailerInfo</a> <a href="#">UnscheduledConsigneeGoodsReceiptDelivery/TrailerInfo</a> <a href="#">deliveryApptAcceptType/TrailerInfo</a> <a href="#">deliveryApptTransportationUpdateRequestType/TrailerInfo</a> <a href="#">deliveryApptUpdateAcceptType/TrailerInfo</a> <a href="#">deliveryApptShellAcceptType/TrailerInfo</a> <a href="#">PartnerApptBlockType/TrailerInfo</a>

**element trailerInfoType/Trailer**

diagram	<pre> sequenceDiagram     trailerInfoType --&gt; *     * --&gt; mailxml_tm:Trailer     mailxml_tm:Trailer ..&gt; *     * --&gt; mailxml_tm:trailerType     mailxml_tm:trailerType ..&gt; *     * --&gt; mailxml_tm:TrailerNumber     mailxml_tm:trailerType ..&gt; *     * --&gt; mailxml_tm:TrailerLength   </pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:trailerType</a>
properties	isRef 0 minOcc 0 maxOcc 2 content complex
children	<a href="#">mailxml_tm:TrailerNumber</a> <a href="#">mailxml_tm:TrailerLength</a>

### element trailerInfoType/Carrier

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:carrierType</a>
properties	isRef 0 minOcc 0 maxOcc 1 content complex
children	<a href="#">mailxml_tm:CarrierName</a> <a href="#">mailxml_tm:CarrierCRID</a> <a href="#">mailxml_tm:CarrierAddress</a> <a href="#">mailxml_tm:URL</a> <a href="#">mailxml_tm:CommonContact</a>

### element trailerInfoType/BillOfLadingNumber


diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_base:s15</a>
properties	isRef 0 minOcc 1 maxOcc 2 content simple
facets	Kind Value annotation minLength 1 maxLength 15 whiteSpace preserve

### complexType trailerType


diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
children	<a href="#">mailxml_tm:TrailerNumber</a> <a href="#">mailxml_tm:TrailerLength</a>

used by	element <a href="#">trailerInfoType/Trailer</a>
---------	---

element **trailerType/TrailerNumber**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s12</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>12</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	12		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	12												
whiteSpace	preserve												

element **trailerType/TrailerLength**

diagram																			
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																		
type	<b>mailxml_base:trailerLengthType</b>																		
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple										
isRef	0																		
minOcc	0																		
maxOcc	1																		
content	simple																		
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>enumeration</td><td>20ft</td><td></td></tr> <tr> <td>enumeration</td><td>40ft</td><td></td></tr> <tr> <td>enumeration</td><td>45ft</td><td></td></tr> <tr> <td>enumeration</td><td>48ft</td><td></td></tr> <tr> <td>enumeration</td><td>53ft</td><td></td></tr> </table>	Kind	Value	annotation	enumeration	20ft		enumeration	40ft		enumeration	45ft		enumeration	48ft		enumeration	53ft	
Kind	Value	annotation																	
enumeration	20ft																		
enumeration	40ft																		
enumeration	45ft																		
enumeration	48ft																		
enumeration	53ft																		

### complexType **transportationContainerBlockType**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
children	<a href="#">mailxml_tm:TransportationID</a> <a href="#">mailxml_tm:StopDesignator</a> <a href="#">mailxml_tm:ContentsBarcode</a> <a href="#">mailxml_tm:ContentsBarcodeType</a> <a href="#">mailxml_tm:ContentsBarcodeStatus</a> <a href="#">mailxml_tm:BarcodeConstructCode</a> <a href="#">mailxml_tm:ThirdPartyJobID</a> <a href="#">mailxml_tm:FASTContentID</a> <a href="#">mailxml_tm:ActualShipperArrivalDate</a>
used by	element <a href="#">transportationGeoDataBlockType/Containers</a>

### element **transportationContainerBlockType/TransportationID**


diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:s05</b>
properties	isRef 0 content simple
facets	Kind Value annotation minLength 1 maxLength 5 whiteSpace preserve

### element **transportationContainerBlockType/StopDesignator**


diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:s10</b>
properties	isRef 0 content simple
facets	Kind Value annotation

	<pre>minLength    1 maxLength    10 whiteSpace   preserve</pre>
--	---


#### element **transportationContainerBlockType/ContentsBarcode**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s05</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>5</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	5		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	5												
whiteSpace	preserve												

#### element **transportationContainerBlockType/ContentsBarcodeType**


diagram																
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm															
type	<b>mailxml_tm:contentsBarcodeTypeType</b>															
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple							
isRef	0															
minOcc	0															
maxOcc	1															
content	simple															
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>enumeration</td><td>A</td><td></td></tr> <tr> <td>enumeration</td><td>B</td><td></td></tr> <tr> <td>enumeration</td><td>D</td><td></td></tr> <tr> <td>enumeration</td><td>O</td><td></td></tr> </table>	Kind	Value	annotation	enumeration	A		enumeration	B		enumeration	D		enumeration	O	
Kind	Value	annotation														
enumeration	A															
enumeration	B															
enumeration	D															
enumeration	O															

#### element **transportationContainerBlockType/ContentsBarcodeStatus**


diagram										
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm									
type	<b>mailxml_tm:contentsBarcodeStatusType</b>									
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple	
isRef	0									
minOcc	0									
maxOcc	1									
content	simple									
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>enumeration</td><td>A</td><td></td></tr> <tr> <td>enumeration</td><td>B</td><td></td></tr> </table>	Kind	Value	annotation	enumeration	A		enumeration	B	
Kind	Value	annotation								
enumeration	A									
enumeration	B									

	enumeration C enumeration D enumeration E enumeration F enumeration G enumeration H enumeration O
--	---


**element transportationContainerBlockType/BarcodeConstructCode**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s05</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 5 whiteSpace preserve

**element transportationContainerBlockType/ThirdPartyJobID**


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s08</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 8 whiteSpace preserve

**element transportationContainerBlockType/FASTContentID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s09</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple

facets	Kind minLength maxLength whiteSpace	Value 1 9 preserve	annotation
--------	--	-----------------------------	------------


#### element **transportationContainerBlockType/ActualShipperArrivalDateTime**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:dateTime</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple


#### complexType **transportationContainerStatusBlockType**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
children	<a href="#">mailxml_tm:ContentsBarcode</a> <a href="#">mailxml_tm:ScanDateTime</a> <a href="#">mailxml_tm:Latitude</a> <a href="#">mailxml_tm:Longitude</a> <a href="#">mailxml_tm:LocationDescription</a> <a href="#">mailxml_tm:City</a> <a href="#">mailxml_tm:State</a> <a href="#">mailxml_tm:ZIP</a> <a href="#">mailxml_tm:ScanEvent</a> <a href="#">mailxml_tm:UserOptionField</a> <a href="#">mailxml_tm:AppointmentNumber</a> <a href="#">mailxml_tm:AppointmentNumberIdentifier</a>
used by	element <a href="#">DispatchContainerInfoNotification/TransportationContainerStatusBlock</a>

#### element transportationContainerStatusBlockType/ContentsBarcode

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s05</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>5</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	5		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	5												
whiteSpace	preserve												

#### element transportationContainerStatusBlockType/ScanDateTime

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>xs:dateTime</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple
isRef	0								
minOcc	0								
maxOcc	1								
content	simple								

#### element transportationContainerStatusBlockType/Latitude


diagram										
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm									
type	<b>mailxml_base:dec18-8</b>									
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple	
isRef	0									
minOcc	0									
maxOcc	1									
content	simple									
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>totalDigits</td><td>18</td><td></td></tr> <tr> <td>fractionDigits</td><td>8</td><td></td></tr> </table>	Kind	Value	annotation	totalDigits	18		fractionDigits	8	
Kind	Value	annotation								
totalDigits	18									
fractionDigits	8									

#### element transportationContainerStatusBlockType/Longitude

diagram					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm				
type	<b>mailxml_base:dec18-8</b>				
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> </table>	isRef	0	minOcc	0
isRef	0				
minOcc	0				

	maxOcc 1 content simple
facets	Kind Value annotation totalDigits 18 fractionDigits 8

#### element **transportationContainerStatusBlockType/LocationDescription**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
properties	isRef 0 minOcc 0 maxOcc 1

#### element **transportationContainerStatusBlockType/City**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s45</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple

facets	Kind Value annotation minLength 1 maxLength 45 whiteSpace preserve
--------	---

#### element **transportationContainerStatusBlockType/State**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:stateCode</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple

facets	Kind Value annotation enumeration AA enumeration AE enumeration AP enumeration AL enumeration AK enumeration AS enumeration AZ enumeration AR
--------	---

	enumeration	CA
	enumeration	CO
	enumeration	CT
	enumeration	DE
	enumeration	DC
	enumeration	FM
	enumeration	FL
	enumeration	GA
	enumeration	GU
	enumeration	HI
	enumeration	IL
	enumeration	IN
	enumeration	IA
	enumeration	ID
	enumeration	KS
	enumeration	KY
	enumeration	LA
	enumeration	MH
	enumeration	MD
	enumeration	MA
	enumeration	ME
	enumeration	MO
	enumeration	MI
	enumeration	MN
	enumeration	MS
	enumeration	MT
	enumeration	NE
	enumeration	NH
	enumeration	NV
	enumeration	NJ
	enumeration	NM
	enumeration	NY
	enumeration	NC
	enumeration	ND
	enumeration	MP
	enumeration	OH
	enumeration	OR
	enumeration	OK
	enumeration	PW
	enumeration	PA
	enumeration	PR
	enumeration	RI
	enumeration	SC
	enumeration	SD
	enumeration	TN
	enumeration	TX

	enumeration UT enumeration VT enumeration VI enumeration VA enumeration WA enumeration WV enumeration WI enumeration WY
--	--

**element transportationContainerStatusBlockType/ZIP**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_defs:zipCode</b>
properties	isRef 0 minOcc 0 maxOcc 1 content complex
facets	Kind Value annotation pattern [0-9]{9}

**element transportationContainerStatusBlockType/ScanEvent**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_tm:scanEventType</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation enumeration A enumeration B enumeration U enumeration E enumeration L enumeration F enumeration G enumeration O

**element transportationContainerStatusBlockType/UserOptionField**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm

type	<b>mailxml_base:s10</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 10 whiteSpace preserve


#### element **transportationContainerStatusBlockType/AppointmentNumber**

diagram	 <a href="#">mailxml_tm:AppointmentNumber</a>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:s10</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 10 whiteSpace preserve

#### element **transportationContainerStatusBlockType/AppointmentNumberIdentifier**

diagram	 <a href="#">mailxml_tm:AppointmentNumb...</a>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:appointmentNumberIdentifierType</a>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation enumeration F enumeration D enumeration O enumeration P enumeration Q enumeration R enumeration S enumeration T enumeration U

### complexType transportationDetailBlockType

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
children	<a href="#">mailxml_tm:TransportationID</a> <a href="#">mailxml_tm:StopDesignator</a> <a href="#">mailxml_tm:AppointmentNumber</a> <a href="#">mailxml_tm:AppointmentNumberIdentifier</a> <a href="#">mailxml_tm:FASTSchedulerID</a> <a href="#">mailxml_tm:EstimatedArrivalDateTime</a> <a href="#">mailxml_tm:ActualShipperArrivalDateTime</a> <a href="#">mailxml_tm:ActualReceiverArrivalDateTime</a> <a href="#">mailxml_tm:StopStatus</a>
used by	element <a href="#">transportationSummaryBlockType/Stops</a>

### element transportationDetailBlockType/TransportationID

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_base:s05</a>
properties	isRef 0 content simple
facets	Kind Value annotation minLength 1 maxLength 5 whiteSpace preserve

### element transportationDetailBlockType/StopDesignator

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_base:s10</a>
properties	isRef 0 content simple
facets	Kind Value annotation

	<pre>minLength    1 maxLength    10 whiteSpace   preserve</pre>
--	---

#### element **transportationDetailBlockType/AppointmentNumber**

diagram	<a href="#">mailxml_tm:AppointmentNumber</a>												
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>												
type	<a href="#">mailxml_base:s10</a>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>10</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	10		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	10												
whiteSpace	preserve												

#### element **transportationDetailBlockType/AppointmentNumberIdentifier**


diagram	<a href="#">mailxml_tm:AppointmentNumb...</a>																														
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																														
type	<a href="#">mailxml_tm:appointmentNumberIdentifierType</a>																														
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple																						
isRef	0																														
minOcc	0																														
maxOcc	1																														
content	simple																														
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>F</td> <td></td> </tr> <tr> <td>enumeration</td> <td>D</td> <td></td> </tr> <tr> <td>enumeration</td> <td>O</td> <td></td> </tr> <tr> <td>enumeration</td> <td>P</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Q</td> <td></td> </tr> <tr> <td>enumeration</td> <td>R</td> <td></td> </tr> <tr> <td>enumeration</td> <td>S</td> <td></td> </tr> <tr> <td>enumeration</td> <td>T</td> <td></td> </tr> <tr> <td>enumeration</td> <td>U</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	enumeration	F		enumeration	D		enumeration	O		enumeration	P		enumeration	Q		enumeration	R		enumeration	S		enumeration	T		enumeration	U	
Kind	Value	annotation																													
enumeration	F																														
enumeration	D																														
enumeration	O																														
enumeration	P																														
enumeration	Q																														
enumeration	R																														
enumeration	S																														
enumeration	T																														
enumeration	U																														

#### element **transportationDetailBlockType/FASTSchedulerID**


diagram	<a href="#">mailxml_tm:FASTSchedulerID</a>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_base:s12</a>

properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 12 whiteSpace preserve


#### element **transportationDetailBlockType/EstimatedArrivalDateTime**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:dateTime</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple

#### element **transportationDetailBlockType/ActualShipperArrivalDateTime**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:dateTime</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple

#### element **transportationDetailBlockType/ActualReceiverArrivalDateTime**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>xs:dateTime</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple

#### element **transportationDetailBlockType/StopStatus**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_tm:stopStatusType</b>

properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation enumeration P enumeration A enumeration U


### complexType transportationGeoDataBlockType

diagram	<pre> classDiagram     class transportationGeoDataBlockType {         TransportationID         LocationDateTime         Latitude         Longitude         City         State         ZIP         LocationStatus         Containers &lt;--&gt; 1..∞     } </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
children	<a href="#">mailxml_tm:TransportationID</a> <a href="#">mailxml_tm:LocationDateTime</a> <a href="#">mailxml_tm:Latitude</a> <a href="#">mailxml_tm:Longitude</a> <a href="#">mailxml_tm:City</a> <a href="#">mailxml_tm:State</a> <a href="#">mailxml_tm:ZIP</a> <a href="#">mailxml_tm:LocationStatus</a> <a href="#">mailxml_tm:Containers</a>
used by	element <a href="#">DispatchContainerInfoNotification/TransportationGeoDataBlock</a>

### element transportationGeoDataBlockType/TransportationID

diagram	<pre> classDiagram     class TransportationID {         &lt; -- mailxml_base:s05     } </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:s05</b>
properties	isRef 0 content simple
facets	Kind Value annotation minLength 1 maxLength 5 whiteSpace preserve

#### element transportationGeoDataBlockType/LocationDateTime

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>xs:dateTime</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple
isRef	0								
minOcc	0								
maxOcc	1								
content	simple								

#### element transportationGeoDataBlockType/Latitude

diagram										
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm									
type	<b>mailxml_base:dec18-8</b>									
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple	
isRef	0									
minOcc	0									
maxOcc	1									
content	simple									
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>totalDigits</td><td>18</td><td></td></tr> <tr> <td>fractionDigits</td><td>8</td><td></td></tr> </table>	Kind	Value	annotation	totalDigits	18		fractionDigits	8	
Kind	Value	annotation								
totalDigits	18									
fractionDigits	8									

#### element transportationGeoDataBlockType/Longitude


diagram										
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm									
type	<b>mailxml_base:dec18-8</b>									
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple	
isRef	0									
minOcc	0									
maxOcc	1									
content	simple									
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>totalDigits</td><td>18</td><td></td></tr> <tr> <td>fractionDigits</td><td>8</td><td></td></tr> </table>	Kind	Value	annotation	totalDigits	18		fractionDigits	8	
Kind	Value	annotation								
totalDigits	18									
fractionDigits	8									

#### element transportationGeoDataBlockType/City

diagram							
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm						
type	<b>mailxml_base:s45</b>						
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1
isRef	0						
minOcc	0						
maxOcc	1						

	content	simple	
facets	Kind	Value	annotation
	minLength	1	
	maxLength	45	
	whiteSpace	preserve	


element **transportationGeoDataBlockType/State**

diagram															
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm														
type	<b>mailxml_base:stateCode</b>														
properties	<table> <tr> <td>isRef</td> <td>0</td> <td></td> </tr> <tr> <td>minOcc</td> <td>0</td> <td></td> </tr> <tr> <td>maxOcc</td> <td>1</td> <td></td> </tr> <tr> <td>content</td> <td>simple</td> <td></td> </tr> </table>			isRef	0		minOcc	0		maxOcc	1		content	simple	
isRef	0														
minOcc	0														
maxOcc	1														
content	simple														
facets	Kind	Value	annotation												
	enumeration	AA													
	enumeration	AE													
	enumeration	AP													
	enumeration	AL													
	enumeration	AK													
	enumeration	AS													
	enumeration	AZ													
	enumeration	AR													
	enumeration	CA													
	enumeration	CO													
	enumeration	CT													
	enumeration	DE													
	enumeration	DC													
	enumeration	FM													
	enumeration	FL													
	enumeration	GA													
	enumeration	GU													
	enumeration	HI													
	enumeration	IL													
	enumeration	IN													
	enumeration	IA													
	enumeration	ID													
	enumeration	KS													
	enumeration	KY													
	enumeration	LA													
	enumeration	MH													
	enumeration	MD													
	enumeration	MA													
	enumeration	ME													
	enumeration	MO													


  |  |

	enumeration MI
	enumeration MN
	enumeration MS
	enumeration MT
	enumeration NE
	enumeration NH
	enumeration NV
	enumeration NJ
	enumeration NM
	enumeration NY
	enumeration NC
	enumeration ND
	enumeration MP
	enumeration OH
	enumeration OR
	enumeration OK
	enumeration PW
	enumeration PA
	enumeration PR
	enumeration RI
	enumeration SC
	enumeration SD
	enumeration TN
	enumeration TX
	enumeration UT
	enumeration VT
	enumeration VI
	enumeration VA
	enumeration WA
	enumeration WV
	enumeration WI
	enumeration WY


#### element **transportationGeoDataBlockType/ZIP**

diagram									
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>								
type	<b>mailxml_defs:zipCode</b>								
properties	<table> <tr><td>isRef</td><td>0</td></tr> <tr><td>minOcc</td><td>0</td></tr> <tr><td>maxOcc</td><td>1</td></tr> <tr><td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
facets	<table> <tr><td>Kind</td><td>Value</td><td>annotation</td></tr> <tr><td>pattern</td><td>[0-9]{9}</td><td></td></tr> </table>	Kind	Value	annotation	pattern	[0-9]{9}			
Kind	Value	annotation							
pattern	[0-9]{9}								

### element transportationGeoDataBlockType/LocationStatus

diagram																									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																								
type	<a href="#">mailxml_tm:locationStatusType</a>																								
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	content	simple																				
isRef	0																								
content	simple																								
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>P</td> <td></td> </tr> <tr> <td>enumeration</td> <td>O</td> <td></td> </tr> <tr> <td>enumeration</td> <td>I</td> <td></td> </tr> <tr> <td>enumeration</td> <td>F</td> <td></td> </tr> <tr> <td>enumeration</td> <td>U</td> <td></td> </tr> <tr> <td>enumeration</td> <td>M</td> <td></td> </tr> <tr> <td>enumeration</td> <td>D</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	enumeration	P		enumeration	O		enumeration	I		enumeration	F		enumeration	U		enumeration	M		enumeration	D	
Kind	Value	annotation																							
enumeration	P																								
enumeration	O																								
enumeration	I																								
enumeration	F																								
enumeration	U																								
enumeration	M																								
enumeration	D																								

### element transportationGeoDataBlockType/Containers

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<a href="#">mailxml_tm:transportationContainerBlockType</a>								
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>1</td> </tr> <tr> <td>maxOcc</td> <td>unbounded</td> </tr> <tr> <td>content</td> <td>complex</td> </tr> </table>	isRef	0	minOcc	1	maxOcc	unbounded	content	complex
isRef	0								
minOcc	1								
maxOcc	unbounded								
content	complex								
children	<a href="#">mailxml_tm:TransportationID</a> <a href="#">mailxml_tm:StopDesignator</a> <a href="#">mailxml_tm:ContentsBarcode</a> <a href="#">mailxml_tm:ContentsBarcodeType</a> <a href="#">mailxml_tm:ContentsBarcodeStatus</a> <a href="#">mailxml_tm:BarcodeConstructCode</a> <a href="#">mailxml_tm:ThirdPartyJobID</a> <a href="#">mailxml_tm:FASTContentID</a> <a href="#">mailxml_tm:ActualShipperArrivalDate</a>								

### complexType transportationSummaryBlockType

diagram	<pre>graph LR; A[transportationSummaryBlockTy...]; A --&gt; B[mailxml_tm:TransportationID]; A --&gt; C[mailxml_tm:LoadTruckDispatch...]; A --&gt; D[mailxml_tm:TargetShipDateTime]; A --&gt; E[mailxml_tm:Stops]; E --- F[0..∞]</pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
children	<a href="#">mailxml_tm:TransportationID</a> <a href="#">mailxml_tm:LoadTruckDispatchNumber</a> <a href="#">mailxml_tm:TargetShipDateTime</a> <a href="#">mailxml_tm:Stops</a>
used by	element <a href="#">DispatchContainerInfoNotification/TransportationSummaryBlock</a>

### element transportationSummaryBlockType/TransportationID

diagram	<pre>graph LR; A[mailxml_tm:TransportationID]</pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:s05</b>
properties	isRef 0 content simple
facets	Kind Value annotation minLength 1 maxLength 5 whiteSpace preserve


### element transportationSummaryBlockType/LoadTruckDispatchNumber

diagram	<pre>graph LR; A[mailxml_tm:LoadTruckDispatch...]</pre>
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>mailxml_base:s10</b>
properties	isRef 0 content simple
facets	Kind Value annotation minLength 1 maxLength 10 whiteSpace preserve


element **transportationSummaryBlockType/TargetShipDateTime**

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>xs:dateTime</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple
isRef	0								
minOcc	0								
maxOcc	1								
content	simple								

element **transportationSummaryBlockType/Stops**

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>mailxml_tm:transportationDetailBlockType</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	unbounded	content	complex
isRef	0								
minOcc	0								
maxOcc	unbounded								
content	complex								
children	<a href="#">mailxml_tm:TransportationID</a> <a href="#">mailxml_tm:StopDesignator</a> <a href="#">mailxml_tm:AppointmentNumber</a> <a href="#">mailxml_tm:AppointmentNumberIdentifier</a> <a href="#">mailxml_tm:FASTSchedulerID</a> <a href="#">mailxml_tm:EstimatedArrivalDateTime</a> <a href="#">mailxml_tm:ActualShipperArrivalDateTime</a> <a href="#">mailxml_tm:ActualReceiverArrivalDateTime</a> <a href="#">mailxml_tm:StopStatus</a>								

### complexType trayHandlingUnitType

diagram																												
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																											
children	<a href="#">mailxml_tm:PreSortLevel</a> <a href="#">mailxml_tm:IMpb</a> <a href="#">mailxml_tm:IMtb</a>																											
used by	element <a href="#">bedloadUnitType/Trays</a>																											
attributes	<table> <tr> <td>Name</td> <td><a href="#">mailxml_tm:Count</a></td> <td>Type</td> <td><a href="#">xs:nonNegativeInteger</a></td> <td>Use</td> <td>required</td> <td>Default</td> <td>Fixed</td> <td>annotation</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td><a href="#">mailxml_tm&gt;Type</a></td> <td></td> <td><a href="#">mailxml_base:trayType</a></td> <td></td> <td></td> <td></td> <td></td> <td>MixedLengthTrays</td> </tr> </table>	Name	<a href="#">mailxml_tm:Count</a>	Type	<a href="#">xs:nonNegativeInteger</a>	Use	required	Default	Fixed	annotation											<a href="#">mailxml_tm&gt;Type</a>		<a href="#">mailxml_base:trayType</a>					MixedLengthTrays
Name	<a href="#">mailxml_tm:Count</a>	Type	<a href="#">xs:nonNegativeInteger</a>	Use	required	Default	Fixed	annotation																				
	<a href="#">mailxml_tm&gt;Type</a>		<a href="#">mailxml_base:trayType</a>					MixedLengthTrays																				


### attribute trayHandlingUnitType/@Count

namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">xs:nonNegativeInteger</a>
properties	isRef 0 use required


### attribute trayHandlingUnitType/@Type

namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																		
type	<a href="#">mailxml_base:trayType</a>																		
properties	isRef 0 default MixedLengthTrays																		
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>enumeration</td> <td>MixedLengthTrays</td> <td></td> </tr> <tr> <td>enumeration</td> <td>1ft Tray</td> <td></td> </tr> <tr> <td>enumeration</td> <td>2ft Tray</td> <td></td> </tr> <tr> <td>enumeration</td> <td>EMM Tray</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Flat Tub</td> <td></td> </tr> </table>	Kind	Value	annotation	enumeration	MixedLengthTrays		enumeration	1ft Tray		enumeration	2ft Tray		enumeration	EMM Tray		enumeration	Flat Tub	
Kind	Value	annotation																	
enumeration	MixedLengthTrays																		
enumeration	1ft Tray																		
enumeration	2ft Tray																		
enumeration	EMM Tray																		
enumeration	Flat Tub																		


### element trayHandlingUnitType/PreSortLevel

diagram																			
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																		
type	<a href="#">mailxml_tm:presortType</a>																		
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>complex</td></tr> </table>	isRef	0	minOcc	0	maxOcc	unbounded	content	complex										
isRef	0																		
minOcc	0																		
maxOcc	unbounded																		
content	complex																		
attributes	<table> <tr> <td>Name</td><td>Type</td><td>Use</td><td>Default</td><td>Fixed</td><td>annotation</td></tr> <tr> <td><a href="#">mailxml_tm:ContainerLevel</a></td><td><a href="#">mailxml_base:containerLevelType</a></td><td>required</td><td></td><td></td><td></td></tr> <tr> <td><a href="#">mailxml_tm:Count</a></td><td><a href="#">xs:nonNegativeInteger</a></td><td>required</td><td></td><td></td><td></td></tr> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:ContainerLevel</a>	<a href="#">mailxml_base:containerLevelType</a>	required				<a href="#">mailxml_tm:Count</a>	<a href="#">xs:nonNegativeInteger</a>	required			
Name	Type	Use	Default	Fixed	annotation														
<a href="#">mailxml_tm:ContainerLevel</a>	<a href="#">mailxml_base:containerLevelType</a>	required																	
<a href="#">mailxml_tm:Count</a>	<a href="#">xs:nonNegativeInteger</a>	required																	


### element trayHandlingUnitType/IMpb

diagram										
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm									
type	<a href="#">mailxml_base:IMpbType</a>									
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple	
isRef	0									
minOcc	0									
maxOcc	1									
content	simple									
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>21</td><td></td></tr> <tr> <td>maxLength</td><td>34</td><td></td></tr> </table>	Kind	Value	annotation	minLength	21		maxLength	34	
Kind	Value	annotation								
minLength	21									
maxLength	34									

### element trayHandlingUnitType/IMtb

diagram										
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm									
type	<a href="#">mailxml_base:IMtbType</a>									
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple	
isRef	0									
minOcc	0									
maxOcc	1									
content	simple									
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>24</td><td></td></tr> <tr> <td>maxLength</td><td>24</td><td></td></tr> </table>	Kind	Value	annotation	minLength	24		maxLength	24	
Kind	Value	annotation								
minLength	24									
maxLength	24									

**complexType uspsClosedBySVType**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
children	<a href="#">mailxml_tm:AutoScan</a> <a href="#">mailxml_tm:ManualScan</a>
used by	element <a href="#">uspsDetailType/USPSClosedBySV</a>

**element uspsClosedBySVType/AutoScan**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>xs:nonNegativeInteger</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple

**element uspsClosedBySVType/ManualScan**

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<b>xs:nonNegativeInteger</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple

complexType **uspsContainerInfoType**

diagram	<pre> classDiagram     class uspsContainerInfoType     class mailxml_tm::MailOwnerCRID     class mailxml_tm::MailOwnerID     class mailxml_tm::USPSPublicationID     class mailxml_tm::ActualPieceCount     class mailxml_tm::ContainerWeight     class mailxml_tm::IMcb     class mailxml_tm::IMcblInfo     class mailxml_tm::SiblingBarcode     class mailxml_tm::PostInductionStatus     class mailxml_tm::ContainerDestination3digitZIP     class mailxml_tm::ContainerDestination5digitZIP      uspsContainerInfoType &lt; --&gt; MailOwnerCRID     uspsContainerInfoType &lt; --&gt; MailOwnerID     uspsContainerInfoType &lt; --&gt; USPSPublicationID     uspsContainerInfoType &lt; --&gt; ActualPieceCount     uspsContainerInfoType &lt; --&gt; ContainerWeight     uspsContainerInfoType &lt; --&gt; IMcb     uspsContainerInfoType &lt; --&gt; IMcblInfo     uspsContainerInfoType &lt; --&gt; SiblingBarcode     uspsContainerInfoType &lt; --&gt; PostInductionStatus     uspsContainerInfoType &lt; --&gt; ContainerDestination3digitZIP     uspsContainerInfoType &lt; --&gt; ContainerDestination5digitZIP   </pre>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
children	<a href="#">mailxml_tm::MailOwnerCRID</a> <a href="#">mailxml_tm::MailOwnerID</a> <a href="#">mailxml_tm::USPSPublicationID</a> <a href="#">mailxml_tm::ActualPieceCount</a> <a href="#">mailxml_tm::ContainerWeight</a> <a href="#">mailxml_tm::IMcb</a> <a href="#">mailxml_tm::IMcblInfo</a> <a href="#">mailxml_tm::SiblingBarcode</a> <a href="#">mailxml_tm::PostInductionStatus</a> <a href="#">mailxml_tm::ContainerDestination3digitZIP</a> <a href="#">mailxml_tm::ContainerDestination5digitZIP</a>
used by	elements <a href="#">bedloadUnitType/USPSCContainerInfo</a> <a href="#">palletUnitType/USPSCContainerInfo</a> <a href="#">palletPresortType/USPSCContainerInfo</a>

element **uspsContainerInfoType/MailOwnerCRID**


diagram	<pre> classDiagram     class mailxml_tm::MailOwnerCRID     0..1   </pre>									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm									
type	<b>mailxml_base:CRIDType</b>									
properties	isRef 0 minOcc 0 maxOcc unbounded content simple									
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>15</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	15	
Kind	Value	annotation								
minLength	1									
maxLength	15									

	pattern	([0-9])*
--	---------	----------


#### element **uspsContainerInfoType/MailOwnerID**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s12</b>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>unbounded</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	unbounded	content	simple				
isRef	0												
minOcc	0												
maxOcc	unbounded												
content	simple												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>12</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	12		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	12												
whiteSpace	preserve												


#### element **uspsContainerInfoType/USPSPublicationID**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s09</b>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>unbounded</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	unbounded	content	simple				
isRef	0												
minOcc	0												
maxOcc	unbounded												
content	simple												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>9</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	9		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	9												
whiteSpace	preserve												

#### element **uspsContainerInfoType/ActualPieceCount**

diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>xs:nonNegativeInteger</b>								
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple
isRef	0								
minOcc	0								
maxOcc	1								
content	simple								

### element **uspsContainerInfoType/ContainerWeight**

diagram	 mailxml_tm:ContainerWeight								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>xs:float</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple
isRef	0								
minOcc	0								
maxOcc	1								
content	simple								


### element **uspsContainerInfoType/IMcb**

diagram	 mailxml_tm:IMcb									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm									
type	<b>mailxml_base:IMcbType</b>									
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	content	simple					
isRef	0									
content	simple									
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>21</td><td></td></tr> <tr> <td>maxLength</td><td>24</td><td></td></tr> </table>	Kind	Value	annotation	minLength	21		maxLength	24	
Kind	Value	annotation								
minLength	21									
maxLength	24									

### element **uspsContainerInfoType/IMcbInfo**


diagram	 mailxml_tm:IMcbInfo									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm									
type	<b>mailxml_tm:IMcbInfoType</b>									
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple	
isRef	0									
minOcc	0									
maxOcc	1									
content	simple									
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>enumeration</td><td>Linked</td><td></td></tr> <tr> <td>enumeration</td><td>Scanned</td><td></td></tr> </table>	Kind	Value	annotation	enumeration	Linked		enumeration	Scanned	
Kind	Value	annotation								
enumeration	Linked									
enumeration	Scanned									

### element **uspsContainerInfoType/SiblingBarcode**

diagram	 mailxml_tm:SiblingBarcode 0..∞								
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>mailxml_base:IMcbType</b>								
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	unbounded	content	simple
isRef	0								
minOcc	0								
maxOcc	unbounded								
content	simple								
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> </table>	Kind	Value	annotation					
Kind	Value	annotation							

	minLength 21 maxLength 24
--	------------------------------

#### element **uspsContainerInfoType/PostInductionStatus**

diagram																																																													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																																												
type	<b>mailxml_defs:containerStatusType</b>																																																												
properties	isRef 0 minOcc 0 maxOcc 1 content simple																																																												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Accepted</td> <td></td> </tr> <tr> <td>enumeration</td> <td>OnHold</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Rejected</td> <td></td> </tr> <tr> <td>enumeration</td> <td>NotPaid</td> <td></td> </tr> <tr> <td>enumeration</td> <td>TransportationInfoUpdated</td> <td></td> </tr> <tr> <td>enumeration</td> <td>DispatchedforInduction</td> <td></td> </tr> <tr> <td>enumeration</td> <td>DispatchedforPickup</td> <td></td> </tr> <tr> <td>enumeration</td> <td>PickedUp</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Warehoused</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Planned</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Docked</td> <td></td> </tr> <tr> <td>enumeration</td> <td>MailReadyforPickUp</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Delivered</td> <td></td> </tr> <tr> <td>enumeration</td> <td>DepositedWithShipper</td> <td></td> </tr> <tr> <td>enumeration</td> <td>eDocSubmitted</td> <td></td> </tr> <tr> <td>enumeration</td> <td>MailReadytobeShipped</td> <td></td> </tr> <tr> <td>enumeration</td> <td>PostageFinalized</td> <td></td> </tr> <tr> <td>enumeration</td> <td>MailVerifiedAndReleased</td> <td></td> </tr> <tr> <td>enumeration</td> <td>MailInCopalPool</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	enumeration	Accepted		enumeration	OnHold		enumeration	Rejected		enumeration	NotPaid		enumeration	TransportationInfoUpdated		enumeration	DispatchedforInduction		enumeration	DispatchedforPickup		enumeration	PickedUp		enumeration	Warehoused		enumeration	Planned		enumeration	Docked		enumeration	MailReadyforPickUp		enumeration	Delivered		enumeration	DepositedWithShipper		enumeration	eDocSubmitted		enumeration	MailReadytobeShipped		enumeration	PostageFinalized		enumeration	MailVerifiedAndReleased		enumeration	MailInCopalPool	
Kind	Value	annotation																																																											
enumeration	Accepted																																																												
enumeration	OnHold																																																												
enumeration	Rejected																																																												
enumeration	NotPaid																																																												
enumeration	TransportationInfoUpdated																																																												
enumeration	DispatchedforInduction																																																												
enumeration	DispatchedforPickup																																																												
enumeration	PickedUp																																																												
enumeration	Warehoused																																																												
enumeration	Planned																																																												
enumeration	Docked																																																												
enumeration	MailReadyforPickUp																																																												
enumeration	Delivered																																																												
enumeration	DepositedWithShipper																																																												
enumeration	eDocSubmitted																																																												
enumeration	MailReadytobeShipped																																																												
enumeration	PostageFinalized																																																												
enumeration	MailVerifiedAndReleased																																																												
enumeration	MailInCopalPool																																																												

#### element **uspsContainerInfoType/ContainerDestination3digitZIP**

diagram							
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm						
type	<b>mailxml_base:ns03</b>						
properties	isRef 0 content simple						
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[0-9]{3}</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	pattern	[0-9]{3}	
Kind	Value	annotation					
pattern	[0-9]{3}						

**element `uspsContainerInfoType/ContainerDestination5digitZIP`**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<code>mailxml_base:ns05</code>
properties	isRef 0 content simple
facets	Kind Value annotation pattern [0-9]{5}

**complexType `uspsDetailType`**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
children	<a href="#">mailxml_tm:USPSMultiApptID</a> <a href="#">mailxml_tm:USPSClosedBySV</a>
used by	element <a href="#">apptBlockGoodsType/USPSDetail</a>

**element `uspsDetailType/USPSMultiApptID`**


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<code>mailxml_base:s12</code>
properties	isRef 0 minOcc 0 maxOcc unbounded content simple
facets	Kind Value annotation minLength 1 maxLength 12 whiteSpace preserve

**element `uspsDetailType/USPSClosedBySV`**

diagram	
---------	--

namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>								
type	<a href="#"><b>mailxml_tm:uspsClosedBySVType</b></a>								
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>complex</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	complex
isRef	0								
minOcc	0								
maxOcc	1								
content	complex								
children	<a href="#"><b>mailxml_tm:AutoScan</b></a> <a href="#"><b>mailxml_tm:ManualScan</b></a>								

complexType **uspsSummaryType**



namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																		
children	<a href="#">mailxml_tm:DestinationDiscountIndicator</a> <a href="#">mailxml_tm:ZoneSkippingIndicator</a> <a href="#">mailxml_tm:FullServiceIndicator</a> <a href="#">mailxml_tm:elInductionIndicator</a> <a href="#">mailxml_tm:Pallets</a> <a href="#">mailxml_tm:Bedload</a> <a href="#">mailxml_tm:Perishable</a> <a href="#">mailxml_tm:MailClass</a> <a href="#">mailxml_tm:RateType</a> <a href="#">mailxml_tm:InHomeStart</a> <a href="#">mailxml_tm:InHomeEnd</a> <a href="#">mailxml_tm:ProcessingCategory</a> <a href="#">mailxml_tm:NewsIndicator</a> <a href="#">mailxml_tm:PriorityMailIndicator</a> <a href="#">mailxml_tm:VerificationLocation</a> <a href="#">mailxml_tm:EvsIndicator</a> <a href="#">mailxml_tm:MailContentName</a> <a href="#">mailxml_tm:MailPreparerID</a> <a href="#">mailxml_tm:MailPreparerCRID</a> <a href="#">mailxml_tm:AdvanceMailingID</a> <a href="#">mailxml_tm:EFileNumber</a> <a href="#">mailxml_tm:ContainsAutoMail</a>																		
used by	elements <a href="#">detailInfoType/USPSSummary</a> <a href="#">recurringApptBlockType/USPSSummary</a>																		
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><a href="#">mailxml_tm:SchedulerContentID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:ConsigneeContentID</a></td> <td><a href="#">mailxml_base:s12</a></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:SchedulerContentID</a>	<a href="#">mailxml_base:s12</a>					<a href="#">mailxml_tm:ConsigneeContentID</a>	<a href="#">mailxml_base:s12</a>				
Name	Type	Use	Default	Fixed	annotation														
<a href="#">mailxml_tm:SchedulerContentID</a>	<a href="#">mailxml_base:s12</a>																		
<a href="#">mailxml_tm:ConsigneeContentID</a>	<a href="#">mailxml_base:s12</a>																		

#### attribute uspsSummaryType/@SchedulerContentID

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<a href="#">mailxml_base:s12</a>												
properties	isRef 0												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>12</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	12		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	12												
whiteSpace	preserve												


#### attribute uspsSummaryType/@ConsigneeContentID

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<a href="#">mailxml_base:s12</a>												
properties	isRef 0												
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>12</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	12		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	12												
whiteSpace	preserve												


#### element uspsSummaryType/DestinationDiscountIndicator

diagram										
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm									
type	<a href="#">mailxml_base:yesNo</a>									
properties	isRef 0 content simple									
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Yes</td> <td></td> </tr> <tr> <td>enumeration</td> <td>No</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	enumeration	Yes		enumeration	No	
Kind	Value	annotation								
enumeration	Yes									
enumeration	No									


**element uspsSummaryType/ZoneSkippingIndicator**

diagram	 mailxml_tm:Zone SkippingIndica...
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation enumeration Yes enumeration No


**element uspsSummaryType/FullServiceIndicator**

diagram	 mailxml_tm:FullServiceIndicator
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation enumeration Yes enumeration No


**element uspsSummaryType/eInductionIndicator**

diagram	 mailxml_tm:eInductionIndicator
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation enumeration Yes enumeration No

### element uspsSummaryType/Pallets

diagram																									
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>																								
type	<a href="#">mailxml_tm:palletUnitType</a>																								
properties	<p>isRef 0  minOcc 0  maxOcc unbounded  content complex</p>																								
children	<a href="#">mailxml_tm:PalletPreSortLevel</a> <a href="#">mailxml_tm:USPSContainerInfo</a>																								
attributes	<table> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td><a href="#">mailxml_tm:Count</a></td> <td><a href="#">xs:nonNegativeInteger</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:HandlingUnitType</a></td> <td><a href="#">mailxml_base:palletHandlingUnitType</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> <tr> <td><a href="#">mailxml_tm:PalletType</a></td> <td><a href="#">mailxml_base:palletType</a></td> <td>required</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	<a href="#">mailxml_tm:Count</a>	<a href="#">xs:nonNegativeInteger</a>	required				<a href="#">mailxml_tm:HandlingUnitType</a>	<a href="#">mailxml_base:palletHandlingUnitType</a>	required				<a href="#">mailxml_tm:PalletType</a>	<a href="#">mailxml_base:palletType</a>	required			
Name	Type	Use	Default	Fixed	annotation																				
<a href="#">mailxml_tm:Count</a>	<a href="#">xs:nonNegativeInteger</a>	required																							
<a href="#">mailxml_tm:HandlingUnitType</a>	<a href="#">mailxml_base:palletHandlingUnitType</a>	required																							
<a href="#">mailxml_tm:PalletType</a>	<a href="#">mailxml_base:palletType</a>	required																							

### element uspsSummaryType/Bedload

diagram	
namespace	<a href="http://idealliance.org/Specs/mailxml23.0/mailxml_tm">http://idealliance.org/Specs/mailxml23.0/mailxml_tm</a>
type	<a href="#">mailxml_tm:bedloadUnitType</a>
properties	<p>isRef 0  minOcc 0  maxOcc 1  content complex</p>

children	<a href="#">mailxml_tm:USPSContainerInfo</a> <a href="#">mailxml_tm:Sacks</a> <a href="#">mailxml_tm:Trays</a> <a href="#">mailxml_tm:Parcels</a> <a href="#">mailxml_tm:Bundles</a>
----------	--

#### element **uspsSummaryType/Perishable**

diagram	 mailxml_tm:Perishable
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration Yes enumeration No

#### element **uspsSummaryType/MailClass**

diagram	 mailxml_tm:MailClass
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:mailClassType</b>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration 1 enumeration 2 enumeration 3 enumeration 4 enumeration 6

#### element **uspsSummaryType/RateType**

diagram	 mailxml_tm:RateType
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:rateType</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation enumeration R enumeration L enumeration B enumeration C enumeration S enumeration S1

	enumeration S2
	enumeration S3
	enumeration S4
	enumeration S5
	enumeration S6
	enumeration S7
	enumeration F
	enumeration A
	enumeration N
	enumeration P
	enumeration T
	enumeration D
	enumeration X
	enumeration H
	enumeration M
	enumeration Z
	enumeration E
	enumeration E4
	enumeration G
	enumeration 1
	enumeration 2
	enumeration 3
	enumeration 4
	enumeration J
	enumeration K
	enumeration V
	enumeration W
	enumeration Y
	enumeration Q

#### element **uspsSummaryType/InHomeStart**


diagram									
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm								
type	<b>xs:dateTime</b>								
properties	<table> <tr><td>isRef</td><td>0</td></tr> <tr><td>minOcc</td><td>0</td></tr> <tr><td>maxOcc</td><td>1</td></tr> <tr><td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple
isRef	0								
minOcc	0								
maxOcc	1								
content	simple								

#### element **uspsSummaryType/InHomeEnd**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm

type	<b>xs:dateTime</b>
properties	isRef 0 minOcc 0 maxOcc 1 content simple


#### element **uspsSummaryType/ProcessingCategory**

diagram																																					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																																				
type	<b>mailxml_base:processingCategoryType</b>																																				
properties	isRef 0 content simple																																				
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>LT</td> <td></td> </tr> <tr> <td>enumeration</td> <td>FL</td> <td></td> </tr> <tr> <td>enumeration</td> <td>CD</td> <td></td> </tr> <tr> <td>enumeration</td> <td>OS</td> <td></td> </tr> <tr> <td>enumeration</td> <td>MP</td> <td></td> </tr> <tr> <td>enumeration</td> <td>IR</td> <td></td> </tr> <tr> <td>enumeration</td> <td>PF</td> <td></td> </tr> <tr> <td>enumeration</td> <td>CM</td> <td></td> </tr> <tr> <td>enumeration</td> <td>NP</td> <td></td> </tr> <tr> <td>enumeration</td> <td>SP</td> <td></td> </tr> <tr> <td>enumeration</td> <td>MB</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	enumeration	LT		enumeration	FL		enumeration	CD		enumeration	OS		enumeration	MP		enumeration	IR		enumeration	PF		enumeration	CM		enumeration	NP		enumeration	SP		enumeration	MB	
Kind	Value	annotation																																			
enumeration	LT																																				
enumeration	FL																																				
enumeration	CD																																				
enumeration	OS																																				
enumeration	MP																																				
enumeration	IR																																				
enumeration	PF																																				
enumeration	CM																																				
enumeration	NP																																				
enumeration	SP																																				
enumeration	MB																																				

#### element **uspsSummaryType/NewsIndicator**


diagram										
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm									
type	<b>mailxml_base:yesNo</b>									
properties	isRef 0 content simple									
facets	<table> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Yes</td> <td></td> </tr> <tr> <td>enumeration</td> <td>No</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	enumeration	Yes		enumeration	No	
Kind	Value	annotation								
enumeration	Yes									
enumeration	No									

#### element **uspsSummaryType/PriorityMailIndicator**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<b>mailxml_base:yesNo</b>
properties	isRef 0 content simple

	default	No
facets	Kind	Value annotation
	enumeration	Yes
	enumeration	No


#### element **uspsSummaryType/VerificationLocation**

diagram	 mailxml_tm:VerificationLocation
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_tm:verificationLocationType</a>
properties	isRef 0 content simple
facets	Kind Value annotation enumeration BMEU enumeration DMU

#### element **uspsSummaryType/EvsIndicator**

diagram	 mailxml_tm:EvsIndicator
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_base:yesNo</a>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation enumeration Yes enumeration No

#### element **uspsSummaryType/MailContentName**

diagram	 mailxml_tm:MailContentName
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	<a href="#">mailxml_base:s30</a>
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 30 whiteSpace preserve

### element **uspsSummaryType/MailPreparerID**

diagram	mailxml_tm:MailPreparerID												
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s12</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>12</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	12		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	12												
whiteSpace	preserve												


### element **uspsSummaryType/MailPreparerCRID**

diagram	mailxml_tm:MailPreparerCRID												
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:CRIDType</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>1</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>15</td><td></td></tr> <tr> <td>pattern</td><td>([0-9])*</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	15		pattern	([0-9])*	
Kind	Value	annotation											
minLength	1												
maxLength	15												
pattern	([0-9])*												

### element **uspsSummaryType/AdvanceMailingID**

diagram	mailxml_tm:AdvanceMailingID 0..∞												
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s09</b>												
properties	<table> <tr> <td>isRef</td><td>0</td></tr> <tr> <td>minOcc</td><td>0</td></tr> <tr> <td>maxOcc</td><td>unbounded</td></tr> <tr> <td>content</td><td>simple</td></tr> </table>	isRef	0	minOcc	0	maxOcc	unbounded	content	simple				
isRef	0												
minOcc	0												
maxOcc	unbounded												
content	simple												
facets	<table> <tr> <td>Kind</td><td>Value</td><td>annotation</td></tr> <tr> <td>minLength</td><td>1</td><td></td></tr> <tr> <td>maxLength</td><td>9</td><td></td></tr> <tr> <td>whiteSpace</td><td>preserve</td><td></td></tr> </table>	Kind	Value	annotation	minLength	1		maxLength	9		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	9												
whiteSpace	preserve												

**element `uspsSummaryType/EFileName`**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm												
type	<b>mailxml_base:s22</b>												
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple				
isRef	0												
minOcc	0												
maxOcc	1												
content	simple												
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>22</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </table>	Kind	Value	annotation	minLength	1		maxLength	22		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	22												
whiteSpace	preserve												

**element `uspsSummaryType/ContainsAutoMail`**

diagram										
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm									
type	<b>mailxml_base:yesNo</b>									
properties	<table> <tr> <td>isRef</td> <td>0</td> </tr> <tr> <td>minOcc</td> <td>0</td> </tr> <tr> <td>maxOcc</td> <td>1</td> </tr> <tr> <td>content</td> <td>simple</td> </tr> </table>	isRef	0	minOcc	0	maxOcc	1	content	simple	
isRef	0									
minOcc	0									
maxOcc	1									
content	simple									
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>enumeration</td> <td>Yes</td> <td></td> </tr> <tr> <td>enumeration</td> <td>No</td> <td></td> </tr> </table>	Kind	Value	annotation	enumeration	Yes		enumeration	No	
Kind	Value	annotation								
enumeration	Yes									
enumeration	No									

**simpleType `appointmentNumberIdentifierType`**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm																														
type	restriction of <b>xs:string</b>																														
used by	elements <a href="#">transportationContainerStatusBlockType/AppointmentNumberIdentifier</a> <a href="#">transportationDetailBlockType/AppointmentNumberIdentifier</a>																														
facets	<table> <tr> <td>Kind</td> <td>Value</td> <td>annotation</td> </tr> <tr> <td>enumeration</td> <td>F</td> <td></td> </tr> <tr> <td>enumeration</td> <td>D</td> <td></td> </tr> <tr> <td>enumeration</td> <td>O</td> <td></td> </tr> <tr> <td>enumeration</td> <td>P</td> <td></td> </tr> <tr> <td>enumeration</td> <td>Q</td> <td></td> </tr> <tr> <td>enumeration</td> <td>R</td> <td></td> </tr> <tr> <td>enumeration</td> <td>S</td> <td></td> </tr> <tr> <td>enumeration</td> <td>T</td> <td></td> </tr> <tr> <td>enumeration</td> <td>U</td> <td></td> </tr> </table>	Kind	Value	annotation	enumeration	F		enumeration	D		enumeration	O		enumeration	P		enumeration	Q		enumeration	R		enumeration	S		enumeration	T		enumeration	U	
Kind	Value	annotation																													
enumeration	F																														
enumeration	D																														
enumeration	O																														
enumeration	P																														
enumeration	Q																														
enumeration	R																														
enumeration	S																														
enumeration	T																														
enumeration	U																														

**simpleType `contentsBarcodeStatusType`**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
-----------	---

type	restriction of <b>xs:string</b>		
used by	element <a href="#"><b>transportationContainerBlockType/ContentsBarcodeStatus</b></a>		
facets	Kind	Value	annotation
	enumeration	A	
	enumeration	B	
	enumeration	C	
	enumeration	D	
	enumeration	E	
	enumeration	F	
	enumeration	G	
	enumeration	H	
	enumeration	O	

#### simpleType **contentsBarcodeTypeType**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm		
type	restriction of <b>xs:string</b>		
used by	element <a href="#"><b>transportationContainerBlockType/ContentsBarcodeType</b></a>		
facets	Kind	Value	annotation
	enumeration	A	
	enumeration	B	
	enumeration	D	
	enumeration	O	

#### simpleType **csaStatusType**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm		
type	restriction of <b>xs:string</b>		
used by	attribute <a href="#"><b>csalInfoType/@CSAStatus</b></a>		
facets	Kind	Value	annotation
	enumeration	ACT	
	enumeration	PEN	
	enumeration	INACT	
	enumeration	INCOMP	
	enumeration	PREAPP	

#### simpleType **csaTemplateType**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm		
type	restriction of <b>xs:string</b>		
used by	attribute <a href="#"><b>csaDispatchType/@CSATemplate</b></a>		
facets	Kind	Value	annotation
	enumeration	PVDS-PER	
	enumeration	DMU-C	
	enumeration	DMU-P	

	enumeration	BMEU
	enumeration	UPVDS-PER
	enumeration	UDMU-C
	enumeration	UDMU-P
	enumeration	UBMEU
	enumeration	U

#### simpleType **IMcbInfoType**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm	
type	restriction of <b>xs:string</b>	
used by	element <a href="#"><b>uspsContainerInfoType/IMcbInfo</b></a>	
facets	Kind	Value annotation
	enumeration	Linked
	enumeration	Scanned

#### simpleType **locationStatusType**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm	
type	restriction of <b>xs:string</b>	
used by	element <a href="#"><b>transportationGeoDataBlockType/LocationStatus</b></a>	
facets	Kind	Value annotation
	enumeration	P
	enumeration	O
	enumeration	I
	enumeration	F
	enumeration	U
	enumeration	M
	enumeration	D

#### simpleType **packageServicesType**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm	
type	restriction of <b>xs:string</b>	
used by	element <a href="#"><b>csaDispatchType/PackageServicesSubClass</b></a>	
facets	Kind	Value annotation
	enumeration	PS
	enumeration	BPM
	enumeration	LIB
	enumeration	MEDIA
	enumeration	PP

#### simpleType **processingCodeType**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm	

type	restriction of <b>xs:string</b>		
used by	element <a href="#"><b>csaDispatchType/ProcessingCode</b></a>		
facets	Kind	Value	annotation
	enumeration	S	
	enumeration	MXDS	
	enumeration	L	
	enumeration	WKG	
	enumeration	A	
	enumeration	MXDA	
	enumeration	SP	

#### simpleType **scanEventType**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm		
type	restriction of <b>xs:string</b>		
used by	element <a href="#"><b>transportationContainerStatusBlockType/ScanEvent</b></a>		
facets	Kind	Value	annotation
	enumeration	A	
	enumeration	B	
	enumeration	U	
	enumeration	E	
	enumeration	L	
	enumeration	F	
	enumeration	G	
	enumeration	O	

#### simpleType **stopStatusType**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm		
type	restriction of <b>xs:string</b>		
used by	element <a href="#"><b>transportationDetailBlockType/StopStatus</b></a>		
facets	Kind	Value	annotation
	enumeration	P	
	enumeration	A	
	enumeration	U	

#### simpleType **valueAddedServiceType**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm		
type	restriction of <b>xs:string</b>		
used by	elements <a href="#"><b>DeliveryApptCreateRequest/ValueAddedService</b></a> <a href="#"><b>DeliveryApptUpdateRequest/ValueAddedService</b></a> <a href="#"><b>DeliveryApptShellCreateRequest/ValueAddedService</b></a> <a href="#"><b>DeliveryApptShellUpdateRequest/ValueAddedService</b></a> <a href="#"><b>DeliveryReApptRequest/ValueAddedService</b></a> <a href="#"><b>apptBlockGoodsType/ValueAddedService</b></a> <a href="#"><b>apptBlockUnscheduledGoodsType/ValueAddedService</b></a>		
facets	Kind	Value	annotation
	enumeration	D1	

	enumeration D2
	enumeration D3
	enumeration D4
	enumeration D5
	enumeration D6
	enumeration D7
	enumeration D8
	enumeration D9
	enumeration D10
	enumeration D11
	enumeration D12
	enumeration D13
	enumeration D14
	enumeration D15
	enumeration D16
	enumeration D17
	enumeration D18
	enumeration D19
	enumeration D20

#### simpleType **verificationLocationType**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml_tm
type	restriction of <b>xs:string</b>
used by	elements <a href="#">apptBlockGoodsType/VerificationLocation contentUspsSummaryType/VerificationLocation contentUspsSummaryUpdateType/VerificationLocation uspsSummaryType/VerificationLocation</a>
facets	Kind Value annotation enumeration BMEU enumeration DMU

XML Schema documentation generated by [XMLSpy](#) Schema Editor <http://www.altova.com/xmlspy>