



Mail.XML Version 23.0

System Messages Specification

September 23, 2019

Working Group Chair

Bob Schimek, Assurety Consulting, Inc.

Technical Director

Shariq Mirza, Idealliance

Editor:

Shariq Mirza, Idealliance

Copyright (c) International Digital Enterprise Alliance, Inc. [Idealliance] (2004 – 2019). All Rights Reserved.

Mail.dat is a registered trademark of Idealliance

Mail.XML is a trademark of Idealliance



Copyright and Legal Notices

© 2001 – 2019 International Digital Enterprise Alliance, Inc. All Rights Reserved.

This document may be downloaded and copied provided that the above copyright notice and this Notice are included on all such copies. This document itself may not be modified in any way, except as needed for the purpose of developing International Digital Enterprise Alliance, Inc. ("Idealliance") specifications. Use of the specification or standard set forth in this document shall not create for the user any rights in or to such specification or standard or this document, which rights are exclusively reserved to Idealliance or its licensors or contributors.

Use of this document and any specification or standard contained herein is voluntary. By making use of this document or any specification or standard contained herein, the user assumes all risks and waives all claims against Idealliance, its licensors and contributors. By making this document available, Idealliance is not providing any professional services or advice to any person or entity. Any person or entity utilizing this document or any specification or standard contained herein should rely upon the advice of a competent professional before using any such information.

NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE REGARDING THE ACCURACY, ADEQUACY, COMPLETENESS, LEGALITY, RELIABILITY OR USEFULNESS OF ANY INFORMATION CONTAINED IN THIS DOCUMENT OR IN ANY SPECIFICATION OR STANDARD OR OTHER PRODUCT MADE AVAILABLE BY IDEALLIANCE. THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN AND INCLUDED IN ANY SPECIFICATION OR STANDARD OR OTHER PRODUCT OR SERVICE OF IDEALLIANCE IS PROVIDED ON AN "AS IS" BASIS. IDEALLIANCE DISCLAIMS ALL WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY ACTUAL OR ASSERTED WARRANTY OF NON-INFRINGEMENT OF PROPRIETARY RIGHTS, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE.

IN NO EVENT SHALL IDEALLIANCE, ITS LICENSEES, CONTRIBUTORS OR THEIR RESPECTIVE OFFICERS, DIRECTORS, EMPLOYEES, AGENTS, REPRESENTATIVES, SUPPLIERS OR CONTENT OR SERVICE PROVIDERS BE LIABLE FOR DAMAGES OF ANY KIND, INCLUDING WITHOUT LIMITATION, DIRECT, INDIRECT, COMPENSATORY, SPECIAL, INCIDENTAL, PUNITIVE OR CONSEQUENTIAL DAMAGES (INCLUDING WITHOUT LIMITATION DAMAGES FROM DATA LOSS OR BUSINESS INTERRUPTION) EVEN IF MADE AWARE OF THE POSSIBILITY OF SUCH DAMAGES, WHETHER IN AN ACTION UNDER CONTRACT, TORT OR ANY OTHER THEORY, ARISING OUT OF OR IN CONNECTION WITH THE USE, INABILITY TO USE OR PERFORMANCE OF THIS DOCUMENT, THE SPECIFICATION OR STANDARD CONTAINED HEREIN, OR ANY OTHER DOCUMENT OR SPECIFICATION OR STANDARD MADE AVAILABLE BY IDEALLIANCE.

Some states do not allow the disclaimer or limitation of damages, so the disclaimers set forth above apply to the maximum extent permitted under applicable law.

Idealliance takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed or implicated with respect to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available. Idealliance does not represent that it has made any effort to identify any such rights. Information on Idealliance's procedures with respect to rights in Idealliance specifications can be found at the Idealliance website at www.Idealliance.org. Copies of third-party claims of rights, assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification, can be obtained from the President of Idealliance at patent-disclosure@Idealliance.org.

Idealliance requests interested parties to disclose any copyrights, trademarks, service marks, patents, patent applications, or other proprietary or intellectual property rights which may cover technology that may be required to implement this specification. Please address the information to the President of Idealliance at patent-disclosure@Idealliance.org.

Abstract

This document describes the messaging protocol for use by mailers and their consignees. The Mail.XML™ Transaction Protocol defines the roles and responsibilities of Shippers and Consignees and defines the format and method for message exchange. This messaging protocol is designed to be XML and Web-Services compliant.

Mail.XML and Mail.dat are trademarks of Idealliance.

About Mail.XML™

Mail.XML™ is bringing a paradigm change to the industry by increasing business function specific B2B (Business to Business) communication within the industry that supports automation and in the end enables cost avoidance and higher profits through improved competence and effectiveness of communication. Mail.XML is designed to increase efficiency and lower costs by removing many manual data entry processes and enabling quick near real time communication between business partners. Mail.XML currently supports container based scheduling, pick up and drop off business processes, as well as identifying different business entities responsible for performing different services such as quality of mailing, address correction, and delivery confirmation on a mailing. The core focus of Mail.XML is communication between industry members and from industry to the final mail processing and delivery organization that delivers the mail to the end consumer, e.g., USPS. In the next few versions of Mail.XML the focus moves across mailing supply chain channels, and includes advanced functions such as payment; automated verification; enabling first, second, and third party communication and incorporating presort planning, printing, and distribution processes.

What's New in Mail.XML Version 23.0?

With this release, the Mail.XML Messaging Protocol moves to Version 23.0. In addition to minor cleanup, this release supports Mail.dat modernization and provides a new message for mailers to notify USPS of transportation dispatch details.

Changes supported by Mail.XML 23.0 include:

- Add a new element as part of MailCharacteristic Incentive block to allow users to provide data associated with Group ID for Electronic Sample of Mailpiece (eMailpieceSampleGroupID).
- Updates to ContainerScanQueryRequest to allow users to enter more than one ContainerID to request for status on more than one containers.

About Mail.XML Schema Modularization

Today Mail.XML messages are grouped into 8 message types.

- Transportation Messages (TM)

- Mailing Messages (MM)
- Data Distribution Messages (DD)
- Dynamic Payment Template Messages
- Identification Messages (ID)
- Supply Chain Messages (SC)
- Informed Visibility (IV)
- System Messages
- Base: Shared simple types
- Definitions: Shared complex types and elements

The simple types shared across 2 or more modules are found in the Base schema. Likewise the shared definitions module contains complex type definitions and elements that are shared across 2 or more modules.

Mail.XML Module Versioning Rules

The following versioning rules will be followed:

- The Mail.XML wrapper schema**(.xsd) will always be given the next higher version number (or Errata designation) when any update is made to base, defs or any module. The name of the .xsd file will indicate the new version and the new version number will be used in the namespace and target declarations: `xmlns:Mail.XML="http://Idealliance.org/Specs/Mail.XML23.0/Mail.XML"`
`targetNamespace="http://Idealliance.org/Specs/Mail.XML23.0/Mail.XML"`
- When updates are made, only those modules that are updated will be given the next higher version number (or Errata letter designation).
- If updates are made to the base or defs, then the base and defs xsds will be given the next higher version number (or Errata designation) and all modules that call to them will also be given the next higher version number (or Errata designation).

For example:

- If the wrapper version is labeled as `xmlns:Mail.XML="http://Idealliance.org/Specs/Mail.XML15.0A/Mail.XML"` then at least one of the XSDs is at same version such as filename = 'Mail.XML_15.0.A.xsd' <- Errata A
- If the wrapper version is labeled as `xmlns:Mail.XML="http://Idealliance.org/Specs/Mail.XML15.0B/Mail.XML"` then at least one of the XSDs is at same version such as filename = 'Mail.XML_15.0B.xsd' <- Errata B

- If the wrapper version is labeled as `xmlns:Mail.XML="http://Idealliance.org/Specs/Mail.XML15.0/Mail.XML"` then at least one of the XSDs is at same version such as filename = 'Mail.XML_15.0.xsd' <- Major Version

Mail.XML 23.0 XSD Modules:

The following Mail.XML XSD modules/namespaces are used:

- Mail.XML_tm.xsd: This module contains all the transportation (or FAST) messages and the attributes, elements and complex types that are unique to these messages. Namespace=Mail.XML_tm:
- Mail.XML_mm.xsd: This module contains all the mailing messages (eDoc) and the attributes, elements and complex types that are unique to these messages. Namespace=Mail.XML_mm:
- Mail.XML_iv.xsd: This module contains informed visibility messages and the attributes, elements and complex types that are unique to these messages. Namespace=Mail.XML_iv:
- Mail.XML_dd.xsd: This module contains all the data distribution messages and the attributes, elements and complex types that are unique to these messages. Namespace=Mail.XML_dd:
- Mail.XML_id.xsd: This module contains all the identification messages and the attributes, elements and complex types that are unique to these messages. Namespace=Mail.XML_id:
- Mail.XML_sc.xsd: This module contains all the supply chain messages and the attributes, elements and complex types that are unique to these messages. Namespace=Mail.XML_sc:
- Mail.XML_defs.xsd: This module contains all the common definitions of attributes, elements and complex types that are used across two or more message types. Namespace=Mail.XML_defs:
- Mail.XML_base.xsd: This module contains simple types that are shared across two or more modules that make up Mail.XML. These can be considered a building block for any message group. Namespace=Mail.XML_base:
- Mail.XML.xsd: This module contains the system messages of Mail.XML and is used to build custom profiles for Mail.XML. Namespace=Mail.XML:

The Mail.XML™ 23 Messaging Documentation Set

The Mail.XML Messaging Specification has been organized into a set of documents. This *Schemas Specification* is one document in a set of documents that make up the Mail.XML Specification 23.0. Updates in this Specification are NOT backwardly compatible with previous versions. Other documents in the specification set include:

- Mail.XML™ 23.0: Transportation Messaging Specification documents all transportation messages
- Mail.XML™ 23.0: Mailing Messaging Specification documents all mailing messages
- Mail.XML™ 23.0: Informed Visibility Specification documents all informed visibility messages

- Mail.XML™ 23.0: Data Distribution Messaging Specification documents all data distribution messages
- Mail.XML™ 23.0: Identification Messaging Specification documents all identification messages
- Mail.XML™ 23.0: Supply Chain Messaging Specification documents all supply chain messages
- Mail.XML™ 23.0: System Messaging Specification documents all systems and fault messages
- Mail.XML™ 23.0: Simple Types Specification documents all simple types used across Mail.XML messages
- Mail.XML™ 23.0: Common Definitions Specification documents all shared elements and complex types.
- Mail.XML™ 23.0: Schemas contains the .XSDs that make up the Mail.XML Messaging Specification

Table of Contents

Abstract	iii
About Mail.XML™	iii
What’s New in Mail.XML Version 23.0?	iii
About Mail.XML Schema Modularization	iii
Mail.XML Module Versioning Rules	iv
The Mail.XML™ 23 Messaging Documentation Set	v
1 Index	8
2 Elements	9

1 Index

schema location: C:\WORK\Idealliance\2-XML\23.0 - internal edits\MailXMLV23-9-23-19\mailxml_23.0.xsd
attribute form default: **qualified**
element form default: **qualified**
targetNamespace: <http://idealliance.org/Specs/mailxm123.0/mailxml>

Elements

[DeliveryResponse](#)

[Fault](#)

[MessageResponseRetrievalRequest](#)

[MessageResponseRetrievalResponse](#)

[NotificationResponse](#)

[SystemVersionQueryRequest](#)

[SystemVersionQueryResponse](#)

Complex types

[messageResponseNotAvailableResponseType](#)

[messageResponseRetrievalRequestType](#)

[messageResponseRetrievalResponseType](#)

2 Elements

element **DeliveryResponse**

diagram	<p>Response sent to USPS by a customer when any delivery is pushed. For example when a delivery point validation delivery is pushed by USPS this response is returned by the receiver.</p>
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml
properties	content complex
children	mailxml:UserLicenseCode mailxml:MaildatJobID mailxml:CustomerGroupID mailxml:MailingGroupID mailxml:PushMessageID mailxml:DeliveryType mailxml:ReturnInfo
used by	element messageResponseRetrievalResponseType/QueryResults
annotation	documentation Response sent to USPS by a customer when any delivery is pushed. For example when a delivery point validation delivery is pushed by USPS this response is returned by the receiver.

element **DeliveryResponse/UserLicenseCode**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml												
type	mailxml_base:userLicenseCodeType												
properties	isRef 0 content simple												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	4		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	4												
whiteSpace	preserve												

element **DeliveryResponse/MaildatJobID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml
type	mailxml_base:jobIDType
properties	isRef 0 content simple

facets	Kind	Value	annotation
	minLength	1	
	maxLength	8	
	whiteSpace	preserve	

element **DeliveryResponse/CustomerGroupID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml
type	mailxml_base:s25
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 25 whiteSpace preserve

element **DeliveryResponse/MailingGroupID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml
type	xs:nonNegativeInteger
properties	isRef 0 content simple

element **DeliveryResponse/PushMessageID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml
type	mailxml_base:s25
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 25 whiteSpace preserve

element DeliveryResponse/DeliveryType

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml
type	xs:string
properties	isRef 0 content simple

element DeliveryResponse/ReturnInfo

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml
type	mailxml_defs:basicReturnInfoType
properties	isRef 0 content complex
children	mailxml_defs:ReturnCode mailxml_defs:ReturnDescription mailxml_defs:errorWarning mailxml_defs:ContainerErrorWarningBlock

element Fault

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml												
properties	content complex												
children	mailxml:ErrorWarning												
used by	element messageResponseRetrievalResponseType/QueryResults												
attributes	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml:TrackingID</td> <td>mailxml_base:s20</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml:TrackingID	mailxml_base:s20				
Name	Type	Use	Default	Fixed	annotation								
mailxml:TrackingID	mailxml_base:s20												
annotation	documentation												

	A fault message.
--	------------------

attribute Fault/@TrackingID

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml		
type	mailxml_base:s20		
properties	isRef 0		
facets	Kind	Value	annotation
	minLength	1	
	maxLength	20	
	whiteSpace	preserve	

element Fault/ErrorWarning

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml
type	mailxml_defs:errorWarningType
properties	isRef 0 content complex
children	mailxml_defs:Code mailxml_defs:Severity mailxml_defs:KeyIDvalues mailxml_defs:SubmissionDate mailxml_defs:ErrorDescription mailxml_defs:Action mailxml_defs:TrackingID mailxml_defs:SubmitterTrackingID mailxml_defs:MailxmlDetail

element MessageResponseRetrievalRequest

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml
properties	content complex
children	mailxml:SubmittingParty mailxml:SubmittingSoftware mailxml:MessageResponse
annotation	documentation Request to send responses once more when the response was interrupted by a system fault.

element MessageResponseRetrievalRequest/SubmittingParty

diagram																																																	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml																																																
type	mailxml_defs:participantIDType																																																
properties	isRef 0 content complex																																																
attributes	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml_defs:MailerID6</td> <td>mailxml_base:mailerID6Type</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MailerID9</td> <td>mailxml_base:mailerID9Type</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:CRID</td> <td>mailxml_base:CRIDType</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:SchedulerID</td> <td>mailxml_base:s12</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:MaildatUserLicense</td> <td>mailxml_base:userLicenseCodeType</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ShippingAgentID</td> <td>mailxml_base:s12</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>mailxml_defs:ReceivingAgentID</td> <td>mailxml_base:s12</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml_defs:MailerID6	mailxml_base:mailerID6Type					mailxml_defs:MailerID9	mailxml_base:mailerID9Type					mailxml_defs:CRID	mailxml_base:CRIDType					mailxml_defs:SchedulerID	mailxml_base:s12					mailxml_defs:MaildatUserLicense	mailxml_base:userLicenseCodeType					mailxml_defs:ShippingAgentID	mailxml_base:s12					mailxml_defs:ReceivingAgentID	mailxml_base:s12				
Name	Type	Use	Default	Fixed	annotation																																												
mailxml_defs:MailerID6	mailxml_base:mailerID6Type																																																
mailxml_defs:MailerID9	mailxml_base:mailerID9Type																																																
mailxml_defs:CRID	mailxml_base:CRIDType																																																
mailxml_defs:SchedulerID	mailxml_base:s12																																																
mailxml_defs:MaildatUserLicense	mailxml_base:userLicenseCodeType																																																
mailxml_defs:ShippingAgentID	mailxml_base:s12																																																
mailxml_defs:ReceivingAgentID	mailxml_base:s12																																																

element **MessageResponseRetrievalRequest/SubmittingSoftware**

diagram	<p>The diagram shows a class <code>mailxml:SubmittingSoftware</code> connected to a complex type <code>mailxml_defs:submittingSoftwareType</code>. This type has an <code>attributes</code> container with five elements: <code>mailxml_defs:SoftwareName</code>, <code>mailxml_defs:Vendor</code>, <code>mailxml_defs:Version</code>, <code>mailxml_defs:ApprovalDate</code>, and <code>mailxml_defs:ApprovalKey</code>. The first three are solid boxes, while the last two are dashed boxes.</p>					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml					
type	mailxml_defs:submittingSoftwareType					
properties	isRef	0	content	complex		
attributes	Name	Type	Use	Default	Fixed	annotation
	mailxml_defs:SoftwareName	xs:string	required			
	mailxml_defs:Vendor	xs:string	required			
	mailxml_defs:Version	xs:string	required			
	mailxml_defs:ApprovalDate	xs:date				
	mailxml_defs:ApprovalKey	xs:string				

element **MessageResponseRetrievalRequest/MessageResponse**

diagram	<p>The diagram shows a class <code>mailxml:MessageResponse</code> connected to a complex type <code>mailxml:messageResponseRetrievalRequestType</code>. This type has an <code>attributes</code> container with one element: <code>mailxml:TrackingID</code>. A multiplicity of <code>1..∞</code> is shown near the connection.</p>					
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml					
type	mailxml:messageResponseRetrievalRequestType					
properties	isRef	0	minOcc	1	maxOcc	unbounded
	content	complex				
attributes	Name	Type	Use	Default	Fixed	annotation
	mailxml:TrackingID	mailxml_base:s20	required			

element **MessageResponseRetrievalResponse**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml
properties	content complex
children	mailxml:MessageResponseRetrievalAccept mailxml:MessageResponseRetrievalReject
annotation	documentation Response to the Message Response Retrieval Request that resends interrupted responses.

element **MessageResponseRetrievalResponse/MessageResponseRetrievalAccept**

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml												
type	mailxml:messageResponseRetrievalResponseType												
properties	isRef 0 content complex												
children	mailxml:QueryResults mailxml_defs:QueryError												
attributes	<table border="1"> <thead> <tr> <th>Name</th> <th>Type</th> <th>Use</th> <th>Default</th> <th>Fixed</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>mailxml:TrackingID</td> <td>mailxml_base:s20</td> <td>required</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Name	Type	Use	Default	Fixed	annotation	mailxml:TrackingID	mailxml_base:s20	required			
Name	Type	Use	Default	Fixed	annotation								
mailxml:TrackingID	mailxml_base:s20	required											

element **MessageResponseRetrievalResponse/MessageResponseRetrievalReject**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml

type	mailxml:messageResponseNotAvailableResponseType					
properties	isRef	0	content	complex		
children	mailxml:ReturnInfo					
attributes	Name	Type	Use	Default	Fixed	annotation
	mailxml:TrackingID	mailxml_base:s20	required			

element NotificationResponse

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml
properties	content complex
children	mailxml:UserLicenseCode mailxml:MaildatJobID mailxml:CustomerGroupID mailxml:MailingGroupID mailxml:PushMessageID mailxml:NotificationDate mailxml:ReturnInfo
used by	element messageResponseRetrievalResponseType/QueryResults
annotation	documentation Standard response to a USPS notification to indicate the notification has been received.


element NotificationResponse/UserLicenseCode

diagram													
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml												
type	mailxml_base:userLicenseCodeType												
properties	isRef 0 content simple												
facets	<table border="1"> <thead> <tr> <th>Kind</th> <th>Value</th> <th>annotation</th> </tr> </thead> <tbody> <tr> <td>minLength</td> <td>1</td> <td></td> </tr> <tr> <td>maxLength</td> <td>4</td> <td></td> </tr> <tr> <td>whiteSpace</td> <td>preserve</td> <td></td> </tr> </tbody> </table>	Kind	Value	annotation	minLength	1		maxLength	4		whiteSpace	preserve	
Kind	Value	annotation											
minLength	1												
maxLength	4												
whiteSpace	preserve												

element **NotificationResponse/MaildatJobID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml
type	mailxml_base:jobIDType
properties	isRef 0 content simple
facets	Kind Value annotation minLength 1 maxLength 8 whiteSpace preserve


element **NotificationResponse/CustomerGroupID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml
type	mailxml_base:s25
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 25 whiteSpace preserve

element **NotificationResponse/MailingGroupID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml
type	xs:nonNegativeInteger
properties	isRef 0 content simple

element **NotificationResponse/PushMessageID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml
type	mailxml_base:s25
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation

	minLength 1
	maxLength 25
	whiteSpace preserve

element **NotificationResponse/NotificationDate**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml
type	xs:date
properties	isRef 0 content simple

element **NotificationResponse/ReturnInfo**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml
type	mailxml_defs:basicReturnInfoType
properties	isRef 0 content complex
children	mailxml_defs:ReturnCode mailxml_defs:ReturnDescription mailxml_defs:errorWarning mailxml_defs:ContainerErrorWarningBlock

element **SystemVersionQueryRequest**


diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml
properties	content complex
children	mailxml:TrackingID mailxml:SubmittingParty mailxml:SubmittingSoftware

annotation	documentation Query request for the receiving system version information.
------------	--

element **SystemVersionQueryRequest/TrackingID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml
type	mailxml_base:s20
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

element **SystemVersionQueryRequest/SubmittingParty**

diagram						
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml					
type	mailxml_defs:participantIDType					
properties	isRef 0 content complex					
attributes	Name	Type	Use	Default	Fixed	annotation
	mailxml_defs:MailerID6	mailxml_base:mailerID6Type				
	mailxml_defs:MailerID9	mailxml_base:mailerID9Type				
	mailxml_defs:CRID	mailxml_base:CRIDType				
	mailxml_defs:SchedulerID	mailxml_base:s12				
	mailxml_defs:MaildatUserLicense	mailxml_base:userLicenseCodeType				
	mailxml_defs:ShippingAgentID	mailxml_base:s12				

	mailxml_defs:ReceivingAgentID	mailxml_base:s12
--	-------------------------------	------------------

element **SystemVersionQueryRequest/SubmittingSoftware**

diagram						
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml					
type	mailxml_defs:submittingSoftwareType					
properties	isRef	0	content	complex		
attributes	Name	Type	Use	Default	Fixed	annotation
	mailxml_defs:SoftwareName	xs:string	required			
	mailxml_defs:Vendor	xs:string	required			
	mailxml_defs:Version	xs:string	required			
	mailxml_defs:ApprovalDate	xs:date				
	mailxml_defs:ApprovalKey	xs:string				

element **SystemVersionQueryResponse**

diagram						
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml					
properties	content	complex				
children	mailxml:QueryResults mailxml_defs:QueryError					
used by	element	messageResponseRetrievalResponseType/QueryResults				
annotation	documentation	Response to a query for the receiving system version information.				

element **SystemVersionQueryResponse/QueryResults**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml
properties	isRef 0 content complex
children	mailxml:TrackingID mailxml:SubmitterTrackingID mailxml:SoftwareStatus mailxml:ReturnInfo

element **SystemVersionQueryResponse/QueryResults/TrackingID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml
type	mailxml_base:s20
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

element **SystemVersionQueryResponse/QueryResults/SubmitterTrackingID**

diagram	
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml
type	mailxml_base:s20
properties	isRef 0 minOcc 0 maxOcc 1 content simple
facets	Kind Value annotation minLength 1 maxLength 20 whiteSpace preserve

element **SystemVersionQueryResponse/QueryResults/SoftwareStatus**

diagram						
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml					
type	mailxml_defs:submittingSoftwareType					
properties	isRef	0	content	complex		
attributes	Name	Type	Use	Default	Fixed	annotation
	mailxml_defs:SoftwareName	xs:string	required			
	mailxml_defs:Vendor	xs:string	required			
	mailxml_defs:Version	xs:string	required			
	mailxml_defs:ApprovalDate	xs:date				
	mailxml_defs:ApprovalKey	xs:string				

element **SystemVersionQueryResponse/QueryResults/ReturnInfo**

diagram						
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml					
type	mailxml_defs:basicReturnInfoType					
properties	isRef	0	minOcc	0	maxOcc	1
	content	complex				
children	mailxml_defs:ReturnCode mailxml_defs:ReturnDescription mailxml_defs:errorWarning mailxml_defs:ContainerErrorWarningBlock					

complexType **messageResponseNotAvailableResponseType**

diagram						
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml					
children	mailxml:ReturnInfo					
used by	element	MessageResponseRetrievalResponse/MessageResponseRetrievalReject				
attributes	Name	Type	Use	Default	Fixed	annotation
	mailxml:TrackingID	mailxml_base:s20	required			

attribute **messageResponseNotAvailableResponseType/@TrackingID**

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml					
type	mailxml_base:s20					
properties	isRef	0	use	required		
facets	Kind	Value	annotation			
	minLength	1				
	maxLength	20				
	whiteSpace	preserve				

element **messageResponseNotAvailableResponseType/ReturnInfo**

diagram						
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml					
type	mailxml_defs:returnInfoType					
properties	isRef	0	content	complex		
children	mailxml_defs:ConsigneeFacility mailxml_defs:ErrorWarning mailxml_defs:ContainerErrorWarningBlock					

complexType messageResponseRetrievalRequestType

diagram						
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml					
used by	element MessageResponseRetrievalRequest/MessageResponse					
attributes	Name	Type	Use	Default	Fixed	annotation
	mailxml:TrackingID	mailxml_base:s20	required			

attribute messageResponseRetrievalRequestType/@TrackingID

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml					
type	mailxml_base:s20					
properties	isRef	0	use	required		
facets	Kind	Value	annotation			
	minLength	1				
	maxLength	20				
	whiteSpace	preserve				

complexType messageResponseRetrievalResponseType

diagram						
namespace	http://idealliance.org/Specs/mailxml23.0/mailxml					
children	mailxml:QueryResults mailxml_defs:QueryError					
used by	element MessageResponseRetrievalResponse/MessageResponseRetrievalAccept					
attributes	Name	Type	Use	Default	Fixed	annotation
	mailxml:TrackingID	mailxml_base:s20	required			

attribute messageResponseRetrievalResponseType/@TrackingID

namespace	http://idealliance.org/Specs/mailxml23.0/mailxml					
type	mailxml_base:s20					
properties	isRef	0	use	required		
facets	Kind	Value	annotation			
	minLength	1				

	maxLength 20
	whiteSpace preserve

element **messageResponseRetrievalResponseType/QueryResults**

diagram



namespace	http://idealliance.org/Specs/mailxml23.0/mailxml
properties	isRef 0 content complex
children	mailxml:Fault mailxml_tm:AllApptCloseoutResponse mailxml_tm:ApptInductionCloseoutResponse mailxml_tm:CustomerSupplierAgreementQueryResponse mailxml_tm:DeliveryApptCancelCreateResponse mailxml_tm:DeliveryApptCancelResponse mailxml_tm:DeliveryApptContentRemoveResponse mailxml_tm:DeliveryApptCreateResponse mailxml_tm:DeliveryApptQueryResponse mailxml_tm:DeliveryApptShellCancelResponse mailxml_tm:DeliveryApptShellCreateResponse mailxml_tm:DeliveryApptShellUpdateResponse mailxml_tm:DeliveryApptStatusQueryResponse mailxml_tm:DeliveryApptTransportationUpdateResponse mailxml_tm:DeliveryApptUpdateResponse mailxml_tm:DeliveryContentCancelResponse mailxml_tm:DeliveryContentCreateResponse mailxml_tm:DeliveryContentQueryResponse mailxml_tm:DeliveryContentUpdateResponse mailxml_tm:GoodsReceiptResponse mailxml_tm:OpenApptQueryResponse mailxml_tm:PartnerApptQueryResponse mailxml_tm:PartnerContentAssignmentResponse mailxml_tm:PickupApptCancelResponse mailxml_tm:PickupApptCreateResponse mailxml_tm:PickupApptUpdateResponse mailxml_tm:RecurringApptQueryResponse mailxml_tm:ScanSTCReconciliationQueryResponse mailxml_tm:USPSDeliveryContentUpdatedQueryResponse mailxml_dd:ByForConflictQueryResponse mailxml_dd:DeliveryPointValidationQueryResponse mailxml_dd:AddressCorrectionQueryResponse mailxml_dd:DataQualityVerificationReportQueryResponse mailxml_dd:NixieDetailQueryResponse mailxml_dd:NonComplianceDataWithPostageOwedReportQueryResponse mailxml_dd:ScanSTCReconciliationQueryResponse mailxml_iv:ContainerVisibilityQueryResponse mailxml_iv:MPSVisQueryResponse mailxml_iv:StartTheClockQueryResponse mailxml_mm:BeginCombinedMailingResponse mailxml_mm:BundleDetailCancelResponse mailxml_mm:BundleDetailCreateResponse mailxml_mm:CloseMailingGroupResponse mailxml_mm:ComponentQueryResponse mailxml_mm:ComponentUpdateResponse mailxml_mm:ConsolidatedPeriodicalStatementCreateResponse mailxml_mm:ContainerBundleReportCancelResponse mailxml_mm:ContainerBundleReportCreateResponse mailxml_mm:ContainerBundleReportQueryResponse mailxml_mm:ContainerManifestCreateResponse mailxml_mm:ContainerManifestUpdateResponse mailxml_mm:ContainerManifestCancelResponse mailxml_mm:ContainerUpdateResponse mailxml_mm:CustomerMailReportCreateResponse mailxml_mm:EndCombinedMailingResponse mailxml_mm:InternationalPostageStatementCreateResponse mailxml_mm:InternationalPostageStatementQueryResponse mailxml_mm:InvoiceQueryResponse mailxml_mm:MailPieceCancelResponse mailxml_mm:MailPieceCreateResponse mailxml_mm:MailPieceUpdateResponse mailxml_mm:MailingGroupQueryResponse mailxml_mm:ManifestCreateResponse mailxml_mm:ManifestCancelResponse mailxml_mm:ManifestPaymentExtractQueryResponse mailxml_mm:OpenMailingGroupResponse mailxml_mm:PaymentMessageQueryResponse mailxml_mm:PeriodicalStatementCreateResponse mailxml_mm:PeriodicalStatementQueryResponse mailxml_mm:PostageStatementCancelResponse mailxml_mm:PostageStatementCreateResponse mailxml_mm:PostageStatementQueryResponse mailxml_mm:PostageStatementStatusQueryResponse mailxml_mm:QualificationReportCreateResponse mailxml_mm:QualificationReportDetailCreateResponse mailxml_mm:QualificationReportQueryResponse mailxml_mm:QualificationReportSummaryCreateResponse mailxml_mm:ReconciliationReportQueryResponse mailxml_mm:SummaryZipDestinationReportCreateResponse mailxml_mm:TMSDataLoggerQueryResponse mailxml_id:CastofCharactersCancelResponse mailxml_id:CastofCharactersCreateResponse mailxml_id:CastofCharactersUpdateResponse mailxml_id:CustomerRelationIdentifyQueryResponse mailxml_id:CustomerRelationIdentifyUpdateResponse mailxml_id:IncentiveEnrollmentCreateResponse mailxml_id:USPSRIDCreateValidateResponse mailxml_id:USPSMIDCreateValidateResponse mailxml_sc:ContainerStatusQueryResponse mailxml_sc:OriginalContainerLinkageCancelResponse mailxml_sc:OriginalContainerLinkageCreateResponse mailxml_sc:PostageAdjustmentCreateResponse mailxml_sc:SiblingContainerCancelResponse mailxml_sc:SiblingContainerCreateResponse mailxml:DeliveryResponse mailxml:NotificationResponse mailxml:SystemVersionQueryResponse mailxml:ReturnInfo

element **messageResponseRetrievalResponseType/QueryResults/ReturnInfo**

<p>diagram</p>	
<p>namespace</p>	<p>http://idealliance.org/Specs/mailxml23.0/mailxml</p>
<p>type</p>	<p>mailxml_defs:basicReturnInfoType</p>
<p>properties</p>	<p>isRef 0 minOcc 0 maxOcc 1 content complex</p>
<p>children</p>	<p>mailxml_defs:ReturnCode mailxml_defs:ReturnDescription mailxml_defs:errorWarning mailxml_defs:ContainerErrorWarningBlock</p>